

WO 92/13313

PCT/US92/00218

9603653-8.
(original)RTMP's
copy.

-1-

MIXED RESOLUTION, N-DIMENSIONAL OBJECT SPACEBACKGROUND OF THE INVENTION

This invention relates to an apparatus and method for generating mixed-resolution, N-dimensional object spaces by transformation of logical object descriptors or sensed physical phenomena. This invention also relates to an apparatus and method for visualizing mixed-resolution, N-dimensional object spaces, by projecting a bit-interleaved object descriptor onto a plane. More particularly, this invention relates to an apparatus and method for encoding spatial locations with a novel k-ary reflected code.

DESCRIPTION OF THE RELEVANT ART

In a survey of research directions related to visualization methods, the Microelectronics and Computer Consortium (MCC) characterized the field of abstract visualization as a mapping of logical object relations into visual space "...so that inferences drawn from the visual representation can be carried back into the abstract domain." Abstract visualization, as described herein, also means the mapping of sensed physical phenomena into a logical space. For applications like exploring high-dimensional multivariate data "...visualization of concrete things is not as important as visualization of abstract entities." In such applications "...the problem of what to represent and how to deliver the representation are the key, while photorealism is not as important."

A significant class of problems related to abstract visualization have solutions which are not arithmetic in nature. Furthermore, the explanation of a particular result is as important to an appropriate solution as the result itself. Ideally, the method employed for solving such problems should enable abstract visualization of the

This Sheet Has Been Replaced



REPLACED SHEETS		SG
☒	Description : paged	to paged 50
☒	Claim(s) : paged 51	to paged 59
☒	Drawing(s) : paged 11/21	to paged 22/22
☐	Abstract : paged	to paged
DATE OF RECEIPT		11/2/96

-2-

problem-solving process itself. The simplification of Boolean function expressions is a particularly well-known example of such problems.

Early approaches to devising a mechanical procedure for improving circuit design included a "chart method" developed by the Harvard University Computation Laboratory, which is described in a book edited by H. H. Aiken entitled, Synthesis of Electronic Computing and Control Circuits, Harvard University Press, 1951. In the article "Sketch for an Algebra for Relay and Contact Circuits," Montgomerie suggests a graphical approach for reducing logic equations. Montgomerie's approach was developed and extended by E. W. Veitch in "A Chart Method for Simplifying Truth Functions," Proceedings of the Association for Computing Machinery, Richard Rimbach Associates, Pittsburgh, 1952, pp. 127-133, and later by Maurice Karnaugh in "The Map Method of Synthesis of Combinational Logic Circuits," AIEE Transactions, Part I, Vol. 72, November 1953, pp. 593-599.

Karnaugh describes a method for mapping abstract representations of circuit inputs into visual space. The Karnaugh map, often called a k-map, is a widely known technique for visualizing logical expressions based on a two-valued Boolean algebra. Entries representing circuit inputs correspond to a position in a k-map derived from visualizing the codes as points in a binary n-space. The k-map is a two-dimensional representation of this space mapped onto the Cartesian plane by labeling each axis with a binary Gray code. Inferences drawn from this visual representation of logic expressions usually result in a reduction of the canonical expression.

A well-known aspect common to all Gray codes is that consecutive codewords differ in only one quantum interval, that is, one bit position in the case of binary Gray



-3-

codes. A Gray code is said to cycle if its first and last codewords differ in only one quantum interval, otherwise it describes a path. Each consecutive codeword in a binary Gray code can be represented

by the bit position that changes. Given an initial codeword and a transition sequence the entire set of codewords can be generated. U.S. Pat. No. 2,632,058 issued to Frank Gray distinguishes between a primary form and secondary variants of the reflected binary code:

Because this code in its primary form may be built up from the conventional binary code by sort of a reflection process and because other forms may in turn be built up from the primary form in similar fashion, the code in question, which has as yet no recognized name, is designated in this specification and in the claims as the 'reflected binary code.'

Some forms of the reflected binary code offer special advantages over others for particular applications.

FIGS. 1A-1E show a prior art method of unfolding a binary 3-cube onto a plane as a k-map, described by Clare in Designing Logic System Using State Machines, 1973, McGraw-Hill, NY, pp. 14-15.

FIG. 2 is a prior art representation of binary n-cubes as k-maps, showing a 0-cube k-map 200, a 1-cube k-map 201, a 2-cube k-map 202, a 2-cube k-map 203, a 3-cube k-map 204, and a 4-cube k-map 205. The 2-cube k-maps 202, 203 are different representations for a two-variable k-map shown by Karnaugh in the article referenced above. Such alternate spatial representations are inconsistent with each other. Furthermore, region identifiers A 206, B 207, and C 208 in the 3-cube k-map 204 of FIG. 2 are located in a manner inconsistent with the diagram of the 2-cube k-map 202.

FIG. 3A shows a four-variable Karnaugh map encoded by labeling each axis with a binary Gray code. Map cells 300 of FIG. 3A correspond to the grid cells 301 of FIG. 3B.



WO 92/13313

-4-

The labeling method of FIG. 3B is a simplification of the method of FIG. 3A. Grid cells 301 in FIG. 3B are distinguished by region identifiers 302. Grid cells 301 in FIG. 3B within a particular region 302 have a logical value of one for the bit position in corresponding map cell 300 names of FIG. 3A.

FIGS. 4A-4B are a prior art method of visualizing the binary 5-cube and the binary 6-cube as k-maps. Clare, in the reference cited above, shows the 5-cube 400 and the 6-cube 402 copied and translated to the right 401 and downward 403, respectively.

FIG. 5 shows a device proposed by Karnaugh, to visualize the synthesis of a network of six variables:

[The three-dimensional cube] ...consists of four 6-inch plexiglass sheets supported at 1-1/2-inch intervals by rods.... In using it we employ movable markers.... The extension to seven variables is probably best accomplished by placing two cubes side by side.... Eight variables can be handled with a set of four cubes, and nine variables require eight cubes. In the latter case it is convenient to make them so as to stack easily into two layers of four each. Beyond nine variables, the mental gymnastics required for synthesis will, in general, be formidable.

The application of k-maps for problems of more than four variables has been described in the literature as tedious; therefore, the k-map's utility is generally limited to the introduction of ideas about logic circuits and their synthesis. An article written by J.P. Roth and entitled, "The Synthesis of Switching Systems I.," Transactions of the American Mathematical Society, Vol. 88, No. 2, July 1958, pp. 301-327, describes an alternate topological representation of Boolean functions called the cubic notation. Although Roth's approach is an improvement

This Sheet Has Been Replaced



-5-

over Karnaugh in the mechanization of Boolean functions, visualization of problems of more than a few variables is not achievable.

An article by Liu and Fu, "Cellwork, Its Network
5 Duals, and Some Applications -- Three-Dimensional Karnaugh Map and Its Virtual Planar Representation," Information Science, Vol. 24, 1981, pp. 93-109, is representative of various attempts to generalize k-map methods to other disciplines. The "virtual planar representation" of a
10 three-dimensional k-map is used to study "cell-work topology" from a network point of view. Other prior art abstract visualization methods include mappings of high-dimensional multivariate functions, presenting a two-dimensional view of a function of many variables. In an
15 article by Patrick et. al., "Mapping Multidimensional Space to One Dimension for Computer Output Display," IEEE Transactions on Computers, Vol. C-17, No. 10, 1968, p. 949, the following problem is presented:

Consider the problem of displaying a real-valued
20 function $f(x_1, x_2, \dots, x[n])$ of $[n]$ real variables on a computer output display. ... If $[n] = 1$, it is clear how $f(x[n])$ can be processed for display on a two-dimensional screen; but if $[n] > 1$, the required processing is not as obvious.

25 Patrick's approach to displaying a two-dimensional view of N -dimensional functions for $n > 1$ establishes a one-to-one correspondence between the N -dimensional domain if " f " is bounded, that is, statically predetermined.

Prior art methods cited above primarily are concerned
30 with the visual representation of logical objects; however, the prior art also teaches methods for the logical representation of visual objects. Srihari in his article, "Representation of Three-Dimensional Images," Computing Surveys, Vol. 13, No. 4, December 1981, pp. 401 & 405,
35 describes symmetric recursive indexing as a method of



-6-

partitioning a volume:

Images that are produced by sensing objects through a form of radiant energy, for example, ...are inherently continuous. Computer representation of 3D images requires a sampling of the volume to extract a discrete set of values.... The cubic space is subdivided into eight subcubes (octants) of equal volume. Each of these octants will either be homogeneous (e.g., uniform attenuation) or have some nonuniformity. The heterogeneous octants are further divided into suboctants. This procedure is repeated as long as necessary until we obtain blocks (possibly single voxels) of uniform properties.

Other prior art methods seek to control the logical representation and visual expression of object relationships. U.S. Patent No. 4,721,952 entitled, "Apparatus and Process for Graphically Representing Three-Dimensional Objects in Two-Dimensions", issued to Huber describes a process for the perspective representation of objects on the screen of a numerically controlled machine tool. The object is resolved into a series of sections (slices) which are represented successively to produce a visual image of the object. Huber's invention claims an improvement of

...a process for controlling a display device to represent a three-dimensional object such as a workpiece, wherein the representation is based upon data and commands stored in a computing device such as a computer.

As machine and process operations become more specialized, controllers that are capable of adapting to changes due to unforeseen application requirements or further specialization become necessary. Federico and Webster in U.S. Patent No. 4,475,156, entitled "Virtual Machine Control," teach that "...a totally hardware



WO 92/13313

PCT/US92/00218

-7-

controller to provide these features is often prohibitive, inflexible, and costly." Problems with prior art controls include a lack of appropriate modularity and a lack of sufficient mechanisms to support appropriate modularity in the firmware. Other prior art controls require a detailed knowledge of the operation of the control kernel for usage. Further problems with prior art controllers include a general lack of appropriate mechanisms for accomplishing the specialized objectives.

Heath in an article "The Hypercube: A Tutorial Overview," Hypercube Multiprocessors 1986, SIAM, Philadelphia, 1986, pp. 7-10, teaches:

...in a hypercube (also variously called the binary N-cube, cosmic cube, homogeneous ensemble machine, etc.), $2N$ processors are consecutively numbered (or tagged) by binary integers (e.g., bit strings of length N) from 0 through 2^n-1 . Each processor is connected to all of the other processors whose binary tags differ from its own by exactly one bit.

Topologically, this arrangement places processors at the vertices (corners) of an N -dimensional cube. In practice, the actual layout of the processors is a linear arrangement in a card cage or a planar arrangement on a printed circuit board; the cube connections are made by wires, conducting layers, or a backplane.

FIGS. 6A-6D are diagrams of a binary 6-cube encoded in accordance with prior art n-cube replication methods. Seitz in the article, "The Cosmic Cube," Communications of the ACM, Vol.28, No. 1, January 1985, p. 22, describes 64 computers "...connected by a network of communication channels in the plan of a binary 6-cube." The interconnection pattern of FIG. 6A is similar to that used by Seitz. Each node of FIG. 6B is linked by arcs to six other nodes.

This Sheet Has Been Replaced



-8-

FIGS. 10A-10B show a diagram of a four-dimensional hypercube, called a binary 4-cube. Each element of FIG. 10A is referred to as a node 1000. The dimensions of FIG. 10A are represented as a link 1001 connecting nodes 1000. The binary 4-cube is shown partitioned 1004 in FIG. 10B as two subspaces: subspace 0CBA 1002 and subspace 1CBA 1003.

Hypercubes of arbitrary dimension can be made using a linear arrangement with connecting wires (FIG. 2). The cube of each dimension is obtained by replicating the one of next lower dimension, then connecting corresponding nodes. The node names resulting from such hypercube interconnection schemes correspond to prior art two-dimensional recursive indexing methods, similar to the method described by Srihari in his article referenced above. Recursive indexing has been independently discovered by practitioners in diverse fields. Recursive indexing is not extendable to generalized N-dimensional resolution, where the resolution of each dimension is permitted to differ. A hypercube, when projected onto a plane using the method of recursive indexing is routinely referred to in prior art literature as a binary n-cube. This binary space partitioning procedure, however, actually describes an k-ary 2-cube, that is, a two-dimensional space with k/2 bits of resolution for each dimension, whose elements are interconnected as a binary n-cube. Such topological ambiguity frustrates the mechanized visualization of higher-order, N-dimensional spaces.

Marihugh and Anderson in their article, "The H Diagram: A Graphical Approach to Logic Design", IEEE Transactions on Computers, Vol. C-20, No. 20, October 1971, pp. 1192-1196, describe a geometric model which is intended to visually aid the analysis of binary functions. Their method is based on geometrically transforming the coordinates of a hypercube onto a plane. The H diagram



WU 92/13313

PCT/US92/00218

-9-

method of visualizing the coordinates of a binary hypercube by transforming its coordinates onto a plane is not extendable to generalized N-dimensional space, where the resolution of each dimension is permitted to differ.

5 Sivilotti in a paper, "A Dynamically Configurable Architecture For Prototyping Analog Circuits," in Advanced Research in VLSI. Proceedings of the Fifth MIT Conference, 1988, MIT, p. 248, describes a binary H-tree hierarchical interconnect structure used to physically place leaf cells and crossbar interconnect switches on a grid with parallel decoders around the chip perimeter as a simpler alternative to a hierarchical decoder. Sivilotti also refers to indirect element name (switch address) transformation as the "...mapping between hierarchical interconnect matrix coordinates and flat Cartesian coordinates performed by the embedding compiler."

10 Colorimetry is a perceptual science which studies and attempts to quantify how the human visual system perceives color. This study of perception has resulted in various systems of color representation, each intending to reduce problems associated with subjective color selection and reproduction. Six color systems often used in association with computer-related information display include: the Munsell color system, HSV hexcone, HSL double hexcone, HSL double cone, HSL cylinder, and the RGB color cube.

20 The Munsell color system is described in an article by Meyer and Greenburg entitled, "Perceptual Color Spaces for Computer Graphics," Computer Graphics, Vol. 14, No. 3, 1980, pp. 254-261, in relation to reproduction of color on a television monitor:

30 Deciding which Munsell notation colors are reproducible on the monitor is difficult because the monitor and Munsell color gamuts (regions of realizable color) have irregular shapes and their intersection is not well defined.

35 This Sheet Has Been Replaced



-10-

A.R. Smith in "Color Gamut Transformation Pairs," ACM Computer Graphics (SIGGRAPH 78), VOL. 12, No. 3, pp. 12-19, describes the HSV (hue, saturation, and value) hexcone, which used a neutral axis from black to white. At the white point is a hexagon with vertices representing the colors at the vertices of the color cube.

D.F. Rogers in his book, Procedural Elements for Computer Graphics, McGraw-Hill, NY, 1985, pp. 403-404, describes the HSL (hue, saturation, and lightness) double hexcone. This color system is similar to the HSV hexcone with the exception that the full colors are represented with a value of 0.5 instead of being equal to white.

Joblove and Greenburg in their paper, "Color Spaces for Computer Graphics," ACM Computer Graphics (SIGGRAPH 78), Vol. 12, No. 3, pp. 20-25, describe a variant of the HSL double hexcone called the HSL double cone, whose cross-section is circular rather than hexagonal. In the same paper Joblove and Greenburg describe the HSL cylinder, which expands the base and top of the double cone into black and white circles.

Each of the color representation systems mentioned above use some variant of a radial coordinate system to compute the location of a particular color sensation in their respective color spaces. Meyer and Greenburg in their article referenced above make the following observation:

...A problem inherent with any color organization such as The Munsell Book of Color that uses a cylindrical coordinate system is that the spacing between colors changes as two radial lines are followed outwards from the center of the cylinder. ...The idea is to define a color system in which an equal perceptual distance separates all of the colors. For example, the grayscale of the system should provide a smooth transition between black white...such an ideal system

This Sheet Has Been Replaced



-11-

has yet to be found....

The RGB color cube represents the red, green, and blue monitor primaries as orthogonal axes. The colors that are displayable on the monitor are within the cube from (0, 0, 0) to (1, 1, 1). The neutral axis is a (diagonal) line from the black point (0, 0, 0) to the white point (1, 1, 1). The color cube has been referred to in the literature as a "natural" coordinate system in the sense that the three color components are mapped into an orthogonal coordinate system in the same fashion as three-dimensional geometry.

Color representations used in computer graphics are closely linked to both the color reproduction device and to a method of color selection. Uniform color spaces can be used to decide at what level of resolution the color information should be encoded. Two-dimensional data plots, for example, require uniform colors spaces to select color scales. In the prior art color systems referred to above the pigment gamut used to derive color spaces is generally smaller than the gamut of a color monitor and the pigment gamut is irregular. According to Meyer and Greenburg, referenced above (p. 260), "...this makes it difficult to find color scales that incorporate the most brilliant monitor colors."

Richard Perez, in his book Electronic Display Devices, TAB Professional and Reference Books, Blue Ridge Summit, PA, 1988, pp. 69-129, presents a detailed description of CRT electronic display device technology. The number of colors that can be produced on a CRT display, for example, depends on the number of steps of gray level obtainable for each phosphor (compounds that emit light when bombarded by electrons). If the electron gun can be stepped over four levels (2 bits), the resulting palette has sixty-four colors. Some systems currently available are capable of 1024 steps of gray from each gun (10 bits). Systems

This Sheet Has Been Replaced



-12-

capable of 256 steps of gray from each gun (8 bits) are more common, however. Such systems can produce a palette of over 16 million unique combinations. The eye is not capable of discriminating many of the small changes in color so that the viewable palette has many fewer colors. In a chapter entitled, "Color Displays and Color Science," Color and the Computer, Academic Press, Boston, 1987, p. 13, the section entitled, "Visual Display Descriptive Systems," Gerald Murch makes the following observation:

...Under optimal conditions, a total of about three million discriminable colors can be produced in a visual display; that is, colors that are recognizably different when placed adjacent to one another. The palette shrinks to about 7000 when colors located at different screen areas must be immediately recognized as different from one another. ...The obtainable level of saturation for additively-mixed colors can be extended by increasing the number of primaries....

The color television industry experimented with four or five primaries but concluded that the improvement in color did not offset the increase in the expenses of production of such receivers. Visual displays followed the lead.

In U.S. Patent No. 4,887,878 entitled, "Optical Modulation Device," Robinson and Sanford teach: "To convey information on an optical wave, some property of that wave has to be modulated or changed in accordance with the information and adopted coding system." Well known in the art are devices which rely on various electro-optical, thermo-optical, or acousto-optical properties of materials for modulating electromagnetic carrier waves in the optical region of the spectrum.

Separation requires couplers, like the one shown in FIG. 7, that are sensitive to wavelength, so light 700 can be directed along different paths 702-706. A diffraction

This Sheet Has Been Replaced



-13-

grating 701 is used to spread out a spectrum of light from the input fiber 700 and focus specific wavelengths in that spectrum onto fibers in a linear array 702-706. Conversely, if the outputs were reversed, the grating 701 would combine the five wavelengths 702-706 into a single output at the top fiber 700.

In the article "Integrated Optics," in Optics Source Book, S. Parker, ed., McGraw-Hill, NY, 1988, pp. 287-291, Streifer describes light transmission in planar waveguides based on "...dielectric structures that confine the propagating light to a region with one or two very small dimensions, on the order of the optical wavelength." FIG. 8 shows prior art prism input coupling 800 and grating output coupling 803 of an external light beam 801 into a thin-film waveguide 802. By reversing the incident 801 and output 804 beam directions the roles of the prism 800 and grating 803 couplers are interchanged. Streifer further describes optical integrated circuit (OIC) switching and modulation applications:

Both lithium niobate and gallium arsenide belong to the family of electro-optically active crystals. When an electric field is applied to these materials, their refractive indices are modified. ...If the waveguides are suitably designed, the applications of specific small voltages to the electrodes will cause the transfer of optical power from one waveguide to its neighbor with high efficiency and little residual power in the initial guide.

FIG. 9 shows a prior art "4 by 4" directional coupler switching network in which each of four input optical signals 900 may be switched to any one of four output ports 904. Conducting electrodes 901 deposited on the surface of a crystalline substrate 902 parallel to two closely-spaced waveguides 903. Such an optical integrated circuit serves to interconnect four computers through optical fibers.

This Sheet Has Been Replaced



-14-

Switches are in effect modulators. Prior art modulation is a process in which information is encoded onto an optical wave. According to Streifer, referenced above, "...Pulse modulation results simply by interrupting or connecting a light wave in a manner intelligible to a receiver. By transferring light into or out of a waveguide in response to an electric signal at a switching electrode, the output optical wave becomes modulated; that is the switch acts as a modulator." Accordingly, the foregoing discussion of the prior art is representative of the problem of representing mixed-resolution, N-dimensional objects and spaces. A long felt need has existed for a solution to this problem.

OBJECTS OF THE INVENTION

An object of the invention is to mechanize the generation of mixed-resolution, N-dimensional object spaces related to complex problems with a large number of variables, where the number of variables is not limited by the method.

Another object of the invention is to generate content-addressable object spaces.

Another object of the invention is the production, interpretation, and manipulation of a novel form of a reflected Gray code referred to herein as the k-ary reflected Gray code.

A further object of the invention is to represent sensed physical phenomena logically.

An additional object of the invention is to mechanize the visualization of mixed-resolution, N-dimensional object spaces related to complex problems with a large number of variables, where the number of variables is not limited by the method.

Another object of the invention is to represent logical objects visually such as logical color



-15-

specifications and visual color sensations.

A further object of the invention is concurrent control of a plurality of views of one or more object spaces.

5 A still further object of the invention is an apparatus described herein as the kernel of a modular object description system.

10 An object of the invention is to dynamically control the logical representation and the visual expression of object descriptions in an object space.

Another object of the invention is concurrent control of a plurality of transition paths in an object space.

An object of the invention is concurrent control of a plurality of element relations in an object space.

15 A further object of the invention is concurrent control of a plurality of regions in an object space.

An additional object of the invention is concurrent control of a plurality of object spaces.

20 An object of the invention is to control various types of machines such as processors and memory, and to control related processors.

Another object of the invention is to control various types of processes such as optical modulation and demodulation.

25 SUMMARY OF THE INVENTION

30 Object spaces representing very simple object descriptions can be formed manually and, in a few instances, mentally; however, description spaces of actual systems quickly exceed the feasible limits of mental visualization and manual procedures. Therefore, an illustrative embodiment of the present invention is an apparatus that is part virtual machine, providing an appropriate level of application independence and device transparency.



-16-

According to the present invention, as embodied and broadly described herein, a process for generating and visualizing mixed-resolution, N-dimensional object spaces using a computing device such as a computer is provided.

5 The computing device may be of the type comprising means for storing data and commands, means for generating a logical representation of the N-dimensional object space in response to the stored data and commands, display logic for generating a virtual image representing the N-dimensional
10 object space in response to the stored data and commands, and display means for displaying a visible representation of the virtual image.

In the case of user-specified attributes the process starts with the user inputting to the computing device the
15 attributes and the computing device generating from the attributes a frame for the N-dimensional object space. The bits of the frame are then interleaved to generate an object descriptor. From the frame and the object descriptor, the computing device generates
20 dimensional-spatial locations of the N-dimensional object space. The computing device also generates object selectors which correspond to interleaved frame data for each dimensional-spatial location in the N-dimensional object space. The computing device generates a virtual image of
25 the N-dimensional object space from the dimensional-spatial locations and the object selectors. A user or an application procedure selects a region of the virtual image. The process may further include the step of displaying the selected region of the virtual image of the
30 N-dimensional object space on the display means.

The process further includes having the computing device generate, from the frame and the object descriptor, resolution-spatial locations for resolution levels of each
35 of the N dimensions for a mixed-resolution, N-dimensional object space. Subsequently an object selector is generated

This Sheet Has Been Replaced



WO 92/13313

PCT/US92/00218

-17-

from the frame data for each resolution-spatial location in the mixed-resolution, N-dimensional object space. A virtual image of the N-dimensional object space is generated from the resolution-spatial locations and the dimensional-spatial locations. A user or an application procedure selects a region of the virtual image. The process may include using the computing device for displaying the selected region of the virtual image of the mixed-resolution, N-dimensional object space on the display means.

The present invention alternatively may be embodied as an apparatus for generation and visualization of mixed-resolution, N-dimensional object spaces. In the case of user object description, a user specifies a particular set of attributes defining dimensions and resolution levels. In the case of an application-driven object description, an application procedure specifies a particular set of attributes defining dimensions and resolution levels. In the case of sensed physical phenomena, such as electromagnetic signals, the apparatus transforms analog signals into a digital form which specifies a particular set of attributes defining dimensions and resolution levels.

The apparatus includes means for generating a frame from the specified attributes for the N-dimensional object space. Means for interleaving bits generates an object descriptor which corresponds to interleaved frame data. Using the frame and the object descriptor the present invention uses means for generating dimensional-spatial locations of the N-dimensional object space. The frame data is used to generate an object selector for each dimensional-spatial location in the N-dimensional object space. The dimensional-spatial locations and the object selectors are used to generate a virtual image of the N-dimensional object space. A region of the virtual image

This Sheet Has Been Replaced



WO 92/13313

PCT/US92/00218

-18-

is selected. Display means may display the selected region of the virtual image of the N-dimensional object space.

The apparatus of the present invention additionally may include means for generating resolution-spatial locations for resolution levels of each of the N dimensions for a mixed-resolution, N-dimensional object space using the frame and the object descriptor. The frame and object descriptor are used to generate an object selector for each resolution-spatial location in the mixed-resolution, N-dimensional object space. Using resolution-spatial locations, the dimensional-spatial locations, called object selectors, a virtual image of the N-dimensional object space is generated, and means is provided for selecting a region of the virtual image. Frame data for a particular object are used to generate a single object selector to reference a particular location in the mixed-resolution, N-dimensional object space.

An illustrative example of the present invention relates to color perception, color specification, and color spaces; and, in particular, to the production and visualization of uniform color spaces. A color naming method for controlling RGB values by indirectly specifying RGB signal voltages and visualizing the resulting distribution of perceivable colors in the RGB color space is presented in accordance with the method disclosed herein.

The color naming method used in accordance with the present invention, is the process by which the name of a particular color experience is encoded for both the purpose of uniform color selection and the purpose of reproduction on an electronic display. The system of color representation used to form a uniform color space is to name colors in terms of the additive relations of red, green and blue. The resultant RGB system specifies a trio

This Sheet Has Been Replaced



-19-

of values ranging from 0 to 1 or 0% to 100% for each of the three primaries. The color relationships that result form a cube. The RGB system is a simple and direct approach to the problem of color description that incorporates the principles of additive color mixture; that is, the user specifies color directly in terms of the electrical activity that the specification will induce. In the reference by Murch, cited in the Description of the Prior Art, the difficulty of specifying additive color relationships is discussed:

...For individuals understanding the nuances of additive color mixture, the RGB system is comfortable. ... Even for those individuals with a clear understanding of additive color, the location and proper specification of colors within the interior of the cube, when some real value for all three primaries is required, proves difficult. Imagine selection of a medium brown, for example. The greatest difficulty is encountered when a color of proper hue and brightness has been located and a shift in saturation is desired. Such a shift would require a disproportionate change in all three values.

The novel method for generating, controlling and visualizing the distribution of perceivable colors in a RGB color space is described below. A primary aspect of the method disclosed herein is that the encoded pattern of bits which specifies (physical) RGB signal voltages also (logically) names a particular location in a displayable uniform color space. Another aspect of the method disclosed herein is that the logical naming method of invention illustrated by the color space example may be generalized to include a novel method for optical modulation.

Additional objects and advantages of the invention ARE set forth in part in the description which follows, and in

This Sheet Has Been Replaced



-20-

part ARE obvious from the description, or may be learned by practice of the invention. The objects and advantages of the invention also may be realized and attained by means of the instrumentalities and combinations particularly pointed out in the appended claims.

BRIEF DESCRIPTION OF THE DRAWINGS

The accompanying drawings, which are incorporated in and constitute a part of the specification, illustrate preferred embodiments of the invention, and together with the description, serve to explain the principles of the invention.

FIGS. 1A-1E are diagrams of the binary 3-cube "unfolded" in accordance with prior art methods;

FIG. 2 is a prior art representation of n-cubes as k-maps;

FIGS. 3A-3B are a prior art representations of a four-variable Karnaugh map;

FIGS. 4A-4B are a prior art representation of a binary 5-cube and a binary 6-cube;

FIG. 5 shows a prior art device for extending the binary 6-cube to visualize higher order spaces;

FIGS. 6A-6D are a diagrams of a binary 6-cube encoded in accordance with prior art two-dimensional recursive indexing methods;

FIG. 7 shows prior art distribution of multiple wavelengths to separate fibers;

FIG. 8 shows prior art prism input coupling and grating output coupling of an external light beam into a thin-film waveguide;

FIG. 9 shows a prior art "4 by 4" directional coupler switch;

FIGS. 10A-10B are prior art diagrams of a four-dimensional hypercube;

FIGS. 11A-11C show an intuitive procedure for

This Sheet Has Been Replaced



-21-

generating spaces, spatial element linkage, and a binary 4-cube projected onto a plane;

FIG. 12 is a flow chart for the case of user-specified attributes which shows the process of the invention;

5 FIG. 13 shows expressions of a zero-cube;

FIG. 14 shows expressions of a one-dimensional, object space;

FIG. 15 shows expressions of a two-dimensional, object space;

10 FIG. 16 shows expressions of a three-dimensional, object space;

FIG. 17 shows expressions of a four-dimensional, object space;

15 FIG. 18 shows expressions of a five-dimensional, object space;

FIG. 19 shows expressions of a six-dimensional, object space;

FIGS. 20A-20C are diagrams of a k-ary one-dimensional, object space;

20 FIGS. 21A-21B are diagrams of 4-dimensional object spaces;

FIGS. 22A-22B are diagrams of a mixed-resolution, 4-dimensional object space derived from a binary, 4-dimensional object space;

25 FIG. 23 is a functional diagram of the object description process;

FIGS. 24A-24B show block diagrams of physical modules in an object description system;

30 FIG. 25 shows a functional module of an object description system;

FIG. 26A-26H show the object space configurations formed by the 4-bit frame logic module;

FIGS. 27A-27C are diagrams of an eight-element RGB color space;

35 FIGS. 28A-28C are diagrams of a sixty-four-element RCB

This Sheet Has Been Replaced



color space;

FIG. 29A-29C show relationships between three-dimensional spaces with different resolutions;

FIGS. 30 shows a graph of matching curves for 445 nm, 535 nm, and 630 nm control sources; and

FIGS. 31A-31C show how percentages of spectral intensities over a range of values for each primary are determined in a sixty-four element RGB color space.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

Reference will now be made in detail to the present preferred embodiments of the invention, examples of which are illustrated in the accompanying drawings, wherein like reference numerals indicate like elements throughout the several views.

Given the intellectual process of system description, the present invention mechanizes a novel representation of that system's description. Object descriptions have meaning, that is, they refer to or describe some system with certain physical or conceptual properties.

For color graphics, the objects may be particular color sensations described in terms of attributes such as: red; green; blue; which define a color space. For optical communications, the objects may be a particular coherent light source described in terms of its lightwave components, which define a signal space. The significant aspect of system description is that the actual description is one selected from a set possible descriptions. The invention is a general apparatus and method, designed to operate for each possible problem selection, not just the one which will actually be chosen since this is unknown at the time of design.

The process of the present invention enables representing sensed physical phenomena logically and logical objects visually. Most of the prior art methods



-23-

referred to in Description of the Prior Art sought to visualize some aspect of a problem-solving process by mapping logical objects onto visual space.

5 Most prior art methods assume visual space to be the Cartesian space, in that, logical objects are mapped onto the real line, the plane, or the cubic space. An object's location in visual space, accordingly, is metrically determined relative to one or more coordinate axes. Herein
10 lies the principal departure of the present invention from these prior art methods: the method and apparatus of the present invention define a novel form of object space, such that, object location in this object space is logically, rather than metrically, determined. Other prior art
15 methods referred to in Description of the Prior Art sought to visualize some aspect of the problem-solving process by recursive indexing on some variant thereof. Such prior art methods, however, determine locations by decomposing a domain.

20 The process which forms an object space is directed by object descriptions in accordance with the method of the present invention. Object expressions are represented by a unique binary-coded name which directly correspond to a position in the object space of the present invention. The present invention is first described as the method of
25 reflecting binary N-dimensional object spaces. Then the present invention is described as the generalized method of reflecting mixed-resolution, N-dimensional object spaces. The process of the present invention results in an interleaving of the N-dimensions. Bit interleaving is
30 often employed in structuring data, as well as part of the data representation itself. Samet in his book, The Design and Analysis of Spatial Data Structures, 1989, Addison Wesley, NY, p. 109, states:

35 ...bit interleaving makes it possible to balance a data base of multidimensional point data dynamically.

This Sheet Has Been Replaced



-24-

It leads to logarithmic insertion, deletion and search algorithms. It does have drawbacks, however. First, and most serious, is that bit interleaving is not performed efficiently on general computers. Its complexity depends on the total number of bits in the keys.

Because efficient interleaving of binary-coded data is essential to the visualization process described herein, an embodiment of the invention is described as an apparatus with a virtual component. Before describing an embodiment of the invention in detail the following terminology is defined:

1. Object: a structural and/or behavioral expression of some real-world or imaginary phenomenon.

2. Object descriptor: a collection of attributes which describes a schema for a particular kind of object expression describing the object space.

3. Object selector: a collection of attribute values associated with the descriptor of a specific object expression, defining a location in the object space.

4. Object space: a bit-interleaved representation of an object descriptor.

5. Object name: a binary-encoded representation of an object selector in an object space.

6. Visual space: a space of object names projected onto a plane.

7. Dimension: each attribute of an object descriptor corresponds to a dimension in both object space and visual space.

8. Dimensional resolution: the range of values associated with each attribute of an object descriptor.

9. Quantization: assigning a logical digital code to a range of values.

10. Frame: describes the format of an object descriptor, where each attribute (dimension) is denoted by

This Sheet Has Been Replaced



a "1" followed by "0s" representing the additional bits of resolution.

The present invention provides a process for visualizing N-dimensional, object space using a computing device such as a computer. The computing device may be of the type comprising means for storing data and commands, means for generating a logical representation of the N-dimensional object space in response to the stored data and commands, frame logic for generating a virtual image representing the N-dimensional, object space in response to the stored data and commands, and display means for displaying a visible representation of the virtual image. The process uses the computing device.

FIGS. 11A-11C show an intuitive procedure for reflecting a mixed-resolution, 4-dimensional, object space onto a plane. Referring to FIG. 12, a flow chart showing the case for user-specified attributes, the process starts with the step of inputting the attributes 1201 to the computing device. The attributes describe the problem. A color display, for example, may have the attributes of three primary colors: red; green; and blue. Each attribute corresponds to a dimension of the problem. For the color display, each of the three primary colors may be considered a dimension, giving a dimension of three ($N = 3$). The computer generates 1202, from the user specified attributes, a frame for the N-dimensional object space. The frame is a coded representation of attribute descriptions for a particular problem domain. In a color space each attribute corresponding to a primary hue is described by a bitfield in the frame. The first bit of each bitfield is always a logical one. Subsequent bits in a given bitfield are logical zeros. Each logical zero represents an additional bit of resolution.

As a first example, a three-dimensional object space, with two bits resolution on each dimension would have a

This Sheet Has Been Replaced



-26-

frame (0, 1, 0, 1, 0, 1). Each 1-bit represents each dimension, and the 0-bit placed before the corresponding 1-bit indicates a second bit of resolution. For the color display, two bits of resolution on each of three dimensions might correspond to four levels of intensity for each of the primary colors.

As a second example, a three-dimensional, object space with three bits of resolution on the first dimension, one bit of resolution on the second dimension, and two bits of resolution on the third dimension, would have the frame: (0, 1, 1, 0, 0, 1). For color space: the right three bits might represent eight levels of resolution or saturation of the red attribute; the center bit might represent two levels resolution or saturation of the green attribute; and the left two bits might represent four levels of resolution or saturation of the blue attribute.

As a third example, for a three dimensional, object space with one bit resolution on each dimension would have a frame (1, 1, 1). Each bit, from right to left, might represent the red attribute, the green attribute and the blue attribute, respectively. The frame is a positional notation which denotes the number of attributes and the resolution of each attribute. The frame data are the values or sense of each bit position in a given frame.

Referring to FIG. 12, the bits of the frame are interleaved 1203 to generate an object descriptor. For the first example, the object descriptor is (0, 0, 0, 1, 1, 1) for the frame (0, 1, 0, 1, 0, 1). For the second example, the object descriptor is (0, 0, 0, 1, 1, 1) for the frame (0, 1, 1, 0, 0, 1). For the third example, the object descriptor is (1, 1, 1) for the frame (1, 1, 1). The computing device generates 1204 from the frame and the object descriptor, dimensional-spatial locations of the N-dimensional object space. For each 1-bit from the object

This Sheet Has Been Replaced



-27-

description, the computing device generates a dimension of dimensional-spatial locations. The dimensional-spatial locations correspond to the attributes of the problem.

FIGS. 13 through 19 illustrate n-cube projection in accordance with methods of the invention now further described as a process to mechanize and visualize reflected N-dimensional-object spaces for any N, where N is a positive integer. It should be noted that each of the FIGS. 13 through 19 show three expressions of n-cube element configurations.

The n-cube of FIG. 13 is referred to herein as a 0-dimensional object space. FIG. 13 shows that an object space with a dimension of zero ($n = 0$) has only one element; that is, one dimensional-spatial location.

The binary 1-cube of FIG. 14 is referred to herein as a 1-dimensional object space with one bit of resolution. FIG. 14 shows that an object space with a dimension of one ($n = 1$) has two elements; that is, two dimensional-spatial locations. The 1-d, 1-bit object space of FIG. 14 can be visualized as a linear region comprising two elements "named" logical zero and logical one, respectively. The linear region of FIG. 14 is generated by reflecting a first 0-dimensional object space named "0" to the right. Thereby, a second 0-dimensional object space named "1" is produced. The name of a dimensional-spatial location is called an object selector.

FIGS. 15 through 19 show the progressive projection of reflected binary n-cubes, where N varies from two to six. In FIGS. 15-19, each dimensional-spatial location is represented as a cell, which is drawn as a square. N-dimensional object spaces are reflected as regions in an orthogonal direction determined by control signals from an apparatus described below. Referring to FIGS. 15 through 19, it should be noted that the values of the n-1 rightmost object selector bits in a second (reflected)

This Sheet Has Been Replaced



-28-

region are the same as the $n-1$ rightmost object selector bits of the corresponding object selectors which comprise a first region (i.e., where N is the number of bits in an object selector). It should be further noted that the value of the leftmost object selector bit of a first region is always a logical zero, and the leftmost selector bit of a second region is always a logical one.

The binary 2-cube of FIG. 15 is referred to herein as a 2-dimensional object space with one bit of resolution. FIG. 15 shows that an object space with a dimension of two ($n = 2$) has four elements; that is, dimensional-spatial locations. The 2-dimensional, 1-bit object space of FIG. 15 can be visualized as two linear regions comprising four elements "named" in accordance with a reflected binary Gray code (e.g., 00, 01, 11, 10). The object space of FIG. 15 is generated by reflecting a first linear region upward. Thereby, producing a second (reflected) linear region. The resulting object space can be visualized as a square region. It should be noted that the corresponding object selectors in each linear region have the same value in the rightmost bit position; however, the values differ in the leftmost bit position. The leftmost bit of the first linear region's object selectors is a logical zero. The leftmost bit of the second (reflected) linear region's object selectors is a logical one.

The binary 3-cube of FIG. 16 is referred to herein as a 3-dimensional object space with one bit of resolution. FIG. 16 shows that an object space with a dimension of three ($n = 3$) has eight elements; that is, dimensional-spatial locations. The 3-dimensional, 1-bit object space of FIG. 16 can be visualized as two square regions, each comprising four elements. These eight elements are named in accordance with a reflected binary Gray code (e.g., 000, 001, 011, 010, 110, 111, 101, 100). The object space of FIG. 16 is generated by reflecting a



-29-

first square region comprising four elements to the left. Thereby, a second square (reflected) region is produced. It should be noted that the values of the two rightmost object selector bits in the second (reflected) square region are the same as the two rightmost bits of the corresponding object selectors, which comprise the first square region. The value of the leftmost object selector bit of the first square region is a logical zero. The value of the leftmost object selector bit of the second square region is a logical one.

The binary 4-cube of FIG. 17 is referred to herein as a 4-dimensional object space with one bit of resolution. FIG. 17 shows that an object space with a dimension of four ($n = 4$) has sixteen elements; that is, dimensional-spatial locations. The 4-dimensional, 1-bit object space of FIG. 17 can be visualized as two rectangular regions, each comprising eight elements. These sixteen elements are named in accordance with a reflected binary Gray code. The object space of FIG. 17 is generated by reflecting a first rectangular region comprising eight elements downward. Thereby, a second rectangular (reflected) region is produced.

The binary 5-cube of FIG. 18 is referred to herein as a 5-dimensional object space with one bit of resolution. FIG. 18 shows that an object space with a dimension of five ($n = 5$) has thirty-two elements; that is, dimensional-spatial locations. The 5-dimensional, 1-bit object space of FIG. 18 can be visualized as two square regions, each comprising sixteen elements. These thirty-two elements are named as described above in accordance with a reflected binary Gray code. The object space of FIG. 18 is generated by reflecting a first square region comprising sixteen elements to the right. Thereby, a second square (reflected) region is produced.

The binary 6-cube of FIG. 19 is referred to herein as

This Sheet Has Been Replaced



-30-

a 6-dimensional object space with one bit of resolution. FIG. 19 shows that an object space with a dimension of six ($n = 6$) has sixty-four elements; that is, dimensional-spatial locations. The 6-dimensional, 1-bit object space of FIG. 19 can be visualized as two rectangular regions, each comprising thirty-two elements. These sixty-four elements are named in accordance with a reflected binary Gray code as described above. The object space of FIG. 19 is generated by reflecting a first rectangular region comprising thirty-two elements upward. Thereby, a second rectangular (reflected) region is produced.

The process of naming spatial elements for any N-dimensional space is intuitively understood as a "function" of reflecting its subspaces. The space generation method illustrated by FIGS. 13 through 19, when projected onto a plane, results in a two-dimensional visual representation of reflected N-dimensional spaces. The novel method of the present invention can be used for visualizing progressive space generation for any N-dimensional, object space.

The dimensional-spatial locations can be produced by reflecting cells right, up, left, down, right, up, left, down, etc., in what is considered a counter-clockwise direction. Alternatively, the dimensional-spatial locations can be produced by reflecting cells to the left, up, right, down, left, up, right, down, etc., in what is considered a clockwise direction. The dimensional-spatial locations may be reflected in a clockwise or counter-clockwise direction. Further, the dimensional-spatial locations can be produced by reflecting cells in a single direction or selected direction. For illustrative purposes the counter-clockwise embodiment for producing dimensional-spatial locations is used throughout this disclosure, with the understanding that the alternative

This Sheet Has Been Replaced



-31-

embodiments produce equivalent dimensional-spatial locations.

Referring to FIG. 12, when all the dimensional-spatial locations are generated 1205 representing all the dimensions of the problem, then the computing device gets 1206 the first attribute bitfield in the frame. From this bitfield, the computing device determines 1207 whether resolution-spatial locations need to be generated from this bitfield. If no resolution-spatial locations are to be generated, then the computing device determines 1206 whether this is the last bitfield of the frame. If yes, then the computing device checks 1211 if there are any additional resolution-spatial locations to be generated for any bitfield. If no resolution levels are required, then the computing device generates 1212 an object selector which corresponds to interleaved frame data for each dimensional-spatial location in the N-dimensional object space. The object selectors are an interleaved bitfield of the frame data. The object selectors define a location in the cells representing the dimensional-spatial locations.

If all object selectors have been generated 1213 for all the dimensional-spatial locations for the N-dimensional, object space, then the computing device generates 1214 a virtual image of the N-dimensional, object space from the dimensional-spatial locations and the object selectors. A user or application procedure may select 1215 a region of the virtual image for machine control, display, or other application-driven function. The process further may include using the computing device for displaying the selected region of the virtual image of the N-dimensional, object space on the display means. The process additionally may use the computing device for generating 1208, from the frame and the object descriptor, resolution-spatial locations for resolution levels of each of the N dimensions for a mixed-resolution, N-dimensional,

This Sheet Has Been Replaced



object space.

FIGS. 20-22 illustratively show the generation of resolution-spatial locations. Referring to FIG. 20, the number of elements in a k-ary 1-cube is determined by the number of bits of resolution as a power of two. For example, a 4-ary 1-cube with two bits of resolution has four elements and an 8-ary 1-cube with three bits of resolution has eight elements. When elements of k-ary 1-cubes are reflected linearly as shown in FIGS. 20A-20C, the element transition sequences correspond to the primary form of the reflected binary code, but may be interpreted as a reflected k-ary code.

FIG. 20A shows a binary 1-cube referred to herein as a 1-dimensional object space with one bit of resolution. The 1-dimensional, 1-bit object space of FIG. 20A comprises two object selectors named "0" and "1" respectively. The object selectors of a 1-dimensional, 1-bit object space represent dimensional-spatial locations.

FIG. 20B illustrates a 1-dimensional object space with two bits of resolution. In this case, the original dimensional-spatial locations of FIG. 20A have been reflected to the right to increase the resolution in the direction of the first dimension. Note that the reflection for increased resolution is in the same direction as the reflection which generated the dimension. The object selectors of the original dimensional-spatial locations have a 0-bit placed in front of them, and the newly generated resolution-spatial locations have the original object selectors reflected therein with a 1-bit placed in front of them.

FIG. 20C shows a 1-dimensional object space with three bits of resolution, which has been generated from the 1-dimensional, 2-bit object space of FIG. 20B. In this case object selectors from the 1-dimensional, 2-bit object space (2-ary 1-cube), have a 0-bit placed in front of them,



-33-

and the object selectors generated by reflection have a 1-bit placed in front of them. FIGS. 21A-21B are diagrams of 4-dimensional object spaces. FIG. 21A shows a 4-dimensional object space with one bit of resolution. FIG. 21B shows a 4-dimensional object space with two bits of resolution, in each dimension. In this case, after generating all of the dimensional-spatial locations for the four dimensions, the resolution-spatial locations are generated. Accordingly, the sixteen dimensional-spatial locations for the four dimensions are reflected initially to the right to generate two levels of resolution for the first dimension. At this stage, there are thirty-two dimensional-spatial locations and resolution-spatial locations. To generate two levels of resolution in the second dimension, thirty-two resolution-spatial locations are generated by reflecting in an upward direction the combination of thirty-two dimensional-spatial locations and resolution-spatial locations. Now there are a total of sixty-four spatial locations. The two level resolution-spatial locations for the third dimension are generated by reflecting sixty-four resolution-spatial locations to the left of the previously generated sixty-four spatial locations. The two level resolution-spatial locations may be generated for the fourth dimension by reflecting 128 resolution-spatial locations in a downward direction from the mixture of 128 mixed-resolution spatial locations from the first, second, and third dimensions. Accordingly, a total of 256 spatial locations are generated for the 4d, 2-bit object space. Object selectors are generated in a similar fashion as previously described for each mixed-resolution spatial location.

FIGS. 22A-22D are diagrams of a mixed-resolution, 4-dimensional object space derived from a binary, 4-dimensional object space. FIG. 22A again shows the

This Sheet Has Been Replaced



-34-

4-dimensional object space with one bit of resolution.

FIG. 22B shows a mixed-resolution, 4-dimensional object space. In a mixed-resolution object space the number of bits of resolution for each dimension is permitted to differ. Prior art methods for naming elements of an object space can be characterized as container-oriented in that the number of addressable element locations are a function of the container's extent. Alternatively, the method disclosed herein is characterized as content-addressable, in that, the extent and configuration of an object space is a function of its contents. In the object space of FIG. 22B the first and third dimensions each have two bits of resolution and the second and fourth dimensions have only one bit of resolution. Therefore, the object selectors for the object space of FIG. 22B have a total of six bits. Recall that the number of bits in an object selector, when viewed as a power of two, describes the number of elements in a given object space. Therefore, the object space of FIG. 22B comprises sixty-four elements. It should be noted that prior art representations of higher-dimensional spaces typically fix the resolution for each dimension relative to the greatest number of bits required for any dimension. Thereby, an inefficient spatial representation is created. The method of the present invention generates logical object spaces by a process which relies on a novel object description rather than a process of spatial decomposition. In the case of FIG. 22D, the dimensional-spatial locations for one bit of resolution in each of the four dimensions are generated. Then, the resolution-spatial locations for the first and the third dimensions are generated. Sixteen dimensional-spatial locations comprise a first square region. A first square region of sixteen elements is reflected to the right; thereby, producing a second (reflected) square region. The

This Sheet Has Been Replaced



-35-

direction (right) of reflection is determined by the additional bit of resolution in the first dimension. This step results in a rectangular region comprising thirty-two elements. The second dimension has no additional bits of resolution and the next orthogonal direction (upward) is bypassed. The third dimension, however, has an additional bit of resolution. Therefore, the rectangular region comprising thirty-two elements is reflected in the next orthogonal direction (left). Thereby a second (reflected) rectangular region is produced. The resulting first and second (reflected) regions account for the sixty-four elements shown in the object space of FIG. 22B.

Given an object space description where one or more dimensions have two or more bits of resolution (e.g., a k-ary n-cube), the object selectors describe a novel form of reflected Gray code called the k-ary reflected Gray code. An object selector is generated 1212, as illustrated in FIG. 12, for each resolution-spatial location in the mixed-resolution, N-dimensional object space. When all object selectors are generated 1213, from the resolution-spatial locations, the dimensional-spatial locations and the object selectors, a virtual image is generated 1214 of the N-dimensional object space. A user or machine may select 1215 a region of the virtual image for use or display. The computing device may display the selected region of the virtual image of the mixed-resolution, N-dimensional object space on the display means.

FIG. 23 shows a functional diagram of the object description process. Four procedures comprise the object description process: expression 2301; quantization 2304; transformation 2307; and execution 2310. In the case of user-specified attributes a user inputs a domain 2300 of an object which is expressed 2301 as an object description 2302. The object description is encoded as a set of

TOTAL P.19

This Sheet Has Been Replaced



-36-

attributes. Each attribute selected corresponds to one dimension of an N-dimensional, object space. The order in which the attributes are specified determines a sequence in which an object space is generated.

5 The range 2303 of possible values of each attribute is encoded by a quantization 2304 procedure which assigns a logical digital code to range 2303 of values. The resolution is the degree of range 2303 of values. The degree of range compression (e.g., scaling of values) is
10 part of the attribute specification. Coded attribute values correspond to the transition sequence of a reflected binary code. Intuitively, the most straightforward way of naming or coding an ordered set of objects, where each codeword is a unique sequence of binary digits, is to count in binary,
15 but consecutive codewords usually differ by more than one bit position. Some forms of the reflected binary code, referenced above in the Description of the Prior Art, offer special advantages over others for particular applications. The maximum number of bits required to
20 represent a coded attribute value defines its dimensional resolution.

 The range 2303 of values associated with each dimension of the object description 2302 is quantized 2304 to form a coded object description 2305, called a frame
25 2306. The format of a frame 2306 is a bit pattern read from the right that represents a contiguous sequence of coded attributes or bitfields. The rightmost bit of each attribute's bitfield is a logical one denoting a spatial dimension. Additional bits of resolution for a given
30 attribute, if any, are assigned a logical zero; e.g., (0, 1, 0, 1) is a frame 2300 for coded object description representing two four-valued attributes.

 The bits of the object frame 2306 are then transformed 2307 to form an interleaved object frame 2308 called a
35 descriptor 2309. The object descriptor represents the name

This Sheet Has Been Replaced



-37-

format for specific object expressions. A collection of coded attribute values associated with the interleaved frame 2308 of a named object expression is called an object selector. The object descriptor 2309 controls the execution process 2310 for forming a visual space 2311. The bitwise control sequence can be understood by considering the interleaved object frame 2306 in an expanded form. The number of dimensions N describing a unit n -cube is defined in the first interval of the expanded frame. Each subsequent interval extends the dimensional resolution of the object space 2311. A blank interval position in the expanded object descriptor 2309 may be thought of as the termination of the spatial control sequence for that particular dimension.

The object spaces shown in FIGS. 14-19 are simple enough to be formed manually and, in a few instances, mentally; however, description spaces of actual systems quickly exceed the feasible limits of mental visualization and manual procedures. Therefore, an embodiment of the present invention is described as an electronic controller. It should be understood that the control of various types of machines and application processes are contemplated within the scope of this invention. A frame controller is the syntactic expression of a visual space. A region controller is part virtual machine which determines semantic expression of an object space as a name space.

Given a user-specified set of attributes defining dimensions and resolution levels in a particular object space, an illustrative embodiment of an object description system comprises a plurality of physical modules which may be operatively coupled in various logical configurations to efficiently mechanize the method of the present invention. There are two kinds of physical modules in an illustrative embodiment of an object description system: modules of a

This Sheet Has Been Replaced




host computing device and object modules operatively coupled to modules of a host computing device.

Referring to FIG. 24A, a computing device 2400 is shown including an input device 2401, a processor 2402, memory 2403, and a display device 2404. The input device 2401, by way of example, may be a key board, computer port, or an application within a computer. The processor 2402 is coupled between the input device 2401, memory 2403 and display device 2404.

FIG. 24B shows object module 2405 having object frame module 2406, object region module 2407, and object selector module 2408 operatively coupled to the computing device 2400. Each object module 2405 comprises at least one register device having at least one storage cell; combinational logic devices which relate to the registers; data signal paths which link devices within a module and which link devices in different modules; and control signal paths which link devices within a module and which link devices in different modules. The region module 2407 is operatively coupled to the input logic 2404 and the object frame module 2406. The object region logic 2407 is used for selecting a region of the virtual image.

As with the process of the present invention, a user may specify semantic expressions for a particular set of attributes defining dimensions and resolution levels in the object space. A user, using the input device 2404, inputs the semantic expressions for the particular set of attributes of a problem for the mixed-resolution, N-dimensional, object space. The input logic 2403 is operatively coupled to the input device 2404 and interfaces the input device 2404 with the memory 2405.

The frame logic 2407 interleaves the frame to generate an object descriptor. The frame logic 2407 also generates, from the frame and the object descriptor, dimensional-spatial locations for N dimensions. From the



-39-

frame and the object descriptor, the frame logic 2407 generates resolution-spatial locations for resolution levels of each of the N dimensions of the mixed-resolution, N dimensional object space.

5 The frame logic 2407 uses frame data to generate, for a particular spatial location, an object selector. The object selector as previously described conforms to a primary form of a reflected binary code. Using the dimensional-spatial locations and the object selectors, the
10 frame logic 2407 generates a virtual image of the N-dimensional, object space. The computing device using region logic 2408 manipulates the virtual image with bit selectors.

15 The apparatus of the present invention may be used for visualizing a mixed-resolution, N-dimensional, object space. The user specifies a frame and frame data for a particular set of attributes defining dimensions and resolution levels in the object space. The user inputs the frame and frame data for N-dimensional, object space using
20 the input device 2401. The frame module 2406 interleaves the frame to generate an object descriptor, and it generates dimensional-spatial locations for N dimensions from the frame and the object descriptor. The frame module 2406 also generates, for each dimensional-spatial location,
25 an object selector. From the dimensional-spatial locations and the object selectors, the frame module 2406 also generates a virtual image of the N-dimensional object space. The region module 2407 is used for selecting one or more elements of the virtual image. The display map 2406
30 stores the selected region of the virtual image and display device 2410 displays the virtual image of the N-dimensional object space. The frame module 2406 generates, from the frame and the object descriptor, resolution-spatial locations for resolution levels of each of the N dimensions
35 for a mixed-resolution, N dimensional object space.

This Sheet Has Been Replaced



-40-

Various logical configurations of physical modules implement the procedural behavior of an object description system. An object description system can be regarded as an implementation of procedures that transforms
5 mixed-resolution, N-dimensional object description into a mechanical form which can be logically manipulated. An object description system also can be regarded as an implementation of procedures that transforms
10 mixed-resolution, N-dimensional object descriptions into a perceptible form which can be presented as an image on a graphics display device.

Referring to FIG. 25, these transformation procedures can be organized and abstracted into a functional model 2500 of an object description system. The functional model
15 of an object description system comprises a plurality of logical processors, which perform the correlative functions corresponding to the reference numerals of FIG. 12:

- application input processor 2501 (1201)
- frame processor 2502 (1202)
- 20 descriptor processor 2503 (1203/1204)
- dimension-location processor 2504 (1204/1205)
- resolution-location processor 2505 (1206-1211)
- selector processor 2506 (1212/1213)
- virtual image processor 2507 (1214/1215)

25 A logical processor in the functional model corresponds to one or more physical modules, and two logical processors in the functional model may share a physical module. Similarly, representations of object spaces may exist in one or more different memories.
30 Alternatively, a plurality of such object description systems may be operatively coupled in various logical configurations dictated by the conceptual problem domain, enabling concurrent manipulation of a plurality of object space descriptions or concurrent manipulation of a
35 plurality of views of a particular object space

This Sheet Has Been Replaced



-41-

description.

FIG. 26A-26H shows the object space configurations formed by the 4-bit frame logic module. Each object space 2602 shown in FIGS. 26A through 26H is associated with a diagram of its object frame selector 2600 and the logical names of their frame and interleaved frame 2603. The logical names of the frame and interleave frame 2601 shown in FIGS. 26E through 26H are the same, resulting in the practical observation that the object frames for these spaces are in their interleaved form.

AN ILLUSTRATIVE EMBODIMENT OF THE INVENTION

An example of an object space embodied as a uniform color space generated in accordance with the method of the present invention is now described to better understand how to practice the invention. The discussion of prior art color models referred to in Description of the Prior Art established a long felt need for a method of representing a uniform color space, such that, specific color sensations could be algorithmically specified. In particular, this example demonstrates how a range of color sensations described by an RGB color cube can be uniformly projected onto a plane. This example teaches: how to describe the attributes of an RGB color cube; how the perceptual attributes of a color specification correspond directly to the problem description process of the invention; and this example also teaches the correspondence between the problem description process of the invention and the electronic production of color sensations.

Visible light, called the physical color space, is a small segment of the continuum of electromagnetic radiation, which includes, for example, radio waves, radar, microwaves, infrared and ultraviolet light, x-rays, and gamma rays. A color representation system determines the location of a particular color sensation in a visual space,

-42-

called the logical color space. The system is a color representation system; the input is white light; and the response is a color space generated in accordance with the method of the present invention.

5 A color representation system determines the location of a particular color sensation in a visual space called the color space. Color space expressions indirectly produce physical device control signals for a color display. The RGB color cube represents red, green, and
10 blue primaries as orthogonal axes. The displayable colors are within the cube from (0, 0, 0) to (1, 1, 1). The neutral axis is a (diagonal) line from The black point (0, 0, 0) to the white point (1, 1, 1). The color cube has been referred to in the literature as a "natural"
15 coordinate system in the sense that the three color components are mapped into an orthogonal coordinate system in the same fashion as three-dimensional geometry. In a chapter entitled, "Color Displays and Color Science," Color and the Computer, Academic Press, Boston, 1987, p. 23, the section entitled, "Visual Display Descriptive Systems,"
20 Murch makes the following observation: "...the location and proper specification of colors within the interior of the cube, when some real value for all three primaries is required, proves difficult."

25 Color specification means interactive visualization and control of the perceptual color gamuts (range of producible colors) of color display devices. An ideal color model should accomplish intuitive addressability; uniformity; independent control of lightness and chromatic
30 contrast; display device characterization in perceptual terms; and a basis is for naming color specifications.

Intuitive addressability is the specification of color representations in perceptual terms. Perceptual specifications may include, by way of example, hue,
35 saturation and intensity. Hue is the basic component of

This Sheet Has Been Replaced



-43-

color and is primarily responsible for a specific color sensation (e.g., red, green, blue, etc.). Saturation is most closely related to the number of wavelengths contributing to a color sensation. Saturation depends on the relative dominance of a pure hue in a color specification. Intensity is an increased level of illumination permitting a broader range of hues to be visible.

Uniformity is the regular representation of gradations in perceived color, due to the perceptual relationship of color expressions. Independent control of lightness and chromatic contrast is the opportunity to expand chromatic contrast independently of intensity or vice versa. Display device characterization in perceptual terms chooses appropriate display representations and controls their production. A basis for naming color specifications is the opportunity to use a consistent method of color referencing to construct multidimensional models of process expressions in terms of spectral descriptors.

The illustrative example of the invention applied to the problem of color space description teaches a method for representing visual color sensations logically and reproducing logical color spaces visually. Color specification and color space organization conventionally involve levels of computational indirection between the specification of color in terms of its perceptual attributes (e.g., hue, saturation and intensity) and subsequent production of electronic color signals. The process enables the description of a logical color space expressed in terms of perceptual color attributes to be directly realized in terms of a given display device's physical color space. The approach to the problem is a descriptive specification of color space component relationships.

The domain description of a color representation

This Sheet Has Been Replaced



-44-

system is the human visual system's response to a limited portion of the electromagnetic spectrum called visible light. Light generally refers to electromagnetic radiation from 380 nm to 770 nm. The observed color of light results from a mixture of intensities at different wavelengths. The rate of change in intensity for a given control source is a function of wavelengths. In R. Hall, Illumination and Color in Computer Generated Imagery, Springer-Verlag, NY, 1988, pp. 47-52, the graph of intensity as a function of wavelength is the spectral curve for a given test color. This graph represents a schematic for determining control light intensities for a given test color spectral curve. Each control source spectral curve corresponds to a dimensional component of the color space domain. Colors mixed in a fashion in which bands of wavelengths are added to one another is called an additive color mixture.

The illustrative RGB color space is dimensionally described in terms of three color primaries (e.g., hue = domain dimension): high wavelength (R) red primary; medium wavelength (G) green primary; and low wavelength (B) blue primary. In an N-dimensional color space where each dimension corresponds to a color primary, the resolution of color space is determined by defining the number of values for each primary (e.g., saturation = range resolution). The range of dimensional resolution is determined by one or more bits for each dimension. The number of bits specified for each dimension may differ. Two bits of resolution (e.g., four values) are specified for each primary in the RGB color space generated below.

Value quantization can be described as spectral sampling. In the prior art spectral sampling means reducing a spectral curve to a set of sample values for subsequent color computations. Spectral sampling herein means reducing a spectral curve to a set of intensity values associated with logical names in a color space



-45-

generated by the method of the present invention(e.g., intensity = value).

5 Generation of a logical color space (e.g., a space of color names) is performed as follows. The frame is a coded representation of user-specified attribute descriptions for a problem domain. In a color space each attribute corresponding to a primary hue is described by a bitfield in the frame. The first bit of each bitfield is always a logical one. Subsequent bits in a given bitfield are
10 logical zeros. Each logical zero represents an additional bit of resolution.

In an illustrative color space a frame "010101" comprises three two-bit bitfields where: the rightmost pair of bits represents the red attribute; the center pair of
15 bits represents the green attribute; and the leftmost pair of bits represents the blue attribute. The primary function of a frame is as an interpreter which distinguishes between the possible meanings of an object descriptor or an object selector.

20 In an illustrative color space the object descriptor is the result of a transformation of a frame where the bits of each frame bitfield are interleaved. When, for example, the frame "010101" is interleaved the result is the object descriptor "000111." The primary function of an object
25 descriptor is its role in generating N-dimensional object spaces. Using the frame to distinguish dimensional bits from resolution bits, the object descriptor determines the orthogonal generation of N-dimensional object spaces.

30 There are two notions of cycles associated with the orthogonal generation of N-dimensional object spaces. The first cycle is the order of interpretation of the object descriptor. Object descriptor bits are logically grouped into dimensional intervals, e.g., "000 111". Each dimensional interval is processed as a cycle beginning at
35 the spatial origin.

This Sheet Has Been Replaced



-46-


A second cycle associated with the orthogonal generation of N-dimensional object spaces is the order of reflection for generating the logical selector names. The steps of the reflection cycle may correspond to the four orthogonal directions: right, up, left, and down. A counterclockwise

rather than a clockwise cycle was arbitrarily chosen, but the chosen direction must be strictly adhered to. If the number of dimensions is greater than four, then the reflection process continues in the next orthogonal direction for each non-null position in an expanded form of the object descriptor intervals. The expanded form of an object descriptor inserts null place holders for attributes in the object descriptor whose resolution is less than others in a given interval.

A frame is a positional notation which denotes the number of attributes and the resolution of each attribute. Frame data are the values or sense of each bit position in a given frame. Given the frame "010101" and frame data "000010," the rightmost bitfield of frame data "10" represents a value for a particular intensity of the red attribute in a color specification. The object selector is a transformation of frame data where the frame data is interleaved. The result of interleaving frame data "000010" is the object selector "001000." The name of each location in an N-dimensional space corresponds to an object selector.

FIGS. 27-31 show an illustrative example of a color representation system in accordance with the method of the present invention. FIGS. 27A-27C show how the name space elements of a binary RGB color cube are projected onto a plane in accordance with the method of the present invention. Each axis 2701 of the RGB color cube corresponds to a color primary. Each node 2700, 2702 of the RGB color cube corresponds to a particular color

This Sheet Has Been Replaced



-47-

sensation or element 2703 in a logical color space. The name of each color sensation of an RGB color space corresponds to a particular element location 2702 in a logical color space. FIG. 27C shows how the elements, name space labels, of a binary RGB color space are labeled. The vertical regions labeled "R" 2704 contain elements whose rightmost bit position is set. The horizontal region labeled "G" 2705 contains elements whose middle bit position is set. The left half labeled "B" 2706 contain elements whose leftmost bit position is set.

FIGS. 28A-28C show the elements of a sixty-four element RGB color space. FIG. 28B shows how the elements of a sixty-four element RGB color space are labeled. FIG. 28C shows the object selectors of a sixty-four element RGB color space which correspond to the logical names of each color sensation.

FIGS. 29A-29C show the relationships between three-dimensional spaces with different resolutions. R. Hall in, Illumination and Color in Computer Generated Imagery, Springer-Verlag, NY, 1988, p. 48, plots the intensities of the control lights required to match any wavelength as a function of wavelength.

FIG. 30 shows a graph of the resulting matching curves for 445 nm, 535 nm, and 630 nm control sources. FIGS. 31A-31C show how percentages of spectral intensities over a range of values for each primary are determined in a sixty-four element RGB color space, using the graph of matching curves of FIG. 30.

Manipulation of a logical color space is accomplished by methods associated with a particular logical view, such as: elements; relations; paths; regions; and subspaces. Referencing a particular color sensation as an element of a logical color space may be accomplished in two ways: reference by value or reference by location.

Reference by value means a user or an application

This Sheet Has Been Replaced



-48-

process provides a description of a particular color sensation in terms of its component hues and their respective intensities, typically as Frame data. Recall that the frame is a positional notation which denotes the number of attributes and the resolution of each attribute. Therefore, frame data correspond to the value or sense of each bit position in a given frame. For example, given the frame "010101" and frame data "000010" the rightmost bitfield of frame data "10" represents a value for a particular intensity of the red attribute in a color specification.

Reference by location means a user or an application process selects a particular color sensation in terms of its location; either indirectly by index (e.g., palette entry) or directly by its selector. Recall that the object selector is a transformation of frame data where the bits of each frame data bitfield are interleaved. For example, given the frame "010101" and frame data "000010" where the frame data is interleaved the result is the object selector "001000." The name of each location in an N-dimensional space corresponds to an object selector.

Referencing a set of harmonious color sensations as relations of a logical color space may be accomplished by generating combinations of n-things taken k at a time, where n is the number of elements in a logical color space and k is the number of selector bits. The elements of a set are said to be neighbors or logically adjacent because one can be obtained from the other by switching a "0" and a "1" in a particular selector bit position. The number of elements in each logical relation corresponds to the number of selector bits. Referencing various sets in a logical color space may be accomplished selectively masking one or more selector bits.

Generating a harmonious sequence of color sensations as paths in a logical color space may be accomplished



-49-

because the collection of element names describe a Gray sequence, where the Hamming distance between successive elements is one. The sequence of color sensations is said to cycle if its first and last element codewords differ in only one quantum interval. Otherwise, the sequence of color sensations is known as a path. Given an initial element codeword and a transition sequence the entire set of element codewords in a logical color space can be generated.

Referencing various regions of a logical color space may be accomplished selectively by masking lower-order selector bits. Referencing various subspaces within a logical color space may be accomplished by element scaling; that is, the value of an element location is actually an object descriptor rather than a color sensation.

The process by which a logical color frame is interpreted to electronically produce color sensations is referred to herein as reflected Gray code (RGC) demodulation. RGC demodulation may be generalized as a novel form of digital to analog conversion. The inverse of RGC demodulation is the conversion of analog information to a digital form (e.g., quantization, spectral decomposition, etc.) by the process of RGC modulation. The method of the present invention represents a novel coding system. Object descriptions have meaning, that is, they refer to or describe some system with certain physical or conceptual properties. For color graphics, the objects may be particular color sensations described in terms of attributes such as: red; green; blue; which define a color space. For optical communications, the objects may be a particular coherent light source described in terms of its lightwave components, which define a signal space.

In a U.S. Patent referenced in the Description of the Prior Art, Robinson and Sanford teach: "To convey information on an optical wave, some property of that wave

This Sheet Has Been Replaced



-50-

has to be modulated or changed in accordance with the information and adopted coding system." An aspect of the present invention is its novel application as such a coding system. Given an incident coherent light source dispersed
5 into its component wavelengths as inputs to optical couplers, such as those referenced in the Description of the Prior Art above, the method of the present invention may be employed to modulate the light source as a plurality of wavesets, which correspond to object frames, frame data,
10 object descriptors, and object selectors.

When the method of the present invention may be employed to modulate the light source as a plurality of wavesets, each clock interval in a pulse-coded modulation (PCM) scheme, for example, can contain "n" quantum
15 intervals of information per pulse rather than a single quantum interval, where "n" is the number of component wavelengths. Such an encoding scheme is called parallel, pulse-coded modulation (PPCM). The significant aspect of system description is that the actual description is one
20 selected from a set possible descriptions. The invention is a general apparatus and method, designed to operate for each possible problem selection, not just the one which will actually be chosen since this is unknown at the time of design.

It will be apparent to those skilled in the art that various modifications can be made to the apparatus and method for visualizing mixed-resolution, N-dimensional object space of the instant invention without departing
25 from the scope or spirit of the invention, and it is intended that the present invention cover modifications and variations of the apparatus and method for visualizing
30 mixed-resolution, N-dimensional object space provided they come within the scope of the appended claims and their equivalents.

This Sheet Has Been Replaced



**WE CLAIM:**

1. A process for visualizing N-dimensional-object space using a computing device such as a computer, the computing device of the type comprising means for storing data and commands, and frame logic responsive to the stored data and commands for generating a virtual image representing the N-dimensional-object space, comprising the steps, using said computing device, of:

inputting to said computing device a set of attributes;

generating from the attributes, frame and frame data for the N-dimensional-object space;

interleaving the frame to generate an object descriptor;

generating, from the frame and the object descriptor, dimensional-spatial locations of said N-dimensional-object space;

generating, from the frame and the object descriptor, an object selector for each dimensional-spatial location in said N-dimensional-object space;

generating from said dimensional-spatial locations and said object selectors a virtual image of the N-dimensional-object space; and

selecting a region of said virtual image.

2. The process as set forth in claim 1 further comprising the steps, using said computing device, of:

generating, from said frame and said object descriptor, resolution-spatial locations for resolution levels of each of the N dimensions for a mixed-resolution, N-dimensional-object space;

generating, from said frame and said object descriptor, an object selector for each resolution-spatial





location in said mixed-resolution, N-dimensional-object
10 space;

generating from said resolution-spatial
locations, said dimensional-spatial locations and said
object selectors a virtual image of the
N-dimensional-object space; and

15 selecting a region of said virtual image.

3. A process, using a computing device having a
display device for visualizing a mixed-resolution,
N-dimensional-object space, wherein a user specifies a
frame and frame data for a set of attributes defining N
5 dimensions and defining resolution levels in the object
space, comprising the steps, using said computing device,
of:

interleaving the frame to generate an object
descriptor;

10 generating, from said frame and said object
descriptor, dimensional-spatial locations for N dimensions;

generating, from said frame and said object
descriptor, resolution-spatial locations for resolution
levels of each of the N dimensions of said

15 mixed-resolution, N dimensional-object space;

generating, for each spatial location, an object
selector conforming to a primary form of a reflected binary
code;

20 generating a virtual image of said
N-dimensional-object space from the dimensional-spatial
locations, resolution spatial locations and object
selectors; and

selecting a region of said virtual image.



-53-



4. The process as set forth in claim 1, 2 or 3 further comprising the step, using said computing device, of:

5 displaying the selected region of the virtual image on said display device.

5. The process as set forth in claim 1, 2 or 3 wherein the step of selecting using said computing device, includes:

5 chaining bits in a particular sequence forming a path for a selected path of said virtual image.

6. The process as set forth in claim 1, 2 or 3 wherein the step of selecting, using said computing device, includes:

5 suppressing particular bits of said virtual image for generating a subspace.

7. The process as set forth in claim 1, 2 or 3, further comprising the step for generating an N-dimensional color space, of:

5 encoding a plurality of lightwave components as the set of attributes.

8. An apparatus for visualizing a mixed-resolution, N-dimensional-object space, wherein an object descriptor for a set of attributes defining dimensions and resolution levels in the object space is specified, comprising:

5 means for inputting to said apparatus the set of attributes;

means for generating from the set of attributes, frame and frame data for the N-dimensional-object space;

means for interleaving the frame to generate an

This Sheet Has Been Replaced



WO 92/13313

PCT/US92/00218

-54-



10 object descriptor;

means responsive to the frame and the object descriptor for generating dimensional-spatial locations of said N-dimensional-object space;

15 means responsive to the frame data for generating an object selector for each dimensional-spatial location in said N-dimensional-object space;

means responsive to said dimensional-spatial locations and said object selectors for generating a virtual image of the N-dimensional-object space; and

20 means for selecting a region of said virtual image.

9. The apparatus as set forth in claim 8 further comprising:

5 means responsive to said frame and said object descriptor for generating resolution-spatial locations for resolution levels of each of the N dimensions for a mixed-resolution, N-dimensional-object space;

10 means responsive to said frame data for generating an object selector for each resolution-spatial location in said mixed-resolution, N-dimensional-object space;

means, responsive to said resolution-spatial locations, said dimensional-spatial locations and said object selectors, for generating a virtual image of the N-dimensional-object space; and

15 means for selecting a region of said virtual image.

10. The apparatus as set forth in claim 8 or 9 further comprising:

means for displaying the selected region of the

This Sheet Has Been Replaced



-55-



virtual image of the N-dimensional-object space.

11. The process as set forth in claim 8 or 9 wherein the said selecting means further includes:

means for chaining bits in a particular sequence forming a path for the selected path of said virtual image.

12. The process as set forth in claim 8 or 9 wherein the said selecting means further includes:

means for suppressing particular bits of said virtual image for generating a subspace.

13. An apparatus for generating a mixed-resolution, N-dimensional object space using a computing device, comprising:

means for storing data and commands;

5

means responsive to the stored data and commands for generating a logical representation of the N-dimensional, object space;

display logic responsive to the stored data and commands for generating a virtual image of the N-dimensional, object space;

10

display means for displaying a visible representation of the virtual image.

14. An apparatus for visualizing a mixed-resolution, N-dimensional-object space, wherein a specified frame and frame data and semantic expressions for a particular set of attributes defining dimensions and resolution levels in the object space, comprising:

5

input means for inputting the frame and frame data for the N-dimensional-object space;
frame logic responsive to said frame, for

This Sheet Has Been Replaced





10 interleaving the frame to generate an object descriptor,
for generating, from said frame and said object descriptor,
dimensional-spatial locations for N dimensions, for
generating, for each dimensional-spatial location and using
frame data, an object selector, and for generating from
said dimensional-spatial locations and said object
15 selectors a virtual image of the N-dimensional-object
space; and

region logic for selecting a region of said
virtual image.

15. The apparatus as set forth in claim 14 wherein:
said frame logic generates, from said frame and
said object descriptor, resolution-spatial locations for
resolution levels of each of the N dimensions for a
5 mixed-resolution, N dimensional-object space.

16. The apparatus as set forth in claim 14 or 15
further comprising:

memory means for storing the selected region of
said virtual image; and

5 display means for displaying the selected region
of said mixed-resolution, N-dimensional-object space.

17. In a computing device, a memory having a virtual
image of an N-dimensional, object space, including at least
dimensional-spatial locations, and means for selecting a
region of the virtual image.

18. The computing device as set forth in claim 17
wherein said memory further includes having a virtual image
of an N-dimensional, object space including
resolution-spatial locations.



WO 92/13313

PCT/US92/00218

-57-



19. The computing device as set forth in claim 17 further including means for encoding a plurality of signal components for defining the dimensional-spatial location of the virtual image.

20. The computing device as set forth in claim 18 further including means for encoding a plurality of lightwave components for defining the dimensional-spatial locations and the resolution-spatial locations of the virtual image.

21. A computing device comprising:
a memory;
frame logic for generating a virtual image of an N-dimensional, object space in said memory, including at least dimensional-spatial locations; and
region logic for selecting a region of said virtual image.

22. The computing device as set forth in claim 21 wherein:
said frame logic generates the virtual image with resolution-spatial locations.

23. The computing device as set forth in claim 21 or 22 further including;
means for encoding a plurality of signal component for defining dimensional-spatial locations of the virtual image.

24. The computing device as set forth in claim 21 or 22 further including region logic for selecting a region of

This Sheet Has Been Replaced



-58-



said virtual image.

25. A process for visualizing N-dimensional-color space using a computing device such as a computer, the computing device of the type comprising means for storing data and commands, and frame logic responsive to the stored data and commands for generating a virtual image representing the N-dimensional-color space, comprising the steps, using said computing device, of:

inputting to said computing device a set of attributes including at least red, green and blue hues;

generating from the attributes, frame and frame data for the N-dimensional-color space;

interleaving the frame to generate a color descriptor;

generating, from the frame and the color descriptor, dimensional-spatial locations of said N-dimensional-color space;

generating, from the frame and the color descriptor, an color selector for each dimensional-spatial location in said N-dimensional-color space;

generating from said dimensional-spatial locations and said color selectors a virtual image of the N-dimensional-color space; and

selecting a region of said virtual image.

26. The process as set forth in claim 25 further comprising the steps, using said computing device, of:

generating, from said frame and said color descriptor, resolution-spatial locations for resolution levels of each of the N dimensions for a mixed-resolution, N-dimensional-color space;

generating, from said frame and said color



WO.92/13313

PCT/US92/00218

-59-



descriptor, an color selector for each resolution-spatial
location in said mixed-resolution, N-dimensional-color
space;

generating from said resolution-spatial
locations, said dimensional-spatial locations and said
color selectors a virtual image of the N-dimensional-color
space; and

selecting a region of said virtual image.

27. The process as set forth in claim 25 or 26
further comprising the step, using said computing device,
of:

displaying the selected region of the virtual
image on said display device.

This Sheet Has Been Replaced

