

RTMPIS copy

REPLACED SHEETS		SG
☐	Description : paged	to paged
☒	Claim(s) : paged ..15..	to paged ..19..
☒	Drawing(s) : paged ..1/3..	to paged ..3/2..
☒	Abstract : paged ..20..	to paged

1

TOTE TRANSPORT SYSTEM

The present invention relates to an automatically operated conveyor system for returning totes to point-of-use. The system includes a control system, switches, conveyors, carriers, lifts and transfer stations and operates in a predetermined direction based on tote accumulation. More particularly, the invention relates to baggage handling facilities, such as the transportation and distribution of luggage in airports, using totes, pallets, containers and/or bins for transporting luggage on conveyor systems. For purposes of this document the terms "tote" or "totes" will be understood to be interchangeable with pallets, containers, bins, or other items suitable for this purpose.

The conventional luggage handling systems lack automation for return of luggage totes. A typical system will allow attendants at the check-in point, ticket booth, to retrieve a tote, stored at their station and place an item of luggage in the tote. Then the attendant will place the tote containing the luggage onto the conveyor system. The system will convey the tote to a make-up area typically several floors below the check-in area. At the make-up area a second attendant will remove the luggage from the tote and place the luggage onto a conventional ground cart and the tote onto a tote stack. When required, the attendant will place the stack of totes on a cart and return them to the initial check-in point. This lack of automatic return for the totes requires a supervisor to monitor the stack of totes and schedule periods for attendants to interrupt their duties and return the totes to the check-in

area and distribute the totes to the various check-in points. These manual operations unnecessarily result, at a minimum, in interruptions of the attendants and exposes the delivery system to needless delays resulting from unavailability of totes.

5 There have been attempts to overcome this problem by installing automated tote return systems. There are numerous automated systems in the art such as the one described in U.S. Patent 3,776,395 Lingg et al. which relates to a roller conveyor or belt conveyor system having a series of automated
10 tote stacking and unstacking stations. The problem with this and other return systems whether they comprise their own system of conveyors or take advantage of the return runs of the loaded tote conveyors is that the arrangement of the return system typically does not handle empty totes well -- much less stacked
15 empty totes. In addition, these systems typically require too much valuable building space. These handling and space problems are compounded in systems required to return totes to locations on different floors of a facility.

 We have surprisingly reduced or substantially overcome one
20 or more of the aforementioned problems.

SUMMARY OF THE INVENTION

 This invention relates to an automated system for returning totes from an end-of-use point, reclaim area, back to
25 a point-of-use, ticket counter. This system will generally be used in conjunction with an automated luggage conveyor system.

 This system provides means for an individual to place one or a stack of several totes onto the conveyor system which will

automatically convey the totes to an endless storage conveyor.

These storage conveyors will retain the totes in position for delivery to the ticket counters when the control system senses that the supply is either low or depleted. Once the control
5 system receives a signal that a particular ticket counter requires additional totes the system will move a carrier into a position adjacent to the tote holders at such ticket counter and automatically dispense the totes. The attendants at the ticket counter are then able to readily access these totes.

10 The system is equipped with a system of vertical and horizontal conveyor systems. The system further includes means for transferring totes from a vertical conveyor to a horizontal conveyor and vice versa. The system also includes branch conveyors located adjacent to the main conveyor for enabling
15 the tote carriers to travel, and stop as necessary, in a position relative to the vertical conveyors such that the carrier can either place containers on or remove containers from the vertical conveyors. Also included in the system is a control system directing the totes from the manual load
20 stations through to the ticket counter tote holders. This control scheme directs the totes by controlling the movements of the lifts, horizontal conveyors, transfer devices, and carriers.

Accordingly, it is an object of this invention to provide
25 an automatic tote return system that can be utilized in facilities requiring the use of luggage totes on more than one floor.

It is another object of this invention to provide a tote return system of the above character wherein the delivery of the totes is automated so as to eliminate delays inherent in manual handling.

- 5 It is a further object of the invention to provide a substantially horizontal conveyor means capable of automatically placing and removing totes to and from a substantially vertical conveyor.

10 It is yet another object of the invention to provide a tote return system capable of moving totes in both the horizontal and vertical directions.

It is still another object of the invention to provide an automated tote return system of the above character wherein the totes are automatically delivered to check-in points as needed.

- 15 It is still a further object of the invention to provide a tote conveyor system wherein the totes are transferred onto carriers only once and not removed from such carriers until delivered to the point-of-use even if such final destination is located on a different floor than where the totes were placed
20 onto such carriers.

These and other objects of the present invention will become readily apparent after studying and understanding the present invention, as hereinafter described.

BRIEF DESCRIPTION OF DRAWINGS

FIG. 1 is a side elevation view of one possible layout of a tote conveyor system as it might be utilized in a representative multi-floor facility.

5 FIG. 2 is a schematic diagram plan view of one possible layout of a tote conveyor system.

FIG. 3 is an enlarged plan view of section III-III of FIG.2.

FIG. 4 is a side elevation view of a ticket counter showing the tote conveyor system.

10

Before the invention is explained in detail, it is to be understood that the invention is not limited in its application to the details of construction and the arrangements of components set forth in the following description or
15 illustrated in the drawings. The invention is capable of other embodiments and of being practiced or being carried out in various ways. Also, it is to be understood that the phraseology and terminology used herein is for the purpose of description and should not be regarded as limiting.

20

DETAILED DESCRIPTION OF THE INVENTION

The disclosure provides a tote conveyor system as may be utilized in an airport wherein luggage received at the customer check-in point is placed into a tote and onto a conventional
25 automatic conveyor system. This conveyor system delivers the tote containing the luggage to any one of a number of make-up points. The attendant retrieves the luggage, at the make-up point, and places it onto a conventional cart for delivery to

the plane. The tote is set off to the side to be stacked and/or placed onto the tote return system.

LIFT

5 The system in the form illustrated, in FIG. 1, has a lift
10 10. The lift may be any one of a wide variety of conventional
elevating devices capable of transporting the totes in a more
or less vertical direction. Preferably, this elevating device
will be of a type occupying a minimal area of floor space such
10 as a vertical four chain conveyor having chains attached to the
four-corners of a vertically moving shelf capable of handling a
tote or stack of totes 12. The totes are manually placed on
the lift either individually or preferably stacked at the
manual loading station 14. Typically, the system will have
15 several of these manual loading stations conveniently disposed
about the facility adjacent to the cargo make-up areas 2. It
should be appreciated that the system may comprise a
substantially horizontal conveyor system having manual loading
stations for collecting totes for automatic transfer to a lift.
20 The lift conveys the totes in a substantially vertical
direction to the transfer station 16, the point where the lift
intersects with a loading branch 22 of the substantially
horizontal central conveyor system 20.

25 CENTRAL CONVEYOR

The central conveyor system 20 may be of any type known in
the industry suitable for transporting totes. Typically, the

overhead conveyors will be a powered chain and track system. The central conveyor may comprise a recirculating conveyor, a branch conveyor and multiple carriers 18. The branch conveyors are typically conveyors that on one end receive
5 carriers from the recirculating conveyor and on the other end deliver carriers to the recirculating conveyor. The carrier may be of any type suitable for this purpose such as a frame extending down from a conveyor track engagement means wherein such frame is adapted to hold the totes while remaining open on
10 one side. The engagement means is capable of engaging and disengaging from the conveyor and may be of any type suitable for this purpose such as mechanically or electrically activated jaw, dog, latch or catch. Although this central conveyor is substantially horizontal, it will be appreciated that portions
15 of this conveyor may be directed upwardly and/or downwardly enabling the carriers to be carried to and from different elevations. This central conveyor system may additionally comprise a series of switches 24 and triggers. The switches enable the carriers to move to and from one conveyor track to
20 another, such as a branch conveyor. The triggers, which may be mechanical, electrical, or electro-mechanical, are used for activating the engagement means on the carriers. The central conveyor system is a means for distributing the totes collected from the lifts to other lifts for further transporting or
25 directly to the tote holders.

Alternatively, the central convey system may incorporate another substantially horizontal conveyor or series of conveyors 34, typically, on another level. These additional

conveyors may be composed of at least one recirculating conveyor 36, having at least one branch conveyor 38 for addressing at least one lift. These conveyors can then transport the tote carriers to and from the individual ticket
5 counters 4 such that totes can be delivered to the tote holders
6 typically positioned at the ticket counters.

CARRIER LIFT

The tote conveyor system may also include a carrier lift
10 30 which is capable of vertically conveying carriers 18 including carriers holding totes. The carrier lift 30 may be of any type of lift or elevating means suitable for this purpose and may be of the same type or even the same lift as that described above. Typically, a carrier lift will be
15 equipped with a means 32 for securing the carrier in a manner similar to that of the central conveyor system. This may include a section of a conveyor of the same type as the central conveyor system. For instance if the central conveyor system was of the chain and track type described above the carrier
20 lift may have a section of track capable of securing the carrier during the vertical movements and adapted for transfer operations of the carrier to and from the lift 30.

TRANSFER DEVICES

25 The system will typically include a transfer means at each point throughout the system where it is necessary to transfer the totes and/or carriers from a lift to a conveyor, from a

conveyor to a lift, and/or from a lift and/or conveyor to a tote holder. The transfer means may be of any type suitable for this purpose such as pushers, pullers, slides, tilters and combinations of these. A typical transfer device may be a
5 pusher type 42 where a flatface ram, positioned on the opposite side of the lift from the carrier, is extended by a power source engaging a side of the tote and forcing the tote off the lift and into the carrier. Alternatively, the ram may be positioned behind the carrier opposite the destination point,
10 for instance the tote holder, such that the totes could be pushed off the carrier and presented to the destination point.

The power source may be any source known for this purpose. Typically, the ram will be electro-mechanically and/or hydraulically operated. Another typical transfer device may be
15 an in-line conveyor type 44 in which the carrier is conveyed in close proximity to the lift and allowed to move freely along a track into the lift securing means. The carrier, once transported by the lift to its destination, may freely move from the securing means along a track off the lift to another
20 conveyor system. The carrier transfer between the conveyor system and the lift carrier may be accomplished by designing the conveyor track employed for delivering the carrier to the lift at an elevation higher than the position of the securing means fixed on the lift such that the transfer may at least in-
25 part be assisted by gravity. Similarly, the conveyor track employed for receiving the carrier from the lift may be positioned at an elevation lower than the position of the securing means fixed to the lift. The carrier securing means

positioned on the lift may be of any type suitable for this purpose such as a single section of conveyor track or a more elaborate system composed of moving components for securing the carrier during transport and assisting the transfer of the carrier to and from the conveyors.

CONTROL SYSTEM

It will be readily apparent that in the more advanced forms of this invention, it will be necessary to utilize a mechanism to keep track of the movements of the totes through the system. This can be accomplished in a number of ways, the one described herein utilizing a computer processor system.

The system may comprise a single computer which receives all the signals from the sensors or a master control computer that receives data from satellite computers. The location and identity of the totes may be maintained by a system of sensing elements including mechanical switches, electro-mechanical switches, manual switches, optical sensors, and combinations of these and others. The computer responds to these various input sensors by sending output signals to various activators including switches, triggers, motors, pushers and a variety of elements known to be controlled by computer control systems.

The control system may cause: a lift to move to particular position and stop, a carrier to travel about the conveyor system through a series of switches and disengage from the conveyor to a particular position and stop, or any number of a series of operations required to enable the totes to be conveyed throughout the tote conveyor system.

It should be appreciated that the invention may exist in an infinite number of arrangements. The system should be arranged in accordance to the facility in which it is intended to serve. The system may contain any number or none of any particular component noted above. The system may also combine any number of other components along with the components above.

SIMPLIFIED SYSTEM

A simplified system of the present invention will include at least one lift, at least one substantially horizontal conveyor system, at least one transfer means, at least one tote loading station and at least one tote holder. The system may include varying levels and degrees of control from substantially manual control through to complete automation.

15

EXAMPLE

The invention may be practiced as follows. A tote conveyor system may have a series of tote lifts positioned adjacent to each tote accumulation area throughout the facility. The totes may be manually placed either individually or in a stacked fashion onto the vertical tote lift which will carry the totes up to a transfer station. The tote lift will be of the type having a shelf positioned between and attached to four chains arranged at each of its corners. The chains and shelf will move in a continuous closed loop fashion such that the shelf will move up, over the top, down, around the bottom and up again. Once the vertically rising shelf containing the totes reaches the transfer station the tote lift is stopped. The

totes are pushed off the tote lift onto a carrier positioned adjacent to the lift. This carrier will be on one of several branch lines the are part of the central conveyor system.

The central conveyor system will preferably be an overhead
5 power and free continuous conveyor of the type supplied by
Jervis B. Webb Company under the name Unibilt. The conveyor
system will be composed of a central continuous recirculating
conveyor having several branch conveyors for enabling the
carriers to address the transfer station for each of the tote
10 lifts and carrier lifts. Once the carrier receives the totes,
at the transfer station, from the tote lift it will engage the
branched conveyor chain and travel along the conveyor track
toward the recirculating conveyor. It will pass through a
switching device and engage the recirculating conveyor of the
15 central conveyor system. The carrier will travel around the
recirculating conveyor until it reaches the branch conveyor
that addresses the designated carrier lift. The carrier will
then switch from the central conveyor drive chain onto the
branch conveyor drive chain. This branch chain will transport
20 the carrier up to the carrier lift transfer station. Once the
carrier reaches this position the carrier can be disengaged
from the branch conveyor power chain and travel downwardly onto
the track mounted on the carrier lift.

The system may have a series of carrier lifts positioned
25 around the facility such that the tote conveyor system can
address several groups of ticket counters. The carrier lift
will have a means of securing the carrier in the track mounted
on the lift. And the carrier containing the totes will be

transported up to another level of the facility. Once the carrier reaches the designated carrier lift transfer station the carrier will be released to travel along the track, typically downwardly, onto a branch line of the upper level
5 recirculating conveyor. The carrier will engage the branch line of the upper level recirculating conveyor and travel along the track toward the recirculating conveyor. Once it reaches the upper level recirculating conveyor it will disengage the branch conveyor and engage the upper level recirculating
10 conveyor. The carrier containing totes will enter a storage area where it will wait in a cue. This cue will be composed of carriers circulating on the upper level recirculating conveyor waiting to deliver their totes to a tote holder positioned in proximity to the ticket counter. Once a request is made for
15 more totes the carrier will travel along the upper level recirculating conveyor to a position adjacent to the tote holder. A pusher will be activated to cause the totes to be transferred from the carrier to the tote holder.

The empty carrier will begin its journey back to a tote
20 lift transfer station. The carrier will travel along the upper level recirculating conveyor onto its branch conveyor onto the carrier lift down to the central conveyor system level onto a branch conveyor of the central conveyor system to the recirculating conveyor of the central conveyor system. Once on
25 the recirculating conveyor of the central conveyor system it will circulate until a request is registered for a carrier to be positioned at a tote lift transfer station. In order to respond to the request, the carrier will move along the

recirculating conveyor until it reaches the switch for the desired branch conveyor. The carrier will transfer onto such branch conveyor and travel along the branch conveyor up to the requested tote lift transfer station. At this point the
5 carrier will disengage the drive chain of the branch conveyor and wait to receive a tote or stack of totes from the tote lift.

It has been found that it may be beneficial to incorporate a carrier lift into a tote convey system of this invention, as
10 discussed in the Example. The use of a carrier lift can reduce the number of tote transfers to and from the carriers. Specifically, once the totes are loaded onto the carriers the carrier with totes can be transported around the system, both vertically and horizontally, which may reduce some of the
15 complexities associated with these types of transfers.



What is claimed is:

1. A tote conveyor system comprising:
elevating means for moving at least one tote in a substantially vertical direction;
5 conveying means for moving at least one said tote in a substantially horizontal direction; and
transfer means for transferring at least one said tote between said elevating means and said conveying means.
- 10 2. A tote conveyor system of claim 1 wherein the elevating means moves vertically.
3. A tote conveyor system of claim 1 further comprising:
receiving means for receiving at least one said tote onto
15 said conveying system; and
unloading means for discharging at least one said tote from said conveying system.
4. A tote conveyor system of claim 1 wherein said
20 conveying means is an overhead conveyor.
5. A tote conveyor system of claim 4 wherein said conveying means is a track and chain system.
- 25 6. A tote conveyor system of claim 1 wherein said conveying means has at least one carrier having engagement means for releasably attaching to said chain and means for holding at least one said tote.

This Sheet Has Been Replaced





7. A tote conveyor system of claim 1 wherein said conveying means is comprised of at least one recirculating conveyor and at least one branch conveyor for transporting at least one carrier between said recirculating conveyor and a position adjacent to the elevating means.

8. A tote conveyor system of claim 7 wherein said branch and said recirculating conveyors are the same type.

10

9. A tote conveyor system of claim 6 wherein said system further comprises a second elevating means for moving at least one carrier in a vertical direction and a second transfer means for transferring carriers between said second elevating means and said conveying means.

10. A tote conveying system of claim 9 further comprising a second conveying means for moving said carriers in a substantially horizontal direction.

20

11. A tote conveyor system comprising:

manual loading means enabling an individual to place at least one tote onto said conveyor system;

a first elevating means for moving at least one said tote in a substantially vertical direction between said manual loading means and a first conveyor;

a second elevating means for moving at least one said tote in a substantially vertical direction between a first conveyor

This Sheet Has Been Replaced





and a second conveyor;

at least one carrier means for releasably engaging at least one conveyor and holding at least one tote;

5 a first conveyor capable of transporting at least one said carrier means;

a first transfer means for moving at least one said tote between said first elevating means and said first conveyor;

a second conveyor capable of transporting at least one said carrier means;

10 a second transfer means for transporting at least one said tote between said second elevating means and at least one said transport means; and

unloading means for discharging at least one said tote from at least one conveyor to a discharge station.

15

12. A tote conveyor system of claim 11 wherein said first conveyor comprises:

a recirculating conveyor for moving at least one said carrier means in a substantially horizontal direction; and

20 at least one branch conveyor for transporting at least one said carrier means between said recirculating conveyor and a position in close proximity to at least one said elevating means; and

said second conveyor comprises:

25 a recirculating conveyor for moving at least one said carrier means in a substantially horizontal direction; and

at least one branch conveyor means for moving at least one said carrier means between said recirculating

This Sheet Has Been Replaced





conveyor means and a position in close proximity to said second elevating means.

13. A tote conveyor system as in claim 12 wherein said
5 first conveyor is at an elevation lower than said second conveyor.

14. A tote conveyor system comprising:

manual loading means enabling an individual to place at
10 least one tote onto said conveyor system;

a tote elevating means for moving at least one said tote vertically between said manual loading means and a first transport means;

a carrier elevating means for moving at least one carrier
15 means vertically between a first transport means and a second transport means;

at least one carrier means for releasably engaging at least one transport means and holding at least one said tote;

a first transport means comprising:

20 a first conveyor means for moving at least one said carrier means in a substantially horizontal direction comprising an overhead endless conveyor;

at least one branch conveyor means for transporting at least one said carrier means between said first
25 conveyor means and a position adjacent to said tote elevating means; and

at least one branch conveyor means for transporting at least one said carrier means between said first

This Sheet Has Been Replaced





conveyor means and said carrier elevating means;

at least one tote transfer means for moving at least one said tote between said tote elevating means and said first transport means;

5 a second transport means comprising:

a second conveyor means for moving at least one said carrier means in a substantially horizontal direction; and

at least one branch conveyor means for transporting at least one said carrier means between said second

10 conveyor means and said carrier elevating means;

unloading means for discharging at least one said tote from a carrier means to a discharge station; and

controlling means for directing the movement of said totes and said carrier means about said conveyor system.

This Sheet Has Been Replaced

