

A CLAMPING DEVICE FOR CLAMPING OF TUBES OR THE LIKE

The invention relates to a clamp device for clamping  
5 one or more tubes or the like to a support, comprising a base  
member having at least one outwardly open, at least partly  
cylindrical recess for receiving a tube or the like, possibly a  
top plate for abutment against the base member at the side facing  
away from the support, and at least one fastening element in the  
10 form of a locking screw carried through mutually aligned holes  
in the possible top plate and the base member, and which is of  
the type which, by means of a head at one end and a nut at the  
other end, keeps the components of the clamp device together as  
a completely preassembled ready-to-mount unit without any loose  
15 parts, the head of the screw being located at the end to be  
fastened to the support and being arranged to be carried through  
a hole or groove in the support adapted to the head, and to be  
locked thereto by tightening of the nut.

A clamp device of the above-mentioned type is known  
20 from Norwegian Patent No. 174 402. Such a clamp device has a  
number of advantages in relation to conventional clamp devices  
consisting of several loose parts and therefore being relatively  
time-consuming to mount or dismount. Thus, advantages are  
achieved both with respect to manufacture, storage maintenance,  
25 ordering of parts, mounting/dismounting time and total cost. The  
clamp can be delivered to the user completely assembled with all  
parts, ready for use and consisting of only one unit, without any  
loose parts of any kind. None of the component parts are to be  
separated from the clamp device before mounting, and neither in  
30 case of dismounting. Thus, the clamp is in the same condition  
also after dismounting, and may be used once more.

In the known clamp device of this type the base member  
consists of a single part, and its outwardly open recess is  
formed at its opening with a constricted portion to grip and  
35 retain a tube which is introduced laterally and pressed in place  
in the recess. This entails that the base member exerts a limited  
clamping action on the introduced tube. Therefore, clamps of this  
type are best suited for clamping of quite small tubes where  
there is not required a high strength in the connection.

The object of the invention therefore is to provide a clamp device which is also suited for clamping of tubes of larger dimensions, an efficient clamping of the tube or tubes being obtained when the clamp device is mounted, at the same time as the above-mentioned advantages of this type of clamp device is retained.

The above-mentioned object is achieved with a clamp device of the introductorily stated type which, according to the invention, is characterized in that the base member consists of  
10 to halves of which at least one half has at least one recess for receiving the topical tube or tubes in a clamping manner between the halves when these are pressed against each other, and that the hole or holes through the halves is/are formed with a radial enlargement along at least a part of its length, so that the head  
15 of the associated locking screw can pass at least partly into the half nearest to the support or through this half and partly into the other half, to allow a limited relative movement of the halves and allow a lateral introduction of a tube into the recesses.

20 The clamp device can be used in the clamping of tubes, cables or the like, singly or several next to each other.

In an advantageous embodiment of the clamp device, the base halves are provided with at least one pair of mutually facing, cooperating recesses for the receipt of the respective  
25 tube. In such an embodiment it is also advantageous that at least one of the two cooperating recesses has a constriction portion at its opening, for gripping and retention of a tube introduced into the recess. The desired number of clamp devices then can be snapped onto the tube, so that the tube with applied clamps can  
30 be transported as a unit to the place of mounting. The property that the clamp can be premounted on the tube, in many cases will have great installation advantages.

The invention will be further described below in connection with a number of exemplary embodiments with reference  
35 to the drawings, wherein

Fig. 1 shows a front view of a first embodiment of a clamp device according to the invention;

Fig. 2 shows a side view of the embodiment in Fig. 1;

Fig. 3 shows the embodiment in Fig. 1 prepared for

introduction of a tube which is to be clamped;

Fig. 4 shows a view corresponding to Fig. 3 of an embodiment wherein the top plate is formed as a bow or strap;

Fig. 5 shows a front view of a second embodiment of the  
5 clamp device;

Fig. 6 shows a front view of a third embodiment of the clamp device;

Fig. 7 shows the embodiment in Fig. 6 prepared for introduction of a tube which is to be clamped;

10 Fig. 8 shows a front view of a fourth embodiment of the clamp device;

Fig. 9 shows a view viewed from below of the lower base half in Fig. 8;

Fig. 10 shows a view corresponding to Fig. 9, but of an  
15 alternative embodiment;

Fig. 11 shows a front view of a fifth embodiment of the clamp device;

Fig. 12 shows a front view of an embodiment of the clamp device generally corresponding to Fig. 1, but of an embodi-  
20 ment wherein both recesses grip about the tube;

Fig. 13 shows a side view of the embodiment in Fig. 12 wherein the halves are moved together;

Fig. 14 shows a front view of a sixth embodiment of the clamp device;

25 Fig. 15 shows a plan view of a top plate, as it is formed in the embodiment according to Figs. 1-3 and 6-8;

Fig. 16 shows an embodiment of a separate top plate for building-on of an additional clamp; and

30 Figs. 17 and 18 show a side view and a front view, respectively, of a clamp device having a separate top plate and a built-on additional clamp device thereon.

Corresponding or similar members have been designated by the same reference numerals in the different drawing figures.

35 The embodiment of the clamp device according to the invention shown in Figs. 1-3, comprises a base member 1 consisting of a pair of halves 2, 3 which are provided with a respective one of two mutually facing, cooperating recesses 4, 5 for the receipt of a suitably dimensioned tube or pipe 6. The recesses 4, 5 are partly cylindrical, with an axis which is parallel to the axis

of a tube placed in the recesses. Further, the recesses are formed in such a manner in relation to the tube that this is received in a clamping manner when the base halves 2, 3 are pressed against each other. In the shown embodiment the recesses  
5 have a part-circular contour having the same radius of curvature, as viewed in a cross-section perpendicular to the longitudinal axis of the recesses (and the tube). The cross-sectional contour of the lower recess 5 is somewhat larger than a semi-circle, so that the recess at its opening has opposite constriction portions  
10 7 (see Fig. 3), so that the recess at its opening is narrower than the outer diameter of the tube and thereby grips and retains a tube which is introduced laterally and pressed in place in the recess. To enable introduction of the tube 6 into the recess 5, the base halves in the embodiment shown in Fig. 1-3, and also in  
15 remaining partly corresponding embodiments, are made of a suitable elastic material, such as a suitable plastics. It is clear, however, that with an appropriate dimensional adaptation also the base half having a recess with a constricted opening portion possibly may be of metallic material.

20 The upper recess 4 is shown to have a cross-sectional contour which is somewhat smaller than a semi-circle and is so adapted relative to the other recess that the base halves clamp the tube placed in the recess when they are pressed against each other without their opposite surfaces coming quite into contact  
25 with one another, as appears from Fig. 1.

As will be understood, the recesses may be formed in many different ways with respect to cross-sectional shape. For example, both recesses partly may be formed such that they grip about and retain a positioned tube, as shown in Fig. 12. As  
30 another alternative, both recesses may be formed with a cross-sectional contour which is less than a semi-circle, so that the tube is clamped by the base halves pressed against each other, with a greater distance between the halves than what is shown in Fig. 1. In this case then, none of the recesses are formed to  
35 retain on its own a tube placed therein.

The base halves 2, 3 are fastened to a foundation or support 7 by means of two fixing screws 8, 9 carried through respective mutually aligned holes 10, 11 and 12, 13 extending through the base halves on either side of the recesses 4, 5,

substantially at right angles to the longitudinal axis thereof. A top plate 14 is placed on the upper side of the upper base half 2, and the fixing screws 8, 9 are also carried through respective holes 15, 16 in the top plate, these holes being aligned with the  
5   respective holes 10, 11 and 12, 13 in the base halves 2, 3. The top plate is made of a metallic material which is to ensure the tube or tubes against falling out in a possible fire at the place of use in case the base halves of the clamp are of a combustible material.

10           It is to be remarked that even if the embodiments of the clamp device shown in the drawings are based on the use of a separate top plate, the clamp device may also be without such a top plate, especially in cases wherein a top plate (of metal) is not required to be used for security reasons, e.g. in case of  
15   a fire. As will be clear, a top plate will also be unnecessary in embodiments wherein the base halves, or at least the upper base half, consist of a non-combustible material, for example a metal. It will also be clear that in the embodiment wherein the upper base half is not provided with a recess (see Fig. 14), and  
20   especially where it is made of metal or another non-combustible material, the top plate will be superfluous.

The fixing screws of the clamp device are constituted by head screws keeping the components or constituent parts of the clamp together as a preassembled and ready-to-mount unit without  
25   any loose parts. For this purpose the screws, at the end which is to be fixed to the support, have a head which can be carried through an adapted hole or groove in the support, and be locked against the support by tightening of a locking nut threaded onto a thread at the other end of the screw.

30           In the shown embodiment the fixing screws 8, 9 are locking screws of a known and commercially available type designated T-screws. As shown in Figs. 1-3, these screws have a T-shaped head 17 and 18, respectively, which can be carried through an adapted oblong hole 19 and 20, respectively, in the  
35   support 7, and which under the head has a pair of stop lugs (not shown) where one lug, with 90° rotation of the screw, locks this screw against continued rotation in the hole with tightening of the screw's associated nut 21 and 22, respectively, which is of the locking-nut type and consequently sits sluggishly on the

screw thread, to ensure rotation of the screw to the locking position and loosening position, respectively, of the head. (The other lug prevents rotation of the screw when loosening the nut in question.) The holes in the support may have the same shape  
5 as the holes shown in the separate top plate in Fig. 16 to be described later.

As an alternative to the above-mentioned T-screws, the fixing screws may be locking screws having a head which can be carried through a keyhole-shaped hole in the support, and having  
10 a shoulder formed under the head, usually with a rectangular cross-section, and which, when introduced into the narrow portion of the "keyhole", locks the screw against rotation, so that its nut can be tightened. (This embodiment is not shown in the drawings).

15 It will be clear that the length of the locking screw in practice will be adapted to the thickness of the topical support, so that the desired locking is achieved immediately when the locking screws of the clamp device are moved in place in the intended holes in the support and the locking nuts are tightened  
20 with a suitable spanner.

In order to be able to carry out a lateral introduction of a tube into a clamp device according to the invention, or to be able to remove a mounted clamp device from a tube, the base halves must be able to be moved sufficiently far away from each  
25 other to allow such an introduction or removal, at the same time as a possible preventing locking screw must be able to be pulled away from the introduction or dismounting opening, and at the same time as the components of the clamp device all the time are to be kept together as a unit without any loose parts. To be able  
30 to carry out these operations, the hole or holes through the base halves is/are formed with a radial extension or enlargement along at least a part of its length, so that the head of the associated locking screw can pass at least partly into the half nearest to the support or through this half and partly into the other half.  
35 In this manner one obtains the necessary "freeing movement" of the locking screws, in order to allow a limited relative movement of the halves, and to allow a lateral introduction of a tube or the like into the recesses.

The embodiments shown in the drawings, wherein the

locking screws 8, 9 are so-called T-screws with laterally projecting head portions 23, the above-mentioned radial extension or enlargement consists of diametrically opposite, axially extending spaces 24 to make room and passage for the projecting head portions 23. This embodiment with a radial enlargement of the screw holes in the form of axially extending spaces 24 is also shown in Fig. 9.

In the embodiment according to Figs. 1-3, the two base halves 2, 3 are connected to each other in a hinge portion 25 located at one side edge of the halves and having a hinge axis which is parallel to the longitudinal axis of the recesses 4, 5. Further, the holes for the locking screws 8, 9 are shaped such that the radial enlargement 24 of each of the two pairs 10, 11 and 12, 13 of aligned holes in the halves 2, 3 extends through the half 3 nearest to the support 7 and a limited distance into the other half 2, as best shown in Fig. 2. Thus, the head of the locking screw can pass freely through the holes in the base half 3, the hinge portion keeping the base halves together.

When a tube which is to be clamped, is to be inserted into the clamp device according to Figs. 1-3, the top plate 14 together with the locking screws 8, 9 are lifted up to the position shown in Fig. 3. Thereafter the upper half 2 is turned about the hinge 25, so that a free opening for lateral introduction of the tube 6 is provided. When the tube is located over the recess 5, the base half 3 is pressed in place on the tube. Thereafter the upper base half 2 is pivoted down onto the tube, and the locking screws 8, 9 are carried through the holes in the lower half 3 and the holes in the support at the same time as the top plate 14 is moved down onto the upper base half. Thereafter the nuts 21, 22 can be tightened, so that the clamp device is locked to the support.

When the base halves are made of a plastic material, it may be of interest to have a steel bow or strap around the clamp to prevent the installed tube or tubes from falling out in a possible fire at the place of use. Fig. 4 shows a front view of such an embodiment which is provided with a strap 26 which simultaneously constitutes the top plate of the clamp. In other respects the embodiment corresponds to the embodiment according to Figs. 1-3. Such a strap embodiment or a similar embodiment may

be used in all the illustrated clamp embodiments.

Fig. 5 shows a second embodiment of the clamp device comprising a single locking screw 28 extending through respective aligned holes 29, 30, 31 in the top plate 32 and the base halves 33, 34 at one side of the recesses 4, 5. The base halves 33, 34 are hinged to one another at a hinge portion 35 in a corresponding manner as in the embodiment according to Figs. 1-3. The radial enlargement of the pair of aligned holes 30, 31 in the base halves 33, 34 extends through the entire half 34 nearest to the support 7 and a limited distance into the other half 33. Consequently, the clamp device can be opened for tube introduction in a similar manner as described above in connection with Fig. 3.

Figs. 6 and 7 show a third embodiment of the clamp device resembling the embodiment according to Figs. 1-3, the embodiment comprising two base halves 36, 37 which are hinged to one another at a hinge portion 38, and two locking screws 8, 9 extending through respective aligned holes 15, 39, 40 and 16, 41, 42, respectively, in the top plate 14 and the base halves on either side of the recesses 43, 44. Whereas the embodiments according to Figs. 1-3 and Fig. 5 in principle can have more than one pair of cooperating recesses 4, 5 to receive one or more tubes, cables or the like, each base half in the embodiment in Fig. 6 has a single recess 43 and 44, respectively, each recess also having a laterally debouching portion 45 and 46, respectively, on the side of the half located opposite to the hinge portion 38, so that there is formed a lateral introduction opening for a tube (not shown). The pair of aligned holes 39, 40 at the laterally debouching portions 45, 46 has a radial enlargement (24 in Fig. 2) extending through the entire half 37 nearest to the support 7 and a limited distance into the other half 36, whereas the other pair of aligned holes 41, 42 is without such a radial enlargement.

As shown in Fig. 6, in this embodiment it is only necessary to lift up one locking screw 8 to make room for introduction of the tube which is to be clamped, there being no need for a larger movement in the hinge 38 than what is allowed by the clearance between the locking screw 9 and the holes 41, 42 through the base halves 36, 37. Thus, this embodiment of the

clamp device can be fastened with the one screw 9 to the support 7 before the tube is moved in place in the recesses. This may often be a great installation advantage.

Fig. 8 shows a fourth embodiment of the clamp device according to the invention. The embodiment comprises a pair of separate base halves 47, 48, i.e. which are not connected to one another in a hinge portion, and a pair of locking screws 8, 9 extending through respective aligned holes 15, 49, 50 and 16, 51, 52, respectively, in the top plate 14 and the base halves on either side of the recesses 4, 5. The radial enlargement (24 in Fig. 2) of one pair of aligned holes 49, 50 extends through the entire base half 48 nearest to the support 7 (Fig. 1) and a limited distance into the other half 47, whereas the radial enlargement of the second pair of aligned holes 51, 52 extends only a chosen distance into the half 48 nearest to the support.

Fig. 9 shows a plan view of the lower base half 48 in Fig. 8, to visualize the radial enlargements 24 which are shown to consist of diametrically opposite, axially extending grooves for receiving the projecting portions 23 (Fig. 1) of the heads 17, 18 of the locking screws 8, 9.

Fig. 10 shows a bottom view corresponding to that of Fig. 9, but of an alternative embodiment wherein the radial enlargements of the holes through the base half in question consist of circularly cylindrical enlargements, i.e. enlarged or extended holes 54 and 55, respectively, with a sufficiently large diameter to accommodate the heads 17, 18 of the locking screws with a certain play or clearance. This embodiment of the radial enlargements may be advantageous as it does not require any orientating turning of the locking screws in dismounting of a clamp device, for positioning of the projecting portions of the screw heads in alignment with the axial grooves, as in the embodiments described above. However, this embodiment requires somewhat larger base halves, to accommodate the extended, larger holes.

Fig. 11 shows a fifth embodiment of the clamp device wherein the base halves 56, 57 are separate parts as in Fig. 8, but where the device comprises a single locking screw 28, as in Fig. 5. The radial enlargement (24 in Figs. 2 and 9) of the pair of aligned holes 58, 59 here extends only a chosen distance into

the base half 57 nearest to the support 7 (Fig. 5), so that the halves can be moved sufficiently far from one another to allow introduction of a tube into the recesses 4, 5.

In the exemplary embodiments according to Figs. 1, 5, 8 and 11 the recess in one of the base halves is shaped to "grip around" the topical tube which is to be clamped. Also in the embodiment according to Fig. 6 the recesses are shaped so that they together grip around the tube which is to be clamped, so that the clamps can be clipped onto a tube before final mounting to a support.

Figs. 12 and 13 show a front view and a side view, respectively, of an alternative embodiment having a pair of hinged base members 60, 61 wherein both recesses 62, 63 in the base halves are shaped so that they partly grip about the tube to be clamped, each recess along a part of its length having a cross-sectional contour which is somewhat larger than a semi-circle, like the recess 5 in the previous embodiments. As appears from Fig. 13, each recess has a stepped portion 64, 65 along half of its length, to make room for the tube-gripping portion of the other recess when the base halves are moved together.

Fig. 14 shows a front view of a sixth embodiment of the clamp device wherein the base halves 66, 67 of the device are provided with two pairs for cooperating recesses 4, 5 for clamping of two tubes. The base halves are hinged to each other in a hinge portion 68, and the top plate 69 is shaped as a U-formed bow or strap, in a manner corresponding to that of the embodiment in Fig. 4. The clamp device has a single locking screw 70 extending through aligned holes 71, 72 in the base halves between the two pairs of recesses. The radial enlargement (24 in Fig. 2) of the holes is arranged in the same manner as in the embodiment according to Fig. 1 or Fig. 5.

In the embodiment in Fig. 14, the recesses 4 in the base half 66 are shown to be relatively small or shallow. As suggested with stippled lines at the mouths of the recesses, these recesses possibly may be completely omitted, as also mentioned above. Such an embodiment, wherein only one or the lower base half is provided with one or more recesses, will be suitable for clamping of tubes with different dimensions, as suitable, part-cylindrical bushings or linings can be inserted

into the recesses, for receiving corresponding tubes having smaller dimensions than that which is suitable for the recess 5 in the base half 67.

Fig. 15 shows a plan view of the top plate 14 used in the embodiments according to Figs. 1, 6, 8 and 12. This top plate may be provided with a portion which projects outside the base member of a clamp device, and which is provided with at least one hole or groove which is adapted for introduction and locking of an associated locking screw in an additional, corresponding clamp device.

Instead of a top plate having an integral, projecting portion, as mentioned above, it may be expedient to use a separate top plate or build-on plate when it is of interest to build an additional clamp on top of an already mounted clamp device. An embodiment of such a separate top plate is shown in Fig. 16. This top plate 73 is adapted to be introduced under the top plate 14 of the clamp device parallel with the recess axis, as shown in Fig. 17. The top plate has a pair of outwardly open cutouts or slots 74 for receiving a correspondingly located locking screw (8 and 9 in Fig. 1), and further it has a portion 75 which in mounted position projects outside the base members and which is provided with a pair of holes or grooves 76 for introduction and locking of a respective locking screw in an additional, corresponding clamp device. As shown, the plate 73 is provided with downwardly projecting side flanges 77 for abutment against the side surfaces of an underlying clamp device. Further, the plate at one end has an upwardly projecting flange 78 for guiding abutment against the top plate 14 on the already mounted clamp device, and at the other end has an upwardly projecting flange 79 for abutment against a front edge of the added clamp.

Figs. 17 and 18 show a side view and a front view, respectively, of a clamp device 80 which is mounted on a support 7, and an additional, corresponding clamp device 81 which is built-on onto the first one by means of the separate top plate 73. When mounting the additional clamp device 81, the nuts of the locking screws are first loosened on the already mounted clamp device 80 so much that the adapted end of the separate top plate can be inserted under the assembled top plate 14, the locking

screws being inserted in the slots 74, whereafter the nuts can be tightened again.

It will be clear that separate top plates for building-on of additional clamp devices can be shaped in many different ways, dependent on the intended purpose, for example also for building-on of clamp devices having only one locking screw, e.g. according to the embodiment in Fig. 5. Such separate top plates may also have side flanges projecting quite down to the support, in a manner corresponding to that of the strap-formed plate 26 in Fig. 4. As another alternative in connection with clamp devices having only one locking screw, the separate plate may be shaped as a bracket having a U-formed cross-section, wherein the legs of the U form upper and lower horizontal flanges which are adapted for introduction respectively above and below the already mounted clamp device. With tightening of the nut of the locking screw, the lower flange is clamped between the support and the clamp, and the upper flange is clamped by the top plate of the clamp.

As regards the support for mounting of the clamps according to the invention, this may have a standardized perforation pattern for receiving the topical type of locking screws. It may also be practical to make use of prefabricated brackets with adapted holes, either for welding to a steel support or for screw attachment, or standard elements, such as cableways, cable ladders and profiles/rails having grooves suitable for the screw heads of the clamp device. Such elements are cut to desired lengths on the place of mounting.



THIS SHEET HAS BEEN  
REPLACED

P a t e n t   c l a i m s

5            1. A clamp device for clamping one or more tubes or the like to a support, comprising

          a base member (1) having at least one outwardly open, at least partly cylindrical recess (4, 5) for receiving a tube (6) or the like,

10           possibly a top plate (14) for abutment against the base member (1) at the side facing away from the support (7), and

          at least one fastening element in the form of a locking screw (8 resp. 9) carried through mutually aligned holes (15, 10, 11 resp. 16, 12, 13) in the possible top plate (14) and the base  
15 member (1), and which is of the type which, by means of a head (17 resp. 18) at one end and a nut (21 resp. 22) at the other end, keeps the components of the clamp device together as a completely preassembled ready-to-mount unit without any loose parts,

20           the head (17 resp. 18) of the screw being located at the end to be fastened to the support (7) and being arranged to be carried through a hole (19 resp. 20) or groove in the support (7) adapted to the head, and to be locked thereto by tightening of the nut (21 resp. 22),

25 CHARACTERIZED IN

          that the base member (1) consists of two halves (2, 3) of which at least one half (3) has at least one recess (5) for receiving the topical tube or tubes (6) in a clamping manner between the halves (2, 3) when these are pressed against each  
30 other, and

          that the hole or holes (10, 11, 12, 13) through the halves (2, 3) is/are formed with a radial enlargement (24) along at least a part of its length, so that the head (17 resp. 18) of the associated locking screw (8 resp. 9) can pass at least partly  
35 into the half (3) nearest to the support (7) or through this half and partly into the other half (2), to allow a limited relative movement of the halves and allow a lateral introduction of a tube (6) into the recesses (4, 5).

2. A clamp device according to claim 1, CHARACTERIZED





IN that the base halves (2, 3) are provided with at least one pair of mutually facing, cooperating recesses (4, 5) for the receipt of the respective tube (6).

3. A clamp device according to claim 2, **CHARACTERIZED** IN that at least one (5) of two cooperating recesses (4, 5) at its opening has a constriction portion (7) for gripping and retention of a tube (6) inserted into the recess.

4. A clamp device according to claim 1, 2 or 3, **CHARACTERIZED** IN that it comprises two locking screws (8, 9) extending through respective aligned holes (15, 10, 11 resp. 16, 12, 13) in the top plate (14) and the base halves (2, 3) on either side of the recesses (4, 5).

5. A clamp device according to claim 1, 2 or 3, **CHARACTERIZED** IN that it comprises a single locking screw (28) extending through respective aligned holes (29, 30, 31) in the top plate (32) and the base halves (33, 34) on one side of the recesses (4, 5).

6. A clamp device according to any of the preceding claims, **CHARACTERIZED** IN that the two halves (2, 3; 33, 34; 36, 37) of the base member are connected to each other at a hinge portion (25; 35; 38) located at one side edge of the halves and having a hinge axis which is essentially parallel with the longitudinal axis of the recesses (4, 5; 43, 44).

7. A clamp device according to claim 4, **CHARACTERIZED** IN that the radial enlargement (24) of one pair of aligned holes (49, 50) in the two halves (47, 48) extends through the entire half (48) nearest to the support (7) and a limited distance into the other half (47), whereas the radial enlargement (24) of the other pair of aligned holes (51, 52) extends only a chosen distance into the half (48) nearest to the support (7).

8. A clamp device according to claim 5, **CHARACTERIZED** IN that the radial enlargement (24) of the pair of aligned holes (58, 59) in the two halves (56, 57) extends a chosen distance into the half (57) nearest to the support (7).

9. A clamp device according to claim 4 and 6, **CHARACTERIZED** IN that the radial enlargement (24) of each of the two pairs of aligned holes (10, 11 resp. 12, 13) in the two halves (2, 3) extends through the entire half (3) nearest to the support (7) and a limited distance into the other half (2).





10. A clamp device according to claim 5 and 6, **CHARACTERIZED IN** that the radial enlargement (24) of the pair of aligned holes (30, 31) in the two halves (33, 34) extends through the entire half (34) nearest to the support (7) and a limited distance into the other half (33).

11. A clamp device according to claim 4 and 6, **CHARACTERIZED IN** that each half (36, 37) has a single recess (43 resp. 44), this recess also having a laterally debouching portion (45 resp. 46) on the side of the half located opposite to the hinge portion (38), so that a lateral introduction opening for a tube (6) is formed, the radial enlargement (24) of the pair of aligned holes (39, 40) at the laterally debouching portions (45, 46) extending through the entire half (37) nearest to the support (7) and a limited distance into the other half (38), whereas the other pair of aligned holes (41, 42) is without such a radial enlargement.

12. A clamp device according to any of the preceding claims, wherein the locking screws (8, 9) are so-called T-screws having laterally projecting head portions (23), **CHARACTERIZED IN** that the radial enlargement consists of diametrically opposite, axially extending spaces (24) to make room and passage for the projecting head portions (23).

13. A clamp device according to any of the preceding claims, **CHARACTERIZED IN** that the top plate is of metal and is shaped as a strap (26; 69) having legs which are adapted to project down to the support (7) along opposite side portions of the clamp halves (2, 3; 66, 67) on each side of a clamped tube (6).

14. A clamp device according to any of the preceding claims, **CHARACTERIZED IN** that it comprises a separate top plate (73) adapted to be inserted under the top plate (14) of the clamp device (80) parallel to the recess axis, the separate top plate (73) having at least one outwardly open cutout (74) for receiving a correspondingly located locking screw (8 resp. 9), and further has a portion (75) which, in the mounted position of the plate (73), projects outside the base member (1) and which is provided with at least one hole or groove (76) for introduction and locking of a respective locking screw on an additional corresponding clamp device (81).

