



(51) International Patent Classification:
F25B 31/02 (2006.01)

(21) International Application Number:
PCT/US2010/060010

(22) International Filing Date:
13 December 2010 (13.12.2010)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
61/292,764 6 January 2010 (06.01.2010) US

(71) Applicant (for all designated States except US): **CARRIER CORPORATION** [US/US]; One Carrier Place, P.O. Box 4015, Farmington, Connecticut 06034 (US).

(72) Inventor; and

(75) Inventor/Applicant (for US only): **FLANIGAN, Paul, J.** [US/US]; 8660 Backstretch Path, Cicero, New York 13039 (US).

(74) Agent: **SLATE, William, B.**; Bachman & LaPointe, P.C., 900 Chapel Street, Suite 1201, New Haven, Connecticut 06510 (US).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BR, BW, BY, BZ,

CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PE, PG, PH, PL, PT, RO, RS, RU, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report (Art. 21(3))

— before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments (Rule 48.2(h))

(88) Date of publication of the international search report:
15 December 2011

(54) Title: RECIPROCATING REFRIGERATION COMPRESSOR OIL SEPARATION




FIG. 1

(57) Abstract: A compressor (20) has a case (22) and a crankshaft (38). The case has a number of cylinders (30, 32). For each of the cylinders, the compressor includes a piston (34) mounted for reciprocal movement at least partially within the cylinder. A connecting rod (36) couples each piston to the crankshaft. An electric motor compartment (50) of the case has a stator (42) and a rotor (40). The rotor is mounted to the crankshaft. The case has a wall (56) between the motor compartment and a crankcase compartment/sump (52). The wall bears a feature (120, 132; 420; 460) for coalescing oil entrained in a refrigerant flow (522), which flow exits the gap (90) between the rotor and the stator to prevent the oil from entering the cylinders.

