

METHOD FOR USE IN DETERMINING THE MEASUREMENT FUNCTIONALITY OF A METER

FIELD

5 The present disclosure relates to a method for use in determining the measurement functionality of a meter for use with meters such as smart meters and, in particular though not exclusively, for use with meters for metering any utility, such as electricity, gas, water, sewage or the like. The present disclosure also relates to a model for defining the measurement functionality of a meter and a method for obtaining
10 measurement data from a meter.

BACKGROUND

 Modern electrical meters are capable of supporting 10s of thousands of distinct measurement types. Accurately characterizing and distinguishing each measurement
15 type is a task required of any metrology specification applied to modern meters. Existing metrology specifications such as IEC 61968-9, ANSI C12.19, or DLMS/COSEM each provide methods of specifying and distinguishing many different measurement types. However, some existing metrology specifications may only define a subset of all of the possible measurement types that are supportable by a meter. Meter manufacturers
20 require a method for fully characterizing the set of measurement types a meter supports. Meter manufacturers would also benefit from mapping equivalent measurement types across multiple meter specifications. The number of meter specifications, the complexity of the domain, and the difference in the data structures used by each specification (ANSI's tables, DLMS/COSEM's classes and OBIS codes and IEC CIM's 18 Attribute
25 Reading Type Codes) make it difficult to create and maintain direct mappings across all such meter specifications.

SUMMARY

 According to an aspect of the present disclosure there is provided a method for
30 use in determining the measurement functionality of a meter, wherein the meter is configured for measuring raw data at one or more measurement locations around a system, wherein the measurement functionality of the meter defines the characteristics of measurement data which is derivable from the raw data, and wherein the method comprises:

identifying a set of different measurement points supported by the meter, each measurement point defining the one or more measurement locations, and identifying or defining, for each measurement point, a corresponding name and a corresponding value for each of one or more attributes of a code of a metrology specification;

5 identifying a set of different units of measure supported by the meter, each unit of measure defining the unit of measure for the measurement data, and identifying or defining, for each unit of measure, a corresponding name and a corresponding value for each of one or more attributes of a code of the metrology specification;

10 identifying a set of different data types supported by the meter, each data type defining a transformation for generating the measurement data from the raw data, and identifying or defining, for each data type, a corresponding name and a corresponding value for each of one or more attributes of a code of the metrology specification;

determining different combinations of measurement point, unit of measure, and data type selected from the set of different measurement points, the set of different units of measure, and the set of different data types respectively; and

15 determining, for each combination of measurement point, unit of measure, and data type, a corresponding measurement type, and a corresponding code of the metrology specification, wherein the corresponding measurement type comprises the corresponding measurement point, the corresponding unit of measure, the corresponding data type, and a corresponding measurement type name composed from the name associated with the corresponding measurement point, the name associated with the corresponding unit of measure, and the name associated with the corresponding data type, and wherein the corresponding code of the metrology specification is composed from the values of the code attributes associated with the corresponding measurement point, the corresponding unit of measure, and the corresponding data type.

20 Such a method may allow the functionality of a meter to be defined in terms of the different measurement types supportable by the meter and to be mapped to a metrology specification. Such a method may allow the functionality of any meter, for example a meter of arbitrary complexity, to be fully specified.

Optionally, the metrology specification is the IEC 61968-9 metrology specification and the code of the metrology specification is a reading type code defined according to the IEC 61968-9 metrology specification.

35 Optionally, the metrology specification is the ANSI C12.19 metrology specification and the code of the metrology specification is a code defined according to a relational table structure of the ANSI C12.19 metrology specification.

Optionally, the metrology specification is the COSEM metrology specification and the code of the metrology specification is a class and/or a parameter defined according to the COSEM metrology specification.

5 Such a method may allow the functionality of a meter to be defined in terms of reading type codes of the IEC 61968-9 metrology specification, to be defined in terms of codes defined according to a relational table structure of the ANSI C12.19 metrology specification, or to be defined in terms of a class and/or a parameter defined according to the COSEM metrology specification.

10 Optionally, determining the different combinations of measurement point, unit of measure, and data type comprises:

defining a set of different measurement point groups, each measurement point group including a different selection of one or more of the measurement points of the set of different measurement points;

15 associating each unit of measure of the set of different units of measure with a corresponding unit of measure class;

associating each data type of the set of different data types with a corresponding data type class;

20 defining a set of different class/group combinations, each different class/group combination comprising a different combination of measurement point group, unit of measure class, and data type class; and

determining, for each class/group combination of the set of different class/group combinations, all possible combinations of: i) the measurement points associated with the class/group combination; ii) the units of measure associated with the class/group combination; and iii) the data types associated with the class/group combination.

25 Optionally, the transformation defines an initial aggregation operation and one or more functions, wherein the initial aggregation operation is performed on the raw data to form base data, and wherein the one or more functions operate on the base data to generate the measurement data.

30 Optionally, the meter is configured to perform the initial aggregation operation on the raw data, for example by signal processing of the raw data.

Optionally, the initial aggregation operation comprises averaging the raw data over an aggregation time interval.

Optionally, the initial aggregation operation comprises integrating the raw data over an aggregation time interval.

Optionally, the initial aggregation operation comprises selecting an instantaneous raw data value, for example an instantaneous raw data value at the end of an aggregation time interval.

5 Optionally, the initial aggregation operation comprises determining a count of events derived from the raw data over an aggregation time interval.

Optionally, the raw data comprises raw time-series data.

Optionally, the base data comprises base time-series data.

Optionally, the measurement data comprises measurement time-series data.

10 Optionally, the raw time-series data comprises one or more arrays of raw time-value pairs.

Optionally, the base time-series data comprises one or more arrays of base time-value pairs.

Optionally, the measurement time-series data comprises one or more arrays of measurement time-value pairs.

15 Optionally, each of the one or more functions which operate on the base data to generate the measurement data comprises a time-series function.

Optionally, the method comprises:

identifying or defining, for each measurement point, a corresponding value for each of one or more attributes of a further code of the further metrology specification;

20 identifying or defining, for each unit of measure, a corresponding value for each of one or more attributes of a further code of the further metrology specification;

identifying or defining, for each data type, a corresponding value for each of one or more attributes of a further code of the further metrology specification; and

25 determining, for each combination of measurement point, unit of measure, and data type, the corresponding further code of the further metrology specification composed from the values of the further code attributes associated with the corresponding measurement point, the corresponding unit of measure, and the corresponding data type.

30 Optionally, the further metrology specification is the IEC 61968-9 metrology specification and the further code of the further metrology specification is a reading type code defined according to the IEC 61968-9 metrology specification.

Optionally, the further metrology specification is the ANSI C12.19 metrology specification and the further code of the further metrology specification is a code defined according to a relational table structure of the ANSI C12.19 metrology specification.

Optionally, the further metrology specification is the COSEM metrology specification and the further code of the further metrology specification is a class and/or a parameter defined according to the COSEM metrology specification.

Such a method may allow the functionality of a meter to be defined in terms of the different measurement types supportable by the meter and to be mapped to the metrology specification and to the further metrology specification.

Such a method may allow mapping between the codes of the metrology specification and the further codes of the further metrology specification. In other words, such a method may allow mapping of equivalent measurement types across multiple metrology specifications. This may be particularly beneficial for meter manufacturers.

According to an aspect of the present disclosure there is provided a method for use in identifying inter-operability between head end equipment and a meter, wherein the head end equipment has a known functionality defined as a plurality of codes of a given metrology specification, and wherein the method comprises:

using the method for use in determining the measurement functionality of a meter as claimed in any preceding claim to determine the codes associated with the measurement functionality of the meter for the same given metrology specification;

comparing the plurality of codes of the head end equipment with the determined codes associated with the functionality of the meter; and

determining whether the head end equipment and the meter are inter-operable based on the results of the comparison.

According to an aspect of the present disclosure there is provided a method for obtaining measurement data from raw data measured by a meter, the method comprising:

the method for use in determining the measurement functionality of a meter as described above;

receiving a request for measurement data of a desired measurement type name and/or of a desired code of a metrology specification;

determining whether the desired measurement type is supported by the meter by comparing the desired measurement type name with each determined measurement type name of the determined plurality of measurement type names and/or by comparing the desired metrology specification code with each determined metrology specification code of the determined plurality of metrology specification codes; and

responsive to determining that the desired measurement type name matches one of the determined measurement type names and/or that the desired metrology specification code matches one of the determined metrology specification codes,

deriving the measurement data from the raw data according to the transformation defined by the data type which corresponds to the determined measurement type name and/or according to the transformation defined by the data type which corresponds to the determined metrology specification code which matches the desired metrology specification code.

Optionally, deriving the measurement data from raw data measured by the meter according to the transformation comprises performing an initial aggregation operation on the raw data to form base data and applying one or more functions to the base data to generate the measurement data, wherein the one or more functions are defined according to the transformation.

Optionally, the meter is configured to perform the initial aggregation operation on the raw data, for example by signal processing of the raw data.

Optionally, the method comprises:

performing, at the meter, the initial aggregation operation on the raw data measured by the meter to determine, at the meter, the base data;

using the one or more functions to derive, at the meter, the requested measurement data from the base data; and

transmitting the derived measurement data from the meter to head end equipment located remotely from the meter.

Optionally, the method comprises:

performing, at the meter, the initial aggregation operation on the raw data measured by the meter to determine the base data;

transmitting the base data from the meter to head end equipment located remotely from the meter; and

using the one or more functions to derive, at the head end equipment, the requested measurement data from the base data.

According to an aspect of the present disclosure there is provided a model for defining the measurement functionality of a meter, wherein the meter is configured for measuring raw data at one or more measurement locations around a system, wherein the model defines the characteristics of measurement data which is derivable from the raw data, and wherein the model comprises a plurality of different measurement type data objects, wherein each measurement type data object comprises:

a corresponding measurement point;

a corresponding unit of measure;

a corresponding data type; and

a corresponding measurement type name composed from a name associated with the corresponding measurement point, a name associated with the corresponding unit of measure, and a name associated with the corresponding data type,

5 wherein the corresponding measurement point defines the corresponding measurement location, the corresponding unit of measure defines the unit of measure for the corresponding measurement data, and the corresponding data type defines a corresponding transformation for generating the corresponding measurement data from the corresponding raw data.

10 Optionally, the meter is configured to meter, and possibly also control, the flow of electricity, gas, water or sewage.

According to an aspect of the present disclosure there is provided a method for use in defining a measurement type supported by a meter, wherein the meter is configured for measuring raw data at a measurement location of a system, wherein the measurement type defines the characteristics of measurement data which is derivable
15 from the raw data, and wherein the method comprises:

defining a measurement type comprising a measurement point, a unit of measure, a data type, and a measurement type name,

wherein the measurement point defines the measurement location,

20 wherein the unit of measure defines the unit of measure for the measurement data,

wherein the data type defines a transformation for generating the measurement data from the raw data, and

25 wherein the measurement type name is composed from a name associated with the measurement point, a name associated with the unit of measure, and a name associated with the data type.

Such a method may be used to define the data type of any measurement type supported by the meter unambiguously in terms of the transformation.

30 Optionally, the transformation defines an initial aggregation operation and one or more functions, wherein the initial aggregation operation is performed on the raw data to form base data, and wherein the one or more functions operate on the base data to generate the measurement data.

Optionally, the meter is configured to perform the initial aggregation operation on the raw data, for example by signal processing of the raw data.

35 Optionally, the initial aggregation operation comprises averaging the raw data over an aggregation time interval.

Optionally, the initial aggregation operation comprises integrating the raw data over an aggregation time interval.

Optionally, the initial aggregation operation comprises selecting an instantaneous raw data value, for example an instantaneous raw data value at the end of an aggregation time interval.

Optionally, the initial aggregation operation comprises determining a count of events derived from the raw data over an aggregation time interval.

Optionally, the raw data comprises raw time-series data, the base data comprises base time-series data, and the measurement data comprises measurement time-series data.

Optionally, the raw time-series data comprises one or more arrays of raw time-value pairs, the base time-series data comprises one or more arrays of base time-value pairs, and the measurement time-series data comprises one or more arrays of measurement time-value pairs.

Optionally, each of the one or more functions which operate on the base data to generate the measurement data comprises a time-series function. Time-series functions are mathematical operations performed on time-series data, which may comprise a list or an array of time-value pairs. In reality, electrical meters operate on data continuously. However, if a time-series function is applied to raw time-series data measured by the meter, the mathematical result would be the same. Thus, it should be understood that such a method treats the raw time-series data measured by the meter as a time-series object upon which the one or more time-series functions can be applied. Such a method enables the data type supported by the meter to be specified by identifying or specifying the initial aggregation operation performed by the meter to generate the base time-series data, and by specifying the one or more time-series functions performed upon the base time-series data to generate the measurement time-series data.

Optionally, the method comprises defining a code of a metrology specification corresponding to the measurement type wherein the code of the metrology specification is composed from values of code attributes associated with the measurement point, the unit of measure, and the data type.

Optionally, the metrology specification is the IEC 61968-9 metrology specification and the code of the metrology specification is a reading type code defined according to the IEC 61968-9 metrology specification.

Optionally, the metrology specification is the ANSI C12.19 metrology specification and the code of the metrology specification is a code defined according to a relational table structure of the ANSI C12.19 metrology specification.

Optionally, the metrology specification is the COSEM metrology specification and the code of the metrology specification is a class and/or a parameter defined according to the COSEM metrology specification.

According to an aspect of the present disclosure there is provided a method for
5 obtaining measurement data from raw data measured by a meter, the method comprising:

the method for use in defining a measurement type supported by a meter as described above;

receiving a request for measurement data of the measurement type name and/or
10 of a metrology specification code; and

deriving, in response to the request, the measurement data from the raw data according to the transformation defined by the data type corresponding to the measurement type name and/or corresponding to the metrology specification code.

Optionally, deriving the measurement data from the raw data comprises
15 performing an initial aggregation operation on the raw data to form base data and applying one or more functions to the base data to generate the measurement data, wherein the one or more functions are defined according to the transformation defined by the data type.

Optionally, the meter is configured to perform the initial aggregation operation on
20 the raw data, for example by signal processing of the raw data.

Optionally, the method comprises:

performing, at the meter, the initial aggregation operation on the raw data measured by the meter to determine, at the meter, the base data;

using the one or more functions to derive, at the meter, the measurement
25 data from the base data; and

transmitting the derived measurement data from the meter to head end equipment located remotely from the meter.

Optionally, the one or more functions are stored in a memory of the meter.

Optionally, the method comprises:

performing, at the meter, the initial aggregation operation on the raw data measured by the meter to determine, at the meter, the base data;

transmitting the base data from the meter to head end equipment located remotely from the meter; and

using the one or more functions to derive, at the head end equipment, the
35 measurement data from the base data.

Optionally, the one or more functions are stored in a memory of the head end equipment.

According to an aspect of the present disclosure there is provided a method for defining the measurement functionality of a meter, the method comprising defining a plurality of different measurement types supported by a meter, wherein each measurement type of the plurality of different measurement types is defined according to the method as described above.

According to an aspect of the present disclosure there is provided a measurement type data object for defining a measurement type supported by a meter, wherein the meter is configured for measuring raw data at a measurement location of a system, wherein the measurement type defines the characteristics of measurement data which is derivable from the raw data, and wherein the measurement type data object comprises:

- a measurement point;
- a unit of measure;
- a data type; and
- a measurement type name composed from a name associated with the measurement point, a name associated with the unit of measure, and a name associated with the data type,

wherein the measurement point defines the measurement location, the unit of measure defines the unit of measure for the measurement data, and the data type defines a transformation for generating the measurement data from the raw data.

Optionally, the meter is configured to meter, and optionally also to control, the flow of electricity, gas, water or sewage.

It should be understood that any one or more of the optional features of any one of the foregoing aspects of the present disclosure may be combined with any one or more of the optional features of any of the other foregoing aspects of the present disclosure.

BRIEF DESCRIPTION OF THE DRAWINGS

A method for use in determining the measurement functionality of a meter will now be described by way of non-limiting example only with reference to the drawings of which:

FIG. 1 is a schematic of a metering system;

FIG. 2 is a flow chart illustrating a method for use in determining the measurement functionality of a meter;

FIG. 3 is a flow chart illustrating the method for use in determining the measurement functionality of a meter of FIG. 2 in more detail;

FIG. 4A is a causal graph depicting a data type transformation which transforms base time-series data called "averageBase" to intermediate time-series data called "meanAggregateInterval" and the transformation of the intermediate time-series data "meanAggregateInterval" to the measurement time-series data called "maxAggregateMacroPeriod";

FIG. 4B is a plot of the base time-series data "averageBase" of FIG. 4A;

FIG. 4C is a plot of the intermediate time-series data "meanAggregateInterval" of FIG. 4A;

FIG. 4D is a plot of the measurement time-series data "maxAggregateMacroPeriod" of FIG. 4A;

FIG. 5 is a causal graph depicting a first alternative data type transformation;

FIG. 6 is a causal graph depicting a second alternative data type transformation;

FIG. 7 is a causal graph depicting a third alternative data type transformation;

FIG. 8 is a causal graph depicting a fourth alternative data type transformation;

FIG. 9A shows an example set of measurement points for an electricity meter and the corresponding value of the cimPhases attribute of the cim code of the IEC 61968-9 metrology specification;

FIG. 9B shows a plurality of different measurement point groups, each measurement point group including a different selection of one or more of the measurement points of the set of measurement points of FIG. 9A;

FIG. 10A shows a first part of an example set of units of measure for an electricity meter and the values of the corresponding cim code attributes of the IEC 61968-9 metrology specification;

5 FIG. 10B shows a second part of the example set of units of measure of FIG. 10A;

FIG. 11A shows a first part of an example set of data types for an electricity meter and the values of the corresponding cim code attributes of the IEC 61968-9 metrology specification;

10

FIG. 11B shows a second part of the example set of data types of FIG. 11A;

FIG. 12 shows a set of different class/group combinations of measurement point group (like those discussed with reference to FIG. 9B), unit of measure class (like those discussed with reference to FIGS. 10A and 10B), and data type class (like those discussed with reference to FIGS. 11A and 11B);

15

FIG. 13A is a screenshot of a first part of a Wolfram language environment during the execution of a Wolfram language script for the “maximumMacro” class/group combination of FIG. 12;

20

FIG. 13B is a screenshot of a second part of a Wolfram language environment during the execution of a Wolfram language script for the “maximumMacro” class/group combination of FIG. 12;

25

FIG. 13C is a screenshot of a third part of a Wolfram language environment during the execution of a Wolfram language script for the “maximumMacro” class/group combination of FIG. 12;

30 FIG. 13D is a screenshot of a fourth part of a Wolfram language environment during the execution of a Wolfram language script for the “maximumMacro” class/group combination of FIG. 12; and

FIG. 14 shows a selection of the measurement type names and cim codes corresponding to the “maximumMacro” class/group combination of FIG. 12.

35

DETAILED DESCRIPTION OF THE DRAWINGS

Referring initially to FIG. 1 there is shown a metering system generally designated 2 including a plurality of meters 4 and head end equipment generally designated 6. The plurality of meters 4 and the head end equipment 6 are configured to communicate across a network 8, which may be wired and/or wireless. In the specific example of the metering system 2 of FIG. 1, the metering system 2 may be configured to meter, and possibly also control, the flow of electricity. It should be understood that, in other embodiments, the metering system 2 may be configured to meter, and possibly also control, the flow of any utility, such as gas, water, sewage or the like. The meters 4 may be the same or different.

Referring to FIG. 2 there is shown a method generally designated 200 for use in determining the measurement functionality of any one of the meters 4, wherein the meter 4 is configured for measuring raw data at one or more measurement locations around a system and wherein the measurement functionality of the meter 4 defines the characteristics of measurement data which is derivable from the raw data. The method 200 includes:

identifying 202 a set of different measurement points supported by the meter 4, each measurement point defining the one or more measurement locations, and identifying or defining a corresponding name for each measurement point of the set of different measurement points;

identifying 204 a set of different units of measure supported by the meter 4, each unit of measure defining the unit of measure for the measurement data, and identifying or defining a corresponding name for each unit of measure of the set of different units of measure;

identifying 206 a set of different data types supported by the meter 4, each data type defining a transformation for generating the measurement data from the raw data, and identifying or defining a corresponding name for each data type of the set of different data types;

identifying 212, for each measurement point, a corresponding value of each of one or more attributes of a code of a metrology specification;

identifying 214, for each unit of measure, a corresponding value of each of one or more attributes of the code;

identifying 216, for each data type, a corresponding value of each of one or more attributes of the code; and

determining 208 different combinations of measurement point, unit of measure, and data type selected from the set of different measurement points, the set of different

units of measure, and the set of different data types respectively and determining, for each combination, a corresponding measurement type and a corresponding code of the metrology specification, wherein the measurement type comprises the corresponding measurement point, the corresponding unit of measure, the corresponding data type, and a corresponding measurement type name composed from the name associated with the corresponding measurement point, the name associated with the corresponding unit of measure, and the name associated with the corresponding data type, and wherein the corresponding code of the metrology specification is composed from the code attribute values associated with the corresponding measurement point, the corresponding unit of measure, and the corresponding data type.

As shown in more detail in FIG. 3, determining 208 the different combinations of measurement point, unit of measure, and data type comprises:

defining 208a a set of different measurement point groups, each measurement point group including a different selection of one or more of the measurement points of the set of different measurement points;

associating 208b each unit of measure of the set of different units of measure with a corresponding unit of measure class;

associating 208c each data type of the set of different data types with a corresponding data type class;

defining 208d a set of different class/group combinations, each different class/group combination comprising a different combination of measurement point group, unit of measure class, and data type class; and

determining 208e, for each class/group combination of the set of different class/group combinations, all possible combinations of: i) the measurement points associated with the class/group combination; ii) the units of measure associated with the class/group combination; and iii) the data types associated with the class/group combination and, determining, for each combination, a corresponding measurement type and a corresponding code of the metrology specification, wherein the measurement type comprises the corresponding measurement point, the corresponding unit of measure, the corresponding data type, and a corresponding measurement type name composed from the name associated with the corresponding measurement point, the name associated with the corresponding unit of measure, and the name associated with the corresponding data type, and wherein the corresponding code of the metrology specification is composed from the code attribute values associated with the corresponding measurement point, the corresponding unit of measure, and the corresponding data type.

The steps of the second method 200 will now be described in more detail below with reference to FIGS. 4A to 14 for the specific case of an electricity meter with reference to the reading type codes or cim codes of the IEC 61968-9 metrology specification.

FIG. 4A illustrates how the data type defines a transformation for generating the measurement data from the raw data. Each meter 4 performs initial signal processing on the raw data to generate base data. Specifically, the raw data measured by any one of the meters 4 comprises raw time-series data (i.e. an array of raw time-value pairs upon which time series functions can be applied) and each meter 4 performs initial signal processing on the raw time-series data to generate base time-series data. In general, the base data represents a first aggregation of the raw data. The interval used for aggregation of the raw data to generate the base data may differ across systems, so it is unspecified. There are several types of base data which are defined by the initial signal processing performed by the meter 4. The base data may represent an average of sampled values over the interval, the integral of sampled values over the interval, an instantaneous measurement (often the sample at the end of the interval), or a count of events over the interval. These different types of base data are treated independently because different time-series functions are applicable for each type.

The data type defines a time-series function, or a sequence of time-series functions, which is/are applied to the base time-series data to generate the measurement time-series data. For example, FIGS. 4A-4D illustrate the transformation defined by the data type from base time-series data comprising average values at one minute intervals. The base time-series data is first transformed to intermediate time-series data comprising average values averaged over 15-minute intervals, and then transformed to monthly maximum measurement time series data. More specifically, FIG. 4A is a causal graph which depicts the transformation of one minute average base time-series data called "averageBase" shown in FIG. 4B to fifteen minute average intermediate time-series data called "meanAggregateInterval" shown in FIG. 4C using a first time-series function "TimeSeriesAggregate[input, 15 min, Mean]" and the transformation of the intermediate time-series data "meanAggregateInterval" to the monthly maximum measurement time-series data called "maxAggregateMacroPeriod" shown in FIG. 4D using a second time-series function "TimeSeriesAggregate[input, Month, Max]". Thus, in order to specify the data types supported by a given meter 4, it is necessary to identify the base time-series data generated by the meter 4, and to specify the transformations performed upon the base time-series data. FIGS. 5, 6, 7 and 8 show four alternative causal graphs illustrating the associated transformations for average, integrated, instantaneous and count base time-series data respectively. It should be understood

that the causal graphs of FIGS. 4A, 5, 6, 7 and 8 are not exhaustive, but that they represent some of the most common data types supported by meters 4.

Referring now to FIG. 9A there is shown an example set of different measurement points for an electricity meter and the corresponding value of the cimPhases attribute of the cim code of the IEC 61968-9 metrology specification. It should be understood that the different measurement points in FIG. 9A are derived from the meter manufacturer's specification. However, neither the cim code attribute nor its value is specified in the meter manufacturer's specification. Consequently, the cim code attribute and its value are derived from the units of measure specified in the meter manufacturer's specification using engineering knowledge. It should also be understood that the different measurement points shown in FIG. 9A are not necessarily exhaustive. FIG. 9B shows a plurality of different measurement point groups, each measurement point group including a different selection of one or more of the measurement points of the set of different measurement points of FIG. 9A. It should be understood that each measurement point group is defined using engineering knowledge and represents a common group of measurement locations encountered for an electrical distribution system. It should also be understood that the different measurement point groups shown in FIG. 9B are not necessarily exhaustive.

Referring now to FIGS. 10A and 10B there is shown an example set of different units of measure for an electricity meter and the values of the corresponding cim code attributes of the IEC 61968-9 metrology specification. It should be understood that the different units of measure in FIGS. 10A and 10B are derived from the meter manufacturer's specification. However, neither the cim code attributes nor their values are specified in the meter manufacturer's specification. Consequently, the cim code attributes and their values are derived from the units of measure specified in the meter manufacturer's specification using engineering knowledge. It should also be understood that the different units of measure shown in FIGS. 10A and 10B are not exhaustive. It should also be understood that each unit of measure is assigned to a corresponding unit of measure class using engineering knowledge. For example, in FIGS. 10A and 10B, all of the units of measure are assigned to the unit of measure class "threePhaseEnergy". It should be understood that each unit of measure class is defined using engineering knowledge and that all of the units of measure relating to the same unit of measure class are closely related. It should also be understood that although all of the units of measure in FIGS. 10A and 10B are assigned to the unit of measure class "threePhaseEnergy", in reality, the example set of different units of measure may include many more units of measure than those shown in FIGS. 10A and 10B and that different units of measure

may be assigned to different unit of measure classes. In particular, units of measure may be assigned to unit of measure classes including "threePhaseEnergy", "threePhasePower", "calculatedNetEnergy", "demandTimestamp", "powerFactor" etc.

Referring now to FIGS. 11A and 11B there is shown an example set of different data types for an electricity meter and the values of the corresponding cim code attributes of the IEC 61968-9 metrology specification. It should be understood that the different data types in FIGS. 11A and 11B are derived from the meter manufacturer's specification. However, neither the cim code attributes nor their values are specified in the meter manufacturer's specification. Consequently, the cim code attributes and their values are derived from the data types specified in the meter manufacturer's specification using engineering knowledge. It should also be understood that the different data types shown in FIGS. 11A and 11B are not exhaustive. It should also be understood that each data type is assigned to a corresponding data type class using engineering knowledge. For example, in FIGS. 11A and 11B, the data types are assigned to different data type classes including "integratedMacro", "accumulatingMacro", "mme", "meanVA", "minimumMacro", "maximumMacro" and "meanMacro". It should be understood that each data type class is defined using engineering knowledge and that all of the data types relating to the same data type class are closely related.

Referring now to FIG. 12 there is shown a set of different class/group combinations of measurement point group (like those discussed with reference to FIG. 9B), unit of measure class (like those discussed with reference to FIGS. 10A and 10B), and data type class (like those discussed with reference to FIGS. 11A and 11B). It should be understood that the different class/group combinations shown in FIG. 12 are derived from engineering knowledge of the operation of electricity meters at step 208d of the method 200 of FIG. 3. It should also be understood that the set of different class/group combinations shown in FIG. 12 are not necessarily exhaustive.

FIGS. 13A-13D are screenshots of different parts of a Wolfram language environment during the execution of a Wolfram language script for the case of a single one of the class/group combinations from FIG. 12 called "maximumMacro" which corresponds to a combination of a measurement point group of "oneThroughFour", a unit of measure class of "threePhasePower" and a data type class of "maximumMacro". The different measurement points and their corresponding cim codes corresponding to measurement point group "oneThroughFour", the different units of measure and their corresponding cim codes corresponding to unit of measure class "threePhasePower", and the different data types and their corresponding cim codes corresponding to data type class "maximumMacro" are read into the Wolfram language environment as shown

in Fig. 13A. All of the different members of the “maximumMacro” data type class, the “threePhasePower” unit of measure class, and the “oneThroughFour” measurement point group are listed as shown in FIG. 13B. All possible combinations of the different measurement points and their corresponding cim codes corresponding to measurement point group “oneThroughFour”, the different units of measure and their corresponding cim codes corresponding to unit of measure class “threePhasePower”, and the different data types and their corresponding cim codes corresponding to data type class “maximumMacro” are then generated. The possible combinations of the different measurement points corresponding to measurement point group “oneThroughFour”, the different units of measure corresponding to unit of measure class “threePhasePower”, and the different data types corresponding to data type class “maximumMacro” are shown in Fig. 13C. As shown at FIG. 13D, for each combination of measurement point, unit of measure, and data type class, measurement type names are then generated or constructed from the name associated with the corresponding measurement point, the name associated with the corresponding unit of measure, and the name associated with the corresponding data type.

The measurement type names and cim codes for each combination of the different measurement points corresponding to measurement point group “oneThroughFour”, the different units of measure corresponding to unit of measure class “threePhasePower”, and the different data types corresponding to data type class “maximumMacro” corresponding to the “maximumMacro” class/group combination are then stored. FIG. 14 shows a small selection of the measurement type names and cim codes for each combination of the different measurement points corresponding to measurement point group “oneThroughFour”, the different units of measure corresponding to unit of measure class “threePhasePower”, and the different data types corresponding to data type class “maximumMacro” corresponding to the “maximumMacro” class/group combination. FIG. 14 also shows the corresponding “cimDescription” for each combination, where the cimDescription is generated by simply transforming the numerical cim code values to their string enumerations as defined by the IEC 61968-9 metrology specification. Accordingly, it should be understood that the measurement type name and the “cimDescription” are equivalent for each combination. It should be understood that FIG. 14 does not show all of the measurement type names and cim codes corresponding to the “maximumMacro” class/group and that there may be several hundred measurement type names and cim codes corresponding to the “maximumMacro” class/group.

The Wolfram language script is then used to generate and store all of the measurement type names and cim codes corresponding to all of the other class/group combinations defined in FIG. 12 so as to define the functionality of the meter 4 and the corresponding set of cim codes.

5 It should be understood that the method for use in determining the measurement functionality of a meter described above may not only fully define the functionality of the meter than the manufacturer's meter specification, but may also define the corresponding cim code for each measurement type. Moreover, one of ordinary skill in the art will understand that essentially the same method may be used to define the measurement functionality of a meter in terms of codes of a metrology specification other than the IEC 61968-9 metrology specification, for example in terms of codes of the ANSI C12.19 metrology specification, or in terms of codes of the COSEM metrology specification.

10 Furthermore, the same method may be used to define the corresponding codes for each measurement type for a plurality of metrology specifications such as a plurality of metrology specifications selected from the IEC 61968-9 metrology specification, the ANSI C12.19 metrology specification, and the COSEM metrology specification to thereby allow direct mappings to be created and maintained across different metrology specifications. For example, the method may comprise:

20 identifying or defining, for each measurement point, a corresponding value for each of one or more attributes of a further code of a further metrology specification;
 identifying or defining, for each unit of measure, a corresponding value for each of one or more attributes of a further code of the further metrology specification;
 identifying or defining, for each data type, a corresponding value for each of one or more attributes of a further code of the further metrology specification; and
25 determining, for each combination of measurement point, unit of measure, and data type, the corresponding further code of the further metrology specification composed from the values of the further code attributes associated with the corresponding measurement point, the corresponding unit of measure, and the corresponding data type.

30 The further metrology specification may be the IEC 61968-9 metrology specification and the further code of the further metrology specification may be a reading type code defined according to the IEC 61968-9 metrology specification.

35 The further metrology specification may be the ANSI C12.19 metrology specification and the further code of the further metrology specification may be a code

defined according to a relational table structure of the ANSI C12.19 metrology specification.

The further metrology specification may be the COSEM metrology specification and the further code of the further metrology specification may be a class and/or a parameter defined according to the COSEM metrology specification.

Such a method may be used for determining inter-operability between a meter 4 and the head end equipment 6, wherein the functionality of the head end equipment 6 is defined using codes of a given metrology specification. For example, for head end equipment 6 having a functionality defined as a plurality of codes of a given metrology specification, a method for use in identifying inter-operability between the head end equipment 6 and the meter 4 of the metering system 2 may comprise:

using the method as described above to determine the codes associated with the measurement functionality of the meter 4 for the same given metrology specification;
comparing the codes associated with the known functionality of the head end equipment 6 and the determined codes associated with the determined measurement functionality of the meter 4; and
determining whether the head end equipment 6 and the meter 4 are inter-operable based on the results of the comparison.

The determined measurement types and/or the determined metrology specification codes may be used to determine whether a desired measurement type is supported by the meter and to obtain measurement data of the desired measurement type from raw data measured by the meter.

For example, a method for obtaining measurement data from raw data measured by a meter may comprise:

receiving a request for measurement data of a desired measurement type name and/or of a desired code of a metrology specification;
determining whether the desired measurement type is supported by the meter by comparing the desired measurement type name with each determined measurement type name of the determined plurality of measurement type names and/or by comparing the desired metrology specification code with each determined metrology specification code of the determined plurality of metrology specification codes; and

responsive to determining that the desired measurement type name matches one of the determined measurement type names and/or that the desired metrology specification code matches one of the determined metrology specification codes, deriving the measurement data from the raw data according to the transformation defined by the data type which corresponds to the determined measurement type name which

matches the desired measurement type name and/or according to the transformation defined by the data type which corresponds to the determined metrology specification code which matches the desired metrology specification code.

5 It should be understood that, when the meter 4 or head end equipment 6 receives a request for a specific measurement type, the measurement data is determined by first performing, at the meter, the initial aggregation operation on the raw data to calculate the base data. As previously described with reference to the examples of the causal graphs of FIGS. 4A, 5, 6, 7 and 8, the sequence of time-series functions that must then be applied to calculate the requested measurement data from the base data is defined
10 by the sequence of time-series functions traversed from the base data vertex of the relevant causal graph to the requested measurement data vertex of the relevant causal graph. As discussed above, the method may fully define the functionality of the meter. Put another way, the method may define all of the measurement types supported by the meter thereby allowing measurement data of all of the measurement types supported by
15 the meter to be derived from raw data measured by the meter.

The meter 4 may use the relevant sequence of time-series functions to derive the measurement data from the base data and the derived measurement data may be transmitted from the meter 4 to the head end equipment 6. This may require the meter 4 to calculate and persist or store the base data and the measurement data, but may
20 avoid any requirement for the meter 4 to transmit the base data to the head end equipment 6.

Alternatively, the base data may be transmitted from the meter 4 to the head end equipment 6, and the head end equipment 6 may use the relevant sequence of time-series functions to derive the measurement data from the base data. This may require
25 the meter 4 to calculate and persist or store the base data and for the base data to be transmitted from the meter 4 to the head end equipment 6, but may avoid any requirement for the meter 4 to derive the measurement data from the base data.

The method may comprise publicizing or indicating to a user of the meter 4 and/or of the head end equipment 6 the determined measurement types to allow the user to
30 select which one or more measurement types should be used to derive the measurement data from the raw data measured by the meter 4.

One of skill in the art will understand that the methods described above may be used to generate a model for defining the measurement functionality of a meter, wherein the meter is configured for measuring raw data at one or more measurement locations
35 around a system, wherein the model defines the characteristics of measurement data which is derivable from the raw data, and wherein the model comprises a plurality of

different measurement type data objects, wherein each measurement type data object comprises:

a corresponding measurement point;

a corresponding unit of measure;

5 a corresponding data type; and

a corresponding measurement type name composed from a name associated with the corresponding measurement point, a name associated with the corresponding unit of measure, and a name associated with the corresponding data type,

10 wherein the corresponding measurement point defines the corresponding measurement location, the corresponding unit of measure defines the unit of measure for the corresponding measurement data, and the corresponding data type defines a corresponding transformation for generating the corresponding measurement data from the corresponding raw data.

One of ordinary skill in the art will also understand that various modifications are possible to any of the methods described above. For example, although the methods above for use in determining the measurement functionality of a meter are described in the context of a meter 4 and metering system 2 for electricity, one of skill in the art will understand that similar methods may be used for determining the measurement functionality of a meter in the context of a meter 4 and a metering system 2 for any utility, such as gas, water, sewage or the like.

Although several specific initial aggregation operations are described above for determining base data from raw data, the initial aggregation operations described are not necessarily exhaustive and other initial aggregation operations are possible. For example, rather than the base data representing an instantaneous measurement value at the end of an aggregation interval, the base data may represent an instantaneous measurement value at any defined time within the aggregation interval such as at the beginning or at the middle of the aggregation interval.

The different sequences of time-series functions described with reference to FIGS. 4A to 8 are not necessarily exhaustive.

30 The different measurement points described with reference to FIG. 9A are not necessarily exhaustive. The different measurement point groups described with reference to FIG. 9B are not necessarily exhaustive. The different units of measure described with reference to FIGS. 10A and 10B are not necessarily exhaustive. The different unit of measure classes described with reference to FIGS. 10A and 10B are not necessarily exhaustive. The different data types described with reference to FIGS. 11A

and 11B are not necessarily exhaustive. The different data type classes described with reference to FIGS. 11A and 11B are not necessarily exhaustive.

It should be understood that the embodiments of the present disclosure are illustrative only and that the claims are not limited to the embodiments. Those skilled in the art will be able to make modifications to the embodiments of the present disclosure and to contemplate alternatives to the embodiments which fall within the scope of the appended claims. Each feature described above and/or shown in any of the accompanying drawings may be incorporated in any embodiment, whether alone or in any appropriate combination with any other feature described and/or shown in the drawings. In particular, one of ordinary skill in the art will understand that one or more of the features of an embodiment described above and/or shown in any of the accompanying drawings may produce effects or provide advantages when used in isolation from one or more of the other features of the same embodiment and that different combinations of the features are possible other than the specific combinations of the features of the embodiments described above and/or shown in any of the accompanying drawings.

The skilled person will understand that in the preceding description and the appended claims, positional terms such as 'above', 'along', 'side', etc. are made with reference to the accompanying drawings. These terms are used for ease of reference but are not intended to be limiting in nature. These terms are to be understood as referring to an object when in an orientation as shown in the accompanying drawings.

Use of the term "comprising" when used in relation to a feature of an embodiment does not exclude other features or steps. Use of the term "a" or "an" when used in relation to a feature of an embodiment of the present disclosure does not exclude the possibility that the embodiment may include a plurality of such features.

The use of reference signs in the claims should not be construed as limiting the scope of the claims.

CLAIMS

1. A method for use in determining the measurement functionality of a meter, wherein the meter is configured for measuring raw data at one or more measurement locations around a system, wherein the measurement functionality of the meter defines the characteristics of measurement data which is derivable from the raw data, and wherein the method comprises:
- identifying a set of different measurement points supported by the meter, each measurement point defining the one or more measurement locations, and identifying or defining, for each measurement point, a corresponding name and a corresponding value for each of one or more attributes of a code of a metrology specification;
- identifying a set of different units of measure supported by the meter, each unit of measure defining the unit of measure for the measurement data, and identifying or defining, for each unit of measure, a corresponding name and a corresponding value for each of one or more attributes of a code of the metrology specification;
- identifying a set of different data types supported by the meter, each data type defining a transformation for generating the measurement data from the raw data, and identifying or defining, for each data type, a corresponding name and a corresponding value for each of one or more attributes of a code of the metrology specification;
- determining different combinations of measurement point, unit of measure, and data type selected from the set of different measurement points, the set of different units of measure, and the set of different data types respectively; and
- determining, for each combination of measurement point, unit of measure, and data type, a corresponding measurement type and a corresponding code of the metrology specification, wherein the corresponding measurement type comprises the corresponding measurement point, the corresponding unit of measure, the corresponding data type, and a corresponding measurement type name composed from the name associated with the corresponding measurement point, the name associated with the corresponding unit of measure, and the name associated with the corresponding data type, and wherein the corresponding code of the metrology specification is composed from the values of the code attributes associated with the corresponding measurement point, the corresponding unit of measure, and the corresponding data type.
2. The method of claim 1,

wherein the metrology specification is the IEC 61968-9 metrology specification and the code of the metrology specification is a reading type code defined according to the IEC 61968-9 metrology specification,

5 wherein the metrology specification is the ANSI C12.19 metrology specification and the code of the metrology specification is a code defined according to a relational table structure of the ANSI C12.19 metrology specification, or

10 wherein the metrology specification is the COSEM metrology specification and the code of the metrology specification is a class and/or a parameter defined according to the COSEM metrology specification.

3. The method of claim 1 or 2, wherein determining the different combinations of measurement point, unit of measure, and data type comprises:

15 defining a set of different measurement point groups, each measurement point group including a different selection of one or more of the measurement points of the set of different measurement points;

associating each unit of measure of the set of different units of measure with a corresponding unit of measure class;

20 associating each data type of the set of different data types with a corresponding data type class;

defining a set of different class/group combinations, each different class/group combination comprising a different combination of measurement point group, unit of measure class, and data type class; and

25 determining, for each class/group combination of the set of different class/group combinations, all possible combinations of: i) the measurement points associated with the class/group combination; ii) the units of measure associated with the class/group combination; and iii) the data types associated with the class/group combination.

4. The method of any preceding claim, wherein each transformation defines a corresponding initial aggregation operation and one or more corresponding functions, 30 wherein the corresponding initial aggregation operation is performed on the raw data to form base data, and wherein the one or more corresponding functions operate on the base data to generate the measurement data.

5. The method of claim 4, wherein the meter is configured to perform the initial 35 aggregation operation on the raw data, for example by signal processing of the raw data.

6. The method of claim 4 or 5, wherein the initial aggregation operation comprises:
averaging the raw data over an aggregation time interval;
integrating the raw data over an aggregation time interval;
selecting an instantaneous raw data value, for example an instantaneous raw
5 data value at the end of an aggregation time interval; or
determining a count of events derived from the raw data over an aggregation time
interval.
7. The method of any one of claims 4 to 6, wherein the raw data comprises raw
10 time-series data, the base data comprises base time-series data, and the measurement
data comprises measurement time-series data, for example wherein the raw time-series
data comprises one or more arrays of raw time-value pairs, the base time-series data
comprises one or more arrays of base time-value pairs, and the measurement time-
series data comprises one or more arrays of measurement time-value pairs.
- 15 8. The method of claim 7, wherein each of the one or more functions which operate
on the base data to generate the measurement data comprises a time-series function.
9. The method of any preceding claim, comprising:
20 identifying or defining, for each measurement point, a corresponding value for
each of one or more attributes of a further code of a further metrology specification;
identifying or defining, for each unit of measure, a corresponding value for each
of one or more attributes of a further code of the further metrology specification;
identifying or defining, for each data type, a corresponding value for each of one
25 or more attributes of a further code of the further metrology specification; and
determining, for each combination of measurement point, unit of measure, and
data type, the corresponding further code of the further metrology specification
composed from the values of the further code attributes associated with the
corresponding measurement point, the corresponding unit of measure, and the
30 corresponding data type.
10. The method of claim 9,
wherein the further metrology specification is the IEC 61968-9 metrology
specification and the further code of the further metrology specification is a reading type
35 code defined according to the IEC 61968-9 metrology specification,

wherein the further metrology specification is the ANSI C12.19 metrology specification and the further code of the further metrology specification is a code defined according to a relational table structure of the ANSI C12.19 metrology specification, or

5 wherein the further metrology specification is the COSEM metrology specification and the further code of the further metrology specification is a class and/or a parameter defined according to the COSEM metrology specification.

11. A method for use in identifying inter-operability between head end equipment and a meter, wherein the head end equipment has a known functionality defined as a plurality
10 of codes of a given metrology specification, and wherein the method comprises:

using the method for use in determining the measurement functionality of a meter as claimed in any preceding claim to determine the codes associated with the measurement functionality of the meter for the same given metrology specification;

15 comparing the plurality of codes of the head end equipment with the determined codes associated with the functionality of the meter; and

determining whether the head end equipment and the meter are inter-operable based on the results of the comparison.

12. A method for obtaining measurement data from raw data measured by a meter,
20 the method comprising:

the method for use in determining the measurement functionality of a meter of any one of claims 1 to 10;

receiving a request for measurement data of a desired measurement type name and/or of a desired code of a metrology specification;

25 determining whether the desired measurement type is supported by the meter by comparing the desired measurement type name with each determined measurement type name of the determined plurality of measurement type names and/or by comparing the desired metrology specification code with each determined metrology specification code of the determined plurality of metrology specification codes; and

30 responsive to determining that the desired measurement type name matches one of the determined measurement type names and/or that the desired metrology specification code matches one of the determined metrology specification codes, deriving the measurement data from the raw data according to the transformation defined by the data type which corresponds to the determined measurement type name which
35 matches the desired measurement type name and/or according to the transformation

defined by the data type which corresponds to the determined metrology specification code which matches the desired metrology specification code.

- 5 13. The method of claim 12, wherein deriving the measurement data from raw data measured by the meter according to the transformation comprises performing an initial aggregation operation on the raw data to form base data and applying one or more functions to the base data to generate the measurement data, wherein the one or more functions are defined according to the transformation.
- 10 14. The method of claim 13, wherein the meter is configured to perform the initial aggregation operation on the raw data, for example by signal processing of the raw data.
- 15 15. The method of any one of claims 12 to 14, comprising:
performing, at the meter, the initial aggregation operation on the raw data measured by the meter to determine, at the meter, the base data;
using the one or more functions to derive, at the meter, the requested measurement data from the base data; and
transmitting the derived measurement data from the meter to head end equipment located remotely from the meter.
- 20 16. The method of any one of claims 12 to 14, comprising:
performing, at the meter, the initial aggregation operation on the raw data measured by the meter to determine the base data;
transmitting the base data from the meter to head end equipment located remotely from the meter; and
25 using the one or more functions to derive, at the head end equipment, the requested measurement data from the base data.
- 30 17. A model for defining the measurement functionality of a meter, wherein the meter is configured for measuring raw data at one or more measurement locations around a system, wherein the model defines the characteristics of measurement data which is derivable from the raw data, and wherein the model comprises a plurality of different measurement type data objects, wherein each measurement type data object comprises:
a corresponding measurement point;
35 a corresponding unit of measure;
a corresponding data type; and

a corresponding measurement type name composed from a name associated with the corresponding measurement point, a name associated with the corresponding unit of measure, and a name associated with the corresponding data type,

5 wherein the corresponding measurement point defines the corresponding measurement location, the corresponding unit of measure defines the unit of measure for the corresponding measurement data, and the corresponding data type defines a corresponding transformation for generating the corresponding measurement data from the corresponding raw data.

10 18. The method for use in determining the measurement functionality of a meter of any one of claims 1 to 10, the method for use in identifying inter-operability between head end equipment and a meter of claim 11, the method for obtaining measurement data from raw data measured by a meter of any one of claims 12 to 16, the model for defining the measurement functionality of a meter of claim 17, wherein the meter is
15 configured to meter, and possibly also control, the flow of electricity, gas, water or sewage.

19. A method for use in defining a measurement type supported by a meter, wherein the meter is configured for measuring raw data at a measurement location of a system,
20 wherein the measurement type defines the characteristics of measurement data which is derivable from the raw data, and wherein the method comprises:

defining a measurement type comprising a measurement point, a unit of measure, a data type, and a measurement type name,

wherein the measurement point defines the measurement location,

25 wherein the unit of measure defines the unit of measure for the measurement data,

wherein the data type defines a transformation for generating the measurement data from the raw data, and

30 wherein the measurement type name is composed from a name associated with the measurement point, a name associated with the unit of measure, and a name associated with the data type.

20. The method of claim 19, wherein the transformation defines an initial aggregation operation and one or more functions, wherein the initial aggregation operation is
35 performed on the raw data to form base data, and wherein the one or more functions operate on the base data to generate the measurement data.

21. The method of claim 20, wherein the meter is configured to perform the initial aggregation operation on the raw data, for example by signal processing of the raw data.

- 5 22. The method of claim 20 or 21, wherein the initial aggregation operation comprises:
- averaging the raw data over an aggregation time interval;
 - integrating the raw data over an aggregation time interval;
 - selecting an instantaneous raw data value, for example an instantaneous raw
 - 10 data value at the end of an aggregation time interval; or
 - determining a count of events derived from the raw data over an aggregation time interval.

23. The method of any one of claims 20 to 22, wherein the raw data comprises raw
- 15 time-series data, the base data comprises base time-series data, and the measurement data comprises measurement time-series data.

24. The method of claim 23, wherein the raw time-series data comprises one or more
- 20 arrays of raw time-value pairs, the base time-series data comprises one or more arrays of base time-value pairs, and the measurement time-series data comprises one or more arrays of measurement time-value pairs.

25. The method of any one of claims 20 to 24, wherein each of the one or more
- 25 functions which operate on the base data to generate the measurement data comprises a time-series function.

26. The method of any one of claims 19 to 25, comprising defining a code of a
- 30 metrology specification corresponding to the measurement type wherein the code of the metrology specification is composed from values of code attributes associated with the measurement point, the unit of measure, and the data type.

27. The method of claim 26, wherein the metrology specification is the IEC 61968-9 metrology specification and the code of the metrology specification is a reading type code defined according to the IEC 61968-9 metrology specification,

wherein the metrology specification is the ANSI C12.19 metrology specification and the code of the metrology specification is a code defined according to a relational table structure of the ANSI C12.19 metrology specification, or

5 wherein the metrology specification is the COSEM metrology specification and the code of the metrology specification is a class and/or a parameter defined according to the COSEM metrology specification.

28. A method for obtaining measurement data from raw data measured by a meter, the method comprising:
10 the method for use in defining a measurement type supported by a meter of any one of claims 19 to 27;
receiving a request for measurement data of the measurement type name and/or of a metrology specification code; and
deriving, in response to the request, the measurement data from the raw data
15 according to the transformation defined by the data type corresponding to the measurement type name and/or corresponding to the metrology specification code.

29. The method of claim 28, wherein deriving the measurement data from the raw data comprises performing an initial aggregation operation on the raw data to form base data and applying one or more functions to the base data to generate the measurement data, wherein the one or more functions are defined according to the transformation defined by the data type.
20

30. The method of claim 29, wherein the meter is configured to perform the initial aggregation operation on the raw data, for example by signal processing of the raw data.
25

31. The method of claim 29 or 30, comprising:
performing, at the meter, the initial aggregation operation on the raw data measured by the meter to determine, at the meter, the base data;
30 using the one or more functions to derive, at the meter, the measurement data from the base data; and
transmitting the derived measurement data from the meter to head end equipment located remotely from the meter.

32. The method of claim 31, wherein the one or more functions are stored in a memory of the meter.
35

33. The method of claim 29 or 30, comprising:
performing, at the meter, the initial aggregation operation on the raw data
measured by the meter to determine, at the meter, the base data;
5 transmitting the base data from the meter to head end equipment located
remotely from the meter; and
using the one or more functions to derive, at the head end equipment, the
measurement data from the base data.
- 10 34. The method of claim 33, wherein the one or more functions are stored in a
memory of the head end equipment.
35. A method for defining the measurement functionality of a meter, the method
comprising defining a plurality of different measurement types supported by a meter,
15 wherein each measurement type of the plurality of different measurement types is
defined according to the method as claimed in any one of claims 19 to 27.
36. A measurement type data object for defining a measurement type supported by
a meter, wherein the meter is configured for measuring raw data at a measurement
20 location of a system, wherein the measurement type defines the characteristics of
measurement data which is derivable from the raw data, and wherein the measurement
type data object comprises:
a measurement point;
a unit of measure;
25 a data type; and
a measurement type name composed from a name associated with the
measurement point, a name associated with the unit of measure, and a name associated
with the data type,
wherein the measurement point defines the measurement location, the unit of
30 measure defines the unit of measure for the measurement data, and the data type
defines a transformation for generating the measurement data from the raw data.
37. The method for use in defining a measurement type supported by a meter of any
one of claims 19 to 27, the method for obtaining measurement data from a meter of any
35 one of claims 28 to 34, the method for defining the measurement functionality of a meter
of claim 35, or the measurement type data object of claim 36, wherein the meter is

configured to meter, and optionally also to control, the flow of electricity, gas, water or sewage.