

PATENT SPECIFICATION (11)

1 492 121

1 492 121

- (21) Application No. 37221/75 (22) Filed 10 Sept. 1975 (19)
 (31) Convention Application No. 49/116 206 (32) Filed 25 Sept. 1974 in
 (33) Japan (JA)
 (44) Complete Specification published 16 Nov. 1977
 (51) INT. CL.³ A44B 19/34 19/12 D04B 21/20 A44B 19/04
 (52) Index at acceptance
 E2S 1A1 1A2A 1A2B12
 D1K 24A11 24A6 24B



(54) CONCEALED SLIDING CLASP FASTENERS

(71) We, YOSHIDA KOGYO K.K., a corporation duly organized under the laws of Japan and existing at No. 1, Kanda Izumi-cho, Chiyoda-ku, Tokyo, Japan, do hereby declare the invention, for which we pray that a patent may be granted to us, and the method by which it is to be performed, to be particularly described in and by the following statement:—

This invention relates to sliding clasp fasteners, more particularly to a slider-operated fastener of the concealed or masked type which in its closed disposition substantially simulates a garment seam.

Sliding clasp fasteners are well known which comprise a pair of rows of interlocking fastener elements formed from a continuous filament or wire and secured to respective folded edges of opposed stringer tapes, and such fasteners when closed by the slider mask the elements from external view, only leaving a linear seam in the junction of the opposed tapes.

In such known concealed or masked type of fastener, there were used support tapes of a warp-knit structure, as contrasted to conventional woven fabric tapes, for supporting thereon respective rows of fastener elements. The warp-knit tape inherently has a multiplicity of wales and interwale grooves on one or the other or both of its surfaces, which wales and interwale grooves can be conveniently utilized for securing the fastener element firmly to the tape for example by engaging the wales with recesses formed in the elements. While fasteners including stringers of the character described are advantageous from the point of view of attaching the fastener elements securely to the respective support tapes, they have presented a difficulty in sewing the fastener properly into position on a garment fabric or other articles. This difficulty arose from the fact that the portion of the support tape at and along which the fastener was to be sewn to the garment was structurally identical to and as hard and heavy as the remaining portions of the tape, with the wales at the first-mentioned tape portion often interfer-

ring with or obstructing the normal thrusting action of the sewing needle.

According to the invention, there is provided a concealed type of sliding clasp fastener comprising a pair of warp-knit support tapes each having a longitudinal element-carrying edge inwardly folded on itself, rows of fastener elements sewn to respective element-carrying edges, each of said fastener elements having leg portions, a coupling head portion merging into said leg portions and connecting portions remote from said coupling head and connecting the element to respective adjacent elements, and said support tapes having on one surface a multiplicity of longitudinally extending alternated wales and interwale grooves, the number of knitting threads forming the wales being reduced at the wale region of each support tape which is located adjacent the intended path of a sewing needle as compared to the number of knitting threads at the remaining regions of the tape, whereby each support tape can be sewn onto a garment fabric in a manner that said sewing needle provides a sewn seam at and along the inwardly folded edge of the tape.

The invention will be described by way of example with reference to the accompanying drawings illustrating a preferred embodiment which the invention may assume in practice. In the drawings:—

Figure 1 is a transverse cross-sectional view of a concealed type of sliding clasp fastener forming the said preferred embodiment of the invention;

Figure 2 is a transverse cross-sectional view of one of the pair of stringers of the fastener of Figure 1 disposed for sewing onto a garment fabric; and

Figure 3 is a diagram schematically illustrating a preferred knit pattern employed for the support tape of the fastener of Figure 1.

Referring now to the drawings and Figure 1 in particular, there is shown a sliding clasp fastener 10 which essentially comprises a pair of oppositely disposed stringers or support tapes 11 and a row of fastener elements 12 secured to each support tape, which fas-

(12)

tener elements are shown for purposes of illustration to be in the form of a continuous, helically coiled structure. This structure when taken as an individual convolution 12a comprises an upper leg portion 13, a lower leg portion 14, a coupling head 15 merging into these leg portions and connecting portions 16 remote from the coupling head 15 and connecting the convolution 12a to respective adjacent convolutions. One of the two leg portions 13, 14 is provided at its outer surface with cutaway recesses 17a 17b for purposes hereafter described. There is provided a longitudinally extending filler cord 18 which is inserted in and through the space defined between the upper and lower legs 13 and 14 of the fastener element 12. The support tape 11 is made of a warp-knitted fabric having on one surface a multiplicity of alternate wales 19 and interwale grooves 20, with the other surface rendered flat as shown. The tape 11 has an element-carrying edge 21 inwardly folded on itself about a fold 22 and adapted for mounting thereon the row of fastener elements 12, the arrangement being that when the two opposed rows of fastener elements are taken into coupling engagement with each other, the folded edges of the respective support tapes 11 are brought closely together to form a junction 23 which conceals or masks the elements 12 from external view, as shown in Figure 1.

A preferred warp-knit structure for the support tape 11 is diagrammatically shown in Figure 3 and comprises chain stitches 11a, tricot stitches 11b in the lay 1-2/1-0, stitches 11c in the lay 0-1/4-3 and reinforcing warp threads 11d. The number of knitting threads or yarns which form the wales is reduced at the region of the support tape 11 which is located adjacent the path P of sewing needle N as compared to the number of knitting threads or yarns arranged at the remaining regions of the tape 11. In the illustrated embodiment, the region of the tape 11 adjoining the path P of sewing needle N corresponds in position to an interwale groove 20a between the third wale 19c and the fourth wale 19d counting from the innermost or first wale 19a. It is to be noted that the fourth wale 19d is constituted only by 1-2/1-0 tricot stitches 11b and 0-1/4-3 stitches 11c, with chain stitches 11a and reinforcing warp threads 11d removed from this region of the tape 11, so that the loop density of the fourth wale 19d is reduced to an extent to make this portion of the tape highly flexible.

According to the illustrated embodiment, the rows of fastener elements 12 are secured by sewn stitches 24 to the element-carrying edges 21 of respective support tapes 11 with the first wale 19a and the second wale 19b anchored in place respectively at the re-

cesses 17a and 17b of the elements 12. When attaching the fastener 10 to a garment fabric F, the former is laid over the latter with the waled side of the support tape 11 faced down as seen in Figure 2. The sewing needle N is operated to thrust through the third interwale groove 20a adjoining the fourth wale 19d, when this wale being flexible can yield itself to the sewing pressure without restricting the thrusting action of the needle N. Flexibility of the fourth wale 19d further ensures that should the needle N sway slightly out of line during the course of its sewing operation, it can still continue to sew the tape 11 substantially along the path P within the interwale groove 20a so as to provide a sewn seam on the garment fabric F where desired above the folded edge of each tape to maintain the effect of concealing the fastener elements from external view. A further advantage of the fourth wale 19d being pliable or flexible as compared to the remaining wales of the tape is that the respective support tapes 11 can be easily folded as desired into the position of Figure 1 in which the third wales 19c of the opposed tapes are brought together into abutting engagement as the rows of fastener elements 12 are taken into coupling engagement by the action of a slider not shown.

WHAT WE CLAIM IS:—

1. A concealed type of sliding clasp fastener comprising a pair of warp-knit support tapes each having a longitudinal element-carrying edge inwardly folded on itself, rows of fastener elements sewn to respective element-carrying edges, each of said fastener elements having leg portions, a coupling head portion merging into said leg portions and connecting portions remote from said coupling head and connecting the element to respective adjacent elements, and said support tapes having on one surface a multiplicity of longitudinally extending alternate wales and interwale grooves, the number of knitting threads forming the wales being reduced at the wale region of each support tape which is located adjacent the intended path of a sewing needle as compared to the number of knitting threads at the remaining regions of the tape, whereby each support tape can be sewn onto a garment fabric in a manner that said sewing needle provides a sewn seam at and along the inwardly folded edge of the tape.

2. A concealed type of sliding clasp fastener as claimed in claim 1 wherein the wale region adjacent the intended path of the sewing needle consists of tricot stitches in the lay 1-2/1-0 and stitches in the lay 0-1/4-3, while the remaining regions of the support tape consist of chain stitches, tricot stitches in the lay 1-2/1-0, stitches

tener elements are shown for purposes of illustration to be in the form of a continuous, helically coiled structure. This structure when taken as an individual convolution 12a comprises an upper leg portion 13, a lower leg portion 14, a coupling head 15 merging into these leg portions and connecting portions 16 remote from the coupling head 15 and connecting the convolution 12a to respective adjacent convolutions. One of the two leg portions 13, 14 is provided at its outer surface with cutaway recesses 17a 17b for purposes hereafter described. There is provided a longitudinally extending filler cord 18 which is inserted in and through the space defined between the upper and lower legs 13 and 14 of the fastener element 12. The support tape 11 is made of a warp-knitted fabric having on one surface a multiplicity of alternate wales 19 and interwale grooves 20, with the other surface rendered flat as shown. The tape 11 has an element-carrying edge 21 inwardly folded on itself about a fold 22 and adapted for mounting thereon the row of fastener elements 12, the arrangement being that when the two opposed rows of fastener elements are taken into coupling engagement with each other, the folded edges of the respective support tapes 11 are brought closely together to form a junction 23 which conceals or masks the elements 12 from external view, as shown in Figure 1.

A preferred wark-knit structure for the support tape 11 is diagrammatically shown in Figure 3 and comprises chain stitches 11a, tricot stitches 11b in the lay 1-2/1-0, stitches 11c in the lay 0-1/4-3 and reinforcing warp threads 11d. The number of knitting threads or yarns which form the wales is reduced at the region of the support tape 11 which is located adjacent the path P of sewing needle N as compared to the number of knitting threads or yarns arranged at the remaining regions of the tape 11. In the illustrated embodiment, the region of the tape 11 adjoining the path P of sewing needle N corresponds in position to an interwale groove 20a between the third wale 19c and the fourth wale 19d counting from the innermost or first wale 19a. It is to be noted that the fourth wale 10d is constituted only by 1-2/1-0 tricot stitches 11b and 0-1/4-3 stitches 11c, with chain stitches 11a and reinforcing warp threads 11d removed from this region of the tape 11, so that the loop density of the fourth wale 19d is reduced to an extent to make this portion of the tape highly flexible.

According to the illustrated embodiment, the rows of fastener elements 12 are secured by sewn stitches 24 to the element-carrying edges 21 of respective support tapes 11 with the first wale 19a and the second wale 19b anchored in place respectively at the re-

cesses 17a and 17b of the elements 12. When attaching the fastener 10 to a garment fabric F, the former is laid over the latter with the waled side of the support tape 11 faced down as seen in Figure 2. The sewing needle N is operated to thrust through the third interwale groove 20a adjoining the fourth wale 19d, when this wale being flexible can yield itself to the sewing pressure without restricting the thrusting action of the needle N. Flexibility of the fourth wale 19d further ensures that should the needle N sway slightly out of line during the course of its sewing operation, it can still continue to sew the tape 11 substantially along the path P within the interwale groove 20a so as to provide a sewn seam on the garment fabric F where desired above the folded edge of each tape to maintain the effect of concealing the fastener elements from external view. A further advantage of the fourth wale 19d being pliable or flexible as compared to the remaining wales of the tape is that the respective support tapes 11 can be easily folded as desired into the position of Figure 1 in which the third wales 19c of the opposed tapes are brought together into abutting engagement as the rows of fastener elements 12 are taken into coupling engagement by the action of a slider not shown.

WHAT WE CLAIM IS:—

1. A concealed type of sliding clasp fastener comprising a pair of warp-knit support tapes each having a longitudinal element-carrying edge inwardly folded on itself, rows of fastener elements sewn to respective element-carrying edges, each of said fastener elements having leg portions, a coupling head portion merging into said leg portions and connecting portions remote from said coupling head and connecting the element to respective adjacent elements, and said support tapes having on one surface a multiplicity of longitudinally extending alternate wales and interwale grooves, the number of knitting threads forming the wales being reduced at the wale region of each support tape which is located adjacent the intended path of a sewing needle as compared to the number of knitting threads at the remaining regions of the tape, whereby each support tape can be sewn onto a garment fabric in a manner that said sewing needle provides a sewn seam at and along the inwardly folded edge of the tape.

2. A concealed type of sliding clasp fastener as claimed in claim 1 wherein the wale region adjacent the intended path of the sewing needle consists of tricot stitches in the lay 1-2/1-0 and stitches in the lay 0-1/4-3, while the remaining regions of the support tape consist of chain stitches, tricot stitches in the lay 1-2/1-0, stitches



* C L M S *



3

1,492,121

(12)
3

in the lay 0—1/4—3 and reinforcing warp threads.

3. A concealed type of sliding clasp fastener as claimed in claim 1 wherein one of the leg portions is provided on its outer surface with recesses adapted to anchor therein the wales extending along the folded element-carrying edge of each support tape.

10 4. A concealed type of sliding clasp fastener substantially as herein described with reference to and as illustrated in the accompanying drawings.

5. A garment comprising garment fabric and a concealed type of sliding clasp fastener as claimed in any preceding claim, each support tape having been sewn onto the garment fabric in a manner that said sewing needle has provided a sewn seam at and along the inwardly folded edge of the tape. 15

MARKS & CLERK,
Chartered Patent Agents,
Agents for the Applicants.

Printed for Her Majesty's Stationery Office by Burgess & Son (Abingdon), Ltd.—1977.
Published at The Patent Office, 25 Southampton Buildings, London, WC2A 1AY,
from which copies may be obtained.