

DESCRIPTION

Title of the Invention: MOBILE COMMUNICATION METHOD AND MOBILE STATION

5 Technical Field

[0001]

The present invention relates to a mobile communication method in which a mobile station to perform communication via a first connection between the mobile station and a radio base station and a second connection between the radio base station and a switching center by use of a first protocol function and a second protocol function, and relates to the mobile station.

Background Art

15 [0002]

In a mobile communication system according to the LTE (Long Term Evolution) scheme defined by the 3GPP, an AS (Access Stratum) function (hereinafter an LTE-AS function) of a mobile station UE is configured to perform a reconnection procedure upon detection of a "Radio Link Failure" attributable to a handover failure or deterioration in radio quality.

Summary of the Invention

Problems to be Solved by the Invention

25 [0003]

Here, the LTE-AS function can perform the reconnection procedure only for a radio base station eNB (a cell) having "UE Context" of the mobile station UE.

[0004]

Specifically, when the LTE-AS function transmits an "RRC Connection Reestablishment Request (a reestablishment request)" to a radio base station eNB (a cell) not having the "UE Context" of the mobile station UE, the LTE-AS function
5 receives an "RRC Connection Reestablishment Reject (a reestablishment rejection response)". In this case, an RRC connection between the mobile station UE and the radio base station eNB is changed to an idle state without waiting for expiration of a T311 timer.

10 [0005]

In this case, an S1 connection between the radio base station eNB and a switching center MME is maintained without being cut off because the T311 timer has not been expired. For this reason, when the switching center MME receives an incoming
15 signal, data or the like addressed to the mobile station UE, the switching center MME transmits the incoming signal and the like to the radio base station eNB whose RRC connection with the mobile station UE is released. This produces a problem that the mobile station UE cannot receive the incoming signal and
20 the like.

[0006]

To solve this problem, the execution of a reconnection procedure by use of a NAS (Non Access Stratum) function of the mobile station UE is under study. However, a specific
25 reconnection procedure using the NAS function of the mobile station UE has not been studied as yet.

[0007]

The present invention has been made in view of the foregoing problem, and an objective thereof is to provide a

mobile communication method and a mobile station which are capable of resolving the above-described defect of the LTE-AS function by defining a specific reconnection procedure performed by the NAS function of a mobile station.

5 [0008]

A first aspect of the present invention is summarized as a mobile communication method in which a mobile station performs communication via a first connection between the mobile station and a radio base station and a second connection
10 between the radio base station and a switching center by use of a first protocol function and a second protocol function, wherein the first protocol function performs processing corresponding to a first protocol which terminates between the mobile station and the radio base station; the second protocol
15 function performs processing corresponding to a second protocol which is an upper protocol of the first protocol and terminates between the mobile station and the switching center; and the method includes the steps of: transmitting, from the first protocol function to the second protocol function, a
20 reconnection request, when the first protocol function detects that the first connection is changed to an idle state; and transmitting, at the second protocol function, a service request, when the second protocol function receives the reconnection request and detects that the first protocol
25 function is in a coverage area.

[0009]

A second aspect of the present invention is summarized as a mobile station configured to perform communication via a first connection between the mobile station and a radio base

station and a second connection between the radio base station and a switching center by use of a first protocol function and a second protocol function, wherein the first protocol function is configured to perform processing corresponding to a first
5 protocol which terminates between the mobile station and the radio base station; the second protocol function is configured to perform processing corresponding to a second protocol which is an upper protocol of the first protocol and terminates between the mobile station and the switching center; the first
10 protocol function is configured to transmit a reconnection request to the second protocol function, upon detecting that the first connection is changed to an idle state; and the second protocol function is configured to transmit a service request, when the second protocol function receives the reconnection
15 request and detects that the first protocol function is in a coverage area.

Effect of the Invention

[0010]

20 As described above, the present invention can provide a mobile communication method and a mobile station which are capable of resolving the above-described defect of the LTE-AS function by defining a specific reconnection procedure performed by the NAS function of a mobile station.

25

Brief Description of the Drawings

[0011]

[Fig. 1] Fig. 1 is an overall configuration diagram of a mobile communication system according to a first embodiment

of the present invention.

[Fig. 2] Fig. 2 is a functional block diagram of a mobile station according to the first embodiment of the present invention.

5 [Fig. 3] Fig. 3 is a sequence diagram showing operations of the mobile communication system according to the first embodiment of the present invention.

[Fig. 4] Fig. 4 is a sequence diagram showing operations of the mobile communication system according to the first
10 embodiment of the present invention.

[Fig. 5] Fig. 5 is a sequence diagram showing operations of the mobile communication system according to the first embodiment of the present invention.

[Fig. 6] Fig. 6 is a sequence diagram showing operations
15 of the mobile communication system according to the first embodiment of the present invention.

[Fig. 7] Fig. 7 is a sequence diagram showing operations of the mobile communication system according to the first embodiment of the present invention.

20

Best Modes for Carrying Out the Invention

[0012]

(Configuration of mobile communication system according to first embodiment of the present invention)

25 A mobile communication system according to a first embodiment of the present invention will be described with reference to Fig. 1 to Fig. 6.

[0013]

As shown in Fig. 1, the mobile communication system

according to this embodiment includes a core network CN, a switching center SGSN of the UMTS (Universal Mobile Telecommunications System) scheme, a radio control station RNC of the UMTS scheme, a radio base station NB of the UMTS scheme, a switching center MME of the LTE scheme, and a radio base station eNB MME of the LTE scheme.

[0014]

As shown in Fig. 2, a mobile station UE includes an ESM function, an EMM function and an LTE-AS function, as functions of the LTE scheme. The mobile station UE includes an SM/SMS function, a GMM function and an UMTS-AS function, as functions of the UMTS scheme.

[0015]

Here, the LTE-AS function and the UMTS-AS function are configured to perform processing corresponding to an AS protocol (a first protocol) which terminates between the mobile station UE and the radio base station eNB/NB.

[0016]

Meanwhile, the EMM function and the GMM function are configured to perform processing corresponding to a NAS protocol (a second protocol) which is an upper protocol of the AS protocol (the first protocol) and terminates between the mobile station UE and the switching center MME/SGSN.

[0017]

Here, the mobile station UE is configured to perform communication via an RRC connection (a first connection) between the radio base station eNB/NB and mobile station UE and via an S1 connection and an Iu connection (a second connection) between the radio base station eNB/NB and the switching center

MME/SGSN.

[0018]

Now, operations of the mobile communication system according to this embodiment will be described below with
5 reference to Fig. 3 to Fig. 6.

[0019]

Firstly, an operation (1) to be performed when a reconnection procedure using the NAS function is normally completed in the mobile communication system according to this
10 embodiment will be described with reference to Fig. 3.

[0020]

As shown in Fig. 3, when communication via the RRC connection is performed between the LTE-AS function of the mobile station UE and a radio base station eNB-A in step S1000,
15 the LTE-AS function starts a T311 timer when a "Radio Link Failure" is detected in the RRC connection in step S1001.

[0021]

The LTE-AS function performs cell search in step S1002. When a cell in which communication can be performed (which is
20 a cell under the control of a radio base station eNB-B in the example of Fig. 3) is detected before the expiration of the T311 timer in step S1003, the LTE-AS function transmits an "RRC Connection Reestablishment Request (a reestablishment request)" to the radio base station eNB-B in step S1004.

25 [0022]

In step S1005, the radio base station eNB-B transmits an "RRC Connection Reestablishment Reject (a reestablishment rejection response)" to the LTE-AS function of the mobile station UE, because the radio base station eNB-B does not have

"UE Context" of the mobile station UE.

[0023]

In step S1006, the RRC connection between the mobile station UE and the radio base station eNB is changed to an idle state without waiting for expiration of the T311 timer, because
5 the LTE-AS function receives the "RRC Connection Reestablishment Reject (the reestablishment rejection response)".

[0024]

10 When there is a cell in which communication can be performed (i.e., within a coverage area), the LTE-AS function transmits an in-coverage notification indicating that fact to the EMM function in step S1007, and transmits "Reconnect request (a reconnection request)" to the EMM function in step S1008.

15 [0025]

Upon receipt of the "Reconnect request (the reconnection request)", the EMM function starts a "Reconnect timer (a service request timer)". Note that time to be measured with the "Reconnect timer" may be set up through a network or
20 set to a fixed value.

[0026]

Here, the EMM function detects that the LTE-AS function is in the coverage area before expiration of the Reconnect timer by way of receiving the above-described in-coverage
25 notification. Accordingly, the EMM function transmits a "Service Request (a service request)" to the LTE-AS function in step S1009.

[0027]

In step S1010, the LTE-AS function transmits an "RRC

Connection Request (an RRC connection request)" to the radio base station eNB-B controlling the cell in which communication can be performed, in response to the "Service Request (the service request)".

5 [0028]

In step S1011, the radio base station eNB-B transmits an "RRC Connection Setup (an RRC connection setting)" to the LTE-AS function. In step S1012, the LTE-AS function transmits an "RRC Connection Setup Complete (RRC connection setting completion)" and a "Service Request (a service request)" to the radio base station eNB-B.

[0029]

In step S1013, the radio base station eNB-B transmits an "S1 Initial UE Message" to the switching center MME. In step S1014, the switching center MME returns an "S1 Initial UE Context Setup" to the radio base station eNB-B.

[0030]

In step S1015, the radio base station eNB-B transmits an "S1 Setup Complete" to the switching center MME. In step S1016, the switching center MME transmits an "S1 Release" to the radio base station eNB-A to instruct release of the S1 connection established between the radio base station eNB-A and the switching center MME.

[0031]

25 In step S1017, the radio base station eNB-A releases the S1 connection established with the switching center MME, and then transmits an "S1 Release Complete" indicating that fact to the switching center MME.

[0032]

In step S1018, an outgoing call procedure is continued, i.e., an authentication procedure, a security procedure, and a call control procedure are performed after establishment of the above-described S1 connection. This enables
5 communications between the LTE-AS function and the radio base station eNB-B as well as between the LTE-NAS function and the switching center MME.

[0033]

Secondly, an operation (2) to be performed when a
10 reconnection procedure using the NAS function is normally completed in the mobile communication system according to this embodiment will be described with reference to Fig. 4.

[0034]

As shown in Fig. 4, when communication via the RRC
15 connection is performed between the LTE-AS function of the mobile station UE and a radio base station eNB-A in step S2000, the LTE-AS function starts a T311 timer when a "Radio Link Failure" is detected in the RRC connection in step S2001.

[0035]

20 The LTE-AS function performs cell search in step S2002. When a cell in which communication can be performed (which is a cell under the control of a radio base station eNB-A in the example of Fig. 4) is detected before expiration of the T311 timer in step S2003, the LTE-AS function transmits an "RRC
25 Connection Reestablishment Request (a reestablishment request)" to the radio base station eNB-A in step S2004.

[0036]

In step S2005, the RRC connection between the mobile station UE and the radio base station eNB is changed to the idle

state, because the T311 timer is expired before the LTE-AS function receives a response to the "RRC Connection Reestablishment Request (the reestablishment request)".

[0037]

5 In step S2007, the LTE-AS function checks that there are no cell in which communication can be performed (i.e., out of the coverage area) and transmits an out-of-coverage notification indicating that fact to the EMM function. Moreover, the LTE-AS function transmits a "Reconnect request (the reconnection request)" to the EMM function in step S2008.

[0038]

 Upon receipt of the "Reconnect request (the reconnection request)", the EMM function starts a "Reconnect timer".

15 [0039]

 Thereafter, in step S2008, the LTE-AS function checks that there is a cell in which communication can be performed now (i.e., within a coverage area now) and transmits an in-coverage notification which indicates that fact to the EMM function.

 Here, the EMM function detects that the LTE-AS function is in the coverage area before expiration of the Reconnect timer by means of receiving the above-described in-coverage notification. Accordingly, the EMM function transmits a "Service Request (the service request)" to the LTE-AS function in step S2009.

[0040]

 In step S2010, the LTE-AS function transmits an "RRC Connection Request (an RRC connection request)" to the radio

base station eNB-A controlling the cell in which communication can be performed, in response to a "Service Request (the service request)".

[0041]

5 In step S2011, the radio base station eNB-A transmits an "RRC Connection Setup (an RRC connection setting)" to the LTE-AS function. In step S2012, the LTE-AS function transmits an "RRC Connection Setup Complete (RRC connection setting completion)" and a "Service Request (a service request)" to the
10 radio base station eNB-A.

[0042]

 Here, when the S1 connection is not established between the radio base station eNB-A and the switching center MME, the radio base station eNB-A transmits an "S1 Initial UE Message"
15 to the switching center station MME in step S2013. The switching center MME returns an "S1 Initial UE Context Setup" to the radio base station eNB-B in step S2014. The radio base station eNB-A transmits an "S1 Setup Complete" to the switching center MME in step S2015.

20 [0043]

 Thereafter, in step S2016, an outgoing call procedure is continued, i.e., an authentication procedure, a security procedure, and a call control procedure are performed. This enables communications between the LTE-AS function and the
25 radio base station eNB-A as well as between the LTE-NAS function and the switching center MME.

[0044]

 Thirdly, an operation to be performed when a reconnection procedure using the NAS function is abnormally

completed in the mobile communication system according to this embodiment will be described with reference to Fig. 5.

[0045]

As shown in Fig. 5, when communication via the RRC
5 connection is performed between the LTE-AS function of the mobile station UE and a radio base station eNB-B in step S3000, the LTE-AS function starts a T311 timer when a "Radio Link Failure" is detected in the RRC connection in step S3001.

[0046]

10 The LTE-AS function performs the cell search in step S3002. Since the LTE-AS function cannot detect the cell in which communication can be performed before expiration of the T311 timer in step S3003, the RRC connection between the mobile station UE and the radio base station eNB is changed to the idle
15 state in step S3004.

[0047]

In step S3005, the LTE-AS function checks that there are no cell in which communication can be performed (i.e., out of the coverage area) and transmits an out-of-coverage
20 notification indicating that fact to the EMM function. Moreover, the LTE-AS function transmits an "Reconnect request (the reconnection request)" to the EMM function in step S3006.

[0048]

Upon receipt of the "Reconnect request (the
25 reconnection request)", the EMM function starts a "Reconnect timer".

[0049]

Thereafter, since the EMM function cannot detect that the LTE-AS function is in the coverage area before expiration

of the Reconnect timer, the EMM function does not transmit a "Service Request (the service request)" to the LTE-AS function in step S3007, even when an in-coverage notification is received from the LTE-AS function.

5 [0050]

Fourthly, an operation (3) to be performed when a reconnection procedure using the NAS function is normally completed in the mobile communication system according to this embodiment will be described with reference to Fig. 6.

10 [0051]

As shown in Fig. 6, when communication via the RRC connection is performed between the LTE-AS function of the mobile station UE and a radio base station eNB-A in step S4000, the LTE-AS function starts a T311 timer when a "Radio Link Failure" is detected in the RRC connection in step S4001.

[0052]

The LTE-AS function performs the cell search in step S4002, and detects a cell in which communication can be performed of a UTRA (UMTS Terrestrial Radio Access) scheme in step S4003 before expiration of the T311 timer.

[0053]

In this case, in step S4004, the RRC connection between the mobile station UE and the radio base station eNB is changed to the idle state without transmitting an "RRC Connection Reestablishment Request (the reestablishment request)" by the LTE-AS function and without waiting for expiration of the T311 timer.

[0054]

In step S4005, a change is made so as to allow the UMTS-AS

function to perform the reconnection procedure instead of the LTE-AS function.

[0055]

5 In step S4006, the UMTS-AS function transmits a "Reconnect request (the reconnection request)" to the GMM function in step S4006. In step S4007, the UMTS-AS function checks that there is a cell in which communication can be performed (i.e., within the coverage area) and transmits an in-coverage notification indicating that fact to the GMM
10 function.

[0056]

Alternatively, after the RRC connection between the mobile station UE and the radio base station eNB is changed to the idle state as described above in step S4004, the LTE-AS
15 function may transmit a "Reconnection request (the reconnection request)" to the EMM function in step S4004A, and may change RAT in step S4005 (see Fig. 7). In this case, the EMM function needs to transmit the "Reconnect request (the reconnection request)" to the GMM function in step S4006.

20 [0057]

Upon receipt of the "Reconnect request (the reconnection request)", the GMM function starts a "Reconnect timer".

[0058]

25 Here, the GMM function detects that the UMTS-AS function is in the coverage area before expiration of the Reconnect timer by way of receiving the above-described in-coverage notification. Accordingly, the GMM function transmits a "Service Request (a service request)" to the UMTS-AS function

in step S4008.

[0059]

In step S4009, the UMTS-AS function transmits an "RRC Connection Request (an RRC connection request)" to the radio base station NB and the radio control station RNC controlling the cell in which communication can be performed, in response to the "Service Request (the service request)".

[0060]

In step S4010, the radio control station RNC transmits an "RRC Connection Setup (an RRC connection setting)" to the UMTS-AS function. In step S4011 and step 4012, the UMTS-AS function transmits an "RRC Connection Setup Complete (RRC connection setting completion)" and a "Service Request (a service request)" to the radio base station NB and the radio control station RNC.

[0061]

In step S4013, the radio control station RNC transmits an "S1 Initial UE Message" and a "Service Request" to the switching center SGSN.

[0062]

Thereafter, the switching center SGSN transmits an "S1 Release" to the switching center MME to instruct the release of the S1 connection established between the radio base station eNB and the switching center MME.

[0063]

Here, when the S1 connection is established, the switching center MME transmits an "S1 Release" to the radio base station eNB to instruct the release of the S1 connection established between the radio base station eNB and the switching

center MME in step S4015.

[0064]

In step S4016, the radio base station eNB releases the S1 connection established with the switching center MME, and
5 then transmits an "S1 Release Complete" indicating that fact to the switching center MME.

[0065]

In step S4017, an outgoing call procedure is continued, i.e., an authentication procedure, a security procedure, and
10 a call control procedure are performed, after establishment of the above-described Iu connection. This enables communications between the UMTS-AS function and both of the radio base station NB and the radio control station RNC, as well as between the UMTS-NAS function and the switching center SGSN.

15 [0066]

(Advantageous Effects of mobile communication system according to first embodiment of the present invention)

According to the mobile communication system of the first embodiment of the present invention, when the RRC
20 connection is in the idle state, the EMM function can release the S1 connection that remains without being cut off after the RRC connection turns into the idle state by transmitting the Service Request in response to receipt of the in-coverage notification and the Reconnect request from the LTE-AS
25 function.

[0067]

As a result, it is possible to eliminate a trouble that would be caused when the switching center MME transfers an incoming signal and the like addressed to the mobile station

UE to the radio base station eNB with which the RRC connection is not established.

[0068]

Moreover, according to the mobile communication system of the first embodiment of the present invention, the EMM function is configured not to transmit the Service Request even when the LTE-AS function enters the coverage area after expiration of the Service Request timer. Thereby, it is possible to avoid useless transmission of the Service Request.

[0069]

(Modification)

Note that operation of the above described switching center MME, the radio base station eNB and the mobile station UE may be implemented by means of hardware, a software module executed by a processor, or a combination of both.

[0070]

The software module may be provided in any type of storage medium such as an RAM (Random Access Memory), a flash memory, a ROM (Read Only Memory), an EPROM (Erasable Programmable ROM), an EEPROM (Electrically Erasable and Programmable ROM), a register, a hard disk, a removable disk, or a CD-ROM.

[0071]

The storage medium is connected to the processor so that the processor can read and write information from and to the storage medium. Also, the storage medium may be integrated into the processor. Also, the storage medium and the processor may be provided in an ASIC. The ASIC may be provided in the switching center MME, the radio base station eNB and the mobile

station UE. Also, the storage medium and the processor may be provided in the switching center MME, the radio base station eNB and the mobile station UE as a discrete component.

[0072]

5 Hereinabove, the present invention has been described in detail using the above embodiment; however, it is apparent to those skilled in the art that the present invention is not limited to the embodiment described herein. Modifications and variations of the present invention can be made without
10 departing from the spirit and scope of the present invention defined by the description of the scope of claims. Thus, what is described herein is for illustrative purpose, and has no intention whatsoever to limit the present invention.

CLAIMS

[Claim 1]

A mobile communication method in which a mobile station
5 performs communication via a first connection between the
mobile station and a radio base station and a second connection
between the radio base station and a switching center by use
of a first protocol function and a second protocol function,
wherein

10 the first protocol function performs processing
corresponding to a first protocol which terminates between the
mobile station and the radio base station;

the second protocol function performs processing
corresponding to a second protocol which is an upper protocol
15 of the first protocol and terminates between the mobile station
and the switching center; and

the method comprises the steps of:

transmitting, from the first protocol function to the
second protocol function, a reconnection request, when the
20 first protocol function detects that the first connection is
changed to an idle state; and

transmitting, at the second protocol function, a
service request, when the second protocol function receives the
reconnection request and detects that the first protocol
25 function is in a coverage area.

[Claim 2]

A mobile station configured to perform communication
via a first connection between the mobile station and a radio

base station and a second connection between the radio base station and a switching center by use of a first protocol function and a second protocol function, wherein

5 the first protocol function is configured to perform processing corresponding to a first protocol which terminates between the mobile station and the radio base station;

10 the second protocol function is configured to perform processing corresponding to a second protocol which is an upper protocol of the first protocol and terminates between the mobile station and the switching center;

 the first protocol function is configured to transmit a reconnection request to the second protocol function, upon detecting that the first connection is change to an idle state; and

15 the second protocol function is configured to transmit a service request, when the second protocol function receives the reconnection request and detects that the first protocol function is in a coverage area.