C L A I M S

1. A method for wireless communication, comprising:

receiving, by a first node, a downlink control information (DCI) command scheduling a transmission of a first signal comprising a physical downlink shared channel (PDSCH);

determining, by the first node, a transmission configuration indicator (TCI) state for transmission of a second signal based on the DCI command, wherein the second signal comprises an uplink signal, and wherein the TCI state is indicated by at least one TCI field and comprises a quasi-co location (QCL) type D reference signal; and

communicating, by the first node, the second signal with a second node according to the TCI state.

2. The method of claim 1, wherein the second signal comprises at least one of: a physical uplink control channel (PUCCH), a channel-state information reference signal (CSI-RS), a sounding reference signal (SRS), or a physical uplink shared channel (PUSCH).

3. The method of claim 1, wherein the TCI state is determined according to a second transmission parameter in a radio resource control (RRC) signaling.

4. The method of claim 3, wherein the second transmission parameter is configured as enabled.

5. The method of claim 3, wherein the second signal comprises a sounding reference signal (SRS).

6. The method of claim 1, wherein the TCI state is determined based on the DCI command after one or more symbols after a time that a response signal associated with the DCI command is communicated.

7. The method of claim 6, wherein the response signal comprises a hybrid automatic repeat request (HARQ) signal for the PDSCH scheduled by the DCI command.

8. A wireless communications apparatus comprising:

a memory storing a plurality of instructions; and

a processor configured to execute the plurality of instructions, and upon execution of the plurality of instructions, is configured to:

receive a downlink control information (DCI) command scheduling a transmission of a first signal comprising a physical downlink shared channel (PDSCH);

determine a transmission configuration indicator (TCI) state for transmission of a second signal based on the DCI command, wherein the second signal comprises an uplink signal, and wherein the TCI state is indicated by at least one TCI field and comprises a quasi-co location (QCL) type D reference signal; and

communicate the second signal with a second node according to the TCI state.

9. The wireless communications apparatus of claim 8, wherein the second signal comprises at least one of: a physical uplink control channel (PUCCH), a channel-state information reference signal (CSI-RS), a sounding reference signal (SRS), or a physical uplink shared channel (PUSCH).

10. The wireless communications apparatus of claim 8, wherein the processor is configured to determine the TCI state for the transmission of the second signal according to a second transmission parameter in a radio resource control (RRC) signaling.

11. The wireless communications apparatus of claim 10, wherein the second transmission parameter is configured as enabled.

12. The wireless communications apparatus of claim 10, wherein the second signal comprises a sounding reference signal (SRS).

13. The wireless communications apparatus of claim 8 wherein the processor is configured to determine the TCI state for the transmission of the second signal based on the DCI command after

one or more symbols after a time that a response signal associated with the DCI command is communicated.

14. The wireless communications apparatus of claim 13, wherein the response signal comprises a hybrid automatic repeat request (HARQ) signal for the PDSCH scheduled by the DCI command.

15. A method for wireless communication, comprising:

transmitting, by a second node, a downlink control information (DCI) command scheduling a transmission of a first signal comprising a physical downlink shared channel (PDSCH), wherein the DCI command indicates to a first node receiving the DCI command to determine a transmission configuration indicator (TCI) state for transmission of a second signal based on the DCI command, wherein the second signal comprises an uplink signal, and wherein the TCI state is indicated by at least one TCI field and comprises a quasi-co location (QCL) type D reference signal; and

communicating, by the second node, the second signal with the first node according to the TCI state.

16. The method of claim 15, wherein the second signal comprises at least one of: a physical uplink control channel (PUCCH), a channel-state information reference signal (CSI-RS), a sounding reference signal (SRS), or a physical uplink shared channel (PUSCH).

17. The method of claim 15, wherein the TCI state for the transmission of the second signal is determined according to a second transmission parameter in a radio resource control (RRC) signaling.

18. The method of claim 17, wherein the second transmission parameter is configured as enabled.

19. The method of claim 17, wherein the second signal comprises a sounding reference signal (SRS).

20. The method of claim 15, wherein the TCI state for the transmission of the second signal based on the DCI command is determined after one or more symbols after a time that a response signal associated with the DCI command is communicated.

21. The method of claim 20, wherein the response signal comprises a hybrid automatic repeat request (HARQ) signal for the PDSCH scheduled by the DCI command.

22. A wireless communications apparatus comprising:

a memory storing a plurality of instructions; and

a processor configured to execute the plurality of instructions, and upon execution of the plurality of instructions, is configured to:

transmit a downlink control information (DCI) command scheduling a transmission of a first signal comprising a physical downlink shared channel (PDSCH), wherein the DCI command indicates to a first node receiving the DCI command to determine a transmission configuration indicator (TCI) state for transmission of a second signal based on the DCI command, wherein the second signal comprises an uplink signal, and wherein the TCI state is indicated by at least one TCI field and comprises a quasi-co location (QCL) type D reference signal; and

communicate the second signal with the first node according to the TCI state.

23. The wireless communications apparatus of claim 22, wherein the second signal comprises at least one of: a physical uplink control channel (PUCCH), a channel-state information reference signal (CSI-RS), a sounding reference signal (SRS), or a physical uplink shared channel (PUSCH).

24. The wireless communications apparatus of claim 22, wherein the TCI state for the transmission of the second signal is determined according to a second transmission parameter in a radio resource control (RRC) signaling.

25. The wireless communications apparatus of claim 24, wherein the second transmission parameter is configured as enabled.

26. The wireless communications apparatus of claim 24, wherein the second signal comprises a sounding reference signal (SRS).

27. The wireless communications apparatus of claim 22, wherein the TCI state for the transmission of the second signal based on the DCI command is determined after one or more symbols after a time that a response signal associated with the DCI command is communicated.

28. The wireless communications apparatus of claim 27, wherein the response signal comprises a hybrid automatic repeat request (HARQ) signal for the PDSCH scheduled by the DCI command.