

PCT


WORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : H04M	A2	(11) International Publication Number: WO 97/37478 (43) International Publication Date: 9 October 1997 (09.10.97)
(21) International Application Number: PCT/US97/04616 (22) International Filing Date: 21 March 1997 (21.03.97) (30) Priority Data: 08/620,474 22 March 1996 (22.03.96) US (71) Applicant: ERICSSON INC. [US/US]; 7001 Development Drive, Research Triangle Park, NC 27709 (US). (72) Inventors: GESSEL, Robert, J.; 3908 E. Park Boulevard, Plano, TX 75074 (US). AUTREY, Kevin; 629 Kirkwood Drive, Dallas, TX 75218 (US). (74) Agents: SMITH, Steven, W. et al.; Smith & Catlett, P.C., Suite 707, 2011 North Collins Boulevard, Richardson, TX 75080-2645 (US).		(81) Designated States: AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GH, HU, IL, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG SI, SK, TJ, TM, TR, TT, UA, UG, UZ, VN, YU, ARIPO patent (GH, KE, LS, MW, SD, SZ, UG), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG). Published Without international search report and to be republished upon receipt of that report.

(54) Title: PROTOCOL INTERFACE GATEWAY



(57) Abstract

A protocol interface gateway (84) connects a telecommunication system emulator (72) to a communications network (79). The gateway (84) receives signals from the network (79) and sends signals to the network that are formatted in a network protocol. The gateway converts signals received from the network into instructions in emulator code, and sends the instructions in emulator code to the emulator (72) for processing. The emulator executes code in blocks of application software (85) utilized in a target telecommunications node. The gateway then receives the processed instructions in emulator code from the emulator, converts the processed instructions into signals formatted in the network protocol, and sends the signals to the communications network (79). The protocol interface gateway (84) utilizes a UNIX socket (83) that replaces Open Systems Interconnection (OSI) layers (1 and 2) of the network protocol to send and receive the signals from the network.