

Description

This invention relates to electrical connector systems and, more particularly, relates to zero insertion force type systems adapted for use in high density electronic packaging.

In the field of electronic circuit packaging with the progression towards increasingly dense packages, delicate components, and increasingly finer pitch lines, there is a need for reliable interconnection between a multiplicity of contact points (as for example, between circuit cards and mother boards) wherein the forces required to be exerted in order to effect such interconnections is minimized or ideally eliminated. Accordingly, connector systems have been developed in the industry which avoid the destructive forces exerted by conventional systems on these delicate and dense circuit packages occurring during the act of effecting interconnections, for example by the insertion of a printed circuit card into a conventional edge connector.

Accordingly, a type of connector known in the art as a zero insertion force connector has been developed. Typically, in the operation of such connectors, pins carried on a package to be interconnected to a host board, card, or the like carry a plurality of pins which mate into a like pattern of holes disposed in the host receptacle. A variety of mechanical mechanisms are provided whereby once these pins are inserted into the holes, lateral forces are imparted on the pins by metallic contacts carried by the host thereby effecting the desired electrical interconnections. The holes are usually sized relative to the pins so that the initial insertion force is minimal, with the primary forces necessary to effect the interconnections being side forces. The benefits of such zero insertion force connectors are that the risk of damage to the circuitry is certainly reduced during the interconnection operation. A representative example of such a zero insertion force connector system is described in IBM Technical Disclosure Bulletin, Vol. 17, No. 2, July 1974, pages 440-441 (see also US-A-3.495.132).

Notwithstanding the development of such connector systems numerous problems still remain which are compounded by the increasingly denser modern packaging techniques. These techniques have resulted in increasingly more delicate circuit lines and circuit packages which cannot withstand the forces circuit packages are subjected to upon insertion into conventional connector systems. One problem, as is clearly evident in the hereinbefore noted connector system is the sheer mechanical complexity of these systems giving rise to reliability problems, unacceptable manufacturing costs and the like. This mechanical complexity is due in part to the need to provide for these lateral con-

necting forces after the initial contact between the circuit package and the host. As a result of this mechanical complexity, the density of contact points on a circuit package which might be reliably interconnected is severely restricted.

Another approach known in the art for minimizing the forces necessary to be exerted on a contact point to effect electrical interconnections employs the properties of buckling beams, the general concepts of which may be found discussed in "Engineering Mechanics of Deformation Bodies", second edition 1969, Chapter 11 by Snyder Byars. The fundamental concept is to capitalise on the property of a buckling beam that a readily constant predetermined and controllable force is necessary to compress the buckling beam member in its longitudinal direction. Two contact points to be electrically interconnected are urged into contact with respective ends of the beam and by further thereafter urging them towards one another, which requires a relatively constant nominal force which might be preselected and controlled by exercising good design, the desired interconnection is effected. This technique has been employed typically, for example, in probes, used in various types of test equipment.

However several serious obstacles remain in transferring the benefits of the properties of buckling beams into the electrical connector art. First, applications of such buckling beams wherein the electrical interconnections are effected by longitudinal movement of the contact points into engagement with the buckling beam ends is typically limited to applications wherein permanent electrical interconnections is not desired but rather only ones of a temporary nature as, for example, in the case of test probes and related equipment. Although the forces required for effecting interconnections by use of the buckling beam principle are admittedly reduced from those of more conventional approaches such as those encountered in typical press fit edge connectors, means are typically not provided for maintaining these forces permanently in the context of connector systems. This is quite understandable in the application to test equipment wherein the desired interconnections are intended to be quite momentary. Furthermore, application of this technique is also typically encountered with single probes wherein again the need is for effecting only a momentary contact. Whereas it is true that for example in the connector disclosed in the aforementioned Technical Disclosure Bulletin provision is made for a plurality of such buckling beams, it is further typical that the actual mechanical interconnection to the plurality of pins is effected by means of side forces.

Furthermore, yet an additional drawback to attempted applications of buckling beams in connec-

tor systems remains. Although it is true the necessary insertion force for contact might be significantly reduced over that required by conventional systems, such force is nevertheless still required (as contrasted, for example, with the true zero insertion force connectors known in the art with their attendant mechanical complexities). With the increased density of contact points in modern electronic packaging technology, such reduced forces when multiplied by the number of necessary connections to be made still heretofore render the cumulative longitudinal compressional buckling forces unacceptable for the connector makeup.

For the foregoing and other reasons, an electrical connector system has been long needed in the art which provides the benefits of both zero insertion force connectors as well as interconnections effected by means of buckling beams wherein the contacts might be made by contact points on the ends of circuit packages when brought into engagement with the buckling beams rather than through the conventional use of lateral forces. Such a connector system has been further highly sought after which call not only provide for end point contacts, but is mechanically simply, reliable, inexpensive to manufacture, and readily adaptable to the vastly increased contact point densities and connector requirements wherein even minute insertion forces are intolerable. These and other deficiencies of the connector systems of the prior art are overcome by the subject invention.

Therefore, in accordance with the present invention there is provided electrical connector apparatus for interconnecting a circuit package to a card according to claim 1.

According to a preferred feature of one embodiment of the invention the apparatus further comprises a second buckling beam strip and the buckling controller also applies a force on the second buckling beam strip and also selectively urges the second buckling beam strip into a second cavity portion defined by the housing, to establish pre-buckling of the second buckling beam strip

In another embodiment of the invention the housing defines a cavity and includes an extension receivable by the cavity; and the buckling beam strip is disposed between the cavity and the extension whereby upon urging of the extension into the cavity the pre-buckling of the buckling beam strip occurs.

According to a preferred feature of this embodiment invention during the pre-buckling, the buckling beam strip is urged into the cavity by contact with the extension.

According to another preferred feature of the invention the housing engages the circuit package.

According to another preferred feature of the invention the releasing means includes means for

the effecting of the releasing in functional response to the engaging of the housing by the circuit package.

According to an alternative preferred feature of the invention the housing includes a means for urging the buckling beam strip into a cavity defined within the housing means by rotation of the urging means.

According to another preferred feature of the invention the urging means is within the cavity.

According to another preferred feature of the invention the cavity is comprised of a left and a right portion; and the urging means includes means for alternately urging each strip into and out of a corresponding one of the cavity portions and into and out of the buckling state.

According to another aspect of the invention there is provided a method for establishing a plurality of electrical interconnections, each being between one of a plurality of first contact points and one of a plurality of second contact points, comprising disposing a buckling beam contact means having a plurality of contact wires between the first and second pluralities of contact points; pre-buckling the buckling beam contact means; and releasing the buckling of the buckling beam contact means until each of the contact wires establishes one of the interconnections.

According to a preferred feature of this aspect of the invention the step of disposing the buckling beam contact means comprises positioning a housing defining a cavity therein between the pluralities of first and second contact points; and disposing the buckling beam contact means within the housing with the axial direction of the contact wires oriented towards the pluralities of first and second contact points.

According to another preferred feature of the invention the pre-buckling comprises urging the buckling beam contact means into the cavity.

According to another preferred aspect of the invention the urging is in a direction transverse to the axial direction.

According to another preferred aspect of the of the invention the buckling beam contact means comprises first and second buckling beam strips disposed in parallel within the housing; the cavity defines first and second portions; and the step of urging of the buckling beam contact means comprises urging the first and the second strips away from each other and into the first and second cavity portions, respectively.

According to another preferred feature of the invention the method further includes urging the first plurality of contact points in the axial direction toward the housing. The releasing of the buckling is in response to the urging of the first plurality of contact points.

According to an alternative preferred feature of the invention the housing includes a buckling controller disposed between the first and the second strips; and the pre-buckling includes the step of rotating the controller to a first position. The releasing step includes the step of rotating the controller to a second position.

It is a preferred feature of the invention that the first plurality of contact points are disposed in a circuit package; and that the method further includes releasably interconnecting the circuit package to the housing.

According to another preferred feature of the invention the step of releasing the buckling is during the releasable interconnection of the circuit package to the housing.

The invention will be best understood by reference to the following description of the embodiments, when read in conjunction with the accompanying figures, wherein:

Fig. 1 is a pictorial illustration of the connector system of the present invention in assembly with a circuit package and board;

Fig. 2 is an exploded pictorial view of the illustration of the connector system of Fig. 1;

Fig. 3 is a front pictorial view of the second housing half portion of the connector system of Fig. 1 when viewed from lines 3-3;

Figs. 4a-e are simplified end elevational views of the connector system of the present invention depicted in Fig. 1 taken along line 4-4 illustrating the sequence of steps for effecting electrical interconnections between the circuit package and board of Fig. 1 in the manner of the invention;

Fig. 5 is an enlarged pictorial view of one of the buckling beam strips and the elastomeric connector strip of Fig. 1;

Fig. 6 is a simplified elevational end view in section of an alternate embodiment of the housing of Fig. 1 prior to assembly;

Fig. 7 is another simplified end view in section of the alternate embodiment of the housing depicted in Fig. 6 in assembly;

Fig. 8 is a simplified elevational end view in section of the alternate embodiment of the connector system of Fig. 6 when installed on a card and prior to effecting electrical interconnection between the card and the circuit package.

Referring first to Fig. 1, a connector system 10 of the present invention is shown in assembly with a circuit package 22 and board 36. The circuit package includes an elastomeric connector strip 28 (shown in greater detail in Fig. 5) having a plurality of first contacts 122, Fig. 5, and a board 36 having disposed thereon a second plurality of contacts 130. It will be recalled that the purpose of the connector system 10 is to effect a reliable intercon-

nection between preselected ones of the first contacts with corresponding preselected ones of the second contacts. The manner in which this is accomplished will be discussed only in a general way with reference to only those components necessary to gain a general understanding of the operation of the invention with particular reference to the sequence of operation depicted in Figs. 4a-e before thereafter describing the various components in greater detail. The purpose in effecting such interconnections by the invention is to interconnect circuits in a desired fashion at one location such as on the carrier 24 with those disposed at another location such as on the board 36. However, although in the embodiments depicted herein these circuits which are desired to be interconnected are shown as being disposed on carrier 24 and boards 36, it will be readily appreciated that the invention is far broader in scope and not intended to be limited to any particular locations wherein circuits reside which are to be connected.

Still referring to Fig. 2, the connector system 10 includes a housing comprised of first and second halves 12, 14, respectively, a buckling controller 16, and one or more buckling beam strips, each carrying a plurality of buckling beams or contact wires, such as the first and second strips 18, 20, respectively. These strips may, for example, be fabricated from a polymer film carrier having laminated thereon a metal foil with preselected spring properties. After lamination, lithographic techniques are used to form a series of electrically isolated metallic beams or contact wires on the carrier.

With more particular reference to the components of the circuit package 22, residing on the carrier 24 are a plurality of circuit modules 26. The carrier 24 is circuitized as desired including interconnections to the circuit modules 26 or other components as desired and has lead outs to the carrier edge 30. Further comprising the circuit package 22 is a carrier housing 32 defining a plurality of apertures 80 into which the modules 26 extend. Heat sinks 34 may be provided which may be affixed to the modules 26 as desired.

As shown in Fig. 4c, with the circuit package 22 in assembly the elastomeric strip 28 is retained at the lower edge of housing 32 in a pocket defined by housing lip 82 and carrier edge 30 of the carrier 24. With the first and second housing halves disposed together on the board 36 with the buckling controller 16 and buckling strips 18, 20 disposed therein in the manner shown in Fig. 1 and Figs. 4a-4e, the operation of the connector system 10 may now be generally understood with reference to these Figs. 4a-4e which depict the sequence of operation in effecting the desired interconnections.

The general sequence is that first the buckling strips 18, 20 are pre-buckled, i.e., spread laterally

outwards from the orientation shown in Fig. 4a to that of Fig. 4b by proper rotation of the buckling controller 16 in preparation for receipt of the circuit package 22. With the buckling beams thus readied and in a pre-buckled state, as shown in Fig. 4c the preassembled circuit package 22 is urged downwards into the position shown in Fig. 4d whereby the lower portion of the circuit package 22 including the elastomeric strip 28 is retainedly disposed in the carrier housing cavity 44 (Fig. 4a).

Comparison of Figs. 4d and 4e indicates that upon subsequent rotation of the buckling controller 16 an additional 90 degrees, the buckling strips 18, 20 are thereby returned to their more elongate configurations shown in Fig. 4e thereby resembling their initial unbuckled states of Fig. 4a by re-extending themselves in the direction shown by arrows 54. The effect of such reconfiguring of the strips 18, 20 is to effect the desired electrical interconnections between each preselected one of the plurality of first contacts on the circuit package 22 with a corresponding preselected one of the plurality of second contacts 130 disposed on the board 36. More particularly, as may be more clearly seen with reference to Fig. 5, by the aforementioned release of the pre-buckled wires or beams 120, for example, of strip 18, they may be brought into mating electrical engagement with pads 122 of elastomeric strip 28. Pre-buckled wires 123 may, in like manner, be brought into like engagement with pads 130 carried on board 36 to thereby complete the desired interconnections. Moreover, remaining ones of such wires as, for example, wires 121 may remain in electrical isolation with respect to strip 28 and board 36 by reason of separation of pads 122 in the elastomeric strip 28 by non-conducting pads 124 and the omission of contacts in vertical registry with these wires 121 on the surface of board 36.

Now that a general understanding of the construction of the connector system 10 and its operation has been provided a more detailed discussion hereinafter follows of more particular features of the invention.

Referring back to Fig. 2, the buckling beam strips 18 and 20, as previously indicated with reference to Fig. 5, include pluralities of first contacts comprised of wire-like extensions 19, 21, 23, and 25. Each of these extensions is actually only an exposed portion of a thin contact wire or buckling beam member extending through a carrier 143, 144.

Still referring to Fig. 2 in the embodiment depicted therein the housing may be seen to actually be comprised of first and second housing halves 12 and 14 having inner faces 60 and 62 (Fig. 3), respectively. With the housing halves 12, 14 assembled in the manner shown in Fig. 1 and Figs. 4a - 4e, these inner faces 60, 62 define a cavity

bifurcated by the first and second strips 18, 20 into first and second cavity portions 38 and 40 into which the strips 18, 20 are urged upon rotation of the controller 16. The housing halves 12, 14 may be releasably held together with a number of appropriate means such as the clips 146 shown in Fig. 1. Slots 64 extend through the opposing ends of first housing half 12 so as to slidably and matingly receive guide members 66 on opposing ends of the second housing half 14. Apertures 68 are further disposed in the opposing ends of first housing half 12 in the longitudinal direction thereof so as to communicate with the slots 64. These apertures 68 are intended to matingly and rotatably receive cylindrical nubs 70 disposed on extending ends of the buckling controller 16 and may include slots 74. By means of these slots 74, when the buckling controller is thereby installed in assembly and retainably held within the housing halves 12, 14 (by reason of insertion of these nubs 70 into their respective mating apertures 68) the buckling controller 16 may fully rotated about its longitudinal axis 42 very readily. More particularly by accessing these slots 74 through their respective apertures 68 by an appropriate tool such as a screwdriver or the like the controller 16 may be rotated.

From the preceding discussion of the general operation of the connector system 10 it will be appreciated that the purpose for effecting such rotation of the buckling controller, is to pre-buckle and effect release of such pre-buckling forces in the buckling strips in the manner illustrated in the drawing sequence of Figs. 4a-4e. The ends of the guides 66 on the opposing ends of the second housing half 14 may be seen to be semicircularly shaped so as to readily conform about the screw heads 70 of the buckling controller 16 when the controller 16 and first and second halves are in assembly. Apertures 72 may also be provided in the opposing ends of the first housing half 12 to receive nubs 71 extending axially outwards from opposing ends of the second housing half 14. These nubs will receive retention screws through apertures 72 to hold the housing halves and controller 16 in assembly.

Still referring to Fig. 2, the upper portion of the housing lip 82 may preferably include a retention surface 78 intended to matingly engage a like second housing half retention surface 76 and housing half 14. As may be seen from Fig. 4d, upon insertion of the lower end of the circuit package 22 into the carrier housing cavity 44, these surfaces 76-78 thereby engage one another so as to retain the circuit package 22 within the cavity 44. This is so notwithstanding the upward force acting upon the package 22 by release of the pre-buckling forces when the buckling controller 16 is reoriented about its longitudinal controller axis 42 from the

position shown in Fig. 4d to that of Fig. 4e. Slots 56, 58, Fig. 2, may be provided extending vertically downwards into the first housing half 12 from the upper surface thereof, the purpose of which is to matingly and slidably receive corresponding edges 58a, 56a, respectively, of the carrier 24 when the lower end of the circuit package 22 is disposed within the carrier housing cavity 44, as shown in Fig. 4d.

The buckling controller 16 may be seen to include an elongate paddle-like or vane shaped extension 72 extending along the longitudinal axis 42 of the controller in opposing directions normal thereto. The purpose of this extension 72 it will be recalled is twofold. First, with the plane defined by the extension 72 extending in a generally upwards direction parallel to the planes defined by the vertically extending buckling strips 18, 20, as shown in Fig. 4a, the strips 18, 20, are in an unbuckled state. However, upon rotation of the controller 16 about the axis 42 in either direction 90 degrees so as to bring the extension 72 into the position shown in Fig. 4b, opposing outward forces are thereby exerted by the extension 72 on the strips 18, 20 so as to urge them into their respective first and second cavity portions 38, 40 as shown in Fig. 4b, thereby effecting the first purpose of the controller 16, namely to place the buckling beam strip in a pre-buckled state.

The second purpose of the controller 16 and extension 72 may be further recalled with reference to Figs. 4d and 4e whereby upon subsequent rotation again of the extension 72 in yet an additional 90 degrees relative to the position shown in Fig. 4d after insertion of the lower portion of the circuit package 22 into the housing cavity 44, this pre-buckling state of the buckling beam strip is thereby released. This in turn causes the upper wire extension 19, 23 of corresponding strips 18 and 20 to contact the elastomeric strip 28 at locations 46, 48, respectively as shown in Fig. 4d. Similarly, this release of the pre-buckling forces also causes more secure engagement of the lower wire extension 21, 25, Fig. 2, with desired ones of the plurality of second contacts carried on the board 36 such as those depicted at reference numerals 130, Fig. 5 as shown at locations 50, 55, Fig. 4a.

With reference now to Figs 6 and Fig. 7, an alternate embodiment connector system 88 is depicted therein employing only one buckling beam strip. More particularly, in Fig. 6, this alternate connector system 88 is shown in a preassembled state whereas in Fig. 7 it is shown in an assembled state in preparation for effecting the desired interconnection between the plurality of first and second contacts. Referring first to Fig. 6 in more detail, first and second housing halves 90, and 92 are shown which are correlative to first and second housing

halves 12, 14 of the embodiment of Fig. 1. Moreover, in like manner, the first housing member 90 is seen to include an inner surface 96 defining a cavity 98. This surface may be conductive and in electrical contact with one or more of the wires or beams of the buckling beam strip it contains.

The second housing half 92 includes an extension 104 extending longitudinally the length of the housing halves 90, 92, as does the cavity 98. A single elastomeric strip 94 is provided in this embodiment having the axially outwardly extending wire contact portions 110, 112 in opposing relationship.

In assembly, as shown by comparison of Fig. 6 and 7, by urging the first and second housing halves 90, 92 towards one another in the direction shown by arrows 100, 102, the housing is thereby accordingly urged into assembly the intermediate stage of which is shown in Fig. 7. As was the case with respect to the embodiment shown in Fig. 1 when the extension vane 72 was oriented in the configuration of Fig. 4c, by such assembly of the housing halves in the manner shown in Fig. 7 the buckling beam strip 94 is accordingly deformed or pre-buckled by means of the extension 104 acting against the central portion of the buckling beam strip 94 thereby urging it inwardly into the cavity 98. Pluralities of first and second contacts functionally analogous to those on elastomeric strip 28 and board 36 are shown schematically at reference numerals 106, 108, respectively. Upon release of this pre-buckling force in a manner to be hereinafter described with reference to Fig. 8, it will be appreciated that the similar operation of electrical interconnections as desired between first and second contact points 106, 108 is thereby effected through the buckling beam strip 94.

Thus, with reference now to Fig. 8, there will be seen depicted therein schematically a board 112 carrying a board housing 110 which has a cavity 118 disposed therein for retainably receiving the housing assembly shown in Figs. 6-7. The card 112 will be seen to have disposed thereon a plurality of second contacts 108. In like manner, a circuit package 114 may be seen to include a plurality of first contacts 106. The circuit package 114 further may preferably include a wedge pry mechanism 116. Upon urging the circuit package 114 in a generally downwards direction as shown by arrow 150 whereby the wedge pry mechanism 116 is thereby caused to engage the upper surface of the housing assembly, the first and second housing assembly halves 90, 92 are thereby moved laterally in opposing directions from those shown by the arrows 100, 102 in Fig. 6. In this manner (similarly to the effect of rotating the extension vane 72 from the orientation of Fig. 4d to that of Fig. 4e, the pre-buckling shown in Fig. 7 of the buckling strip is

thereby released so as to effect the various electrical interconnections between the first and second contacts 106, 108 as desired. By provision of members 152 on the circuit package 114 and 154 on the housing 110, by interaction therebetween as shown in Fig. 8 during the urging of the circuit package 114 toward the card 112, the package 114 is thereby latched to the board housing 110.

Therefore, in an embodiment of the invention there is provided apparatus for providing low insertion force electrical interconnections between high density contacts for use in interconnecting circuit packages. A housing has disposed therein one or more pre-buckled beam connectors. Each connector has a resilient insulating strip carrying a plurality of buckling beams electrically isolated from each other. The beams are aligned on the plane defining the strip in parallel with ends extending away from the strip edges in opposing directions. Means are provided for deforming the strip within the housing prior to effecting desired interconnections whereby the beams are pre-buckled. Upon urging contacts into proximity with the beam ends, the buckling force is released causing each beam's ends to be urged away from the strip into engagement with respective contacts, thereby effecting desired interconnection between contacts and through one or more beams.

While the invention has been shown and described with reference to particular embodiments thereof, it will be understood by those skilled in the art that the foregoing and other changes in form and details may be made therein without departing from the scope of the invention as defined by the claims.

Claims

1. Electrical connector apparatus for interconnecting a circuit package (22) to a card (36) comprising:
 - at least one buckling beam strip (18, 20; 94) carrying a plurality of contact wires (19, 21, 23, 25; 110, 112) for electrically connecting each of a plurality of first contacts on the circuit package to a corresponding one of a plurality of second contacts on the card;
 - a housing (12, 14; 90, 92) retaining the first buckling beam strip;
 - a buckling controller (16; 104), disposed within the housing, for alternately establishing and releasing pre-buckling of the buckling beam strip by applying a force on the first buckling beam strip to selectively urge the first buckling beam strip into a first cavity portion defined by the housing, thereby establishing pre-buckling of the first buckling beam strip, wherein in use the axial direction of the contact

wires is oriented towards the pluralities of first and second contacts and said force is applied in a direction substantially transverse to the axial direction of the contact wires.

2. Electrical connector apparatus as claimed in claim 1 comprising a second buckling beam strip (18, 20) and wherein the buckling controller (16) is also for applying a force on the second buckling beam strip and also for selectively urging the second buckling beam strip into a second cavity portion defined by the housing, to establish pre-buckling of the second buckling beam strip.
3. Electrical connector apparatus as claimed in claim 1 or claim 2 wherein the forces are applied by rotation of the buckling controller (16).
4. Electrical connector apparatus as claimed in claim 1 wherein the buckling controller comprises an extension (104) receivable by the cavity (96) and is an integral part of the housing and wherein the first buckling beam strip is disposed between the cavity and the extension whereby upon urging of the extension into the cavity the pre-buckling of the buckling beam strip occurs.
5. Electrical apparatus as claimed in any preceding claim wherein the housing engages the circuit package.
6. Electrical connector apparatus as claimed in any preceding claim wherein the releasing of the pre-buckling is effected in functional response to the engaging of the housing by the circuit package.
7. A method for establishing a plurality of electrical interconnections using apparatus as claimed in any preceding claim, each being between one of a plurality of first contact points and one of a plurality of second contact points, comprising disposing the buckling beam strip (18, 20; 94) between the first and second pluralities of contact points; pre-buckling the buckling beam strip; and releasing the buckling of the buckling beam strip until each of the contact wires (19, 21, 23, 25; 110, 112) establishes one of the interconnections.
8. A method as claimed in claim 7 wherein the step of disposing the buckling beam strip comprises positioning the housing between the pluralities of first and second contact points; and disposing the buckling beam strip within the



thereby released so as to effect the various electrical interconnections between the first and second contacts 106, 108 as desired. By provision of members 152 on the circuit package 114 and 154 on the housing 110, by interaction therebetween as shown in Fig. 8 during the urging of the circuit package 114 toward the card 112, the package 114 is thereby latched to the board housing 110.

Therefore, in an embodiment of the invention there is provided apparatus for providing low insertion force electrical interconnections between high density contacts for use in interconnecting circuit packages. A housing has disposed therein one or more pre-buckled beam connectors. Each connector has a resilient insulating strip carrying a plurality of buckling beams electrically isolated from each other. The beams are aligned on the plane defining the strip in parallel with ends extending away from the strip edges in opposing directions. Means are provided for deforming the strip within the housing prior to effecting desired interconnections whereby the beams are pre-buckled. Upon urging contacts into proximity with the beam ends, the buckling force is released causing each beam's ends to be urged away from the strip into engagement with respective contacts, thereby effecting desired interconnection between contacts and through one or more beams.

While the invention has been shown and described with reference to particular embodiments thereof, it will be understood by those skilled in the art that the foregoing and other changes in form and details may be made therein without departing from the scope of the invention as defined by the claims.

Claims

1. Electrical connector apparatus for interconnecting a circuit package (22) to a card (36) comprising:
 - at least one buckling beam strip (18, 20; 94) carrying a plurality of contact wires (19, 21, 23, 25; 110, 112) for electrically connecting each of a plurality of first contacts on the circuit package to a corresponding one of a plurality of second contacts on the card;
 - a housing (12, 14; 90, 92) retaining the first buckling beam strip;
 - a buckling controller (16; 104), disposed within the housing, for alternately establishing and releasing pre-buckling of the buckling beam strip by applying a force on the first buckling beam strip to selectively urge the first buckling beam strip into a first cavity portion defined by the housing, thereby establishing pre-buckling of the first buckling beam strip, wherein in use the axial direction of the contact wires is oriented towards the pluralities of first and second contacts and said force is applied in a direction substantially transverse to the axial direction of the contact wires.
2. Electrical connector apparatus as claimed in claim 1 comprising a second buckling beam strip (18, 20) and wherein the buckling controller (16) is also for applying a force on the second buckling beam strip and also for selectively urging the second buckling beam strip into a second cavity portion defined by the housing, to establish pre-buckling of the second buckling beam strip.
3. Electrical connector apparatus as claimed in claim 1 or claim 2 wherein the forces are applied by rotation of the buckling controller (16).
4. Electrical connector apparatus as claimed in claim 1 wherein the buckling controller comprises an extension (104) receivable by the cavity (96) and is an integral part of the housing and wherein the first buckling beam strip is disposed between the cavity and the extension whereby upon urging of the extension into the cavity the pre-buckling of the buckling beam strip occurs.
5. Electrical apparatus as claimed in any preceding claim wherein the housing engages the circuit package.
6. Electrical connector apparatus as claimed in any preceding claim wherein the releasing of the pre-buckling is effected in functional response to the engaging of the housing by the circuit package.
7. A method for establishing a plurality of electrical interconnections using apparatus as claimed in any preceding claim, each being between one of a plurality of first contact points and one of a plurality of second contact points, comprising disposing the buckling beam strip (18, 20; 94) between the first and second pluralities of contact points; pre-buckling the buckling beam strip; and releasing the buckling of the buckling beam strip until each of the contact wires (19, 21, 23, 25; 110, 112) establishes one of the interconnections.
8. A method as claimed in claim 7 wherein the step of disposing the buckling beam strip comprises positioning the housing between the pluralities of first and second contact points; and disposing the buckling beam strip within the



housing with the axial direction of the contact wires oriented towards the pluralities of first and second contact points.

9. A method as claimed in claim 8 wherein the pre-buckling comprises urging the buckling beam strip into the cavity. 5
10. A method as claimed in claim 9 wherein the apparatus comprises first and second buckling beam strips disposed in parallel within the housing; wherein the cavity has first and second portions; and the step of urging of the buckling beam contact means comprises urging the first and the second strips away from each other and into the first and second cavity portions, respectively. 10
11. A method as claimed in claim 10 further including urging the first plurality of contact points in the axial direction toward the housing and wherein the releasing of the pre-buckling is in response to the urging of the first plurality of contact points. 15
12. A method as claimed in claim 11 wherein the housing includes a buckling controller disposed between the first and the second strips and wherein the pre-buckling includes the step of rotating the controller to a first position. 20
13. A method as claimed in claim 12 wherein the step of releasing the pre-buckling comprises the step of rotating the buckling controller to a second position. 25
14. A method as claimed in claim 13 wherein the first plurality of contact points are disposed in a circuit package; and wherein the method further includes releasably interconnecting the circuit to the housing. 30
15. A method as claimed in claim 14 wherein the step of releasing the pre-buckling is during the releasable interconnection of the circuit package to the housing. 35

Patentansprüche

1. Elektrische Verbindungsvorrichtung zum Verbinden einer Schaltungspackung (22) mit einer Schaltkarte (36), umfassend:
zumindest eine sich auswölbende Trägerleiste (18, 20; 94), die eine Anzahl von Kontaktdräh-
ten (19, 21, 23, 25; 110, 112) trägt zum elektri-
schen Verbinden jedes einer Anzahl erster
Kontakte auf der Schaltungspackung mit einem
entsprechenden einer Anzahl von zweiten Kon- 50

takten auf der Schaltkarte,
ein Gehäuse (12, 14; 90, 92), das die erste
sich auswölbende Trägerleiste festhält,
einen Schalter für das Auswölben (16; 104),
der in dem Gehäuse angeordnet ist, um ab-
wechselnd ein Vor-Auswölben der sich auswöl-
benden Trägerleiste hervorzurufen und aufzu-
heben durch Aufbringen einer Kraft auf die
erste sich auswölbende Trägerleiste, um se-
lektiv die erste sich auswölbende Trägerleiste
in einen Hohlraumteil zu zwingen, der durch
das Gehäuse begrenzt ist, wodurch ein Vor-
Auswölben der ersten sich auswölbenden Trä-
gerleiste begründet wird, wobei die axiale
Richtung der Kontaktdrähte auf die Anzahl der
ersten und die der zweiten Kontakte orientiert
ist und die Kraft in einer Richtung aufgebracht
wird, die im wesentlichen senkrecht zu der
axialen Richtung der Kontaktdrähte verläuft.

2. Elektrische Verbindungsvorrichtung nach An-
spruch 1, umfassend eine zweite sich auswöl-
bende Trägerleiste (18, 20) und bei der der
Schalter für das Auswölben (16) auch dazu
dient, eine Kraft auf die zweite sich auswölben-
de Trägerleiste auszuüben und auch dazu, die
zweite sich auswölbende Trägerleiste selektiv
in einen zweiten Hohlraumteil zu zwingen,
der durch das Gehäuse definiert ist, um das
Vor-Auswölben der zweiten sich auswölbenden
Trägerleiste zu begründen. 25
3. Elektrische Verbindungsvorrichtung nach An-
spruch 1 oder Anspruch 2, bei der die Kräfte
durch Drehen des Schalters (16) für das Aus-
wölben aufgebracht werden. 30
4. Elektrische Verbindungsvorrichtung nach An-
spruch 1, bei der der Schalter für das Auswöl-
ben einen Ansatz (104) umfaßt, der von dem
Hohlraum (96) aufnehmbar ist, und der ein
integraler Teil des Gehäuses ist und bei dem
die erste sich auswölbende Trägerleiste zwi-
schen dem Hohlraum und dem Ansatz ange-
ordnet ist, wodurch beim Zwingen des Ansatz-
es in den Hohlraum das Vor-Auswölben der
sich auswölbenden Trägerleiste auftritt. 35
5. Elektrische Vorrichtung nach irgendeinem vor-
hergehenden Anspruch, bei der das Gehäuse
die Schaltungspackung aufnimmt. 40
6. Elektrische Verbindungsvorrichtung nach ir-
gendeinem vorhergehenden Anspruch, bei der
das Aufheben des Vor-Auswölbens von der
Schaltungspackung bewirkt wird in funktioneller
Antwort auf das Aufnehmen durch das Gehä-
use. 45



7. Verfahren zum Herstellen einer Anzahl elektrischer Verbindungen unter Benutzung einer Vorrichtung, wie sie in jedem vorhergehenden Anspruch beansprucht ist, wobei jede zwischen einem aus einer Anzahl erster Kontaktpunkte und einem aus einer Anzahl zweiter Kontaktpunkte besteht, umfassend das Anordnen der sich auswölbenden Trägerleiste (18, 20; 94) zwischen der ersten und der zweiten Anzahl von Kontaktpunkten, das Vor-Auswölben der sich auswölbenden Trägerleiste und das Aufheben des sich Auswölbens der sich auswölbenden Trägerleiste, bis jeder der Kontaktdrähte (19, 21, 23, 25; 110, 112) eine der Verbindungen herstellt.
8. Verfahren nach Anspruch 7, bei dem der Schritt des Anordnens der sich auswölbenden Trägerleiste das Positionieren des Gehäuses zwischen der Anzahl erster und der zweiten Kontaktpunkte umfaßt, und das Anordnen der sich auswölbenden Trägerleiste innerhalb des Gehäuses so, daß die axiale Richtung der Kontaktdrähte nach der Anzahl erster und der zweiten Kontaktpunkte orientiert ist.
9. Verfahren nach Anspruch 8, bei dem das Vor-Auswölben das Zwingen der sich auswölbenden Trägerleiste in den Hohlraum umfaßt.
10. Verfahren nach Anspruch 9, bei dem die Vorrichtung erste und zweite sich auswölbende Trägerleisten umfaßt, die parallel innerhalb des Gehäuses angeordnet sind, wobei der Hohlraum erste und zweite Teile aufweist, und der Schritt des Zwingens der sich auswölbenden Trägerleistenmittel das Zwingen der ersten und zweiten Leisten voneinander weg und in die ersten bzw. zweiten Hohlraumteile umfaßt.
11. Verfahren nach Anspruch 10, weiter einschließend das Zwingen der ersten Anzahl von Kontaktpunkten in die axiale Richtung zu dem Gehäuse hin, und bei dem das Aufheben des Vor-Auswölbens als Antwort auf das Zwingen der ersten Anzahl von Kontaktpunkten erfolgt.
12. Verfahren nach Anspruch 11, bei dem das Gehäuse einen Schalter für das Auswölben einschließt, der zwischen den ersten und zweiten Leisten angeordnet ist, und bei dem das Vor-Auswölben den Schritt des Drehens des Schalters in eine erste Position einschließt.
13. Verfahren nach Anspruch 12, bei dem der Schritt des Aufhebens des Vor-Auswölbens den Schritt des Drehens des Schalters für das Auswölben in eine zweite Position umfaßt.

14. Verfahren nach Anspruch 13, bei dem die erste Anzahl von Kontaktpunkten in einer Schaltungspackung angeordnet ist, und bei dem das Verfahren weiter das aufhebbare Verbinden der Schaltung mit dem Gehäuse einschließt.

15. Verfahren nach Anspruch 14, bei dem der Schritt des Aufhebens der Vor-Auswölbung während der aufhebbaren Verbindung der Schaltungspackung mit dem Gehäuse erfolgt.

Revendications

1. Système de connexion électrique pour interconnecter une structure de circuits (22) et une carte (36), comprenant:
 - au moins une bande à poutres de déformation (18, 20; 94) portant une pluralité de fils de contact (19, 21, 23, 25; 110, 112) pour connecter électriquement chacun d'une pluralité de premiers contacts sur la structure de circuits à chacun d'une pluralité de deuxième contacts sur la carte;
 - un logement (12, 14; 90, 92) retenant la première bande à poutres de déformation;
 - un contrôleur de déformation (16, 104) disposé dans le logement pour établir et relâcher alternativement la pré-déformation de la bande à poutres de déformation en appliquant une force sur la première bande à poutres de déformation afin de pousser sélectivement la première bande à poutres de déformation dans une première portion de cavité définie par le logement, établissant de ce fait la pré-déformation de la première bande à poutres de déformation, dans lequel la direction axiale des fils de contact est orientée vers les pluralités de premiers et deuxièmes contacts, et ladite force est appliquée dans une direction sensiblement transversale à la direction axiale des fils de contact.
2. Système de connexion électrique selon la revendication 1, comprenant une deuxième bande à poutres de déformation (18, 20) et dans lequel le contrôleur de déformation (16) sert également à appliquer une force sur la deuxième bande à poutres de déformation et également à pousser sélectivement la deuxième bande à poutres de déformation dans une deuxième portion de cavité définie par le logement afin d'établir la pré-déformation de la deuxième bande à poutres de déformation.
3. Système de connexion électrique selon les revendications 1 ou 2, dans lequel les forces sont appliquées par rotation du contrôleur de déformation (16).



4. Système de connexion électrique selon la revendication 1, dans lequel le contrôleur de déformation comprend une extension (104) recevable par la cavité (96) et qui fait partie intégrante du logement, et dans lequel la première bande à poutres de déformation est disposée entre la cavité et l'extension ce qui fait que, par pression de l'extension dans la cavité, il y a pré-déformation de la bande à poutres de déformation.

5. Système de connexion électrique selon l'une quelconque des revendications précédentes, dans lequel la structure de circuits est insérée dans le logement.

6. Système de connexion électrique selon l'une quelconque des revendications précédentes, dans lequel le relâchement de la pré-déformation est effectué en réponse fonctionnelle à l'insertion de la structure de circuits dans le logement.

7. Procédé pour établir une pluralité d'interconnexions en utilisant le système tel qu'il est revendiqué dans l'une quelconque des revendications précédentes, chacune se faisant entre un point de contact parmi une pluralité de premiers points de contact et un point de contact parmi une pluralité de deuxième points de contact, comprenant la disposition de la bande à poutres de déformation (18, 20; 94) entre les première et deuxième pluralités de points de contacts; la pré-déformation de la bande à poutres de déformation; et le relâchement de la déformation de la bande à poutres de déformation jusqu'à ce que chacun des fils de contact (19, 21, 23, 25; 110, 112) établisse une des interconnexions.

8. Procédé selon la revendication 7, dans lequel l'étape de disposition de la bande à poutres de déformation comprend le positionnement du logement entre les pluralités de premiers et deuxièmes points de contact; et la disposition de la bande à poutres de déformation dans le logement avec la direction axiale des fils de contact orientée vers les pluralités de premiers et deuxièmes points de contact.

9. Procédé selon la revendication 8, dans lequel la pré-déformation comprend la pression de la bande à poutres de déformation dans la cavité.

10. Procédé selon la revendication 9, dans lequel le système comprend des première et deuxième bandes à poutre de déformation disposées en parallèle dans le logement, dans lequel la

cavité a des première et deuxième portions; et l'étape de pression du moyen de contact de la poutre de déformation comprend l'écartement entre elles des première et deuxième bandes et leur pression dans les première et deuxième portions de cavité respectives.

11. Procédé selon la revendication 10, comprenant en outre la pression de la première pluralité de points de contact dans la direction axiale vers le logement, et dans lequel le relâchement de la pré-déformation se fait en réponse à la pression de la première pluralité de points de contact.

12. Procédé selon la revendication 11, dans lequel le logement comprend un contrôleur de déformation disposé entre les première et deuxième bandes, et dans lequel la pré-déformation comprend l'étape de rotation du contrôleur sur une première position.

13. Procédé selon la revendication 12, dans lequel l'étape de relâchement de la pré-déformation comprend l'étape de rotation du contrôleur de déformation sur une deuxième position.

14. Procédé selon la revendication 13, dans lequel la première pluralité de points de contact est disposée dans une structure de circuits; et dans lequel le procédé comprend en outre l'interconnexion détachable de la structure de circuits avec le logement.

15. Procédé selon la revendication 14, dans lequel l'étape de relâchement de la pré-déformation se fait durant l'interconnexion détachable de la structure de circuits avec le logement.

5

10

15

20

25

30

35

40

45

50

55

10