

Systems And Methods For Behavioral Threat Detection

BACKGROUND

[0001] The invention relates to computer security systems and methods, and in particular to systems and methods for detecting malicious software and/or an intrusion into a computer system and/or communication network.

[0002] In recent years, computer and network security have become increasingly important for private individuals and companies alike. The rapid development of electronic communication technologies, the increasing reliance on software in daily activities, and the advent of the Internet of Things have left companies and individuals vulnerable to loss of privacy and data theft.

[0003] A skilled attacker may attempt to infiltrate a corporate network using various techniques, for instance using a backdoor installed on a corporate computer by malicious software. The attacker may then gain access to, modify, or destroy sensitive information. Other exemplary attacks include, among others, disabling or otherwise incapacitating physical security systems (e.g., a burglar alarm), installing spying software, and interfering with automated systems that control manufacturing or distribution of goods and services (e.g., the power grid).

[0004] Software executing on a computer system may be used to automatically detect and/or prevent unauthorized intrusion and other malicious activities. Such software, commonly known as an intrusion detection system (IDS), may monitor network and/or computer activities for unusual events or policy violations. A typical IDS records information related to observed events, notifies a user or network administrator, and produces reports. Some IDSs may go further to prevent the intruder from performing malicious activities, for instance, by changing security settings (e.g. reconfiguring a firewall) in response to detecting an intrusion.

[0005] However, as software services are progressively delocalized and the amount of data flowing over information networks increases, it becomes increasingly impractical for security software to sift through this vast amount of information for indicators of malicious activity.

Therefore, there is substantial interest in developing more robust and scalable intrusion detection systems and methods.

SUMMARY

[0006] According to one aspect, a server computer system comprises at least one hardware processor configured to assign events of a training corpus to a plurality of event categories, the training corpus comprising a collection of events having occurred on a plurality of client systems. The hardware processor is further configured, in response to assigning events to event categories, to assign client systems of the plurality of client systems to a plurality of client clusters according to the plurality of event categories. The hardware processor is further configured, in response to assigning the plurality of client systems to client clusters, to transmit a client cluster membership indicator to an anomaly detector configured to determine whether a target event occurring on a target client system is indicative of a computer security threat. Assigning events to event categories comprises selecting a plurality of events from the training corpus, the plurality of events having occurred on a client system of the plurality of client systems, and arranging the plurality of events according to a time of occurrence to form an event sequence. Assigning events to event categories further comprises, in response, assigning a selected event of the event sequence to a selected event category according to a first event preceding the selected event and further according to second event following the selected event within the event sequence. Assigning client systems to client clusters comprises assigning the client system to a selected client cluster according to an event profile determined according to a count of events occurring on the client system and belonging to the selected event category. The anomaly detector is configured to determine whether the target event is indicative of the computer security threat according to a behavior model trained on a client-cluster-specific sub-corpus of events, the client-cluster-specific sub-corpus selected from the training corpus to include only events that have occurred on a plurality of members of a target cluster of the plurality of client clusters.

[0007] According to another aspect, a computer-implemented method comprises computer-implemented method comprises employing at least one hardware processor of a computer system

to assign events of a training corpus to a plurality of event categories, wherein the training corpus comprises a collection of events occurring on a plurality of client systems. The method further comprises, in response to assigning events to event categories, employing at least one hardware processor of the computer system to assign client systems of the plurality of client systems to a plurality of client clusters according to the plurality of event categories. The method further comprises, in response to assigning client systems to client clusters, employing at least one hardware processor of the computer system to transmit a client cluster membership indicator to an anomaly detector configured to determine whether a target event occurring on a target client system is indicative of a computer security threat. Assigning events to event categories comprises selecting a plurality of events from the training corpus, the plurality of events having occurred on a client system of the plurality of client systems, and arranging the plurality of events according to a time of occurrence to form an event sequence. Assigning events to event categories further comprises, in response, assigning a selected event of the event sequence to a selected event category according to a first event preceding the selected event and further according to second event following the selected event within the event sequence. Assigning client systems to client clusters comprises assigning the client system to a selected client cluster according to an event profile determined according to a count of events occurring on the client system and belonging to the selected event category. The anomaly detector is configured to determine whether the target event is indicative of the computer security threat according to a behavior model trained on a client-cluster-specific sub-corpus of events, the client-cluster-specific sub-corpus selected from the training corpus to include only events that have occurred on a plurality of members of a target cluster of the plurality of client clusters.

[0008] According to another aspect, a non-transitory computer-readable medium stores instructions which, when executed by at least one hardware processor of a computer system, cause the computer system to assign events of a training corpus to a plurality of event categories, the training corpus comprising a collection of events having occurred on a plurality of client systems. The instructions further cause the computer system, in response to assigning events to event categories, to assign client systems of the plurality of client systems to a plurality of client clusters according to the plurality of event categories. The instructions further cause the

computer system, in response to assigning the client systems to client clusters, to transmit a client cluster membership indicator to an anomaly detector configured to determine whether a target event occurring on a target client system is indicative of a computer security threat. Assigning events to event categories comprises selecting a plurality of events from the training corpus, the plurality of events having occurred on a client system of the plurality of client systems, and arranging the plurality of events according to a time of occurrence to form an event sequence. Assigning events to event categories further comprises, in response, assigning a selected event of the event sequence to a selected event category according to a first event preceding the selected event and further according to second event following the selected event within the event sequence. Assigning client systems to client clusters comprises assigning the client system to a selected client cluster according to an event profile determined according to a count of events occurring on the client system and belonging to the selected event category. The anomaly detector is configured to determine whether the target event is indicative of the computer security threat according to a behavior model trained on a client-cluster-specific sub-corpus of events, the client-cluster-specific sub-corpus selected from the training corpus to include only events that have occurred on a plurality of members of a target cluster of the plurality of client clusters.

BRIEF DESCRIPTION OF THE DRAWINGS

[0009] The foregoing aspects and advantages of the present invention will become better understood upon reading the following detailed description and upon reference to the drawings where:

[0010] FIG. 1 shows several exemplary interconnected client systems, with a security server acting as intrusion detection system according to some embodiments of the present invention.

[0011] Fig. 2 shows an exemplary data exchange carried out to protect a client system according to some embodiments of the present invention.

[0012] Fig. 3-A illustrates an exemplary hardware configuration of a client system according to some embodiments of the present invention.

[0013] Fig. **3-B** illustrates an exemplary hardware configuration of a security server according to some embodiments of the present invention.

[0014] Fig. **4** shows exemplary software components executing on a protected client system according to some embodiments of the present invention.

5 [0015] Fig. **5** shows an exemplary software architecture of a security server according to some embodiments of the present invention.

[0016] Fig. **6** illustrates an exemplary operation of a profiling engine according to some embodiments of the present invention.

10 [0017] Fig. **7** shows an exemplary sequence of steps carried out by the profiling engine according to some embodiments of the present invention.

[0018] Fig. **8-A** shows an exemplary training of an event encoder according to some embodiments of the present invention.

[0019] Fig. **8-B** shows an alternative exemplary training of the event encoder according to some embodiments of the present invention.

15 [0020] Fig. **9** shows an exemplary sequence of steps performed to train the event decoder in the configuration of Fig. **8-A**.

[0021] Fig. **10** illustrates an exemplary event embedding space and a set of exemplary event clusters according to some embodiments of the present invention.

20 [0022] Fig. **11** illustrates an exemplary client profile space and a set of client clusters according to some embodiments of the present invention.

[0023] Fig. **12** shows an exemplary event profile of a client system according to some embodiments of the present invention.

[0024] Fig. 13 shows exemplary components and operation of an anomaly detector according to some embodiments of the present invention.

[0025] Fig. 14 illustrates an exemplary sequence of steps performed by the anomaly detector during training, according to some embodiments of the present invention.

5 [0026] Fig. 15 shows exemplary components of a behavior model forming part of the anomaly detector according to some embodiments of the present invention.

[0027] Fig. 16 illustrates an exemplary sequence of steps performed by the trained anomaly detector according to some embodiments of the present invention.

10 [0028] Fig. 17-A shows results of an experiment comprising employing some embodiments of the present invention to detect actual computer security threats.

[0029] Fig. 17-B shows other experimental results of using some embodiments to detect actual computer security threats.

DETAILED DESCRIPTION OF PREFERRED EMBODIMENTS

15 [0030] In the following description, it is understood that all recited connections between structures can be direct operative connections or indirect operative connections through intermediary structures. A set of elements includes one or more elements. Any recitation of an element is understood to refer to at least one element. A plurality of elements includes at least two elements. Unless otherwise specified, any use of "OR" refers to a non-exclusive or. Unless otherwise required, any described method steps need not be necessarily performed in a particular
20 illustrated order. A first element (e.g. data) derived from a second element encompasses a first element equal to the second element, as well as a first element generated by processing the second element and optionally other data. Making a determination or decision according to a parameter encompasses making the determination or decision according to the parameter and optionally according to other data. Unless otherwise specified, an indicator of some
25 quantity/data may be the quantity/data itself, or an indicator different from the quantity/data itself. A computer program is a sequence of processor instructions carrying out a task.

Computer programs described in some embodiments of the present invention may be stand-alone software entities or sub-entities (e.g., subroutines, libraries) of other computer programs. Unless otherwise specified, computer security encompasses protecting equipment and data against illegitimate access, modification, and/or destruction. Computer readable media encompass non-transitory media such as magnetic, optic, and semiconductor storage media (e.g. hard drives, optical disks, flash memory, DRAM), as well as communication links such as conductive cables and fiber optic links. According to some embodiments, the present invention provides, *inter alia*, computer systems comprising hardware (e.g. one or more processors) programmed to perform the methods described herein, as well as computer-readable media encoding instructions to perform the methods described herein.

[0031] The following description illustrates embodiments of the invention by way of example and not necessarily by way of limitation.

[0032] FIG. 1 shows an exemplary set of client systems **10a-h** protected from computer security threats according to some embodiments of the present invention. Client systems **10a-h** generically represent any electronic device having a processor, a memory, and a communication interface. Exemplary client systems **10a-h** include personal computers, laptops, tablet computers, mobile telecommunication devices (e.g., smartphones), media players, TVs, game consoles, home appliances (e.g., refrigerators, intelligent heating and/or lighting systems), and wearable devices (e.g., smartwatches, fitness equipment), among others. Client systems **10a-h** may execute various software, e.g., document processing, gaming, electronic messaging, and social media applications, among others. Some clients may exchange information with a remote content server **17**, for instance, Internet browsing.

[0033] The illustrated client systems are connected by local networks **12a-b**, and further to an extended network **14**, such as a wide area network (WAN) or the Internet. In one example, client systems **10a-d** represent a family's electronic devices, interconnected by a home network **12a**. Meanwhile, client systems **10e-g** may denote individual computers and/or a corporate mainframe

inside an office building. Local network **12-b** may then represent a section of a corporate network (e.g., a local area network – LAN).

[0034] A router comprises an electronic appliance enabling communication between multiple client systems and/or access of the respective clients to extended network **14**. In the example of Fig. **1**, routers **15a-b** interconnect clients on local networks **12a-b** and/or enable clients **10a-g** to access the Internet. Routers **15a-b** may act as gateways between local networks **12a-b**, respectively, and extended network **14** and may further provide a set of network services to client systems **10a-g**. Such services include, for instance, distributing network configuration parameters to client systems **10a-g** (e.g., assigning network addresses via Dynamic Host Configuration Protocol – DHCP), and routing communications through a sequence of network nodes. Some client systems, such as exemplary client system **10h**, may connect directly to extended network **14**, for instance via a telecommunication relay.

[0035] Fig. **1** further shows a security server **16** connected to extended network **14**. Server **16** generically represents a set of communicatively coupled computer systems, which may or may not be in physical proximity to each other. Server **16** protects client systems **10a-h** against computer security threats such as malicious software and intrusion. In some embodiments, such protection comprises security server **16** detecting suspicious activity occurring at a client system, for instance an action of an attacker controlling the respective client system.

[0036] An exemplary data exchange between security server **16** and a client system **10** is illustrated in Fig. **2**. Client system **10** may represent any client **10a-h** in Fig. **1**. In some embodiments, server **16** is configured to receive an event indicator **20a** from client system **10**, indicator **20a** indicative of the occurrence of a particular type of event during execution of software on client **10**. Examples of such events include the launch of a process/thread (e.g., a user launches an application, a parent process creates a child process, etc.), an attempt to access an input device of the respective client system (e.g., camera, microphone), an attempt to access a local or remote network resource (e.g., a hypertext transfer protocol – HTTP request to access a particular URL, an attempt to access a document repository over a local network), a request

formulated in a particular uniform resource identifier scheme (e.g., a mailto: or a ftp: request), an execution of a particular processor instruction (e.g., system call), an attempt to load a library (e.g., a dynamic linked library – DLL), an attempt to create a new disk file, an attempt to read from or write to a particular location on disk (e.g., an attempt to overwrite an existing file, an attempt to open a specific folder or document), and an attempt to send an electronic message (e.g., email, short message service – SMS, etc.), among others. In some embodiments, periods of inactivity, i.e., time gaps between events and/or time intervals when the respective client system is idle, registers no user activity, or carries out only internal system tasks, also qualify as events and may be reported via event indicators to the security server. Such inactive periods may be further differentiated into short time gaps (e.g., of the order of a seconds) and long time gaps (e.g., of the order of minutes to hours). Detected events may or may not be indicative of malice *per se*; some events may be malice-indicative when occurring together with other events and/or when occurring in a particular sequence. Other events may be malicious when they occur at certain times of the day or with an unusual frequency, for instance a sequence of 1000 reads from a particular disk folder in an interval of a few seconds.

[0037] Each event indicator **20a** may comprise, among others, an indicator of a type of the respective event and a timestamp indicative of a moment in time when the respective event has occurred. Event indicator **20a** may further include an identifier (client ID) of the respective client system and/or an indicator of a user (user ID) currently operating the respective client system. For instance, when the communicated event comprises a process creation, a user indicator may indicate the owner of the parent process. Event indicator **20a** may encode other parameters such as a process name, a file system location/path of a process being launched, a network address (e.g., Internet protocol – IP address), a universal resource locator (URL) of an HTTP request, etc.

[0038] In some embodiments, server **16** may also harvest information from routers **15a-b**, as illustrated by an event indicator **20b** in Fig. 2. Such event indicators may include, for instance, indicators of network events such as network access requests issued by client systems connected to the respective router/gateway. For instance, event indicator **20b** may include an originating IP

address, a destination IP address, a timestamp, and a payload size. In some embodiments, event indicator **20b** comprises client event data aggregated by the respective router according to various data processing protocols (e.g., network flows, network logs, etc.).

[0039] Security server **16** maintains a set of user behavior models representing a baseline, normal, and/or legitimate manner of operating a subset of client systems **10a-h**. Such behavior models are herein deemed client profiles. Parameters of such behavior models are generically represented as profile database **19** in Fig. **1** and may include an output of an event and/or client clustering algorithm, as shown in detail below. In one exemplary embodiment wherein a profile is represented by a client or event cluster, parameters of the respective profile may include coordinates of a cluster centroid and a set of numbers indicating a range of the respective cluster along various axes. Other profile parameters may include, among others, an eccentricity measure of the respective cluster, and an average distance between cluster members and the cluster's centroid, among others. Client profiles may be generated automatically, using supervised or unsupervised learning methods and algorithms, as shown below.

[0040] A client profile may capture the behavior of a single user or may collectively capture the behavior of multiple users. To give some examples, a smartphone may be used primarily by a single user, therefore a client profile attached to the respective smartphone may essentially capture a baseline behavior of its primary user. In contrast, computers belonging to a university computer lab may be used by many different students; a client profile attached to one of these machines may collectively represent a baseline behavior of all the respective students. One client profile may be attached to a single client system/physical machine (e.g., smartphone, laptop). In some embodiments, one client profile may collectively represent a plurality of physical machines. In one such example, client systems **10a-d** in Fig. **1** may be collectively represented by a single client profile which captures a normal or baseline behavior of the members of a particular family. In another example, one client profile is used to represent all computers in the accounting department of a corporation, while another client profile represents all computers used by the respective corporation's research and development team. In a cloud computing embodiment, such as a virtual desktop infrastructure (VDI) environment wherein a

physical machine may execute a plurality of virtual machines for various distributed users, one client profile may be attached to multiple virtual machines executing on the respective physical machine.

[0041] In some embodiments, a single user may be represented by a plurality of distinct client profiles. For instance, the same person may have one client profile/baseline behavior while at work and a distinct client profile/baseline behavior while at home. Other examples of client profiles may be associated with users of a particular age group (e.g., teenagers), a particular personal interest (e.g., gaming), a particular occupation (e.g., engineer, artist, educator), etc. In yet another exemplary embodiment, distinct client profiles may correspond to distinct computer activities, e.g., to using distinct computer programs: browsing the Internet, using social media, doing office work, etc. Yet other exemplary client profiles may be attached to distinct device types (e.g., smartphone vs. PC). Collective profiles may be devised according to more complex criteria, for instance a client profile indicating a typical/baseline manner in which an engineer from company X browses the Internet. Another such exemplary profile may indicate a typical manner in which young people use tablet computers.

[0042] A subset of event indicators **20a-b** may be collected to form an event corpus further used to derive client profiles as shown in detail below. Another subset of event indicators may be used to detect security threat. For instance, in response to receiving event indicators **20a-b**, security server **16** may determine whether the event communicated by the respective event indicator is consistent with a client profile selected according to the respective client indicator. Stated otherwise, security server **16** may determine whether the respective event matches a pattern of normality/baseline behavior encoded in the respective client profile. When no, the respective event may indicate suspicious activity, in which case some embodiments may take protective action, for instance sending security alerts **22a-b** to the respective client system and/or to an administrator of the respective client system. In another example of protective action, some embodiments instruct a router which belongs to the same local network as the suspect client system to block communications to and/or from the respective suspect client system.

Client profiles and processing of event indicators by security server **16** are further described below.

[0043] Fig. **3-A** shows an exemplary hardware configuration of a client system according to some embodiments of the present invention. Client system **10** may represent any of client systems **10a-h** in Fig. **1**. For clarity, the illustrated client system is a computer system. Other client systems such as mobile telephones, tablet computers, and wearable devices may have slightly different configurations. Processor **32** comprises a physical device (e.g. microprocessor, multi-core integrated circuit formed on a semiconductor substrate) configured to execute computational and/or logical operations with a set of signals and/or data. Such signals or data may be encoded and delivered to processor **32** in the form of processor instructions, e.g., machine code. Memory unit **34** may comprise volatile computer-readable media (e.g. dynamic random-access memory – DRAM) storing data/signals accessed or generated by processor **32** in the course of carrying out operations.

[0044] Input devices **36** may include computer keyboards, mice, and microphones, among others, including the respective hardware interfaces and/or adapters allowing a user to introduce data and/or instructions into client system **10**. Output devices **38** may include display devices such as monitors and speakers among others, as well as hardware interfaces/adapters such as graphic cards, enabling the respective client system to communicate data to a user. In some embodiments, input and output devices **36-38** share a common piece of hardware (e.g., a touch screen). Storage devices **42** include computer-readable media enabling the non-volatile storage, reading, and writing of software instructions and/or data. Exemplary storage devices include magnetic and optical disks and flash memory devices, as well as removable media such as CD and/or DVD disks and drives. Network adapter(s) **44** enable client system **10** to connect to an electronic communication network (e.g., networks **12, 14** in Fig. **1**) and/or to other devices/computer systems.

[0045] Controller hub **40** generically represents the plurality of system, peripheral, and/or chipset buses, and/or all other circuitry enabling the communication between processor **32** and

the rest of the hardware components of client system **10**. For instance, controller hub **40** may comprise a memory controller, an input/output (I/O) controller, and an interrupt controller. Depending on hardware manufacturer, some such controllers may be incorporated into a single integrated circuit, and/or may be integrated with the processor. In another example, controller hub **40** may comprise a northbridge connecting processor **32** to memory **34**, and/or a southbridge connecting processor **32** to devices **36**, **38**, **42**, and **44**.

[0046] Fig. **3-B** shows an exemplary hardware configuration of security server **16** according to some embodiments of the present invention. Server **16** comprises at least one hardware processor **132** (e.g., microprocessor, multi-core integrated circuit), a physical memory **134** (e.g., DRAM), server storage devices **142**, and a set of server network adapters **144**. Server processors **132** may include a central processing unit (CPU) and/or an array of graphics processing units (GPU). Adapters **144** may include network cards and other communication interfaces enabling security server **16** to connect to communication network **14**. Server storage devices **142** may store data such as event indicators and/or client profile parameters. In some embodiments, server **16** further comprises input and output devices, which may be similar in function to input/output devices **36** and **38** of client system **10**, respectively.

[0047] Fig. **4** shows exemplary software components executing on client system **10** according to some embodiments of the present invention. Such software may include an operating system (OS) **46** providing an interface between the hardware of client system **10** and other computer programs such as a user application **48** executing on the respective client system. Exemplary operating systems include, among others, Windows®, MacOS®, iOS®, and Android®. User application **48** generically represents any application such as word processing, image processing, spreadsheet, calendar, online games, social media, web browser, and electronic communication applications, among others. In some embodiments, a security application **50** is configured to protect client system **10** against computer security threats such as malicious software and intrusion. Among other functions, security application **50** is configured to transmit event indicators to security server **16** and/or to receive security alerts. In some embodiments, application **50** further comprises an event harvester **52** and a network filter **53**. Some

functionality of network filter **53** may be implemented directly in hardware. When client system **10** operates a hardware virtualization platform wherein OS **46** and application **48** execute within a virtual machine (for instance, in a cloud computing environment), event harvester **52** and/or network filter **53** may execute outside the respective virtual machine, e.g., at a level of a
5 hypervisor exposing the respective virtual machine, using techniques known in the art as introspection.

[0048] Event harvester **52** is configured to detect various events occurring during execution of software by client system **10**. Some embodiments may timestamp each detected event to record a time of occurrence of the respective event. Monitored events may be machine and/or operating
10 system-specific. Exemplary events include, among others, a process launch, a process termination, the spawning of child processes, an access requests to peripherals (e.g., hard disk, network adapter), a command entered by the user into a command-line interface, etc. Such hardware and/or software events may be detected using any method known in the art of computer security, for instance by hooking certain functions of the operating system, detecting
15 system calls, employing a file system minifilter, changing a memory access permission to detect an attempt to execute code from certain memory addresses, etc.

[0049] Some embodiments monitor hardware and/or software events using system logging tools built into OS **46** (e.g., Syslog in UNIX®). Such tools may generate a list of event descriptors including a timestamp for each event, a numerical code identifying an event type, an indicator of
20 a type of process or application that generated the respective event, and other event parameters. Security application **50** may extract such information from the respective system log to formulate event indicators. Exemplary syslog entries are given below:

```
<30>Feb 8 21:36:51 dtm charon: 12[IKE] establishing CHILD_SA dtmhq5{5}
<30>Feb 8 21:36:51 dtm charon: 12[IKE] establishing CHILD_SA dtmhq5{5}
25 <187>Feb 8 21:37:56 example.domain.biz dhcpd: DHCPDISCOVER from 0c:14:7b:11:
    14:64 via eth1: network eth1: no free leases
```

[0050] Network filter **53** detects a set of network events occurring during electronic communications over networks **12-14** between client system **10** and other parties. Exemplary events detected by network filter **53** include events forming part of establishing a connection between client system **10** and another network entity (e.g., requesting a network address, transmitting a network address, handshake events, etc.), events that configure an encrypted connection (secure socket layer – SSL, virtual private network – VPN), transmitting data, and receiving data, among others. In some embodiments, network filter **53** collects metadata from intercepted network traffic. Such metadata may include, for instance, an originating network address (e.g., internet protocol – IP address), a destination address, a timestamp of a data packet, an indicator of a type of communication protocol, and a size of a data packet. Other exemplary metadata may include an indicator of a type of hypertext transfer protocol (HTTP) user agent transmitting the respective communication/data packet. Some embodiments organize communication metadata into specialized data structures, known in the art as network flows (for instance, NetFlow® from Cisco Systems, Inc.). Table **1** shows examples of communication metadata represented as flows according to some embodiments of the present invention.

Table 1

Flow #	Destination		Source		Protocol	Number of bytes	Number of packets	TCP Flags
	address	port	address	port				
1	10.10.12.71	443	192.168.127.10	54321	TCP	12300	21	SA
2	192.168.127.10	54321	10.10.12.71	443	TCP	2156980	413	FSPA

[0051] In some embodiments, security application **50** formulates event indicators according to hardware, software, and/or network events detected by harvester **52** and network filter **53**. Application **50** may further manage communication with security server **16**, to transmit event indicators and/or receive security notifications, among others.

[0052] In an alternative embodiment, instead of processing network communication at the client as shown above, network filter **53** and/or router **15** may be configured to re-route to security server **16** at least a part of electronic communications going in and/or out of client system **10**.

For instance, the network configuration parameters of client system **10** may be set to indicate server **16** as the default network gateway. Some embodiments then employ security server **16** to extract event indicators from the respective re-routed traffic.

[0053] Fig. **5** shows exemplary software executing on security server **16** according to some
5 embodiments of the present invention. The illustrated software includes a profiling engine **60**
and an anomaly detector **62** further connected to an alert manager **64**. A skilled artisan will
appreciate that not all illustrated components need to execute on the same machine/processor; for
instance, profiling engine **60** may execute on a dedicated cluster of processors, while instances of
anomaly detector **62** may run on other machines/processors.

10 [0054] In some embodiments, profiling engine **60** is configured to analyze events occurring on a
set of client systems (e.g., a subset of clients **10a-h** in Fig. **1**) and to construct a plurality of client
profiles representing a baseline, normal, and/or legitimate manner of operating the respective
client systems. A subset of event indicators **20a-b** received from clients may be used to
assemble a training event corpus, denoted as corpus **18** in Figs. **1**, **5**, and **6**. Profiles are then
15 determined according to event corpus **18**. Determining a client profile may include, among
others, representing events in an abstract multi-dimensional event space and carrying out data
clustering procedures, as shown in more detail below. Constructed profiles may then be stored
as entries in profile database **19**. An exemplary profile database entry comprises a set of profile
parameters such as a set of coordinates of a cluster centroid, a measure of the cluster's diameter
20 and/or eccentricity, etc.

[0055] Fig. **6** illustrates exemplary components and operation of profiling engine **60**. In some
embodiments, engine **60** comprises an event encoder **70**, an event clustering engine **72**, and a
client clustering engine **74** connected to event encoder **70** and event clustering engine **72**. An
exemplary sequence of steps performed by profiling engine is illustrated in Fig. **7**.

25 [0056] In a sequence of steps **202-204-206**, profiling engine **60** may assemble training event
corpus **18** according to event indicators received from selected client systems and/or router(s).
Some embodiments accumulate events indicators until some accumulation condition is satisfied.

Accumulation conditions may be determined according to a count of events (gather a corpus of 1 million events), according to a time condition (e.g., record all events received within a 1h interval, etc.), according to an identity of a client system and/or user (e.g., record all events received from corporation X, IP range Y, subscription account Z, etc.), or according to any other method known in the art. Individual events may be labeled according to their origin and may comprise a timestamp characterizing a moment in time when the respective even has occurred, or has been detected, or has been received at security server **16**, etc. In some embodiments, event corpus **18** is refreshed periodically and/or on demand by incorporation of newly received event indicators.

[0057] In some embodiments, event encoder **70** (Fig. **6**) is configured to input an event record **26** comprising data characterizing an event that has occurred on a client system (e.g., the launch of a process on a client machine), and in response, to output an event vector **28a** comprising a representation of the respective event as a vector in an abstract multi-dimensional space usually deemed *embedding space* in the art. An exemplary embedding space is spanned by a set of axes, wherein each axis represents a distinct event feature. Exemplary features may include, in the case of a network event, a source IP address, a source port, a destination IP address, a destination port, and an indicator of the transport protocol, among others. In another example, each axis of the embedding space corresponds to a linear combination of event features (for instance, in a principal component/singular value decomposition embodiment). In preferred embodiments, events are analyzed in the context of other events, which precede and/or follow the respective event. In such cases, encoder **70** is configured to represent events as vectors in an embedding space of contexts, wherein two events that occur predominantly in similar contexts are located relatively close together. Some embodiments choose the dimensionality of the embedding space according to a size of the event vocabulary N , i.e., the count of distinct event types that the respective security system is monitoring (for more on the event vocabulary, see below). For instance, the dimensionality of the event space may of the order of the quadratic root of N , or of a logarithm of N . A typical embodiment of the present invention uses an embedding context space having several hundred to several thousand dimensions.

[0058] Event encoder **70** may be constructed using any method known in the art of automated data processing. In a preferred embodiment, encoder **70** comprises an artificial intelligence system, for instance a multilayer artificial neural network (e.g., a recurrent and/or feed-forward neural network). To achieve the desired representation of event vectors, parameters of encoder **70** may be tuned until some performance condition is satisfied. Such tuning is herein referred to as *training* and is represented by step **208** in Fig. **7**. In a neural network embodiment, exemplary tunable parameters of event encoder **70** include a set of synapse weights, among others. In some embodiments, training encoder **70** amounts to constructing the embedding space itself. Stated otherwise, the embedding space is not pre-determined, but instead depends on the composition of event corpus **18** and on the selected training procedure.

[0059] Exemplary training procedures are shown in Figs. **8-A-B** and comprise versions of the word2vec algorithm, such as a skip-gram algorithm and a continuous bag-of-words algorithm. In such embodiments, events are not analyzed in isolation, but as constituents of an event sequence **25** consisting of multiple events ordered according to a time of occurrence or detection. In some embodiments, all events of the respective sequence are selected so that they occur on the same client system. Event sequence **25** comprises a central event E_0 and an event context consisting of a subset of events $E_{-k} \dots E_{-1}$ ($k \geq 0$) preceding the central event and/or a subset of events $E_1 \dots E_p$ ($p \geq 0$) following the central event. Typical embodiments use a symmetric event context ($p=k$), with p in the range of 2 to 5. Each individual event E_i ($-k \leq i \leq p$) may be represented as an N -by-1 vector of numbers, wherein each line represents a distinct event type (e.g., launching a browser, initiating a file download, writing data to disk, etc.), N represents a size of a “vocabulary” of event types, and a non-zero element indicates that the respective event is of the respective event type. Such a representation is commonly known in the art as a 1-hot encoding. An exemplary size N of the event vocabulary ranges from several hundred to several thousands of distinct event types, but can go up to several million for specific applications. A skilled artisan will appreciate that the one-hot encoding is herein used only as an example, and by no means limits the scope of the present invention.

- [0060] In the exemplary training procedures, an event encoder is paired and co-trained with an event decoder, both of which may comprise parts of a feed-forward and/or recurrent neural network. In general, the encoder-decoder pair may be configured to input a first subset of a training sequence (e.g., central event E_0) and to output a “prediction” for a second subset of the respective sequence (e.g., some context event E_i , $i \neq 0$). In the examples of Figs. 8-A-B, the predictions are illustrated as one-hot vectors; alternative embodiments may use a different representation. For instance, a prediction may be represented as a N -dimensional vector of numbers, each number indicating a likelihood that a corresponding event type is present in the second subset.
- [0061] In a skip-gram training procedure illustrated in Figs. 8-A, the encoder-decoder pair is trained to produce the correct *event context* given the *central event* E_0 . For each sequence of events drawn from event corpus 18, an encoder 70a is configured to input a one-hot encoding of central event E_0 and to produce event vector 28c comprising a representation of central event E_0 in the embedding context space. In turn, a decoder 76a is configured to input event vector 28c and output a plurality of guessed vectors, each representing a “predicted” context event E_i ($i \neq 0$) of the respective event sequence. The encoder-decoder pair may then be trained by adjusting parameters of encoder 70a and/or decoder 76a in an effort to reduce the prediction error, i.e., to correct a mismatch between the “predicted” context and the actual context of the respective training sequences.
- [0062] An alternative training procedure using a continuous bag-of-words training algorithm and aims to produce the correct *central event* E_0 of a training sequence given the respective *event context*. In one such example illustrated in Fig. 8-B, an event encoder 70b is configured to input a set of one-hot vectors representing context events E_i ($i \neq 0$) of sequence 25, and to output embedded event vectors 28d-f determined for each respective context event. In contrast to the skip-gram embodiment illustrated in Fig. 8-A, encoder 70b is now paired with an event decoder 76b configured to input the plurality of event vectors 28d-f, and to produce a prediction or “guess” for the central event E_0 of sequence 25. The encoder-decoder pair may then be trained by adjusting parameters of encoder 70b and/or decoder 76b in an effort to reduce the

prediction error, i.e., the mismatch between the “predicted” central event and the actual central event of the respective training sequences.

[0063] An exemplary sequence of steps implementing training of an event encoder is illustrated in Fig. 9. A step 222 retrieves a set of event records from event corpus 18 and identifies an event sequence 25 according to event timestamps and according to a source of the respective events (i.e., client systems where the respective events have occurred). In a skip-gram embodiment, a step 224 then executes event encoder 70a to produce an embedding-space representation of event E_0 (event vector 28c in Fig. 8-A). In a step 226, profiling engine 60 executes event decoder 76a to produce a set of predictions or “guesses” for events preceding and/or following central event E_0 within sequence 25. A step 228 compares each predicted context event with the respective actual context event E_i ($i \neq 0$) of sequence 25, thus determining a numerical prediction error. The prediction error, which may be interpreted as a cost function or an objective function, may be calculated according to any method known in the art of artificial intelligence. Such calculations may comprise determining a distance, for instance a Levenshtein, Euclidean, or cosine distance between the predicted and actual events. Some embodiments determine an objective function according to a cross entropy measure. In a step 230, profiling engine may adjust parameters of encoder 70a in the direction of minimizing the calculated prediction error. Some exemplary algorithms used for training include backpropagation using a gradient descent, simulated annealing, and genetic algorithms, among others. Some embodiments then repeat steps 222-230 until a termination condition is satisfied, for instance until the average prediction error over event corpus 18 drops below a pre-determined threshold. In another embodiment, training proceeds for a pre-determined amount of time, or for a pre-determined count of iterations. A skilled artisan will know that the sequence of steps illustrated in Fig. 9 is equally suited to a bag-of words embodiment (Fig. 8-B), with minor adaptations.

[0064] In response to training the event encoder as shown above, some embodiments further transform the generated embedding space to reduce its dimensionality. This operation may comprise any data dimensionality reduction algorithm, for instance a principal component analysis (PCA) or a singular value decomposition (SVD).

[0065] Following training and optional dimensionality reduction (step **208** in Fig. 7), event encoder **70** is capable of representing each event as a vector in a multidimensional embedding space of event contexts, wherein two events that occur frequently within the same event context occupy similar positions. Stated otherwise, two such events are separated in the embedding space by a distance smaller than the distance between two events which occur predominantly in different contexts.

[0066] Returning to components of profiling engine **60** (Fig. 6), event clustering engine **74** is configured to organize event vectors produced by trained event encoder **70** and representing members of training corpus **18**, into clusters according to a position of each event vector within the embedding space (see also step **207** in Fig. 7). In some embodiments, a cluster comprises a plurality of events that are relatively close together in embedding space, or stated otherwise, a plurality of events characterized by a relatively small inter-event distance in embedding space. In an alternative embodiment, a cluster consists of events that occupy a cluster-specific region of embedding space. Such regions may be mutually exclusive or partially overlapping. Fig. **10** illustrates an exemplary embedding space and a set of event clusters **80a-b** according to some embodiments of the present invention. The illustrated axes may comprise, for instance, the first and second principal components of the illustrated event vectors (vectors **28g-h-k**). In an embodiment using an embedding space of event contexts, a cluster may selectively contain events which occur primarily within a similar event context. Furthermore, the same cluster may include events occurring on various client systems and/or representing the activity of various users.

[0067] To construct event clusters, profiling engine **60** may employ any data clustering algorithm known in the art, for instance a variant of a k-means algorithm. Another exemplary embodiment may train a set of perceptrons to carve the embedding space into distinct regions and assign event vectors located within each region to a distinct event cluster. The number of clusters and/or regions may be pre-determined (e.g., according to a count of protected client systems and/or monitored event types) or may be dynamically determined by the clustering algorithm itself. An outcome of event clustering comprises a set of event cluster parameters **54**

(Fig. 6), which may include, for each cluster, the coordinates of the cluster's centroid and a measure of the cluster's extent, e.g., a diameter and/or eccentricity. Other exemplary cluster parameters **54** may include, among others, a list of members of the respective cluster, and a selected member of the respective cluster considered as representative/archetypal of the
5 respective cluster. Cluster parameters may be passed on to client clustering engine **74**.

[0068] Client clustering engine **74** (Fig. 6) is configured to determine a set of client profiles according to event clusters computed by event clustering engine **72**. Such client profiles are illustrated in Fig. 11. In some embodiments, each client profile comprises a selected subset (cluster) of the protected client systems **10a-h**. Some client profiles may include multiple client
10 clusters. In some embodiments, a client profile may comprise a profile archetype, which may be an actual member of the respective client cluster, or a fictional client system characterized by a specific position in profile space. For instance, a profile archetype may comprise a centroid of a client cluster determined by client clustering engine **74**.

[0069] To compute client profiles, some embodiments of client clustering engine **74** assign client
15 systems **10a-h** to clusters according to an event profile indicative of a typical distribution of events occurring on the respective client systems. In one exemplary embodiment, an event profile of a client system comprises a vector of numbers, each determined according to a count of events occurring on the respective client system and belonging to a distinct event cluster previously determined by event clustering engine **72**. In the example illustrated in Fig. 12, each
20 component of the event profile is determined according to a cluster allegiance measure indicative of a proportion of events belonging to the respective event cluster C_i , determined as a fraction of a total count of events available from the respective client system. For instance, when event clustering engine **72** has identified three event clusters C_1 , C_2 , and C_3 , an event profile vector $[0.1, 0.75, 0.15]$ may represent a client system wherein 10% of events occurring on the
25 respective client system belong to event cluster C_1 , while 75% of events belong to event cluster C_2 and 15% of events belong to event cluster C_3 .

[0070] In the exemplary embodiment illustrated in Fig. 11, each client system is represented in a multi-dimensional profile space according to the respective event profile. Stated otherwise, each coordinate of a client system represents a component of the respective client's event profile. Fig. 11 shows three exemplary client clusters/profiles **82a-c**. A skilled artisan may use any method known in the art of machine learning or data mining to construct such profiles; exemplary methods include variants of a k-means clustering algorithm and neural networks, among others. Alternative embodiments may use other criteria of assigning a client system to a cluster, or use such criteria in addition to the event profile of the respective client. Exemplary additional client clustering criteria include, among others, an owner and/or user of the respective client system, a network address of the respective client system, a device type of the respective client system, etc. For instance, clients belonging to the same family, the same corporation, or the same network domain may be grouped together in the same cluster.

[0071] Following client clustering, profiling engine **60** may save cluster parameters, such as a list of client systems assigned to each cluster/profile, coordinates of cluster archetypes (e.g., centroids), cluster diameters, etc., to profile database **19**.

[0072] Fig. 13 illustrates exemplary components and operation of anomaly detector **62** according to some embodiments of the present invention (see also Fig. 5). Anomaly detector **62** is configured to receive an event stream **24** comprising event indicators indicative of events occurring on various client systems, and in response, to output a security label **88** indicating whether the respective events are indicative of a security threat such as intrusion or execution of malicious software. In some embodiments, anomaly detector **62** comprises a profile manager **84** configured, in response to receiving an event notification indicative of an event occurring on a protected client system, to select a client profile according to the respective event. Profile manager **84** is further connected to a behavior model **86** configured to determine whether the respective event fits a pattern of normal/baseline behavior represented by the respective profile. When no, the respective event may be considered an anomaly, thus indicative of a possible attack on the respective client system.

[0073] In preparation for performing anomaly detection as shown below, some embodiments of anomaly detector **62** are first trained on an event corpus, using an output of profiling engine **60**. One purpose of training anomaly detector **62** is to determine a normal/baseline user behavior for each client profile identified by profiling engine **60**. Training comprises adjusting a set of parameters of behavior model **86** until a termination criterion is satisfied. The event corpus used for training anomaly detector **62** may differ from training corpus **18** used to train components of profiling engine **60**.

[0074] Fig. **14** shows an exemplary sequence of steps performed by anomaly detector **62** during a training procedure according to some embodiments of the present invention. In response to anomaly engine **60** constructing a set of client profiles, a step **242** selects one such client profile from profile database **19**. In some embodiments, each such client profile comprises a set of client clusters, for instance cluster **82a** in Fig. **11**. Each client cluster further includes a selected subset of protected client systems. A step **244** may select a training set of events registered as occurring on any client system associated with the respective profile/cluster. In some embodiments, step **244** may comprise selected the training set of events from training corpus **18** already used for constructing client profiles as shown above. A further step **246** may use the respective training set of events as training corpus to train behavior model **86**.

[0075] In some embodiments, behavior model **86** comprises components which are similar in structure and function to some components of profiling engine **60**. For instance, some embodiments of model **86** include an encoder-decoder pair as illustrated in Fig. **15**, which may be constructed using neural network technology and trained according to a member of the word2vec family of algorithms (see description above in relation to Figs. **8-A-B**). Training behavior model **86** may then amount to adjusting parameters of encoder **70c** and/or decoder **76c** (e.g., a set of synapse weights) with the aim of representing each event from the respective client cluster/profile as a vector in an event embedding space. In a preferred embodiment, encoder **70c** analyzes each event in the context of an event sequence and generates an embedding space wherein events that occur predominantly in similar contexts are separated by a smaller distance, compared to events that occur in other contexts. However, the event embedding space (i.e., the

meaning of the axes, size of inter-event distances, etc.) resulting from training encoder **70c** may differ substantially from the event embedding space resulting from training event encoder **70**, because the training corpora used for the two encoders are distinct.

[0076] In a preferred embodiment, step **246** comprises training the encoder-decoder pair using a version of the bag-of-words algorithm (see Fig. **8-B**). In one such example, the encoder-decoder pair (Fig. **15**) is configured to receive a plurality of events $E_k \dots E_{l-1}, E_l, \dots E_p$ representing an event context of a currently analyzed event sequence, and to produce an N -dimensional prediction score vector **90**, wherein each element is associated with a distinct event type, each element representing a likelihood that the central event of the respective event sequence is of the respective event type. For instance, a higher score value may indicate that the respective event type is more likely to occur as the central event of the respective event sequence than other event types having lower scores. In such embodiments, an exemplary training of model **86** may comprise selecting event sequences from the subset of events identified in step **244** (Fig. **14**), inputting the event context of the respective sequence to encoder **70c**, executing decoder **76c** to produce a prediction for the central event E_0 of the respective event sequence, and punishing incorrect predictions by backpropagating the prediction error through the neural networks that form encoder **70c** and/or decoder **76c**. In response to a successful training, a step **248** may save parameter values of the trained behavior model. The training procedure may be repeated for each client profile identified by profiling engine **60**.

[0077] Fig. **16** illustrates an exemplary sequence of steps performed by anomaly detector **62** to protect a target client system (such as clients **10a-h** in Fig. **1**) against computer security threats according to some embodiments of the present invention. The target client system may or may not be a member of the subset of clients providing the training corpus of events that produced behavior models and/or client profiles as shown above. To protect the target client system, events may be detected at the target client system and/or other devices such as routers **15a-b** (see Fig. **1**) and may be communicated to security server **16** in the form of event indicators. Such event indicators may be then pre-processed according to their source, event type, timing, service account settings, etc., and organized as event stream **24**. Events may be processed individually

or in batches. In response to receiving an event indicator from the target client system, in a step **254** anomaly detector **62** may assemble an event sequence to analyze according to the respective event indicator. Step **254** may include identifying the event source (i.e., client system where the respective event has occurred), selecting from event stream **24** a plurality of other events to form an event sequence. In some embodiments, members of the sequence are chosen so they all originated at the same target client system. In another example, all members of the sequence must occur on a pre-determined subset of client systems, such as a network subdomain, or a common IP address, for instance. Chosen events may also be ordered according to their time of occurrence and/or detection, for instance using a timestamp provided with the incoming event indicator. The event sequence may be further split into parts, for instance identifying a central event and an event context (see e.g., Fig. **8-A**).

[0078] In a step **256**, profile manager **84** may select a client profile according to the respective event indicator, e.g., according to an identity of the target client system where the respective event has occurred. When the respective target client system has provided training events for the development of client profiles and/or for the training of behavior models, step **256** may comprise selecting a client profile/cluster having the respective target client system as a member. Other profile selection criteria may also be used. For instance, step **256** may comprise selecting a client profile according to a position of the target client system within a client profile space (see Fig. **11**), e.g., by comparing the position of the target client system with a set of cluster archetypes or centroids and selecting the cluster/profile whose centroid is closest to the target client system. In one such example, the client profile may be selected according to an event profile determined for the target client system (e.g., according to a count of events received from the target client system, that fit into a particular event category/cluster). Other client profile selection criteria may include selecting the client profile according to a network address of the target client system (e.g., selecting a client profile containing clients having the same IP address as the target client system), to an owner/user of the target client system (e.g., selecting a profile containing members of the same household as the target client system), etc.

[0079] In a further step 258, anomaly detector may instantiate behavior model 86 with parameter values specific to the respective selected client profile. In some embodiments, following profile-specific instantiation, executing model 86 (step 260) comprises projecting events of the respective event sequence in the event embedding space associated with the respective client profile.

[0080] A step 262 may now determine whether the event(s) of the respective event sequence are representative of the normal/baseline user behavior associated with the respective client profile or not. In one embodiment, in step 260 comprises feeding the event context ($E_i, i \neq 0$) of the respective sequence to behavior model 86 and computing the prediction score vector 90 of the respective sequence. Step 262 may then comprise identifying the element of vector 90 corresponding to the event type of the actual central event E_0 of the sequence, and comparing the respective score to a pre-determined threshold (e.g., 0.95). In some embodiments, a score value lower than the threshold indicates that the respective event E_0 is substantially unlikely to occur in the respective event context, and therefore indicates an anomaly consistent with a potential computer security threat. In some embodiments, a user or administrator of security server 16 may tune the sensitivity of the method by adjusting the value of the threshold. In one such example, different threshold values are associated with different groups of client systems.

[0081] In an alternative embodiment, step 260 may comprise using model 86 to determine a representation of an event E_i of the sequence in the event embedding space specific to the respective client profile. Step 262 may then comprise determining whether event E_i fits a pattern of normal behavior for the respective client profile according to a position of the respective event within the embedding space. For instance, an event may be deemed normal when it is positioned within a cluster of training events (e.g., closer to a cluster centroid than a pre-determined threshold). In another example, an event may be considered normal/benign when located in certain regions of the embedding space, and anomalous when located in other regions.

[0082] When an event of the sequence (e.g., E_0) is considered an anomaly, or in other words not fitting the pattern of normalcy established through training for the respective client profile, a

step **264** may mark the respective event for further analysis. In some embodiments, an anomaly may trigger the transmission of a security alert by an alert manager **64** of security server **16** (see Fig. **5**). Security alerts may go out to the client system where the anomalous event has occurred and/or to an administrator of the respective client system. Incidents of anomalous events may
5 also be gathered and reported for further analysis to a computer security lab.

[0083] The exemplary systems and methods described above allow an efficient detection of computer security threats such as malicious software and intrusion. The disclosed systems and methods implement a behavioral approach to computer security, wherein a normal/baseline user behavior is automatically inferred by the system according to a training corpus of events, and
10 wherein a departure from a baseline behavior pattern may indicate a threat.

[0084] Some embodiments detect various events occurring at a plurality of client systems, e.g., computers, mobile telephones, network appliances, and virtual machines. Exemplary events include specific process launches, attempts to access certain files or network locations, and network traffic events like accessing certain ports and addresses, among others. A skilled artisan
15 will understand that the systems and methods described herein may be adapted to other kinds of events, such as events related to a user's activity on social media, a user's browsing history, and a user's gaming activity, among others. Event notifications are aggregated at a security server. A collection of such events may be used as a training corpus to construct a set of client profiles, wherein each client profile may represent a single user, a single machine, or multiple
20 users/machines. In some embodiments, each client profile comprises a subset of client systems and/or a subset of events that have occurred on the respective subset client systems. Each client profile may represent a normal and/or benign pattern of usage of the respective client systems. Such client profiles may then be used to detect incidents of anomalous behavior, which may be indicative of a computer security threat.

[0085] Some conventional computer security operate according to a set of rules that quantify behavior that is indicative of malice. Since developers are typically interested in offering such
25 solutions to a wide variety of clients, behavioral rules are usually generic and not tailored to

specific users. However, in practice, users are very heterogeneous. Even within the same company or family, the manner in which each member uses a computer may vary substantially. A set of actions that may be considered normal for a software developer or engineer may be very unusual when detected on a computer in the accounting department. Furthermore, the same user
5 may have substantially different behaviors at work versus at home. Therefore, generic behavioral rules may not capture the diversity and specificity of real users. In contrast to such conventional systems, in some embodiments of the present invention, events occurring on each client system are reviewed and analyzed selectively against a model capturing a normal/baseline behavior of the respective client system itself and/or of similar clients. Stated otherwise,
10 boundaries of behavioral “normality” may be defined with substantial specificity: a specific client machine, a specific group of users (e.g., a particular department of a company, members of a family, a particular age group), etc.

[0086] Due to the proliferation of software and Internet use, an attempt to develop highly specific behavior profiles, for instance profiles attached to each individual user, may require
15 unreasonable computational resources and may therefore be impractical. Furthermore, collecting events from individual users/machines may not provide enough data to develop statistically robust behavior models. In contrast to this approach, some embodiments of the present invention group multiple users and/or machines into a single client profile, thus ensuring a useful trade-off between specificity, robustness, and computational costs. In addition, the manner in which users
20 and machines are grouped into profiles is in itself based on behavioral criteria, to ensure that such grouping preserves specificity. In some embodiments, each client profile groups together users/machines that have substantially similar event profiles. Stated otherwise, all members of a client profile display a similar baseline behavior in terms of a statistic of events occurring on the member machines.

25 [0087] Some conventional computer security systems and methods mostly analyze individual events. Many events occurring during operation of a computer system (e.g., opening a file, accessing a webpage) may not be indicative of malice when taken in isolation. However, they may be malicious when they occur in the context of other events, for instance as a particular

sequence of actions. In contrast to more conventional solutions, some embodiments of the present invention explicitly analyze events in context and are therefore better suited to such event correlation situations. A preferred embodiment represents individual events as vectors in a multidimensional embedding space having the distinctive property that a pair of events that occur with relatively high frequency in the same event context are separated by a smaller distance than another pair of events that occur less frequently in the same event context.

[0088] Successful behavioral modeling may require detecting a large number (e.g., hundreds or thousands) of distinct event types, but not all event types may be equally important in behavioral modelling. Gathering and analyzing statistical data on such numerous event types received from a large number of sources may be impractical. To address this problem, some embodiments group events into event categories or clusters according to a degree of similarity between events, thus creating more robust and/or relevant statistics. Construction of client profiles may be substantially facilitated by such meaningful dimensionality reduction. Event similarity may be determined according to several criteria, for instance, according to a distance separating two events in an event embedding space. In a preferred embodiment, two events may be considered similar if they occur predominantly in the same context (e.g., events *A* and *B* are considered similar when both *A* and *B* are frequently preceded by event *X* and/or followed by event *Y*, i.e., as in exemplary sequences *XAY* and *XBY*).

[0089] Figs. 17-A-B illustrate an experiment of applying some of the systems and methods described above to the detection of computer security threats. An event corpus of events collected from multiple monitored clients was used to train components of a profiling engine as shown above, resulting in the monitored clients being divided into 11 client clusters/profiles. Events were binned into event categories according to a representation of each event in a 15-dimensional embedding space. Profile-specific behavior models were developed for each of the respective client clusters. A particular type of attack was then staged on a test machine. Event sequences harvested from the test machine were fed to an anomaly detector instantiated, in turn, with parameters specific to each of the behavior models. Some such event sequences were detected as anomalies.

[0090] Fig. 17-A shows cluster-specific anomaly scores, represented on a scale wherein a score of 1 indicates 100% certainty of an anomaly (e.g., at least one event of an event sequence received from the test machine had not been seen in training). The graph represents score values averaged over anomalous event sequences, and the associated standard deviations. The figure shows that the same sequence(s) may be considered anomalies with a certainty level that is cluster-specific. Stated differently, the same event sequences are considered “less anomalous” on certain clients than on others. For instance, behavior models associated with clusters 1, 2, and 7 not only detect the attack relatively higher efficiency than other models, but all event sequences associated with the attacks were considered “equally anomalous”. In contrast, the models associated with clusters 0 and 9 indicate some event sequences of the same attack as “less anomalous” than others.

[0091] Fig. 17-B shows profile-specific average detection rates achieved for three distinct types of attacks. Event sequences collected from the test machine during each type of attack were analyzed using each of the 11 profile-specific trained behavior models. The detection rate differs among models and types of attack, which further attests to the specificity of some of the systems and methods described herein.

[0092] Such experimental results indicate another potential application of some embodiments of the present invention. A centralized computer security solution may selectively develop protection strategies for each set of clients identified by a client profile and/or for other clients that bear a similarity to an archetype of each client cluster. Some embodiments may identify clusters of clients for which methods described herein offer a satisfactory degree of security, and other clusters of clients which require additional security measures. Tailoring protection to each cluster of clients may improve user experience and reduce unnecessary computational expense.

[0093] It will be clear to one skilled in the art that the above embodiments may be altered in many ways without departing from the scope of the invention. Accordingly, the scope of the invention should be determined by the following claims and their legal equivalents.

CLAIMS

1
2
1
2
3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26

1. A server computer system comprising at least one hardware processor configured to:
assign events of a training corpus to a plurality of event categories, the training corpus
comprising a collection of events having occurred on a plurality of client systems;
in response to assigning events to event categories, assign client systems of the plurality
of client systems to a plurality of client clusters according to the plurality of event
categories; and
in response to assigning client systems to client clusters, transmit a client cluster
membership indicator to an anomaly detector configured to determine whether a
target event occurring on a target client system is indicative of a computer
security threat;
wherein assigning events to event categories comprises:
selecting a plurality of events from the training corpus, the plurality of events
having occurred on a client system of the plurality of client systems,
arranging the plurality of events according to a time of occurrence to form an
event sequence, and
in response, assigning a selected event of the event sequence to a selected event
category according to a first event preceding the selected event and further
according to second event following the selected event within the event
sequence;
wherein assigning client systems to client clusters comprises assigning the client system
to a selected client cluster according to an event profile determined according to a
count of events occurring on the client system and belonging to the selected event
category; and
wherein the anomaly detector is configured to determine whether the target event is
indicative of the computer security threat according to a behavior model trained
on a client-cluster-specific sub-corpus of events, the client-cluster-specific sub-

27 corpus selected from the training corpus to include only events that have occurred
28 on a plurality of members of a target cluster of the plurality of client clusters.

29

1 2. The computer system of claim 1, wherein assigning events to event categories
2 comprises:

3 determining a position of the selected event in a multidimensional event
4 embedding space according to the first and second events; and
5 assigning the selected event to the selected event category according to the
6 position of the selected event in the event embedding space.

7

1 3. The computer system of claim 2, further configured to determine the selected
2 event category according to a cluster of events occupying similar positions
3 in the event embedding space.

4

1 4. The computer system of claim 2, wherein determining the position of the
2 selected event in the event embedding space comprises training an event
3 encoder to produce a set of coordinates indicating the position, and
4 wherein training the event encoder comprises:

5 coupling the event encoder to an event decoder configured to receive the
6 set of coordinates and to output a prediction indicator indicative of
7 a likelihood that the event sequence comprises the first and second
8 events; and

9 adjusting a set of parameters of the event encoder according to the
10 prediction indicator.

11

1 5. The computer system of claim 2, wherein determining the position of the
2 selected event in the event embedding space comprises training an event
3 encoder to produce a set of coordinates indicating the position, and
4 wherein training the event encoder comprises:

5 coupling the event encoder to an event decoder configured to receive the
6 set of coordinates and to output a predicted context of the selected
7 event, the predicted context comprising a first predicted event and
8 a second predicted event;
9 comparing the first predicted event to the first event and the second
10 predicted event to the second event; and
11 adjusting a set of parameters of the event encoder according to a result of
12 the comparison.
13

1 6. The computer system of claim 1, wherein the event profile comprises a plurality of
2 components, each component determined according to a proportion of events
3 belonging to each event category of the plurality of event categories, the
4 proportion calculated out of a total count of events of the training corpus
5 occurring on the client system.
6

1 7. The computer system of claim 1, wherein assigning client systems to client clusters
2 comprises assigning client systems having similar event profiles to the same client
3 cluster.
4

1 8. The computer system of claim 1, wherein the event of the training corpus comprises a
2 launch of a selected process on a client system of the plurality of client systems.
3

1 9. A computer-implemented method comprising:
2 employing at least one hardware processor of a computer system to assign events of a
3 training corpus to a plurality of event categories, wherein the training corpus
4 comprises a collection of events occurring on a plurality of client systems;
5 in response to assigning events to event categories, employing at least one hardware
6 processor of the computer system to assign client systems of the plurality of client

7 systems to a plurality of client clusters according to the plurality of event
8 categories; and
9 in response to assigning client systems to client clusters, employing at least one hardware
10 processor of the computer system to transmit a client cluster membership
11 indicator to an anomaly detector configured to determine whether a target event
12 occurring on a target client system is indicative of a computer security threat;
13 wherein assigning events to event categories comprises:
14 selecting a plurality of events from the training corpus, the plurality of events
15 having occurred on a client system of the plurality of client systems,
16 arranging the plurality of events according to a time of occurrence to form an
17 event sequence, and
18 in response, assigning a selected event of the event sequence to a selected event
19 category according to a first event preceding the selected event and further
20 according to second event following the selected event within the event
21 sequence;
22 wherein assigning client systems to client clusters comprises assigning the client system
23 to a selected client cluster according to an event profile determined according to a
24 count of events occurring on the client system and belonging to the selected event
25 category; and
26 wherein the anomaly detector is configured to determine whether the target event is
27 indicative of the computer security threat according to a behavior model trained
28 on a client-cluster-specific sub-corpus of events, the client-cluster-specific sub-
29 corpus selected from the training corpus to include only events that have occurred
30 on a plurality of members of a target cluster of the plurality of client clusters.

31
1 10. The method of claim 9, wherein assigning events to event categories comprises:
2 determining a position of the selected event in a multidimensional event
3 embedding space according to the first and second events; and

4 assigning the selected event to the selected event category according to the
5 position of the selected event in the event embedding space.

6
1 11. The method of claim 10, further comprising determining the selected event
2 category according to a cluster of events occupying similar positions in the
3 event embedding space.

4
1 12. The method of claim 10, wherein determining the position of the selected
2 event in the event embedding space comprises training an event encoder to
3 produce a set of coordinates indicating the position, and wherein training
4 the event encoder comprises:
5 coupling the event encoder to an event decoder configured to receive the
6 set of coordinates and to output a prediction indicator indicative of
7 a likelihood that the event sequence comprises the first and second
8 events; and
9 adjusting a set of parameters of the event encoder according to the
10 prediction indicator.

11
1 13. The method of claim 10, wherein determining the position of the selected
2 event in the event embedding space comprises training an event encoder to
3 produce a set of coordinates indicating the position, and wherein training
4 the event encoder comprises:
5 coupling the event encoder to an event decoder configured to receive the
6 set of coordinates and to output a predicted context of the selected
7 event, the predicted context comprising a first predicted event and
8 a second predicted event;
9 comparing the first predicted event to the first event and the second
10 predicted event to the second event; and

adjusting a set of parameters of the event encoder according to a result of the comparison.

14. The method of claim 9, wherein the event profile comprises a plurality of components, each component determined according to a proportion of events belonging to each event category of the plurality of event categories, the proportion calculated out of a total count of events of the training corpus occurring on the client system.

15. The method of claim 9, wherein assigning the plurality of client systems to client clusters comprises assigning client systems having similar event profiles to the same client cluster.

16. The method of claim 9, wherein the event of the training corpus comprises a launch of a selected process on a client system of the plurality of client systems.

17. A non-transitory computer-readable medium storing instructions which, when executed by at least one hardware processor of a computer system, cause the computer system to: assign events of a training corpus to a plurality of event categories, the training corpus comprising a collection of events having occurred on a plurality of client systems; in response to assigning events to event categories, assign client systems of the plurality of client systems to a plurality of client clusters according to the plurality of event categories; and in response to assigning the client systems to client clusters, transmit a client cluster membership indicator to an anomaly detector configured to determine whether a target event occurring on a target client system is indicative of a computer security threat; wherein assigning events to event categories comprises:

13 selecting a plurality of events from the training corpus, the plurality of events
14 having occurred on a client system of the plurality of client systems,
15 arranging the plurality of events according to a time of occurrence to form an
16 event sequence, and
17 in response, assigning a selected event of the event sequence to a selected event
18 category according to a first event preceding the selected event and further
19 according to second event following the selected event within the event
20 sequence;
21 wherein assigning client systems to client clusters comprises assigning the client system
22 to a selected client cluster according to an event profile determined according to a
23 count of events occurring on the client system and belonging to the selected event
24 category; and
25 wherein the anomaly detector is configured to determine whether the target event is
26 indicative of the computer security threat according to a behavior model trained
27 on a client-cluster-specific sub-corpus of events, the client-cluster-specific sub-
28 corpus selected from the training corpus to include only events that have occurred
29 on a plurality of members of a target cluster of the plurality of client clusters.
30