

Method and Device for Producing Individually Coded Read Patterns

Specification

This invention relates to a device for producing individually coded read patterns, a corresponding method as well as a read pattern produced by the method. The read patterns as claimed in the invention are used especially as components of RFID chips.

RFID components are becoming more and more important. The advantage of RFID components in contrast to the still common bar codes is that they can be read out electronically without direct visual contact and can be connected to more and more complex modules in an increasingly extremely cost-effective manner. Thus for example the first RFID components were simple transponders which delivered a response signal to an incoming signal. Currently development is proceeding in the direction of RFID components which can be operated without a power supply only by the induction of the electromagnetic radiation of a high frequency signal even together with other functional modules. Mainly memory modules which can be programmed and read out should be mentioned here. Modern RFID components have a coil, preferably a flat coil, a rectifier for converting the AC signal into DC, as well as the aforementioned functional modules.

In the early years the RFID technology was already being used in industry to mark goods in a production chain. A semifinished product received an RFID "label" and could be tracked, registered and monitored up to final installation within a factory. Furthermore RFID technology was also introduced into retail chains in which goods were protected against theft by RFID. Due to increasing miniaturization these components are not only being provided with more functions, but

also are becoming increasingly smaller and at the same time cheaper.

One of the main problems is the "coding" of the so-called code reflectors (resonators). Each RFID component has its own "number" (coding) which can be read out. The number is not present as software in a memory which must be read out, but is physically coded in a code reflector. The incoming electromagnetic "read wave" in a (flat) coil induces a current which feeds the RFID circuit. The resonator "returns" as the response signal a coded analog and/or digital signal which is emitted via an antenna. The resonators, in primitive terms, consist of line patterns. By providing line patterns at certain locations the resonant frequencies can be set. The problem is that several RFID chips or resonators are produced on one wafer in order to be able to economically produce a plurality of resonators. Of course each of the RFID chips must have its own "identification", therefore its own and mainly unique code. Of course a mask could be produced which justifies this circumstance by there being simply a corresponding pattern in the mask at each chip position. However the cost of preparing one mask per wafer is disproportionate. Since to date there has been no possibility of producing "dynamically variable masks", the production process of the resonators must take place separately from the other structures of the chip.

Until today, to produce resonators lithographic methods have been used in which the line patterns are produced individually. Technical problems are posed by the resolution which constitutes a limiting factor due to the ratio of the wavelength to the aperture. The smaller the patterns, the smaller the wavelengths must also be, and the more complicated the lithographic systems must be; this leads to a corresponding cost explosion.

Embodiments of this invention simplify the production of individually coded read patterns and thus to make available more economical RFID chips.

According to a first aspect, there is provided a device for producing individually coded read patterns, especially resonators for use in RFID chips, with a structuring apparatus for producing a basic pattern with at least one group of individual patterns on a carrier substrate and a processing apparatus for forming from a subset of a total set of the individual patterns of each group at least one read pattern with read elements, each read pattern being individually coded.

According to a second aspect, there is provided a method for producing individually coded read patterns, especially resonators for use with RFID chips, with the following steps, especially the following sequence: producing a basic pattern with at least one group of individual patterns on a carrier substrate by means of a structuring apparatus and forming at least one individually coded read pattern with read elements from a selected or selectable subset of a total set of individual patterns of each group.

According to a third aspect, there is provided a read pattern produced according to the above method and/or produced by the above device.

All combinations of at least two of the features given in the specification, the claims and/or the figures also fall within the scope of the invention. At the given value ranges, values within the indicated limits will also be considered to be disclosed as boundary values and will be claimed in any combination.

Embodiments of this invention first of all form an especially uniform basic pattern which is easy to produce on a carrier substrate and then on the foundation of this basic pattern to form an individually coded read pattern by processing of the basic pattern. Thus, for producing the basic pattern standard methods can be used so that in spite of providing several steps up to production of the read pattern, production is enabled which is more economical compared to the prior art.

An embodiment of the invention is therefore a device for producing individually coded read patterns, especially resonators, with the following features:

- a structuring apparatus, especially in the form of a lithography system, for producing a basic pattern with at least one group of individual patterns on a carrier substrate and
- a processing apparatus which consists of several apparatus for forming at least one individually coded read pattern at a time with read elements from a selected or selectable subset of a total set of the individual patterns of each group.

According to one advantageous embodiment of the invention it is provided that the processing apparatus has application means for at least partial covering of an unselected remaining number of the total number of individual patterns of each group with a fluid, especially a polymer. Thus the formation of read elements or a read pattern on the covered individual patterns can be

prevented by controlled triggering of the application means. This leads to a significant simplification and more economical production of the read patterns.

To the extent the application means have at least one dispenser which has a nozzle, especially a nanodispenser, exact and prompt metering of even extremely small amounts of fluid is possible.

Advantageously it is furthermore provided that the structuring apparatus, especially as an embossing apparatus, is made to produce the individual patterns in alternation as depressions and especially elevations which have been formed by formation of the depressions. The individual patterns can be especially economically produced in this way with extremely small dimensions.

By the device being set up in an advantageous configuration such that each read element is made on one individual pattern at a time, especially exclusively on one depression at a time, the covering of the respective unselected individual pattern can be especially easily and reliably implemented.

Moreover as per embodiments of the invention it is conceivable that the processing apparatus has reducing agents which act especially by etching, for especially uniform reduction of the thickness D_1 of the basic pattern, especially at least by one height h of the depressions (of the carrier substrate). Thus the surface of the depressions after reduction/stripping is formed by the carrier substrate so that material which is then introduced in the depressions for the formation of the read pattern can be joined directly to the carrier substrate.

In another advantageous embodiment of the invention it can be provided that the processing apparatus has coating means for especially blanket coating, especially deposition, of a coating material which at least partially forms the read pattern, on the groups or the basic pattern. The

coating material can be easily applied in this way over the entire surface, unselected individual patterns being impeded from coating by the covering with the fluid. The unselected individual patterns are thus not coated.

Advantageously the processing apparatus has means for especially complete dissolution of the basic pattern which has been reduced especially by the reducing agents from the carrier substrate. Thus, the coating which had been applied in the selected individual patterns, especially depressions, now remains on the carrier substrate so that an individual read pattern results from the selected individual patterns and moreover allows clear delineation between the individual read elements and can be made especially thin.

An embodiment of the invention is a method for producing individually coded read patterns, especially resonators, with the following steps, especially the following sequence:

- producing a basic structure with at least one group of individual patterns on a carrier substrate by means of a structuring apparatus and
- forming at least one individually coded read pattern with read elements from a selected or selectable subset of a total set of individual patterns of each group.

Insofar as features relating to the device have been described, they should also be considered disclosed as features relating to the method.

Furthermore embodiments of this invention relate to a read pattern which has been produced by the described device and the described method.

Embodiments of the invention relate not only to the production of RFID resonators, but in general to the production of individually coded mechanical-electronic binary patterns. The RFIDs are one preferred embodiment or preferred use of the invention. One alternative use of embodiments of the invention

would be the production of mechanical-electronic patterns which provide devices with a serial number in order to uniquely identify them. These serial numbers are stored mainly electronically in the prior art, especially permanently in flash memories, or semipermanently. These memories can however be manipulated, replaced or altered. Thus the embodiment as claimed in the invention allows the production of individually codable patterns in a mass production process. The use of these patterns can be diverse, as shown using some preferred embodiments.

Other advantages, features and details of the invention will become apparent from the following description of the figures. The figures are schematic and highly enlarged.

Figure 1 shows a cross sectional view of a carrier substrate by way of extract, with a basic pattern as claimed in the invention,

Figure 2 shows a schematic of application means which can be aligned and which is located above the basic pattern,

Figure 3 shows the application of a fluid to the basic pattern, as claimed in the invention,

Figure 4 shows a step of reducing/stripping of the thickness D_1 of the basic pattern, as claimed in the invention,

Figure 5 shows a step of coating of the basic pattern, as claimed in the invention, and

Figure 6 shows a step of dissolving the basic pattern, as claimed in the invention.

In the figures, advantages and features of the invention are labeled with these reference numbers which identify them according to embodiments of the invention, components or features with the same function or function with the same effect being labeled with identical reference numbers.

The figures show the features as claimed in the invention not to scale, in order to be able to represent the function of the individual features at all. The ratios of the individual components can be disproportionate; this can be attributed to the individual patterns 4e, 4v which are shown highly enlarged.

Figure 1 shows a carrier substrate 3, especially in the form of a wafer, by way of extract, specifically an extract with a group 2.1 of individual patterns 4v, 4e at least temporarily fixed on a surface 3o of the carrier substrate. On the carrier substrate 3 there is a plurality of groups 2.1 to 2.n which jointly form a basic pattern 2. The latter can also be applied as a continuous basic pattern 2, especially by nanoimprinting, so that the groups 2.1 to 2.n at first cannot be visibly distinguished, but are separated only by later separation/partitioning.

The basic pattern 2 consists of the individual patterns, which in turn consist of depressions 4v and elevations 4e which are formed by the formation of depressions 4v. The basic pattern 2 has an average thickness D_1 which is as uniform as possible. The depressions 4v extend over a height h from the carrier substrate 3. The elevations 4e rise above the depressions 4v by a height H and the depressions have an especially uniform width B . The elevations 4e can have different lengths in depth, and can be made especially as strips.

In Figure 2 an application means 6 in the form of a nanodispenser system for applying a fluid 8 via at least one nozzle 7 can be located opposite the basic pattern 2. Application takes place both locally and also quantitatively exactly controlled, especially by a central control apparatus.

The application means 6 in one special embodiment has several nozzles 7, therefore a type of nozzle array of several nozzles 7. The nozzles 7 can advantageously be triggered individually and can thus deposit several droplets at the same time. The distance between the nozzles is especially

identical to the distance between the depressions 4v, preferably it can be set individually, especially controlled by a central control apparatus.

To form individually coded read patterns 11 (see Figure 6) depressions 4v which have not been selected by the application means are covered with a fluid, especially applied in droplet form. The fluid 8 is a polymer, the volume of the applied fluid being less than 100 μl , especially less than 100 nl, even more preferably less than 10 nl, preferably less than 1 nl. A plurality of droplets is applied on corresponding unselected depressions 4v. The distribution of the unselected depressions later yields an individual read pattern 11. The selection can be especially randomly controlled.

The droplets are applied especially along the entire basic pattern 2, therefore for a plurality of groups 2.1 to 2.n, for each group 2.1 to 2.n there being a different pattern for droplet application.

In the method step which is shown in Figure 4, a part of the exposed outer contour of the basic pattern 2, is stripped by reducing agents, especially uniformly on the entire exposed surface of the outer contour, especially by etching methods, preferably using a fluid etchant.

The thickness D_1 of the basic pattern 2 is stripped at least by the height h of the depressions 4v so that at least the uncovered individual patterns, especially elevations 4e, have a new, especially essentially uniform thickness D_2 . Thus the selected individual patterns are formed by reduced elevations 4e' and especially completely reduced depressions 4v' whose bottom is formed especially completely by the carrier substrate 3.

In the subsequent method step according to Figure 5 the basic pattern 2 is coated with a coating material 10, especially completely (therefore all groups 2.1 to 2.n), therefore both the selected and also the unselected individual patterns, by coating means (deposition means). The coating material 10 is preferably a metal. The coating takes place from a direction perpendicular to

the surface 3o of the carrier substrate 3 on which the basic pattern 2 is located. Thus surfaces which are perpendicular (or essentially perpendicular) to the surface 3o, specifically especially side walls 4s of the individual patterns (which at the same time form the depressions 4v, 4v') are not coated or are coated at least negligibly with the coating material 10. The more dramatically one surface is tilted relative to the surface 3o, the less coating material 10 is applied there. This can be recognized especially well on the droplet-shaped coating of the fluid 8 which becomes thinner and thinner towards the edge which is dropping off more and more steeply. The amount of the coating is such that a thickness d of the coating is smaller than the thickness D2 and/or smaller than the height H of the elevations 4e' (optionally reduced height H'). Thus the side walls 4s are at least partially exposed.

As shown in Figure 6, the basic pattern 2 is stripped by dissolving agents (here by a stripping method) so that only the part of the coating material 10 applied directly on the surface 3o of the carrier substrate 3 remains on the carrier substrate 3 since it is connected to the surface 3o by the coating and not, like the other partial amount of the coating material 10, detached/ stripped/removed with the basic pattern 2 or the fluid 8. The detachment takes place preferably by chemical processes, especially when the coating material 10 is a photoresist. The means for dissolving the basic pattern selectively dissolve the basic pattern 2 and preferably do not attack the coating material 10.

The coating material 10 which remains on the surface 3o corresponds to the shape according to the selected depressions 4v and this part of the coating material 10 forms the read elements 9.

The read elements 9 are coded differently in each group 2.1 to 2.n and can be used as a

resonator for RFID chips. Each group 2.1 to 2.n of read elements 9 thus forms a coded read pattern 11 with a small thickness d.

The groups 2.1 to 2.n with the respectively coded read structure 11 can be separated especially after a back-thinning process of the carrier substrate 3.

Thus, a plurality of differently coded read patterns 11 can be easily produced. Thus, on one carrier substrate 3 several 100 read patterns 11 with different coding can be produced, and for each new carrier substrate a new individual coding can be provided.

The basic patterns 2 and the read patterns 11 can be inspected by means of different measurement methods such as optical microscopy, scanning tunnel microscopy, scanning electron microscopy, AFM (atomic force microscopy) or MFM (magnetic force microscopy) etc., before the method as claimed in the invention, during or after the execution of the method as claimed in the invention.

Reference number list

2	basic pattern
2.1 to 2.n	groups
3	carrier substrate
3o	surface
4v, 4v'	depressions
4e, 4e'	elevations
4s	side walls
6	application means
7	nozzle
8	fluid
9	read elements
10	coating material
11	read pattern
D1	thickness
D2	thickness
d	thickness
h	height
H, H'	height
B	width

Claims

1. A device for producing individually coded read patterns (11), especially resonators for use in RFID chips, with
 - a structuring apparatus for producing a basic pattern (2) with at least one group (2.1 to 2.n) of individual patterns (4v, 4e) on a carrier substrate (3) and
 - a processing apparatus for forming from a subset of a total set of the individual patterns (4v, 4e) of each group (2.1 to 2.n) at least one read pattern (11) with read elements (9), each read pattern (11) being individually coded.
2. The device as claimed in Claim 1, wherein the processing apparatus has application means (6, 7) for at least partial covering of an unselected remaining number of the total number of individual patterns (4v, 4e) of each group (2.1 to 2.n) with a fluid (8), especially a polymer.
3. The device as claimed in Claim 2, wherein the application means (6, 7) have at least one dispenser (6) which has a nozzle (7), especially a nanodispenser.
4. The device as claimed in one of the preceding claims, wherein the structuring apparatus, especially as an embossing apparatus, is made to produce the individual patterns (4v, 4e) in alternation as depressions (4v) and especially elevations (4e) which have been formed by formation of the depressions (4v).
5. The device as claimed in one of the preceding claims, wherein the processing apparatus is set up such that each read element (9) is made on one individual pattern (4e, 4e', 4v, 4v') at a time, especially exclusively on one depression (4v) at a time.

6. The device as claimed in one of the preceding claims, wherein the processing apparatus has reducing agents which act especially by etching, for especially uniform reduction of the thickness (D_1) of the basic pattern (2), especially at least by one height (h) of the depressions (4v, 4v').

7. The device as claimed in one of the preceding claims, wherein the processing apparatus has coating means (10) for especially blanket coating, especially deposition, of a coating material (10) which at least partially forms the read pattern (11), on the groups (2.1 to 2.n) or the basic pattern (2).

8. The device as claimed in one of the preceding claims, wherein the processing apparatus has means for especially complete dissolution of the basic pattern (2) which has been reduced especially by the reducing agents from the carrier (3).

9. A method for producing individually coded read patterns (11), especially resonators for use with RFID chips, with the following steps, especially the following sequence:

- producing a basic pattern (2) with at least one group (2.1 to 2.n) of individual patterns (4v, 4e) on a carrier substrate (3) by means of a structuring apparatus and
- forming at least one individually coded read pattern (11) with read elements (9) from a selected or selectable subset of a total set of individual patterns (4v, 4e) of each group (2.1 to 2.n).

10. The method as claimed in Claim 9, wherein the formation of the read structure (11) comprises an at least partial covering of an unselected residual number of the total number of individual patterns (4e, 4v) of each group (2.1 to 2.n) with a fluid (8), especially a polymer, by applications means.

11. The method as claimed in Claim 9 or 10, wherein the formation of the read structure comprises the following steps, especially the following sequence:

- reduction of the thickness (D1) of the basic pattern (2) by reducing agents,
- especially blanket coating, especially deposition of a coating material (10) which forms at least partially the read pattern (11) and
- dissolution of the basic pattern (2) from the carrier substrate (3).

12. The method as claimed in one or more of Claims 9 to 11, wherein one read pattern (11) at a time is formed from each group (2.1 to 2.n) and each read pattern (11) is coded differently.

13. The method as claimed in one or more of Claims 9 to 12, wherein the individual patterns (4e, 4v) are produced by the structuring apparatus in alternation as depressions (4v) and especially elevations (4e) which have been formed especially by formation of the depressions (4v), especially by imprint lithography.

14. The method as claimed in one or more of Claims 9 to 13, wherein each read element (9) is formed on one individual pattern (4e, 4e', 4v, 4v') at a time, especially exclusively on one depression (4v, 4v') at a time.

15. A read pattern (11), produced according to a method as claimed in one or more of Claims 9 to 14 and/or produced by a device as claimed in one or more of Claims 1 to 8.

4.

Method and Device for Producing Individually Coded Read Patterns

Abstract

This invention relates to a device for producing individually coded read patterns (11), especially resonators for use in RFID chips, with:

- a structuring apparatus for producing a basic pattern (2) with at least one group (2.1 to 2.n) of individual patterns (4v, 4e) on a carrier substrate (3) and
- a processing apparatus for forming at least one individually coded read pattern (11) at a time with read elements (9) from a subset of a total set of the individual patterns (4v, 4e) of each group (2.1 to 2.n).

Furthermore this invention relates to a corresponding method and a read structure, produced according to the described method and/or the described device.

Figure 5