

- 1 -

PHASED ARRAY ANTENNA ASSEMBLY

TECHNOLOGICAL FIELD

This invention relates to phased array antennas, in particular, to cooling and temperature control mechanisms therefore.

BACKGROUND

5 A phased array antenna generally comprises a plurality of individual modules, each having a transmit/receive circuitry. The modules are arranged in an array, usually by mounting each module onto a carrier assembly.

 When mounted onto the carrier assembly, each module is adapted to be connected to additional transmit/receive circuitry so that it may be attached to a
10 mainframe or a control center.

 Electrical work of the modules usually generates heat, which has a negative effect on the electrical performance of power amplifiers comprised within the modules. Therefore, it is required to cool the modules down in order to increase performance of the modules and prevent malfunction thereof.

15 In cooling the modules, not only the overall temperature of a single module has an effect on performance, but also the temperature variation between different modules of the same array. Thus, it is also required to maintain a low temperature variation between modules, i.e. maintain a sufficiently uniform temperature across the entire phased array antenna, allowing it to operate properly.

20 Cooling of the modules, as any other cooling, may be performed by one or more of the three known mechanisms: radiation, convection and conduction. Common methods for cooling the modules includes a system of cooling pipes adapted for the flow of a cooling fluent therein, thereby removing heat from the modules by convection. Also, it is known to attach to the carrier assembly a radiation plate, thereby further
25 removing heat from the modules by radiation.

- 2 -

GENERAL DESCRIPTION

According to one aspect of the disclosed subject matter of the present application, there is provided a carrier plate configured for mounting thereto a plurality of communication units to form a phased array antenna, said carrier plate being
5 integrally formed with a plurality of sockets, each of said sockets being adapted to receive therein one of said plurality of communication units, wherein said carrier plate is further integrally formed with one or more cooling channels extending along said carrier plate and associated with said sockets, and configured for passage of a cooling fluid therethrough for cooling of said plurality of communication units during operation
10 of said antenna.

Under the above arrangement, the carrier plate constitutes, within a single block of material, all of the following:

- the antenna body constituted by the sockets configured for receiving the communication unit);
- 15 - the cooling arrangement constituted by the cooling channels; and
- the supporting structure of the antenna itself.

In connection with the above, it is appreciated that this arrangement provides for a considerably simpler and more efficient design, elegantly eliminating the need for a separate cooling arrangement and/or a support structure, as common in the field.

20 The carrier plate can be configured for mounting thereto, on an opposite side of the sockets, a transmission module configured for connecting to the individual communication units and provide and/or receive signals therefrom. It should be noted that, despite the terms 'transmission' and 'communication', such an antenna can operate at either a transmission only mode, receiving only mode or a combination of both.

25 In this connection, since the cooling arrangement is integrated in the structure of the carrier plate itself (and not individually provided to each transmission module), this configuration allows for a simple plug-in of the transmission modules. Specifically, in order to mount/dismount such a transmission module onto/from the carrier plate, it is not required to attach/detach any cooling pipes or conduits. The transmission module
30 can simply be mounted onto the carrier plate and plug into the leads of the communication units.

The arrangement can be such that when said communication units are placed within said sockets, they are in surface-to-surface contact with the carrier plate, so that

- 3 -

there is provided heat conduction between said communication units via said carrier plate. In particular, the carrier plate can have a cooling surface configured, when the communication units are placed, to be interposed between the cooling channel and the communication unit.

5 One of the advantages of the above design lies in the compact configuration of the antenna which, *inter alia*, reduced the physical distance between the communication units and the transmission module, thereby reducing losses and making the system more efficient.

 In addition, since the carrier plate is made of a single, solid material, it provides
10 the antenna with toughness and stability which are considerably high with respect to its weight, thereby reducing system errors which may be caused by deformation in the array of the communication modules.

 According to a specific design, the carrier plate can be constituted by a plurality of modular carrier plate units, each being integrally formed with its own socket/s and
15 cooling channel/s, the units being configured for successive attachment to one another to form a combined antenna of greater dimensions.

 In particular, the arrangement can be such that, when two or more carrier plates are attached to one another along one direction, the cooling channels thereof are collinear and become interconnected, allowing fluid communication therebetween.
20 When the carrier plates are attached to one another along a second direction, different than the first, the cooling channels can be arranged parallel/angled to one another.

 Per the above, when a plurality of modular units are connected to one another in any way, a distribution arrangement can be provided for interconnecting the cooling channels of each of the modular carrier plate units to provide fluid association between
25 the channels.

 When two or more carrier plates are attached to one another not along the longitudinal direction (e.g. so that the cooling channels thereof are parallel to one another), at least two configuration of the fluid distribution arrangement can be provided:

30 **Parallel cooling** – the distribution arrangement comprises a main feed with a manifold simultaneously connected to first, inlet ends of the cooling channels and a main outlet with a manifold simultaneously connected to second, outlet ends of the cooling channels so that each of the cooling channels simultaneously receives, in

- 4 -

parallel, a cooling fluid. Thus, at all the first ends (inlet) the cooling fluid is of the lowest temperature and at all the second ends (outlet), the cooling fluid is of the highest temperature (having removed heat from the communication units).

In-line cooling – the cooling channels are connected in a consecutive manner, the second end (outlet) of one channel being connected to the first end (inlet) of the cooling channel of the consecutive carrier plate. Thus, the cooling fluid enters the first end of the first cooling channel at the lowest temperature and is emitted from the second end of the last cooling channel at the highest temperature.

However, according to a specific design of the subject matter of the present application, each carrier plate can be formed with a first cooling channel and a second cooling channel. The distribution arrangement can be configured for a unique successive connection of the cooling channels so that fluid is first forced to flow through the first channel of each of the carrier plates and only then returned through the second channel of each of the carrier plates.

With regards to the above, the cooling fluid enters the first channel of the first carrier plate at the lowest temperature t and reaches the outlet end of the first channel of the last carrier plate at a higher temperature $t' > t$. Thereafter, it is returned first through the second channel of the last carrier plate and, after passing through the second cooling channels of all carrier plate units, reaches the outlet end of the second channel of the first carrier plate unit at a temperature $T > t' > t$.

The unique arrangement above provides that the average temperature of the cooling fluid in each carrier plate is approx. t' . This arrangement allows, on the one hand, the simplicity of a successive connection between carrier plates (not requiring a manifold and not limited in size) and, on the other hand, for a uniform average temperature between all carrier plates.

The carrier plate can further be formed with a utility channel configured for accommodating therein all the necessary electronic/mechanical components required for the operation of the communication units. The arrangement can be such that the utility channel is isolated from the one or more cooling channels. In particular, in case the carrier plate is made by extrusion, the material of the carrier plate itself forms the barrier between the one or more cooling channels and the utility channel, providing said isolation.

- 5 -

In addition, according to one example, the modular units may be made of the same material, facilitating uniform heat conduction throughout the carrier plate. Alternatively, according to another example, each of the modular units may be made of a different material, depending on the communication unit adapted to be received in the
5 socket thereof.

According to another aspect of the subject matter of the present application, there is provided a method for configuring a cooling arrangement of a phased array antenna comprising two or more carrier plates of the previous aspect of the present application, each carrier plate having a first cooling channel and a second cooling
10 channel, the method includes the steps of:

- a) providing a fluid inlet associated with a first end of the first channel of the first carrier plate;
- b) consecutively attaching a second end of the first channel of each carrier plate but last to the first end of the first channel of a successive carrier plate;
- 15 c) attaching the second end of the first channel of the last carrier plate with a first end of the second channel of the last carrier plate;
- d) consecutively attaching a second end of the second channel of each carrier plate but first to the first end of the first channel of a successive carrier plate; and
- 20 providing a fluid outlet associated with a second end of the second cooling channel of the first carrier plate.

BRIEF DESCRIPTION OF THE DRAWINGS

In order to better understand the subject matter that is disclosed herein and to exemplify how it may be carried out in practice, embodiments will now be described,
25 by way of non-limiting example only, with reference to the accompanying drawings, in which:

Fig. 1A is a schematic rear isometric view of a portion of a carrier plate of the present application with a plurality of communication units attached thereto;

Fig. 1B is a schematic rear isometric view of the carrier plate shown in Fig. 1A;

30 **Fig. 1C** is a schematic front isometric view of the carrier plate shown in Fig. 1A;

Fig. 1D is a schematic rear view of the carrier plate shown in Fig. 1B;

Fig. 1E is a schematic cross section of the carrier plate shown in Fig. 1B;

- 6 -

Fig. 2A is a rear exploded view of the carrier plate shown in Fig. 1A;

Fig. 2B is a front exploded view of the carrier plate shown in Fig. 1A; and

Fig. 3 is a schematic isometric view of a carrier plate formation constituted by a plurality of carrier plates shown in Fig. 1B.

5 DETAILED DESCRIPTION OF EMBODIMENTS

Attention is first drawn to Figs. 1A to 1E in which a part of a phased array antenna is shown generally designated **1** and comprising a carrier plate **10** and a transmission module **M** mounted thereon. The phased array antenna **1** is further provided with a front cover **P**, configured for shielding.

10 The carrier plate **10** is made of a single extruded body having a rear surface **12** and a front surface **14**, the plate **10** having a longitudinal axis **X** defining a first direction of the plate **10** (parallel to the direction of extrusion).

With particular reference being made to Fig. 1C, the front surface **14** of the carrier plate **10** is formed with a plurality of sockets **11** configured for accommodating
15 therein a corresponding plurality of communication units **C**, which are in turn associated with the transmission module **M**, mounted on the rear surface **12** of the carrier plate **10**. The communication units **C** are shielded by the cover plate **P** (shown Figs. 2A, 2B).

In the course of operation of the phased array antenna **1**, the module **M** and
20 communication units **C** generate a considerable amount of heat which is required to be removed from the antenna.

For this purpose, the carrier plate **10** is formed with a first set of cooling channels **16a**, **16b** and a second set of cooling channels **18a**, **18b**, each extending along the longitudinal axis **X** and being formed during the extrusion process. The cooling
25 channels **16a**, **16b**, **18a**, **18b** are configured for the passage therethrough of a cooling fluid for cooling the module **M** mounted onto the carrier plate **10**, and are each provided with openings at respective ends of the carrier plate **10**, configured for serving as fluid inlets or fluid outlets.

The arrangement is such that the first set of cooling channels **16a**, **16b** is located
30 at a top portion of the carrier plate **10** while the second set of cooling channels **18a**, **18b** is located at a bottom portion of the carrier plate **10**.

- 7 -

Between the top portion and the bottom portion there extends a utility channel **15**, configured for accommodating therein the electronic wiring and utility components required for operation of the antenna. The utility channel **15** is machined out of the solid piece of the carrier plate **10** and is completely isolated from the cooling channels **16a**, **16b**, **18a**, **18b**, so that the above electronic components are protected from coming in contact with any cooling fluid flowing within the channels.

With additional reference being made to Figs. 2A and 2B, the carrier plate **10** is configured for attachment to additional carrier plates **10** along a lateral direction, perpendicular to the longitudinal direction, in order to form a multi-plate (see Fig. 3). For this purpose, each carrier plate **10** is formed, at the bottom portion thereof with a longitudinal protrusion **19a** and at a top portion thereof with a longitudinal groove **19b**. In order to secure carrier plates **10** to each other, securing pins **17** are used, extending between the front surface **14** and the rear surface **12**, passing through the protrusion **19a**.

It is appreciated that since each carrier plate **10** is manufactured by extrusion, and since carrier plates **10** can be attached to each other successively along the above lateral direction, it is possible to construct, using carrier plates **10** of various lengths, almost any desired shape of the multi-plate for the multi-phase antenna.

The carrier plate **10** is also formed with openings **13**, extending between the front surface **14** and the rear surface **12**, each being configured for accommodating therethrough a guide port **22**. Each of these guide ports **22**, in turn, is configured for receiving therein a plug **24** connecting the communication units **C** with the transmission module **M**.

Turning now to Fig. 3, the cooling method of the modules **M** and the carrier plates **10** will now be described, and includes the following steps:

- cooling fluid at temperature T_0 is provided through the inlet **I** of the second set of cooling channels **18a**, **18b** of the first carrier plate;
- the cooling fluid is then passed through the first carrier plate (sections 9, 10, 11 and 12 of the multi-plate, consecutively) being gradually heated as it absorbs heat (by convection) from the modules **M** and communication units **C**;

- 8 -

- the cooling fluid is then emitted from the outlet **II** of the second set of cooling channels **18a, 18b** at the opposite end of the first carrier plate **10** at temperature $T_1 > T_0$;
- the cooling fluid is then passed into the second set of cooling channels **18a, 18b** of the second carrier plate **10** (the plate immediately above it);
- the cooling fluid flows through the second carrier plate (sections 8, 7, 6 and 5 consecutively) being further heated;
- the cooling fluid is emitted from the outlet **III** of the second carrier plate at a temperature $T_2 > T_1 > T_0$;
- the cooling fluid is then passed into the second set of cooling channels **18a, 18b** of the third carrier plate **10**;
- the cooling fluid flows through the third carrier plate (sections 1, 2, 3 and 4 consecutively) being further heated;
- the cooling fluid is emitted from the outlet **IV** of the third carrier plate at a temperature $T_3 > T_2 > T_1 > T_0$.
- the cooling fluid is then passed into the first set of cooling channels **16a, 16b** of the third carrier plate **10** (i.e. the same carrier plate as opposed to the previous 2);
- the cooling fluid flows through the third carrier plate again, but in the opposite direction (sections 4, 3, 2 and 1 consecutively) being further heated;
- the cooling fluid is then emitted from the outlet **V** of the third carrier plate at a temperature $T_4 > T_3 > T_2 > T_1 > T_0$;
- the cooling fluid is then passed into the first set of cooling channels **16a, 16b** of the second carrier plate **10**;
- the cooling fluid flows through the second carrier plate (sections 5, 6, 7 and 8 consecutively) being further heated;
- the cooling fluid is emitted from the outlet **VI** of the second carrier plate at a temperature $T_5 > T_4 > T_3 > T_2 > T_1 > T_0$;
- the cooling fluid is then passed into the first set of cooling channels **16a, 16b** of the first carrier plate **10**;
- the cooling fluid flows through the first carrier plate (sections 12, 11, 10 and 9 consecutively) being further heated;

- 9 -

- the cooling fluid is emitted from the first carrier plate at a temperature $T_6 > T_5 > T_4 > T_3 > T_2 > T_1 > T_0$;

With reference to the above, it is observed that the average temperature of the cooling fluid in each carrier plate is essentially the same:

5 First carrier plate:

Second set of cooling channels – $(T_0 + T_1)/2$;

First set of cooling channels – $(T_5 + T_6)/2$;

Overall temperature - $(T_0 + T_1 + T_5 + T_6)/2$

Second carrier plate:

10 Second set of cooling channels – $(T_1 + T_2)/2$;

First set of cooling channels – $(T_4 + T_5)/2$;

Overall temperature - $(T_1 + T_2 + T_4 + T_5)/2$

Third carrier plate:

Second set of cooling channels – $(T_2 + T_3)/2$;

15 First set of cooling channels – $(T_3 + T_4)/2$;

Overall temperature - $(T_2 + T_3 + T_3 + T_4)/2$

This method of passage of the cooling fluid through the carrier plates elegantly provides for averaging of the temperature in each carrier plate. Furthermore, it also makes sure that the temperature at one end of the carrier plate is not considerably greater/lower than the temperature at the other end of the same carrier plate (as would be the case if cooling fluid was passed in parallel simultaneously through all carrier plates). In particular, $(T_0 + T_6)/2$ (at the inlet end of carrier plate 10) is essentially equal to $(T_1 + T_5)/2$ (at the opposite end of the carrier plate 10).

Those skilled in the art to which this invention pertains will readily appreciate that numerous changes, variations, and modifications can be made without departing from the scope of the invention, *mutatis mutandis*.

CLAIMS:

1. A carrier plate configured for mounting thereto of a plurality of communication units to form a phased array antenna, said carrier plate being integrally formed with a plurality of sockets, each of said sockets being adapted to receive therein at least one of
5 said plurality of communication unit, wherein said carrier plate is further integrally formed with one or more cooling channels extending along said carrier plate and associated with said sockets, and configured for passage of a cooling fluid therethrough for cooling of said plurality of units during operation of said antenna.
2. A carrier plate according to Claim 1, wherein, said units, when placed within
10 said sockets, are in surface-to-surface contact with the carrier plate, so that there is provided heat conduction between said units via said carrier plate.
3. A carrier plate according to Claim 1 or 2, wherein the carrier plate has a cooling surface configured, when the units are placed, to be interposed between the cooling channel and the unit.
- 15 4. A carrier plate according to Claim 1, 2 or 3, wherein the carrier plate is constituted by a plurality of modular carrier plate units, each being integrally formed with its own cooling channel.
5. A carrier plate according to Claim 4, wherein the units are configured for successive attachment to one another to form an antenna of greater dimensions.
- 20 6. A carrier plate according to any one of the preceding Claims, wherein, when two or more carrier plates are attached to one another along one direction, the cooling channels thereof are collinear and become interconnected, allowing fluid communication therebetween.
7. A carrier plate according to Claim 6, wherein, when the carrier plates are
25 attached to one another along a second direction, different than the first, the cooling channels can be parallel/angled to one another.
8. A carrier plate according to Claim 7, wherein, a distribution arrangement is provided for interconnecting the cooling channels to provide fluid association between the channels.
- 30 9. A carrier plate according to Claim 8, wherein said distribution arrangement comprises a main feed with a manifold simultaneously connected to first ends of the cooling channels and a main outlet with a manifold simultaneously connected to second

- 11 -

ends of the cooling channels so that each of the cooling channels simultaneously receives, in parallel, a cooling fluid.

10. A carrier plate according to Claim 8, wherein the cooling channels are connected in a consecutive manner, the second end (outlet) of one channel being connected to the
5 first end (inlet) of the cooling channel of the consecutive carrier plate.

11. A carrier plate according to any one of the preceding Claims, wherein, each carrier plate is formed with a first cooling channel and a second cooling channel.

12. A carrier plate according to Claim 11, wherein the distribution arrangement is configured for a successive connection of the cooling channels so that fluid is first
10 forced to flow through the first channel of each of the carrier plates and only then returned through the second channel of each of the carrier plates.

13. A carrier plate according to any one of the preceding Claims, wherein the carrier plate is further formed with a utility channel configured for accommodating therein all the necessary electronic/mechanical components required for the operation of the units.

14. A carrier plate according to Claim 13, wherein the utility channel is isolated
15 from the one or more cooling channels.

15. A carrier plate according to Claim 14, wherein the material of the carrier itself forms the barrier between the one or more cooling channels and the utility channel, providing said isolation.

16. A carrier plate according to any one of the preceding Claims, wherein the modular units are made of the same material, facilitating uniform heat conduction
20 throughout the carrier plate.

17. A carrier plate according to any one of Claims 1 to 15, wherein each of the modular units is made of a different material, depending on the communication unit
25 adapted to be received in the socket thereof.

18. A method for configuring a cooling arrangement of a phased array antenna comprising two or more carrier plates of the previous aspect of the present application, each carrier plate having a first cooling channel and a second cooling channel, the carrier plates being arranged so that the cooling channels thereof are no co-linear, the
30 method includes the steps of:

- a) providing a fluid inlet associated with a first end of the first channel of the first carrier plate;

- 12 -

- b) consecutively attaching a second end of the first channel of each carrier plate but last to the first end of the first channel of a successive carrier plate;
 - c) attaching the second end of the first channel of the last carrier plate with a first end of the second channel of the last carrier plate;
 - 5 d) consecutively attaching a second end of the second channel of each carrier plate but first to the first end of the first channel of a successive carrier plate; and
 - e) providing a fluid outlet associated with a second end of the second cooling channel of the first carrier plate.
- 10 **19.** A method according to Claim 18, wherein the cooling fluid enters the first channel of the first carrier plate at the lowest temperature t and reaches the outlet end of the first channel of the last carrier plate at a higher temperature $t' > t$, and thereafter returned first through the second channel of the last carrier plate and reaches the outlet end of the second channel of the first carrier plate at a temperature $T > t' > t$.
- 15 **20.** A method according to Claim 19, wherein the average temperature of the cooling fluid in each carrier plate is approximately t' .
- 21.** A phased array antenna comprising two or more communication units mounted on a carrier plate according to any one of Claims 1 to 17.