



- (51) International Patent Classification:
F16L 37/00 (2006.01) *E21B 43/013* (2006.01)
- (21) International Application Number:
PCT/EP2012/071651
- (22) International Filing Date:
1 November 2012 (01.11.2012)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:
20111776 27 December 2011 (27.12.2011) NO
- (71) Applicant: FMC KONGSBERG SUBSEA AS [NO/NO];
P.O. Box 1012, N-3601 Kongsberg (NO).
- (72) Inventor: BEKKEVOLD, Knut; Hulbakkroken 11, N-3090 Hof (NO).
- (74) Agent: SIMONSEN, Kari; c/o ONSAGERS AS,
P.O.BOX 1813 Vika, N-0123 Oslo (NO).
- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT,


HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PA, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

- (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

- with international search report (Art. 21(3))
- before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments (Rule 48.2(h))

- (88) Date of publication of the international search report:
12 December 2013

(54) Title: A SUBSEA CONNECTOR**FIG. 1**

(57) **Abstract:** A connector (1) comprises a plurality of latching fingers (5) arranged around a cylindrical body (9) having a central axis (X_c). Each finger has a first end region (5a) extending beyond an end of the body (9) and comprising a first latching structure (4). Each finger is pivotally supported at an intermediate region (5b) by a portion of the body and being movable between a non-latching position and a latching position in which the first end region (5a) is closer to the central axis (X_c) than in the non-latching position. The connector comprises a first actuating member (14) arranged in contact with the plurality of fingers (5) and operable to move the fingers between the non-latching position and the latching position. An actuating means (17) is operable to force a second end region (5c) of each finger towards the body (9). The connector (1) may be connected to a hub (2) by bringing a connector face (27) into contact with a hub face (28); moving the latching fingers towards the connector until the first latching structures (4) engage in corresponding second latching structures (3) on the hub, and then holding the latching structures (3, 4) together in a latching engagement; and effecting a pressure in the aft region (5c) of each finger, towards the body, following the completion of step b).