

PCTWORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ :

E04F 19/06

A1

(11) International Publication Number:

WO 96/41927

(43) International Publication Date: 27 December 1996 (27.12.96)

(21) International Application Number: PCT/US95/07387

(22) International Filing Date: 9 June 1995 (09.06.95)

(71)(72) Applicants and Inventors: STIBOLT, Paul, E. [US/US];
9801 E. Iliff Avenue, Denver, CO 80231 (US). JUDY,
Russell, E. [US/US]; 14290 Foothills Circle, Golden, CO
80401 (US).(74) Agents: CARSON, W., Scott et al.; Dorr, Carson, Sloan &
Birney, P.C., 3010 E. 6th Avenue, Denver, CO 80206 (US).(81) Designated States: AM, AT, AU, BB, BG, BR, BY, CA, CH,
CN, CZ, DE, DK, EE, ES, FI, GB, GE, HU, IS, JP, KE,
KG, KP, KR, KZ, LK, LR, LT, LU, LV, MD, MG, MN,
MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK,
TJ, TM, TT, UA, UG, UZ, VN, ARIPO patent (KE, MW,
SD, SZ, UG), European patent (AT, BE, CH, DE, DK, ES,
FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent
(BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD,
TG).

Published

With international search report.

(54) Title: DRYWALL CORNER FINISHING DEVICE

(57) Abstract

A finishing device used to form a corner between two panels (804) of drywall has a flexible joint (100) extending along a predetermined axis. Two wings (102, 104) are connected to and extend outwardly in a diverging relation from the flexible joint (100) to form a corner having an adjustable angle. Each wing (102, 104) has a front surface (106), a rear surface (108), and an edge (110) distal from the flexible joint (100). This edge (110) abuts one of said drywall panels (804) and has a thickness approximately equal to the thickness of the drywall panel (804). A layer of primer (300) or adhesive laminate (400) is applied to the front surface (106) of the wings (102, 104) so that paint can bond to the front surface (106). The finishing device is capable of forming both inside and outside corners. To form inside corners, the finishing device bends along the flexible joint (100). To form outside corners, strips (208, 210) parallel to the flexible joint (100) are removed from the rear surface (108) of the wings (102, 104) and the finishing device is folded along the openings thus created.

