

## **ELECTRICAL CONNECTOR**

### **TECHNICAL FIELD**

The present invention relates to an electrical connector, in particular, an electrical connector adapted for high mating cycles.

### **5 BACKGROUND**

The contacts in the connectors that are used in storage devices are generally firmly secured on the passageways configured on the mating parts. During the mating of a header connector with a complementary socket connector, the contacts at the tip of the mating part of the header connector get abraded as a  
10 result of the shear stress on the header connector's contacts by the complementary socket connector's contacts when the two connectors engage. Similar shear stress and abrasion occur when the two connectors disengage during the un-mating of the connectors. Repeated abrasion of the contacts during the mating and un-mating process wear the contacts which ultimately may result  
15 in an electrical connection failure. Conventional storage device connectors are designed to withstand an average life of 500 mating cycles.

Serial Advanced Technology Attachment (also referred to as SATA) connectors and Serial Attached SCSI (Small Computer System Interface) (SAS) connectors are examples of disk interface technologies in use.

20 U.S. Patent No. 6,743,060, U.S. Patent No. 6,331,122 and U.S. Patent No. D469,407 disclose a type of SATA header connector which is to be mounted on a printed circuit board, a type of SATA socket connector which is to be mounted on a printed circuit board and an electrical connector assembly with a SATA connector as a part, respectively. U.S. Patent No. 6,832,934 teaches a type of  
25 SAS connector.

The SAS header connector has generally the same configuration as the SATA header connector except that the SAS connector has a third tongue plate on which a third set of signal contacts are assembled on the surface opposing to the surface where the first two sets of contacts (including one set of power and one set of signal contacts) are assembled. In doing so, a SAS connector is compatible with a SATA connector and users have the ability to integrate either SAS or SATA devices and reduce the costs associated with supporting two different interfaces.

## SUMMARY

It would be desirable to provide an electrical connector which is able to withstand high mating cycles of preferably greater than 500.

In accordance with one embodiment of the present invention, there is provided an electrical connector comprising an insulative housing comprising a longitudinal base having a mating side and a mounting side; a tongue portion extending from the longitudinal base at the mating side, the tongue portion comprising a first tongue section and a second tongue section, each tongue section having a first face and a second face; a plurality of passageways defined on the first faces of the first and the second tongue sections, the passageways extending from the tongue portion to the mounting side of the insulative housing; a recess located at one end of each passageway; and a plurality of conductive contacts received in the passageways, each contact comprising a mating section located at the mating side of the insulative housing, a mounting section located at the mounting side of the insulative housing, and a retainer section bridging the mating section to the mounting section; wherein the mating section of the contact is free to flex into the recess.

In accordance with another embodiment of the present invention, there is provided an electrical connector comprising an insulative housing comprising a

longitudinal base having a first mating side and a second mating side; a tongue portion extending from the longitudinal base at the first mating side and a socket extending from the longitudinal base at the second mating side; wherein the tongue portion comprises a first tongue section and a second tongue section, each tongue section having a first face and a second face; a plurality of passageways defined on the first faces of the first and the second tongue sections, the passageways extending from the tongue portion at the first mating side to the socket at the second mating side; a recess located at one end of each passageway; and a plurality of conductive contacts received in the passageways, each contact comprising a first mating section located at the first mating side of the insulative housing, a second mating section located at the second mating side of the insulative housing, and a retainer section bridging the first mating section to the second mating section; wherein the first mating section of the contact is free to flex into the recess.

The invention further includes any alternative combination of parts or features mentioned herein or shown in the accompanying drawings. Known equivalents of these parts or features which are not expressly set out are nevertheless deemed to be included.

## **BRIEF DESCRIPTION OF THE DRAWINGS**

An exemplary form of the present invention will now be described with reference to the accompanying drawings in which:

**Figure 1A** is an exploded, perspective view of an electrical connector in accordance with the present invention;

**Figure 1B** shows a section of the electrical connector of Figure 1A with a plurality of contacts in place within the electrical connector;

**Figure 1C** shows a side view of a cross-section of the electrical connector of Figure 1B;

**Figure 2** shows a perspective view of one embodiment of a set of contacts according to the present invention;

5        **Figure 3** shows a side view of a cross-section of the electrical connector of Figure 1B engaged with a complementary electrical socket;

**Figure 4** shows a block diagram illustration of a hard disk drive testing setup;

10       **Figure 5A** shows a top perspective view of another embodiment of an exemplary electrical connector according to the present invention;

**Figure 5B** shows a bottom perspective view of the exemplary electrical connector of Figure 5A;

**Figure 6A** shows a front perspective view of another embodiment of an exemplary electrical connector according to the present invention;

15       **Figure 6B** shows a rear perspective view of the exemplary electrical connector of Figure 6A; and

**Figure 7** shows a block diagram illustration of a hard disk drive testing setup with a sacrificial electrical connector.

20       While the above-identified drawing figures set forth several embodiments of the invention, other embodiments are also contemplated, as noted in the discussion. In all cases, this disclosure presents the invention by way of representation and not limitation. It should be understood that numerous other modifications and embodiments can be devised by those skilled in the art, which fall within the scope and spirit of the principles of the invention. The figures may not be drawn

to scale. Like reference numbers have been used throughout the figures to denote like parts.

## DETAILED DESCRIPTION

Figure 1A shows an exploded, perspective view of an exemplary electrical connector in accordance with the present invention. Figures 1B and 1C show views of the electrical connector of Figure 1A with a plurality of contacts in place within the electrical connector.

Referring to Figures 1A, 1B and 1C, the electrical connector **10** comprises an insulative housing **1000** comprising a longitudinal base **1010** having a mating side **1100** and a mounting side **1200**. At the mating side **1100**, there is a tongue portion **1110** extending from the longitudinal base **1010**, the tongue portion **1110** comprising a first tongue section **1111** and a second tongue section **1112**, each tongue section having a first face **1121** and a second face **1122**.

Defined on the first face **1121** of the first tongue section **1111** and of the second tongue section **1112** are a plurality of passageways **1130** extending from the tongue sections **1111**, **1112** to the mounting side **1200**. At one end of each passageway **1130** is a recess **1140** preferably configured near the edge of the tongue sections **1111**, **1112**.

Received in the plurality of passageways **1130** is a set of conductive contacts **1300**, each contact **1300** comprising a mating section **1310** located at the mating side **1100**, a mounting section **1330** located at the mounting side **1200** and a retainer section **1320** bridging the mating section **1310** to the mounting section **1330**. Figure 2 shows another embodiment of the contacts in accordance with this invention.

Preferably, the mating section **1310** of the contact **1300** is configured with a bend **1315** at one end. As shown in Figure 1C, the bend **1315** helps in the

proper positioning of the contact **1300** along the passageway **1130** within the insulative housing **1000** by preventing the contact **1300** from going beyond the tongue portion **1110** as the contact **1300** is inserted into the insulative housing **1000** from the mounting side **1200** during installation.

5           As shown in Figures 1A and 2, in one embodiment, the retainer section **1320** further comprises a plurality of retaining devices **1340** such as, e.g., barbs. The electrical connector **10** may be electrically connected to a printed circuit board via the mounting section **1330** of the contact **1300**. There are many ways of mounting the electrical connector **10** on the printed circuit board including but  
10   not limited to, adapting the mounting section **1330** for surface mounting, press-fitting or through-hole mounting, all of which are within the spirit of this invention.

          In one embodiment of the present invention, the electrical connector **10** further comprises a plurality of alignment guides **1400**, **1410** used for guiding a  
15   complementary electrical connector (not shown) or a printed circuit board (not shown) to engage the electrical connector **10** during mating.

          Figure 3 shows a side view of a part of a cross-section of a complementary electrical connector **15** engaged with the electrical connector **10** when the electrical connector **10** is mated with the complementary electrical connector **15**.  
20   The complementary electrical connector **15** comprises an insulative housing **1500** having a mating end **1510**; a socket **1520** extending from the insulative housing **1500** at the mating end **1510**; a plurality of slots **1530** defined in the insulative housing **1500** extending into the socket **1520**; and wherein in each slot **1530** a terminal **1540** is placed. At one end of the terminal **1540** is a bend **1550**  
25   configured to establish electrical connection with the contact **1300** in the electrical connector **10** when the electrical connector **10** is mated with the complementary electrical connector **15**.

As the socket **1520** of the complementary electrical connector **15** engages the tongue portion **1110** of the electrical connector **10** during mating, the bend **1550** abrades the surface of the contact **1300** as the terminal **1540** moves in a direction opposite to that of the contact **1300**. Similar surface abrasion also takes place during an-mating cycle whereby the socket **1520** of the complementary electrical connector **15** disengages the tongue portion **1110** of the electrical connector **10**. Such repeat abrasions will ultimately wear the contacts **1300** resulting in poor electrical connection between the two connectors when in use.

By having a recess **1140** at one end of the passageway **1130**, preferably in close proximity to the edge of the tongue portion **1110**, the contact **1300** at the mating section **1310** is able to flex towards the recess **1140** as the bend **1550** meets the contact **1300** when the socket **1520** of the complementary electrical connector **15** engages the tongue portion **1110** of the electrical connector **10**. This reduces the amount of force by the terminal **1540** on the contact **1300**, and therefore reduces the amount of abrasion on the surface of the contact **1300** caused during the mating and the un-mating process, thereby prolonging the life (in terms of number of mating cycles) of the electrical connector **10**.

Preferably, there is a slope leading from the passageway **1130** to the recess **1140**. This will further reduce the amount of abrasion on the surface of the contact **1300** especially at the location where the bend **1550** first meets the contact **1300**.

The exemplary electrical connector **10** as mentioned in this specification is useful for many applications including but not limited to, the quality testing of hard disk drives. With reference to Figure 4, in a hard disk drive testing environment, one may find the exemplary connector **10** mounted on a printed circuit board **1610** of a hard disk drive testing equipment **1600** and the complementary electrical connector **15** coupled to a hard disk drive **1620** that is to be tested. The electrical connector **10** is often securely bonded (for example by

means of soldering) to the printed circuit board **1610** so as to prevent the accidental disengagement of the electrical connector **10** from the printed circuit board **1610** caused by the force due to the repeated exchange of the hard disk drives **1620** undergoing testing. Any failure of the electrical connector **10** due to the abrasion of the contacts **1300** will require the electrical connector **10** to be replaced. This may result in a loss of productivity since there is effort required to de-solder the faulty electrical connector and solder a new electrical connector on the printed circuit board before the hard disk drive testing equipment can be used. Therefore, by increasing the life (number of mating cycles) of the electrical connector **10**, the period between the electrical connector replacement will be lengthen and the productivity will be increased since there is less machine downtime.

Figures 5A and 5B show a top perspective view and a bottom perspective view of another embodiment of an exemplary electrical connector **20** in accordance to the present invention. In addition to the elements present in the electrical connector **10** that are mentioned in the earlier sections of this specification, the electrical connector **20** further comprises a third tongue section **1113** connecting with the first and the second tongue sections **1111**, **1112**, the third tongue section **1113** having a first face **1121** and a second face **1122** and with a plurality of passageways **1130** defined on the second face **1122**, and each passageway **1130** having a recess **1140** located at one end. A plurality of conductive contacts **1300** are received in the passageways **1130**, each contact **1300** comprising a mating section **1310**, a mounting section **1330** and a retainer section **1320** bridging the mating section **1310** to the mounting section **1330** wherein the mating section **1310** is free to flex into the recess **1140**.

Figures 6A and 6B show a top perspective view and a bottom perspective view of another embodiment of an exemplary electrical connector **30** in accordance to the present invention. The electrical connector **30** comprises an insulative housing comprising a longitudinal base **3010** having a first mating side

**3100** and a second mating side **3200**. At the first mating side **3100**, there is a tongue portion **3110** extending from the longitudinal base **3010**, the tongue portion **3110** comprising a first tongue section **3111** and a second tongue section **3112**. In another embodiment of the present invention, the tongue portion **3110**  
5 further comprises a third tongue section **3113** connecting with the first and the second tongue sections **3111**, **3112**. Each tongue section in the tongue portion **3110** comprises a first face **1121** and a second face **1122**.

At the second mating side **3200**, there is a socket **1520** extending from the longitudinal base **3010**, the socket **1520** further comprising a mating slot **3210** (as  
10 shown in Figure 6B) which is configured to accept the tongue portion of a complementary connector (not shown).

Defined on the first face **1121** of the first tongue section **3111** and the second tongue section **3112** as well as on the second face **1122** of the third tongue section **3113** are a plurality of passageways **1130** extending from the  
15 tongue portion **3100** to the socket **1520**. At one end of each passageway **1130** is a recess **1140** (as shown in Figure 1C) preferably configured near the edge of the tongue sections **3111**, **3112** and **3113**.

Received in the plurality of passageways **1130** is a set of conductive contacts, each contact comprising a first mating section **3310** located at the first  
20 mating side **3100**, a second mating section **3320** located at the second mating side **3200** and a retainer section (not shown) bridging the first mating section **3310** to the second mating section **3320**.

In one embodiment of the present invention, the electrical connector **30** further comprises a plurality of alignment posts **1420** used for aligning a  
25 complementary electrical connector (not shown) with the electrical connector **30** during mating.

In another embodiment of the present invention, the electrical connector 30 further comprises a plurality of securing devices 1450 used for securing another complementary electrical connector (not shown) to the electrical connector 30 to prevent accidental disengagement of the two connectors when in  
5 use.

To further reduce the loss of productivity arising from machine downtime due to the need to replace the worn out electrical connector (as a result of severely abraded conductive contacts) coupled to the printed circuit board of a hard disk drive testing equipment, the electrical connector 30 may be used as  
10 illustrated in Figure 7. By using the electrical connector 30 as a sacrificial connector, the occurrence of mating and un-mating at the electrical connector coupled to the printed circuit board of the hard disk drive testing equipment, reduces. As a result, the conductive contacts in the electrical connector coupled to the printed circuit board of the hard disk drive testing equipment do not get  
15 abraded easily. Of course, it will be appreciated that the various embodiments of electrical connectors described and shown herein are suitable for this purpose.

The foregoing description of the preferred embodiment of the invention has been presented for purposes of illustration and description. It is not intended to be exhaustive or to limit the invention to the precise forms disclosed, since  
20 many modifications or variations thereof are possible in light of the above teaching. All such modifications and variations are within the scope of the invention. The embodiments described herein were chosen and described in order to best explain the principles of the invention and its practical application, thereby to enable others skilled in the art to use the invention in various  
25 embodiments and with various modifications as are suited to the particular use contemplated thereof. It is intended that the scope of the invention be defined by the claims appended hereto, when interpreted in accordance with the full breadth to which they are legally and equitably entitled.

## CLAIMS

1. An electrical connector comprising:

an insulative housing comprising a longitudinal base having a mating side and a mounting side;

5 a tongue portion extending from the longitudinal base at the mating side, the tongue portion comprising a first tongue section and a second tongue section, each tongue section having a first face and a second face;

a plurality of passageways defined on the first faces of the first and the second tongue sections, the passageways extending from the tongue portion to the  
10 mounting side of the insulative housing;

a recess located at one end of each passageway; and

a plurality of conductive contacts received in the passageways, each contact comprising a mating section located at the mating side of the insulative housing, a mounting section located at the mounting side of the insulative housing, and a  
15 retainer section bridging the mating section to the mounting section; wherein the mating section of the contact is free to flex into the recess.

2. The electrical connector as claimed in claim 1 further comprising a third tongue section connecting with the first and the second tongue sections, the third tongue section having a first face and a second face and with a plurality of  
20 passageways defined on the second face, each passageway having a recess located at one end; a conductive contact received in the passageway comprising a mating section, a mounting section, and a retainer section bridging the mating section to the mounting section; wherein the mating section of the contact is free to flex into the recess.

25 3. An electrical connector comprising:

an insulative housing comprising a longitudinal base having a first mating side and a second mating side;

a tongue portion extending from the longitudinal base at the first mating side and a socket extending from the longitudinal base at the second mating side;  
5 wherein the tongue portion comprises a first tongue section and a second tongue section, each tongue section having a first face and a second face;

a plurality of passageways defined on the first faces of the first and the second tongue sections, the passageways extending from the tongue portion at the first mating side to the socket at the second mating side;

10 a recess located at one end of each passageway; and

a plurality of conductive contacts received in the passageways, each contact comprising a first mating section located at the first mating side of the insulative housing, a second mating section located at the second mating side of the insulative housing, and a retainer section bridging the first mating section to the  
15 second mating section; wherein the first mating section of the contact is free to flex into the recess.

4. The electrical connector as claimed in claim 3 further comprising a third tongue section connecting with the first and the second tongue sections, the third tongue section having a first face and a second face and with a plurality of  
20 passageways defined on the second face, each passageway having a recess located at one end; a conductive contact received in the passageway comprising a mating section, a mounting section, and a retainer section bridging the mating section to the mounting section; wherein the mating section of the contact is free to flex into the recess.

25 5. An interconnect system comprising the electrical connector as claimed in claim 1 and further comprising a first electronic device having a complementary

electrical socket coupled to the electrical connector at the mating side; the electrical connector optionally mounted to a printed circuit board of a second electronic device at the mounting side.

6. An interconnect system comprising the electronic connector as claimed in claim 3 and further comprising a complementary electrical socket coupled to the electrical connector at the first mating side and a complementary electrical header coupled to the electrical connector at the second mating side.