

CLAIMS:

1. A computer-implemented system for propagating timer management and event triggering, the system comprising:
 - a memory storing instructions; and
 - at least one processor configured to execute the instructions to:
 - receive, from a first system via a network, a request to instantiate a timer, the request comprising:
 - an end time for the timer, and
 - an event for triggering at the end time;
 - save the received request to a data store comprising a plurality of requests;
 - trigger the event upon reaching the end time for the timer associated with the request; and
 - responsive to triggering the event, sending, via a network, the event associated with the request.
2. The system of claim 1, wherein the data store comprising the plurality of requests comprises a key-value data structure.
3. The system of claim 2, wherein the received request is stored in the data store by storing the end time for the respective timer as a key and the event as an associated value.
4. The system of claim 3, wherein the instructions further cause the processor to:

maintain a repeating master timer with a pre-defined interval;
determining that the repeating master timer interval has expired; and
based on determining that the repeating master time interval has expired:
 locating one or more keys in the data store;
 comparing the time stored in the located keys to the current time;
 triggering the associated event for at least one located key with an associated time in the past.

5. The system of claim 2, wherein the instructions further cause the processor to:
 periodically store snapshots of the key-value data store on a computer-readable medium;
 determine that data loss has occurred in the key-value data store due to power outage, program error, or other incident;
 reading the stored snapshots; and
 restoring data to the key-value data store using the stored snapshots.
6. The system of claim 1, wherein the instructions further cause the processor to:
 maintain a repeating master timer with a pre-defined interval;
 determining that the repeating master timer interval has expired; and
 based on determining that the repeating master time interval has expired:
 consulting the data store to determine one or more requests whose respective end times have been reached;
 triggering the associated event for the one or more determined requests.

7. The system of claim 1, wherein the event for triggering at the end time comprises
sending a notification to a destination system indicating that the timer
has elapsed, the notification including instructions for
performance by the destination system.
8. The system of claim 1, wherein the instructions further cause the processor to:
receive, from the first system, a request to cancel the timer; and
clear the received request from the data store.
9. The system of claim 1, wherein sending the event comprises sending the event
to the first system.
10. A computer implemented method for propagating timer management and event
triggering, the method comprising:
receiving, from a first system via a network, a request to
instantiate a timer, the request comprising:
an end time for the timer, and
an event for triggering at the end time;
saving the received request to a data store comprising a plurality
of requests;
triggering the event upon reaching the end time for the timer
associated with the request; and
responsive to triggering the event, sending, via a network, the
event associated with the request.

11. The method of claim 10, wherein the data store comprising the plurality of requests comprises a key-value data structure.
12. The method of claim 11, wherein the received request is stored in the data store by storing the end time for the respective timer as a key and the event as an associated value.
13. The method of claim 12, further comprising:
- maintaining a repeating master timer with a pre-defined interval;
 - determining that the repeating master timer interval has expired; and
 - based on determining that the repeating master time interval has expired:
 - locating one or more keys in the data store;
 - comparing the time stored in the located keys to the current time;
 - triggering the associated event for at least one located key with an associated time in the past.
14. The method of claim 11, further comprising:
- periodically store snapshots of the key-value data store on a computer-readable medium;
 - determining that data loss has occurred in the key-value data store due to power outage, program error, or other incident;
 - reading the stored snapshots; and
 - restoring data to the key-value data store using the stored snapshots.

15. The method of claim 10, further comprising:

maintain a repeating master timer with a pre-defined interval;
determining that the repeating master timer interval has expired; and
based on determining that the repeating master time interval has expired:
consulting the data store to determine one or more requests
whose respective end times have been reached;
triggering the associated event for the one or more determined requests.

16. The method of claim 10, further comprising:

sending a notification to a destination system indicating that the timer has elapsed, the notification including instructions for performance by the destination system.

17. The method of claim 10, further comprising:

receive, from the first system, a request to cancel the timer; and
clear the received request from the data store.

18. The method of claim 10, wherein sending the event comprises sending the event to the first system.

19. A computer-implemented system for propagating timer management and event triggering, the system comprising:

a memory storing instructions; and
at least one processor configured to execute the instructions to:

receiving, from a first system via a network, a request to
 instantiate a timer, the request comprising:
 an end time for the timer, and
 an event for triggering at the end time;
saving the received request to a data store comprising a plurality
 of requests;
triggering the event upon reaching the end time for the timer
 associated with the request;
responsive to triggering the event, sending, via a network, the
 event associated with the request;
maintain a repeating master timer with a pre-defined interval;
determining that the repeating master timer interval has expired;
 and
based on determining that the repeating master time interval has
expired:
 locating one or more keys in the data store;
 comparing the time stored in the located keys to the
 current time;
 triggering the associated event for at least one located
 key with an associated time in the past.