

SYSTEM FOR LOADING AND UNLOADING DURING PORT OPERATIONS,
COMPRISING A CRANE, AND A BASE LOCATED IN THE BODY OF THE CRANE
THAT SUPPORTS AND STACKS HATCHWAY COVERS

DESCRIPTION

5 **Field of the Invention**

The invention is related with the tasks of loading and unloading of ships or boats, and is specifically related with the procedure for removal of the hatch covers to allow access or exit of the cargo to the holds of the maritime vessels.

10 The invention consists of a system of loading, unloading and supporting the hatch covers, which comprises a crane and a base for stacking the hatch covers of the ship, so that these covers are not stockpiled somewhere else that it can be used for other operation.

Background of the Invention

15 The holds of ships or boats are the space inside the hull which is used to hold the cargos that are transported. The opening that allows access to the hold for introducing or removing the cargos is the hatch, which in most cases is on the deck of the ship which is the upper outer surface of the hull. When the ship sails these hatches must be closed, both to protect the cargo, and to maintain the water-tightness of the ship and so to not allow water to enter the holds filled with water. The element that closes the hatch
20 is called the hatch cover and should be tight enough so as not to allow water to enter which eventually passes on the deck of the ship during navigation.

During the tasks of loading and unloading of the ships the hatch covers have to be removed from the hatches to allow access or egress of the cargo to the holds. Some ships are equipped with devices for opening and closing the hatch and have sufficient
25 space to retain the hatch cover on the ship once it is removed from the hatch; while other ships neither have the space nor have the devices that will allow them to retain the covers on them, so they must be removed and placed elsewhere, which in most cases is the surface of the docks, breakwaters or rafts used for loading or unloading of the goods.

When hatch covers have to be removed from the boats and arranged on the surface of the docks, breakwaters or rafts or any other surface which is used for this purpose and which is not the ship, the area used may have alternative uses such as gathering the cargos or the transit of the equipment transfer or transportation of goods.

5 In some cases these areas may be critical for efficient operation of transfer and portage (transport of cargo within the port or maritime terminal) of the cargos.

In view of the above, it is necessary to have a place to put the hatch cover, which is other than the surface of the docks, breakwaters or rafts, and which has easy accessibility and adequate capacity. In this way, the hatch covers of the ship would not
10 occupy the area of operation where the cargo or other items can be gathered, used for the transit of the portage equipment or to locate the transfer equipments.

The applicant has developed a system to store or stack the hatch covers, within the same crane that performs the loading and unloading of the goods contained in the holds of ships

15 The document US5538382 describes a system consisting of a crane that has a variable level suspended platform lift type having a mechanism for lifting, wherein said platform is for the transport of the cargo.

The document US4858775 describes a platform lift for the load of a container, which includes its own circulation engines motion to have autonomy of movement along
20 the crane boom.

From the state of the art it can be seen that although there exist platforms associated with loading cranes, these platforms are with elevator movement and are installed on the cranes to assist with the loading and unloading processes in the maritime operations.

25 The objective of the present invention is to provide a means for gathering the hatch covers, so that the hatch covers are not stacked or stored on the surface of the docks, breakwaters or rafts used for loading or unloading of the goods.

Summary of the Invention

The present invention corresponds to a system for loading, unloading in port
30 operations and for supporting hatch covers comprising a crane for loading and

unloading of maritime operations and a base located in the body of the crane to hold and stack the hatch covers.

5 **Brief Description of the Drawings**

The invention will be described below with reference to the accompanying drawings, in which:

Figure 1 shows a side-rear view of the system of the present invention.

Figure 2 shows a side-front view of the system of the present invention.

10 Figure 3 shows a side-rear view for the other side of the system of the present invention.

Figure 4 shows a side view of the outer platform option of the system of the present invention.

Figure 5 shows a side view of figure 1.

15 Figure 6 shows a front view of the system with platform or with one support.

Figure 7 shows a top view of the system of the present invention with stacked covers.

Figure 8 shows another side view of the system of the present invention.

Detailed Description of the Invention

20 The present invention corresponds to a system (1) for loading, unloading in port operations and for supporting hatch covers (11) comprising a crane (2) for loading and unloading of maritime operations and a base to be located in the body of the crane for holding and stacking the hatch covers.

25 The crane (2) for loading and unloading in port operations corresponds to a gantry crane that has an elevated bridge (4) or a gantry supported by two legs (5) by way of an angled arch (15) formed by two verticals profiles, wherein each leg terminates in a horizontal profile base (6); in the bottom half of the legs two lateral horizontal beams are located (7), one on each side of the body of the crane, which links both legs of the crane on their lateral sides, allowing the crane to have free movement of jib
30 trolley (8) in the front and back direction of the crane.

The base to be placed in the body of the crane can be an inner platform (3) or outer platform (12) or only inner cover support (16) or outer cover support (13), said base is of a resistant material, preferably metal and is strongly adhered to the lateral horizontal beams (7) and / or to the verticals profiles of the legs of the crane, either
 5 joined by welding and / or bolted. The installation of the base in the crane (2) may be made on the inside of the body of the crane between its legs or on the outside of the body of the crane as a horizontal extension.

The installation of the platform (3) on the inside of the body of the crane comprises installing small supports attached strongly to the lateral horizontal beams (7)
 10 of the crane; a rear horizontal beam (9) attached to the vertical profiles of the rear leg; a front horizontal beam (10) attached to the lateral horizontal beams; and a platform (3) placed on the supports and the front and rear horizontal beams (10.9), tightly bound. The installation of the outer platform (12) on the outside of the body of the crane comprises installing supports attached to the vertical profiles of the legs of the crane
 15 and a platform on said supports, also includes some higher tensors (14) attached to the top of the crane. The installation of the supports (16) on the inside of the body of the crane comprises placing supports attached to the lateral horizontal profiles where such supports are of an adequate size and sufficient to support the weight of the hatch covers (11). The installation of the outer cover support (13) on the outside of the body of
 20 the crane comprises only installing supports attached to the vertical profiles of the legs of the crane, also including some higher tensors (14) attached to the top of the crane.

The distance between the legs of the crane is about 17 meters and the size of the hatch covers is about 12 to 13 meters, so the size of the platform (3) or the outer platform (12) or the support (16) or the outer cover support (13) has a length of about 14
 25 to less than 17 meters and a width of approximately 10 to 14 meters. The thickness of the inner or outer platform is in the range of 1.20 meters to less than 30 cm.

Optionally the platform (3) or support (16) contains flanges or wedges to make the operation safer.

The procedure of removing, stacking and returning of the hatch covers to the ship
 30 comprises:

1. having a system (1) of loading, unloading and supporting hatch covers (11);
2. removing the hatch cover from the hold of the maritime vessel and moving it with the trolley (8) of the crane (2);
- 5 3. moving the cover and placing it on the installed base in the body of the crane;
4. once the operation of loading and / or unloading of the crane is over returning the cover to the ship moving it from the said base to the ship.

CLAIMS

1. System (1) for loading and unloading in port operations and supporting hatch covers (11) of holds of maritime vessels, wherein it comprises:

a) a crane (2) for loading and unloading of maritime operations; wherein the crane has horizontal lateral beams (7), one on each side of the body of the crane, and two legs (5) with angled shaped arch, each formed by two verticals profiles and a horizontal profile base (6), wherein in the main body of the crane is installed a rear horizontal beam (9) attached to the vertical profiles of the rear leg; a front horizontal beam (10) attached to the lateral horizontal beams (7); and

b) a base located on the body of the crane to hold and stack hatch covers (11), wherein said base comprises:

an inner cover support (16) that is installed on the inside of the body of the crane, wherein the inner cover support (16) is formed by supports which are attached to the lateral horizontal beams, wherein said supports are of a sufficient size and suitably spaced to support the hatch covers (11) and also separated by less than width of the hatch covers (11); or

an outer cover support (13) that is installed on the outside of the body of the crane (2) is formed by supports attached to the vertical profiles of the legs of the crane; and that it further comprises of some higher tensors (14) attached to the top of the crane.

2. Procedure for removing, stacking and returning hatch covers in a system (1) for loading and unloading in port operations and supporting hatch covers of holds of maritime vessels according to claim 1, characterized in that comprises of:

a) having a system (1) for loading and unloading and supporting hatch covers (11) which comprises:

a crane (2) for loading and unloading in port operations; and

a base located in the body of the crane to hold and stack the hatch covers (11);

b) removing the hatch cover (11) from the hold of the maritime vessel and moving it with the trolley (8) of the crane;

c) moving the cover and placing it on the installed base in the body of the crane; and

d) returning the cover to the ship moving it from the said base to the ship, once the operation of loading and/or unloading is over.