CLAIMS

[Claim 1]

A split type air-conditioning apparatus comprising an indoor unit and an outdoor unit, the indoor unit including a housing, an indoor heat exchanger being disposed in the housing and to which flammable refrigerant is supplied, and an indication section being provided on the housing and indicating one or both of an installation height for installation of the indoor unit in a room and an available floor area in the room for the air-conditioning apparatus as stipulated in an international standard.

[Claim 2]

The air-conditioning apparatus of claim 1, wherein the indication section has embossing or debossing indication or printing indication.

[Claim 3]

The air-conditioning apparatus of claim 1 or 2, wherein the indication section is a member having embossing or debossing indication or printing indication that is permanently or removably attached.

[Claim 4]

The air-conditioning apparatus of any one of claims 1 to 3, wherein the housing is configured to be installed on a wall, and the indication section is provided on a lower surface of the housing.

[Claim 5]

The air-conditioning apparatus of any one of claims 1 to 3, wherein the housing is configured to be hung from a ceiling, and the indication section is provided in the housing at a position that faces an air inlet that is open to a lower surface of the housing.

[Claim 6]

The air-conditioning apparatus of any one of claims 1 to 3, wherein the housing is configured to be embedded in a ceiling, and the indication section is provided on a lower surface of an electronics box.

[Claim 7]

The air-conditioning apparatus of any one of claims 1 to 4, wherein the housing is configured to be installed on a wall via an installation board, and the indication section is provided on the installation board.

[Claim 8]

The air-conditioning apparatus of any one of claims 1 to 7, wherein the refrigerant is R32 (CH_2F_2, difluoromethane), which is HFC refrigerant, HFO-1234yf ($CF_3CF = CH_2$, tetrafluoropropene), or HFO-1234ze ($CF_3 - CH = CHF$).

CLAIMS

[Claim 1]

A split type air-conditioning apparatus comprising an indoor unit and an outdoor unit, the indoor unit including a housing, an indoor heat exchanger being disposed in the housing and to which flammable refrigerant is supplied, and an indication section being provided on the housing and indicating an installation height which is set for each type of air conditioning apparatuses and which is for installation in a room as stipulated in an international standard,

wherein the indication section is provided to an electronics box at a position that is capable of being visually observed from an outside when the indoor unit is installed.

[Claim 2]

A split type air-conditioning apparatus comprising an indoor unit and an outdoor unit, the indoor unit including a housing, an indoor heat exchanger being disposed in the housing and to which flammable refrigerant is supplied, and an indication section being provided on the housing and indicating a floor area corresponding to a refrigerant filling level which is set for each type of air conditioning apparatuses and which is for installation in a room as stipulated in an international standard,

wherein the indication section is provided to an electronics box at a position that is capable of being visually observed from an outside when the indoor unit is installed.

[Claim 3]

A split type air-conditioning apparatus comprising an indoor unit and an outdoor unit, the indoor unit including a housing, an indoor heat exchanger being disposed in the housing and to which flammable refrigerant is supplied, and an indication section being provided on the housing and indicating an installation height which is set for each type of air conditioning apparatuses and which is for installation in a room as stipulated in an international standard, and a floor area corresponding to a refrigerant filling level which is set for each type of air conditioning apparatuses and which is for installation in a room as stipulated in an international standard,

wherein the indication section is provided to an electronics box at a position that is capable of being visually observed from an outside when the indoor unit is installed.

[Claim 4]

The air-conditioning apparatus of any one of claims 1 to 3, wherein the housing is configured to be embedded in a ceiling, and the indication section is provided on a lower surface of the electronics box.

[Claim 5]

A split type air-conditioning apparatus comprising an indoor unit and an outdoor unit, the indoor unit including a housing, an indoor heat exchanger being disposed in the housing and to which flammable refrigerant is supplied, and an indication section being provided on the housing and indicating an installation height which is set for each type of air conditioning apparatuses and which is for installation in a room as stipulated in an international standard,

wherein the housing is configured to be installed on a wall via an installation board, and

wherein the indication section is provided to the installation board at a position that is capable of being visually observed from an outside when the indoor unit is installed.

[Claim 6]

A split type air-conditioning apparatus comprising an indoor unit and an outdoor unit, the indoor unit including a housing, an indoor heat exchanger being disposed in the housing and to which flammable refrigerant is supplied, and an indication section being provided on the housing and indicating a floor area corresponding to a refrigerant filling level which is set for each type of air conditioning apparatuses and which is for installation in a room as stipulated in an international standard,

wherein the housing is configured to be installed on a wall via an installation board, and

wherein the indication section is provided to the installation board at a position that is capable of being visually observed from an outside when the indoor unit is installed.

[Claim 7]

A split type air-conditioning apparatus comprising an indoor unit and an outdoor unit, the indoor unit including a housing, an indoor heat exchanger being disposed in the housing and to which flammable refrigerant is supplied, and an indication section being provided on the housing and indicating an installation height which is set for each type of air conditioning apparatuses and which is for installation in a room as stipulated in an international standard, and a floor area

corresponding to a refrigerant filling level which is set for each type of air conditioning apparatuses and which is for installation in a room as stipulated in an international standard,

wherein the housing is configured to be installed on a wall via an installation board, and

wherein the indication section is provided to the installation board at a position that is capable of being visually observed from an outside when the indoor unit is installed.

[Claim 8]

The air-conditioning apparatus of any one of claims 1 to 7, wherein the indication section has embossing or debossing indication or printing indication.

[Claim 9]

The air-conditioning apparatus of any one of claims 1 to 8, wherein the indication section is a member having embossing or debossing indication or printing indication that is permanently or removably attached.

[Claim 10]

The air-conditioning apparatus of any one of claims 1 to 9, wherein the housing is configured to be installed on a wall, and the indication section is provided on a lower surface of the housing.

[Claim 11]

The air-conditioning apparatus of any one of claims 1 to10, wherein the housing is configured to be hung from a ceiling, and the indication section is provided in the housing at a position that faces an air inlet that is open to a lower surface of the housing and that is capable of being visually observed from the outside when the indoor unit is installed.

[Claim 12]

The air-conditioning apparatus of any one of claims 1 to 11, wherein the refrigerant is R32 (CH_2F_2, difluoromethane), which is HFC refrigerant, HFO-1234yf ($CF_3CF = CH_2$, tetrafluoropropene), or HFO-1234ze ($CF_3 - CH = CHF$).