

PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : H02G 5/08	A1	(11) International Publication Number: WO 97/12434
		(43) International Publication Date: 3 April 1997 (03.04.97)

(21) International Application Number: PCT/GB96/02345

(22) International Filing Date: 24 September 1996 (24.09.96)

(30) Priority Data:
9519679.6 27 September 1995 (27.09.95) GB

(71) Applicant (for all designated States except US): KLOCKNER-MOELLER GMBH [DE/DE]; Heine-Moeller-Strasse 7-11, D-53115 Bonn (DE).

(72) Inventors; and

(75) Inventors/Applicants (for US only): BROOKS, Kevin [GB/GB]; 37 Kellynch Close, Alton, Hampshire GU34 2EG (GB). BUTCHER, Robert [GB/GB]; 35 Foxdown, Overton, Hampshire RG25 3JG (GB). REYNOLDS, Andrew [GB/GB]; 9 Stour Walk, Greenmeadow, Swindon, Wiltshire SN2 3LN (GB).

(74) Agent: SKERRETT H.N. & W.S.; Charles House, 148/9 Great Charles Street, Birmingham B3 3HT (GB).

(81) Designated States: AL, AM, AT, AU, AZ, BB, BG, BR, BY, CA, CH, CN, CZ, DE, DK, EE, ES, FI, GB, GE, HU, IL, IS, JP, KE, KG, KP, KR, KZ, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, TJ, TM, TR, TT, UA, UG, US, UZ, VN, ARIPO patent (KE, LS, MW, SD, SZ, UG), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG).

Published

With international search report.

Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.

(54) Title: IMPROVEMENTS IN OR RELATING TO BUSBARS

(57) Abstract

A tapping box (1) has locking legs (4 and 5) provided with hook portions (4a, 5a) which engage over associated busbar flanges (3a, 3b) on rotation of cam member (9) in the direction of arrow A. Rotation of cam member (9) actuates a lid interlock device (10) which prevents or allows the lid to be closed.

