

Device of Automatic Mechanical Wound Opener for Head and Neck Surgery

Technical Field of the Invention

5 The present invention relates to creating a wound opener for head and neck surgery; more particularly, relates to using an automatic mechanic wound opener to control the position and size of a wound for head and neck surgery and to introduce endoscopes or robotic arms through the wound to evaluate and
10 further treat lesions of head and neck, where the surgery can be performed smoothly, the wound size can be reduced, and the wound can be effectively concealed and become invisible.

Description of the Related Art

15 Head/neck surgery is usually performed by an open operation. An incision made at head/neck and soft tissues are pulled outwardly for treating lesions. Hence, the traditional head/neck surgery may result in an obvious visible wound. Furthermore, the issues pertinent to postoperative care and
20 cosmetic results of the wound are also encountered.

 Endoscopes or robotic arms can be used for solving these problems. During the surgery, an operative space is required to be created at first for smoothly introducing the endoscopes or robotic arms to evaluate and further treat lesions. The head
25 and neck of a human body has many different perplexing soft tissues, like muscles, nerves, glands and vessels. In addition,

head and neck have smaller spaces than the other parts of the body for dissection. Until now, no proper wound opener is available for head and neck surgery when the endoscopes or robotic arms are used. As a result, the endoscopes or robotic
5 arms cannot be operated easily, which makes surgical procedures difficult.

Hence, the prior art does not fulfill all users' requests on actual use.

10 **Summary of the Invention**

The main purpose of the present invention is to use a mechanic wound opener to adjust the position and size of a wound for introducing endoscopes or robotic arms to evaluate and further treat lesions of head and neck, where surgery can
15 be performed smoothly, the wound size can be reduced and the wound can be effectively concealed and become invisible.

To achieve the above purpose, the present invention is a device of automatic mechanical wound opener for head and neck surgery, comprising an operating frame and a wound
20 opener, where the wound opener is set at an end of the operating frame; the wound opener comprises a fixed unit and a drawing unit; the drawing unit is movably located on the fixed unit; the supporting unit comprises an adjusting base and a vertical rod set on the adjusting base; the connecting unit
25 comprises a second adjusting base movably set on the vertical rod and a horizontal rod set on the second adjusting base; the

fixed unit comprises an adjusting unit set at an end of the horizontal rod and a plurality of moving track rods movably set in the adjusting unit; the drawing unit includes a blade separately located at an end of each moving track rod; the
5 vertical adjusting plate is set on at least one of the moving track rods; one of the blades is connected to the vertical adjusting plate; the adjusting unit has a chute to be movably combined with the moving track rods; and each moving track rod has a locking unit to be movably combined with one of the
10 blades. Accordingly, a novel device of automatic mechanical wound opener for head and neck surgery is obtained.

Brief Descriptions of the Drawings

The present invention will be better understood from the
15 following detailed description of the preferred embodiment according to the present invention, taken in conjunction with the accompanying drawings, in which

FIG.1 is the perspective view showing the preferred embodiment according to the present invention;
20 FIG.2 is the side view showing the preferred embodiment;
FIG.3 is the top-down view showing the preferred embodiment;
FIG.4 is the perspective view showing the wound opener; and
FIG.5 is the view showing the state of use of the preferred
25 embodiment.

Description of the Preferred Embodiment

The following description of the preferred embodiment is provided to understand the features and the structures of the present invention.

5 Please refer to FIG.1 to FIG.5, which are a perspective view, a side view and a top-down view showing a preferred embodiment according to the present invention; a perspective view showing the wound opener; and a view showing a state of use of the preferred embodiment. As shown in the figures, the
10 present invention is a device of automatic mechanical wound opener for head and neck surgery, comprising an operating frame 1 and a wound opener 2.

 The operating frame 1 comprises a supporting unit 11; and a connecting unit 12 movably connected with the supporting
15 unit 11, where the supporting unit 11 comprises a first adjusting base 111 and a vertical rod 112 set on the first adjusting base 111; and the connecting unit 12 comprises a second adjusting base 121 movably set on the vertical rod 112 and a horizontal rod 122 set on the second adjusting base 121.

20 The wound opener 2 is set at an end of the horizontal rod 122 of the connecting unit 12 of the operating frame 1. Therein, the wound opener 2 comprises a fixed unit 21 and a drawing unit 22 movably set on the fixed unit 21; the fixed unit 21 comprises an adjusting unit 211 set at an end of the horizontal
25 rod 122 and a plurality of moving track rods 212 movably set in the adjusting unit 211; the drawing unit 22 includes a blade 221

separately set at an end of each one of the moving track rods 212; the adjusting unit 211 is set with a chute 213 for movably combining the moving track rods 212; each moving track rod 212 is separately set with a locking unit 214 for movably
5 combined with the blade 221; a vertical adjusting plate 215 is set on at least one moving track rod 212 (at an upper side); and, one blade 221 (the blade at the upper side) is connected with the vertical adjusting plate 215.

Thus, a novel device of automatic mechanical wound
10 opener of head/neck soft tissues is obtained.

Using the present invention, the first adjusting base 111 of the supporting unit 11 of the operating frame 1 is set at a side of an operating bed 3 to establish the wound opener 2. A height of the vertical rod 112 and a fixed position of the
15 vertical rod 112 corresponding to the operating bed 3 are adjusted before setting the first adjusting base 111. In addition, an operational length of the horizontal rod 122 is adjusted by the second adjusting base 121 before being fixed for adjusting the wound opener 2 according to a patient's position. Thus, the
20 operating frame 1 and the wound opener 2 are fixed on the operating bed 3 for preventing sway during surgery.

After the supporting unit 11 and the connecting unit 12 of the operating frame 1 are adjusted to proper positions, the drawing unit 22 of the wound opener 2 is set at a wound on skin
25 of the patient for surgery and each blade 221 is introduced into the wound from outward to inward for hooking head/neck soft

tissues at upper and lower sides. The blade 221 brings the moving track rod 212 to move along the chute 213 of the adjusting unit 211 as the blade 221 moves; or, the vertical adjusting plate 215 is used to adjust the position of the blade 221 at the upper side. After each blade 221 is moved to a fixed position, the adjusting unit 211 is fixed to decide wound size, where each blade 221 is adjusted to create a sufficient operative space and to be fixed for maintaining the space. Thus, each blade 221 is used to create the operative space, where endoscopes or robotic arms can be smoothly introduced to evaluate and treat lesions; The wound opener 2 helps operators (doctors) on head and neck surgeries, where the wound size can be further reduced and the wound can be effectively concealed.

During practical use, each blade 221 can be changed based on different requirement. For changing the blade 221, the locking unit 214 at the end of the moving track rod 212 is removed; then, the original blade 221 on the moving track rod 212 is taken off; then, a proper blade is re-set on the moving track rod 212; and, then, the locking unit 214 is locked at the end of the moving track rod 212. Thus, the blade 221 is changed to meet special needs of distinct situations.

To sum up, the present invention is a device of automatic mechanical wound opener for head and neck surgery, where a mechanic wound opener is used to adjust position and size of a wound for introducing endoscopes or robotic arms to evaluate

and treat head and neck lesions; and, thus, the present invention facilitates surgical procedure, reduces wound size and effectively conceals the wound to make it become invisible.

5 The preferred embodiment herein disclosed is not intended to unnecessarily limit the scope of the invention. Therefore, simple modifications or variations belonging to the equivalent of the scope of the claims and the instructions disclosed herein for a patent are all within the scope of the
10 present invention.

Claims

1. A device of automatic mechanical wound opener for head and neck surgery, comprising
 - 5 – an operating frame; and
 - a wound opener, said wound opener being located at an end of said operating frame, said wound opener comprising
 - a fixed unit; and
 - 10 – a drawing unit, said drawing unit being movably located on said fixed unit.
2. The device according to claim 1,
wherein said operating frame comprises a supporting unit
15 and a connecting unit; said connecting unit is movably combined with said supporting unit; and said wound opener is located at an end of said connecting unit.
3. The device according to claim 2,
20 wherein said supporting unit comprises an adjusting base and a vertical rod and said vertical rod is located on said adjusting base.

4. The device according to claim 2 or 3,
wherein said connecting unit comprises a second adjusting
base and a horizontal rod; said second adjusting base is
movably located on said vertical rod; said horizontal rod is
5 located on said second adjusting base; and said horizontal
rod is perpendicular to said vertical rod.

5. The device according to any of the preceding claims,
wherein said fixed unit of said wound opener comprises an
10 adjusting unit and a plurality of moving track rods; said
adjusting unit is located at an end of said horizontal rod;
and said moving track rods are movably located in said
adjusting unit; and
wherein said drawing unit includes a blade separately
15 located at an end of each one of said moving track rods;
said vertical adjusting plate is located on at least one of
said moving track rods; and one of said blades is
connected to said vertical adjusting plate.

20 6. The device according to claim 5,
wherein said adjusting unit has a chute to be movably
combined with said moving track rods; and each moving
track rod has a locking unit to be movably combined with
one of said blades.

25