VOLUMETRIC PUMP WITH RECIPROCATED AND ROTATED PISTON

The present invention concerns a volumetric pump which may be used in different fields such as medical drug or fluid delivery (infusion Pump, IV pump, enteral pump, parenteral pump) or food, chemical or other industry, for example in conjunction with a compressor or an internal combustion engine.

Piston pumps with fluid modules are already part of the prior art. US 2004/101426 discloses a device comprising a cylindrical piston chamber whose upper and lower ends' profile have a specific gradient, said piston chamber containing a rotatable and axially movable pump piston. The profile of the upper and lower end surfaces of the piston has been determined to run concomitantly in contact with the respective two end surfaces of the chamber as the piston rotates. This rotation causes the piston to move alternately upwards and downwards permitting one-way suction and one-way propulsion of a fluid respectively into and out of the pump chambers. The rotational movement of the piston acts as a valve opening and closing alternately the inlet and outlet ports. The drawback of such system results essentially from the difficulties encountered when assembling the piston with the cylindrical chamber.

GB 2060131, US 4,767,399 and US 4,850,980 disclose a pumping mechanism device whose suction and propulsion phases are achieved by means of a bidirectional linear movement of a piston inside a chamber. Unlike US 2004/101426, such pumping mechanism has a device acting as a valve on the inlet/outlet ports which is independent of the piston's movement. Accordingly, the movement of the valve as well as its synchronization with the piston's movement requires more parts thus increasing the cost of the pumping mechanism.

The aim of the present invention is to propose a low cost volumetric pump constituted of a reduced number of parts and having a trouble free assembly of the piston with the chamber.

This aim is achieved by a volumetric pump as set out in claim 1. This volumetric pump comprises at least one piston in a hollow cylinder, the pump having at least one inlet port through which a liquid can be sucked into a pump chamber during an instroke of said piston, and at least one outlet port through which the liquid can be expelled during an outstroke of the piston. The piston or the hollow cylinder can be actuated directly or indirectly by a rotor. This rotor transmits on the one hand a bi-directional linear movement to the piston or to the cylinder and on the other hand, a bi-directional angular movement either to the piston or to another rotable element in order to open and close alternately the inlet and outlet ports.

Unlike US 2004/101426, the combined bi-directional linear and angular movement transmitted by the rotor has for consequence to deliver a steady fluid rate of flow from the volumetric pump. Furthermore, this volumetric pump is highly accurate as the amount of fluid delivered by said pump is closely related to the relative position between the piston and the hollow cylinder housing.

The invention will be better understood thanks to the following detailed description of several embodiments with reference to the attached drawings, in which:

- Figure 1 is a perspective view of a volumetric pump with a piston located in a hollow cylinder according to a first embodiment of the invention, with the rotor removed

- Figure 2 is a perspective view of a rotor comprising an eccentric shaft of the first embodiment.

- Figure 3 is a cross-sectional view showing the engagement of this eccentric shaft in a receptacle adjacent the top of the piston.

- Figure 3a shows a detail of Figure 3.

- Figure 4 is a perspective view of the first embodiment of volumetric pump at the beginning of a revolution cycle of the rotor.

- Figure 4a is an axially sectioned rear view of Figure 4 and Figure 4b is a cross-sectional view taken on the line A-A in Figure 4a.

- Figure 5 is a perspective view of the volumetric pump after a 90° rotation of the rotor.

- Figure 5a is an axially sectioned rear view of Figure 5 and Figure 5b is a cross-sectional view taken on the line A-A in Figure 5a.

- Figure 6 is a perspective view the volumetric pump after a 180° rotation of the rotor.

- Figure 6a is an axially sectioned rear view of Figure 6 and Figure 6b is a cross-sectional view taken on the line A-A in Figure 6a.

- Figure 7 is a perspective view of the volumetric pump after a 270° rotation of the rotor.

- Figure 7a is an axially sectioned rear view of Figure 7 and Figure 7b is a cross-sectional view taken on the line A-A in Figure 7a.

- Figure 8 is a perspective view of the volumetric pump according to a second embodiment of the invention comprising a piston head.

- Figure 8a is a perspective view of said piston head connected to the shaft of the rotor.

- Figure 8b is a perspective view of the piston of the second embodiment of the invention.

- Figure 9 is a perspective top view of the volumetric pump according to a third embodiment of the present invention showing the pump in transparency without the rotor.

- Figure 9a is a perspective bottom view of the third embodiment showing the outside of the volumetric pump without the rotor.

- Figure 10 is a perspective view of one of the two cylindrical parts constituting the hollow cylindrical housing of the third embodiment.

- Figure 10a is a perspective view of another rotable element fitted into the cylindrical part of Figure 10.

- Figure 11 is a front view of this rotable element and Figure 11a a cross-sectional view of said element taken on the line A-A in Figure 11.

- Figure 12a is an end view of Figure 9 and Figure 12b a cross-sectional view taken on the line A-A in Figure 12a at the beginning of a cycle.

- Figure 13a is an end view of Figure 9 and Figure 13b a cross-sectional view taken on the line A-A in Figure 13a after a 90° rotation of the rotor.

- Figure 14a is an end view of Figure 9 and Figure 14b a cross-sectional view taken on the line A-A in Figure 14a after 180° rotation of the rotor.

- Figure 15a is an end view of Figure 9 and Figure 15b a cross-sectional view taken on the line A-A in Figure 15a after 270° rotation of the rotor.

- Figure 16 is a perspective view of the volumetric pump according to a forth embodiment of the invention.

- Figure 16a is an axially sectioned view of Figure 16 taken along an axe connected to a least one rotor.

- Figure 17 is a perspective view of the volumetric pump according to a further embodiment of the invention.

- Figure 17a is an axially sectioned view of Figure 17 taken along an axe connected to at least one rotor.

According to the preferred embodiment of the invention, Figure 1 shows the volumetric pump (1) comprising a cylindrical piston (2) and a hollow cylinder (3) mounted on a support (4). This cylinder (3) has an upper open end wherein the piston (2) slidably fits. Piston (2) is actuated by a rotor (5) bearing an eccentric shaft (6) that is mounted on a spring (7).

As shown by Figure 3 and Figure 3a, the shaft (6) ends with a spherical extremity (8) which is clipped into a piston receptacle (9) in order to transform the angular motion of the rotor (5) into a bi-directional linear and angular movement of the piston (2). This piston (2) slides to and fro inside the cylinder (3) while having a bi-directional angular movement.

Shaft (6) transmits the movement of the piston (2) inside cylinder (3) as described below, while the spring (7) insures a smooth articulation of the extremity (8) inside the receptacle (9). Spring (7) is compressed when the piston (2) reaches the ends of the suction and propulsion strokes (Figure 4 and Figure 6).

When the piston (2) is in the suction or propulsion cycle (Figure 5 and Figure 7) spring (7) is relaxed.

The bidirectional angular movement of the piston (2) acts as a valve for inlet and outlet ports (10, 11) that are located on opposite sides of the hollow cylinder (3). Piston (2) contains two channels (12,13), which cause the inlet port (10) and the outlet port (11) to open and close alternately while the piston (2) moves angularly. At first, the instroke (or upstroke) of the piston (2) opens the inlet port (10) and closes the outlet port (11), sucking a fluid (15) from the inlet port (10) through the first channel (12) into the lower part of the hollow cylinder (3) (Figure 5a and Figure 5b). Then, the outstroke (or down stroke) of the piston (2) closes the inlet port (10) and opens the outlet port (11), propelling the fluid (15) from said lower part of the pump chamber (3) through the second channel (13) to the outlet port (11) (Figure 7a and Figure 7b).

Said channels (12, 13) have been curve-shaped according to both bidirectional angular and linear movement of the piston (2) in order to ensure a constant opening of the inlet (10) and the outlet (11) during respectively the instroke phase and the outstroke phase of piston (2). This ensures a constant flow of liquid (15) from the inlet port (10) through the piston (2) to the lower part of the cylindrical chamber (3') during the instroke of piston (2) and a constant flow of the liquid (15) from the lower part of the pump chamber (3') to the outlet during the outstroke of the piston (2).

Several specifically shaped gaskets or standard Orings (14) are positioned around the inlet port (10) and the outlet port (11) in order to seal off the existing play between the external diameter of the piston (2) and the internal diameter of the cylindrical chamber (3'). Said gaskets, which comprise specific sealing rib design, are part of the piston (2) or cylinder (3).

The present invention may be adapted for medical use as a parenteral system. The piston (2) and the cylindrical chamber (3') can constitute a disposable. Unlike existing pumps with disposables composed by soft parts such as a flexible membrane or tube as in a peristaltic pump, the disposable piston (2) and cylindrical chamber (3') can be produced by injection molding methods as hard plastic parts and are therefore not influenced by pressure and temperature. As a result, such system allows an accurate release of a specific amount of a drug by a preset angular shift of the rotor (5). A single dose is produced by a 360° rotation of said rotor (5). Several doses can be released with such system at fixed intervals of time by simply actuating the rotor.

In the second embodiment of the present invention (Figure 8, 8a), the upper-end of the piston (2) comprises a ball-and-socket joint (16) which is firmly connected to a piston head (17) through two lugs (18). The rotor (5) bearing the eccentric shaft (6) transmits through piston head (17) a combined bidirectional angular and linear movement to the piston (2), the piston head (17) having a hole into which a shaft (19) is driven in for guidance. Such embodiment avoids abutment which may occur in the first embodiment of the present invention between the spherical extremity (8) of the shaft (6) and the piston receptacle (9) when the piston (2) is in the suction or propulsion cycle as shown by Figure 5 and Figure 7.

In the third embodiment, (Figures 9 to 15), a first and a second piston (20, 21) are fixedly positioned opposite to each other inside a hollow cylindrical mobile

housing (22) as shown by Figure 9. Said housing (22) is made up of two identical cylindrical parts (23, 23') assembled end-to-end facing each other. A disc (24) (Figures 10a, 11, 11a) comprising the inlet and outlet ports (10, 11) located preferably laterally at 180° from each other and a hole (25) on its underneath part (Figure 9a), is mounted midway inside said housing (22) between the two cylindrical parts (23, 23'). Such assembling creates a first and a second chamber (26, 26') (Figure 12b, 14b). The disc (24) is angularly movable relative to the housing (22) formed by parts (23, 23').

A shaft (not shown) is inserted into the hole (25), said shaft being mounted on a rotor (5), as described in the first embodiment of the invention, for transmitting to the disc (24) a combined bi-directional linear and angular movement.

Such movement of the disc (24) causes the cylindrical housing (22) to slide back and forth following the axis of the two pistons (20, 21) while closing the inlet and outlet ports (10, 11) so as to ensure on the one hand an alternate sucking of the fluid (15) from the inlet port (10) to respectively the first and second chamber (26, 26') and on the other hand an alternate expelling of the fluid (15) from respectively the first and second chambers (26, 26') to the outlet port (11).

The optimum synchronization of the suction and propulsion phases between the two chambers (26, 26') is achieved by a first and a second T-shaped channel (27, 27') located inside the disc (24) and in its inlet/outlet as shown by Figure 11a. Channels (27, 27') connect alternately the inlet port (10) to the first and second chambers (26, 26',) and the first and the second chamber (26, 26') to the outlet port (11) when said channels (27, 27') overlap alternately the first and the second opening (28, 28') located on the end of both cylindrical parts (23, 23') (Figure 10). This particular embodiment of the invention allows the volumetric pump to provide a continuous flow.

In a forth embodiment of the invention, the combined bidirectional linear and angular movement of the piston (2) is imparted by mean of an axe (28) which passes through an upper part (29) rigidly connected with the piston head (17) as shown by Figure 16 and 16a. Said axe (28) can be actuated by at least one rotor (5). The movement of the axe (28) transmits to the piston (2) a movement such as described in the second embodiment of the invention.

Such transmission can be adapted to the third embodiment of the invention (Figure 17 and 17a).

In a further embodiment of the present invention (not shown in the drawings), the pump (1) is actuated by two rotors (5, 5') operatively connected to the upper and lower parts of said piston (2) as described in the first embodiment. The first rotor (5) transmits to the piston (2) the movement required by the suction phase while the second rotor (5') transmits to said piston (2) the movement required by the propulsion phase.

All embodiments of the present invention can be adapted so as to dissociate the relative linear movement of the piston with its angular movement. The linear movement can be transmitted by a first rotor and the angular movement can be transmitted by a second rotor. The movement of the piston can be converted from a linear movement to an angular movement at any time of its stroke.

In another variant of the present invention, the pump (1) can be used as a compressor. A sealed tight tank can be fitted on the outlet port, sucking the air through the inlet (10) into the chamber and propelling the air into the tank by the same mechanism described in the first embodiment.

The mechanism of this volumetric pump (1) can also be adapted for an internal combustion engine. Thus, another aspect of the invention is an internal combustion engine comprising a volumetric pump according to the invention, as described herein.

Although the present invention has been described with reference to specific embodiments, this description is not meant to be construed in limiting sense. Various other fields of application of the invention can be contemplated without departing from the scope of the invention as defined in the appended claims.

CLAIMS

1. A volumetric pump (1) comprising at least one piston (2) in a hollow cylinder (3), said pump (1) having a least one inlet port (10) through which a liquid (15) can be sucked into at least one pump chamber (3') during an instroke of said piston (2), and at least one outlet port (11) through which the liquid (15) can be expelled during a outstroke of the piston (2), characterized in that the piston (2) or the hollow cylinder (3) can be actuated directly or indirectly by at least one rotor (5), said rotor (5) being arranged to transmit, on the one hand, a bi-directional linear movement to the piston (2) or to the cylinder (3), to cause said piston (2) to slide to and fro inside and relative to said cylinder (3) and, on the other hand, a bi-directional angular movement either to the piston (2) or to another element (24) angularly movable relative to the cylinder (3) in order to open and close alternately the inlet and outlet ports (10, 11).

2. A volumetric pump (1) according to claim 1, wherein the alternate opening and closing of said inlet and outlet ports (10, 11) are either in synchronization with the suction and expulsion phases of the pump (1) or at anytime during the stroke of said piston (2).

3. A volumetric pump (1) according to claim 2, wherein the piston (2) is movably mounted inside a fixed hollow cylinder (3), said piston (2) being actuated by a shaft (6) mounted eccentrically on said rotor (5), said shaft (6) providing an instroke of the piston (2) for sucking fluid (15) from the inlet port (10) through a first channel (12) into the pump chamber (3'), followed by an outstroke of said piston (2) for expelling fluid (15) from said chamber (3') through a second channel (13) to the outlet port (11).

4. A volumetric pump (1) according to claim 3, wherein said channels (12, 13) are curved to ensure a flow of the liquid (15) alternately from the inlet port (10) to the chamber (3') during the instroke of the piston (2) and from said chamber (3') to the outlet (11) during the outstroke of the piston (2).

5. A volumetric pump (1) according to claim 4, comprising a piston head (17) connected to the shaft (5) of the rotor (6) for driving said piston (2).

6. A volumetric pump (1) according to claim 2, comprising a first and a second piston (20, 21) fixedly positioned opposite to each other inside a hollow cylindrical movable housing (22) made up of two identical cylindrical parts (23, 23') assembled end-to-end facing each other, and a disc (24), that comprises the inlet and outlet ports (10, 11) mounted midway inside said housing (22), the assembly of the cylindrical parts (23, 23') providing a first and a second chamber (26, 26') in said cylindrical parts, said disc (24) being arranged to be animated by a combined bidirectional linear and angular movement to cause the cylindrical housing (22) to slide back and forth following the axis of the two pistons (20, 21) while closing the inlet and outlet ports (10, 11) synchronically to ensure a continuous flow delivery.

7. A volumetric pump (1) according to any one of the preceding claims, wherein said piston (2) and cylindrical chamber (3) are disposables.

8. A volumetric pump (1) according to any one of the preceding claims, wherein said shaft (6) ends with a generally spherical extremity (8) which is received in a cavity (9) adjacent to the top part of the piston (2).

9. A volumetric pump (1) according to claim 2, wherein said shaft (6) is mounted on a spring (7).

10. A volumetric pump (1) according to any one of the preceding claims, wherein a plurality of gaskets or O rings (14) are positioned around the inlet and outlet port (10, 11), said gaskets being part of the piston (2), cylinder (3) or disc (24).

11. A volumetric pump according to any one of the preceding claims, wherein said pump is reversible.

12. A volumetric pump according to any one of the preceding claims, comprising a first rotor for imparting relative linear movement to the piston (2) or to the cylinder (3) and a second rotor for independently imparting an angular movement to the piston (2) whereby the relative linear movement of the piston (2) is dissociated from its angular movement.

13. A volumetric pump according to any one of the preceding claims, comprising more than two pistons.

14. A compressor comprising a tank that is sealed tight to the outlet port (11) of a volumetric pump (1) according to claim 1.

15. An internal combustion engine comprising a volumetric pump (1) according to claim 1.