(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau

(43) International Publication Date
19 April 2001 (19.04.2001)

PCT

(10) International Publication Number
WO 01/27225 A1

(51) International Patent Classification[7]: C10G 67/04

(21) International Application Number: PCT/US00/27718

(22) International Filing Date: 6 October 2000 (06.10.2000)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
60/159,043 12 October 1999 (12.10.1999) US
09/678,510 2 October 2000 (02.10.2000) US

(71) Applicant: EXXON RESEARCH AND ENGINEERING COMPANY [US/US]; P.O. Box 900, 1545 Route 22 East, Annandale, NJ 08801-0900 (US).

(72) Inventors: BEARDEN, Roby, Jr.; 505 Stanford Avenue, Baton Rouge, LA 70808 (US). HOU, Zhigou; 2028 Oakdale Drive, Baton Rouge, LA 70810 (US). GORBATY, Martin, Leo; 204 Twin Oaks Terrace, Westfield, NJ 07090 (US). FERRUGHELLIG, David, Thomas; 10 Hardy Drive, Flemington, NJ 08822 (US). MYERS, Ronald, Damian; Box 35, Site 2, R.R. 8, Calgary, Alberta T2J 2T9 (CA).

(74) Agents: BAKUN, Estelle, C. et al.; ExxonMobil Research and Engineering Company, P.O. Box 900, Annandale, NJ 08801-0900 (US).

(81) Designated States *(national)*: AU, CA, JP, NO, SG.

(84) Designated States *(regional)*: European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE).

Published:
— *With international search report.*

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: COMBINATION SLURRY HYDROCONVERSION PLUS SOLVENT DEASPHALTING PROCESS



(57) Abstract: The invention described herein is directed to: (a) slurry hydroprocessing (SHP) of a feed under SHP conditions; (b) deasphalting, under deasphalting conditions the product obtained from said step (a) and recovering a solvent deasphalted oil and solvent deasphalted rock; (c) calcining said solvent deasphalted rock at a temperature of ≤ about 1200 °F to produce an ash catalyst precursor; (d) recycling said ash catalyst precursor to said step (a).

WO 01/27225 A1