

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
17 January 2002 (17.01.2002)

PCT

(10) International Publication Number
WO 02/04322 A2

(51) International Patent Classification⁷: **B65G**

(21) International Application Number: PCT/US01/21694

(22) International Filing Date: 10 July 2001 (10.07.2001)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
60/217,204 10 July 2000 (10.07.2000) US

(71) Applicant: **ASYST TECHNOLOGIES, INC.** [US/US];
48761 Kato Road, Fremont, CA 94538 (US).

(72) Inventors: **SMITH, Mark, V.**; 6470 Bugle Drive, Colorado Springs, CO 80918 (US). **WARTENBERGH, Robert, P.**; 630 Old La Honda Road, Woodside, CA 94062 (US). **PENNYBACKER, William, P.**; 874 Cobalt Court, Tracy, CA 95376 (US).

(74) Agents: **MILLER, Mark, E.** et al.; Fliesler Dubb Meyer & Lovejoy LLP, 4th floor, Four Embarcadero Center, San Francisco, CA 94111-4156 (US).

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, UZ, VN, YU, ZA, ZW.

(84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).

Published:

— without international search report and to be republished upon receipt of that report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: SMIF CONTAINER LATCH MECHANISM

(57) **Abstract:** The present invention includes a latch assembly, such as may be useful for SMIF pods. SMIF pods are in general comprised of a pod door which mates with a pod shell to provide a sealed environment in which wafers may be stored and transferred. During wafer storage and transport, the pod door is typically held affixed to the pod shell by a latch assembly. When it is desired to separate the pod door from the pod shell, each latch must be actuated outwardly, to withdraw each engagement portion from the pod door, at which time the pod door may be separated. The present invention includes an improved such latch assembly.

WO 02/04322 A2