

- 1 -

DYNAMIC MIXER

The present invention relates to a dynamic mixer, comprising a rotor housing in which a mixing rotor is arranged and
5 which is closed on the inlet side by a cover on which inlets for the components are arranged.

Particularly when mixing components in different volumetric amounts as they are e.g. used for producing dental impression
10 materials the difficulty arises that the two components should be mixed at the correct mixing ratio at the beginning of the mixing process already. If no particular measures are taken, the component whose volumetric content is smaller, e.g. a catalyst, is absent or not present in a sufficient
15 amount at the beginning of the paste strand discharged from the mixer. The result is an unsatisfactory mixing quality such that e.g. the hardening capability of the casting compound is not ensured. Another weakness of the currently available mixers is the inclusion of air bubbles, which
20 affects the impression quality.

EP-A2-1 402 940 discloses a dynamic mixer having a detour channel in order to retard the entrance of the component having the larger volumetric amount into the mixing chamber.
25 This measure has the disadvantage that a high pressure is required for delivering that component to the mixing chamber through the detour channel, particularly if it is highly viscous.

30 On the background of this prior art, the object of the present invention is to provide a dynamic mixer ensuring, in a simple manner and without additional pressure losses, that both components are mixed at the correct ratio without suppressing one of the components, and that air inclusions
35 are avoided.

- 2 -

A dynamic mixer attaining this object is defined in claim 1. The further claims, more particularly claim 2, define preferred embodiments.

5

The invention will be explained in more detail hereinafter with reference to drawings of exemplary embodiments.

10 Figure 1 shows a side elevation and partial section of a first exemplary embodiment of a mixer according to the invention that is secured to a cartridge by means of a bayonet ring,

15 Figure 1A shows a section according to line IA-IA in Figure 1, without the bayonet ring,

Figure 1B shows a section according to line IB-IB in Figure 1, without the bayonet ring,

20 Figure 1C shows a section according to line IC-IC in Figure 1, without the bayonet ring,

25 Figure 1D shows a section according to line ID-ID in Figure 1, without the bayonet ring,

Figure 1E shows a section according to line IE-IE in Figure 1, without the bayonet ring,

30 Figure 2 shows a perspective view of the mixing rotor of Figure 1,

Figure 2A shows a section of mixing blade 15 according to line IA-IA in Figure 1D,

- 3 -

- Figure 2B shows a section of mixing blade 16 according to line IB-IB in Figure 1D,
- 5 Figure 3 shows a lateral view and partial section of the mixing rotor of Fig. 2;
- Figure 4 shows a section according to line IV-IV in Figure 5 of the rotor housing of Figure 1,
- 10 Figure 5 shows the rotor housing of Figure 4 as seen from the inlet side,
- Figure 6 shows a perspective view of the rotor housing of Figure 4,
- 15 Figure 7 shows the cover of the rotor housing of Figure 6 as seen from the outlet side,
- Figure 8 shows a section according to line VIII-VIII in Figure 7,
- 20 Figure 9 shows a perspective view of the rotor housing cover of Figure 7,
- 25 Figure 10 shows a perspective view of a second exemplary embodiment of a mixing rotor,
- Figure 11 shows a lateral view and partial section of the mixing rotor of Fig. 10,
- 30 Figure 12 shows a lateral view and partial section of an assembled mixer including the mixing rotor of Figure 11,

- 4 -

Figure 12A shows a section according to line XIIA-XIIA in Figure 12,

5 Figure 12B shows a section according to line XIIB-XIIB in Figure 12,

Figure 12C shows a section according to line XIIC-XIIC in Figure 12, and

10 Figure 12D shows a section according to line XIID-XIID in Figure 12.

Figure 1 shows the dynamic mixer which is connected to larger outlet 1 and smaller outlet 2 of a double cartridge 3
15 and secured by means of a bayonet ring 4 and which serves for mixing two components in different volumetric amounts. Hereinafter, the component having the larger volumetric amount will be designated as component A and the component having the smaller volumetric amount as component B.

20 The mixer includes a mixing rotor 10, a rotor housing 20 and rotor housing cover 30. In order to set mixing rotor 10 in rotation, it is coupled on the inlet side to a driver 5 of mixer drive shaft 6.

25 As appears in Figures 2 and 3, the inlet end of mixing rotor 10 comprises a driver hub 12 having an opening for engagement with driver 5.

30 Driver hub 12 has a distributor body 13 located on its inlet side as well as a disk portion 14 and mixing blades 15 and 16, respectively, arranged on following rotor hub 11.

Distributor body 13 has a longitudinal cross section that is
35 curved toward rotor hub 11. End portion 18 of distributor

- 5 -

body 13 facing disk portion 14 has a circular rim, also shown in Figure 1B. In the assembled condition of the mixer, this rim is located at a distance from the wall of rotor housing 25 such that a gap forming a passage 19 results between the rim of end portion 18 and the wall of rotor housing 25.

As appears in Figure 1C, disk portion 14 has passageways 20 in the form of slots extending from rotor hub 11 to the edge of disk portion 14. Different passageways and shapes of the latter may alternatively be provided.

Mixing blades 15, 16 are arranged on rotor hub 11 in multiple planes. The shape of mixing blades 15, 16 is designed for favorable flow characteristics, i.e. it is chosen such that the components do not detach therefrom during the mixing operation, thereby avoiding the inclusion of unwanted air bubbles. On each level of rotor hub 11, mixing blades 15 having an essentially rhomboid cross-section, see Figure 2A and mixing blades 16 having an essentially rhomboid cross-section as well (see Figure 2B) are alternately arranged. In Figure 1, the direction of rotation of the mixing rotor is indicated by an arrow, and in Figures 2A and 2B, the direction of rotation is indicated by DR.

In Figure 1 and in cross-section 1D transversally to the axis of rotation of mixing rotor 10, mixing blade 16 has a rectangular shape while mixing blade 15 is curved in the shape of a hook on its side 15a turned away from the rotational direction. In an advantageous embodiment, the end portions of all mixing blades are curved and hook-shaped on their sides turned away from the rotational direction.

- 6 -

Mixing rotor 10 is enclosed in a rotor housing 25 closed by a rotor housing cover 45 that is illustrated in Figures 4 to 6. Rotor housing 25 comprises a disk-shaped housing portion 26 receiving rotor housing cover 45 as well as a cylindrical housing portion 27 receiving rotor hub 11 with mixing blades 15 and 16. On bottom surface 28 of disk-shaped housing portion 26, a deflecting body 29 is arranged whose upper side 30 is slanted and forms part of an inlet channel 50 for component A and whose front side 31 forms part of an antechamber 32, cf. Figure 1.

Disk-shaped housing portion 26 further comprises grooves 33 for forming a snap connection with rotor housing cover 45 and a bearing surface 34 for bayonet ring 4. Cylindrical housing portion 27 has a step 35 on which disk portion 14 of mixing rotor 10 is rotatably seated whereby cylindrical housing portion 27 is divided into a mixing chamber 36 and a post-mixing chamber 37. The end of cylindrical housing portion 27 forms mixer outlet 38.

Figures 7 to 9 show rotor housing cover 45 including a rotor bearing 46 for receiving driver hub 12 as well as two inlets 47 and 48 for component A and B, respectively. For a tight seal of driver hub 12, rotor housing cover 45 comprises a sealing lip 49.

Inlet 47 for component A has a larger cross-section than inlet 48 for component B and leads via a channel 50 to antechamber 32 that is partly confined by a wall 51 constituted by a recess 47A formed in the bottom plate of rotor housing cover 45. Smaller inlet 48 leads to the area of passage 19 at the end of antechamber 32 via a step 52 and an essentially cylindrical inlet channel 53 and inlet aperture 54. "In the area of the passage" means that the inlet may be located either in front of or after or opposite

- 7 -

the passage, depending on the volumetric ratio of the components and the design of the distributor body.

The rim of rotor housing cover 45 is provided with grooves
5 33 for forming a snap connection with grooves 33 of rotor housing 25. Rotor housing cover 45 further comprises mechanical coding means, f. ex. in the form of a coding nose 56 directed toward inlets 47 and 48 fitting into a corresponding recess in cartridge 3, thereby allowing the
10 attachment of the mixer to cartridge 3 in a defined orientation only, see sectional view 1E.

In the attached condition of the mixer according to Figure 1, the larger outlet 1 of cartridge 3 is pushed over the
15 larger inlet 47 of the mixer while outlet 2 is pushed into smaller inlet 48 up to step 52, see Figure 8.

Deflecting body 29 shown in Figure 6 is located at the end of inlet channel 50 such that its upper side 30 forms part
20 of inlet channel 50, which leads into antechamber 32 essentially radially with respect to the axis of rotation. Distributor body 13 is arranged in antechamber 32, the latter being confined by the front side 31 of deflecting body 29 and by circular wall 51 of cover 45 shown in Figure
25 7. Inlet aperture 54 of inlet channel 53 leads into antechamber 32 essentially radially.

In the mixing operation within the mixer according to Figure 1, component A is pressed through inlet channel 50 into
30 antechamber 32, guided around the axis of rotation and distributed over the entire cross-section by rotating distributor body 13, and delivered through the passage, i.e. annular gap 19, to mixing chamber 36 in the form of a thin, continuous layer on the entire circumference. Component B is
35 radially delivered through inlet aperture 54 onto the

- 8 -

rotating end portion 18 of distributor body 13 and regularly distributed, as a result of the existing flow and shearing conditions, on the circumference of end portion 18 and premixed with component A.

5

Due to the presence of an antechamber 32, the transport of component A is temporally retarded with respect to component B so that component A reaches mixing chamber 36 a little later than component B rather than before the latter. In
10 this manner it is ensured that the first portion of the mixture also corresponds to the desired mixing ratio. Driven distributor body 13 allows an air-free filling of antechamber 32 with component A as well as its dynamic distribution which, in contrast to a mixer having a
15 stationary detour channel, offers the advantage that the flow resistance remains small. Furthermore, the geometry of inlet channel 50, leading from inlet 47 to antechamber 32 by the shortest possible way, also avoids an increase of the flow resistance so that the required delivery pressure in
20 cartridge 3 and the stresses acting on the dispensing device are altogether low.

When the two premixed components have reached mixing chamber 36, they are essentially directed radially from the
25 periphery toward the center while a further mixing effect results due to the existing flow and shearing conditions. After its passage through slotted disk portion 14, the mixture fills up post-mixing chamber 37 on the entire cross-section thereof and is subjected to another shearing and
30 shifting process. The selected shape of mixing blades 15 and 16 avoids an inclusion of air and thereby prevents the formation of bubbles in the mixture. After flowing through the post-mixing chamber, the mixed composition is finally discharged through mixer outlet 38.

35

- 9 -

Figures 10 and 11 show another embodiment of mixing rotor 60 which is a part of the mixer illustrated in Figure 12.

Components that are equivalent to the mixer according to Figure 1 are designated by the same reference numerals. The
5 required feed pressure is further reduced by conveyor blades 17 provided on distributor body 63 in antechamber 32.

As appears in the sectional view of Figure 12A, end portion 68 of distributor body 63 has an oval shape such that a
10 passage 69 in the form of two rotating gaps results between end portion 68 and the wall of rotor housing 25.

Figure 12B shows the end of channel 53, leading to the edge of end portion 68 of distributor body 63 in antechamber 32
15 through inlet opening 54.

End portion 68 of distributor body 63 is connected by two lateral ridges 65 to a disk portion 64 having a passage aperture 70 in the form of a slot. cf. Figures 10 and 12C.
20 Passage aperture 70 extends from the edge of disk portion 64 through its center up to the area near the opposite edge thereof, cf. Figure 12C.

As further appears in Figure 11, at the edge of its passage aperture, disk portion 64 is connected to rotor hub 61 in
25 such a way that a preponderantly central passage 71 from mixing chamber 36 to post-mixing chamber 37 results.

Mixing blades 15 and 16, arranged in multiple planes on
30 rotor hub 61, are designed for favorable flow characteristics in order to avoid the inclusion of air bubbles cf. Figures 1D and 12D.

In the mixing operation within the mixer according to Figure
35 12, component A is pressed through inlet channel 50 into

- 10 -

antechamber 32, guided around the axis of rotation and distributed over the entire cross-section by rotating distributor body 63, and delivered through the rotating passages 69 to mixing chamber 36 in the form of a thin,
5 continuous layer. Component B is introduced into antechamber 32 radially and premixed with component A. On the outlet side of mixing chamber 36, the components are further mixed in combination with passage aperture 70 and central passage 71 and subsequently reach post-mixing chamber 37 where they
10 are post-mixed and finally discharged.

In the mixer according to Figures 1 and 12, inlet opening 54 to antechamber 32 is arranged in the area of passage 19 or 69, respectively. It is conceivable to provide more than one
15 inlet opening 54 in order to be able to introduce component B in multiple locations. It is further conceivable to arrange inlet opening 54 after passage 19 or 69, respectively, for example in such a manner that inlet channel 53 ends in mixing chamber 36.

20 The optimized design of the mixing operation and the central arrangement of the different mixing elements allow a smaller pressure loss and a reduced mixer drive torque. The reduced friction in the medium reduces energy consumption, thereby
25 resulting in a reduced temperature increase of the mixed material.

The represented arrangements according to Figures 1 and 12 have been described for the case that the volumes of two
30 components are different from each other and that the component having the smaller volumetric amount is therefore delivered to the antechamber in the area of the passage in order to achieve a maximum premixing action. However, the design of the dynamic mixer offers the same advantages when
35 both components have the same volume. In this case, the two

- 11 -

components are symmetrically delivered to the antechamber in the upper area thereof in order to be distributed and premixed therein by the distributor body and to reach the mixing chamber through the passage.

5

In the embodiment having equal volumetric amounts, the inlets and outlets, respectively, are generally identical and the inlets are insertable into the outlets; but other variants are also possible where the outlets are insertable
10 into the inlets.

Furthermore, more than only one additional, smaller component may be admixed to the larger component. In this case, another inlet as well as another channel having an
15 inlet opening near the passage are required. The depicted and disclosed characteristic features may be combined with each other as desired.

20

- - - - -

- 12 -

Claims

1. Dynamic mixer, comprising a rotor housing (25) in which a mixing rotor is arranged and which is closed on the inlet side by a cover (45) on which inlets for the components are arranged, characterized in that the inlets (47, 48) for the components lead to an antechamber (32) that communicates with the following mixing chamber (36, 37) by at least one passage (19, 69) and in that the mixing rotor (10, 60) includes a distributor body (13, 63) located in the antechamber for distributing the components around the axis of rotation of the mixing rotor.
2. Dynamic mixer according to claim 1 for mixing components in different volumetric amounts, characterized in that the inlet (47) for the first component (A) having the larger volumetric amount ends in the upper area of the antechamber (32), the inlet (48) for a second component (B) having a smaller volumetric amount ends in at least one inlet opening (54) located in the area of the passage (19, 69) to the mixing chamber (36), and the distributor body (13, 63) for distributing the two components is arranged around the axis of rotation of the mixing rotor.
3. Dynamic mixer according to claim 1 for mixing components in equal volumetric amounts, characterized in that both inlets (47, 48) for the components end in the upper area of the antechamber (32), and the distributor body (13, 63) for distributing the two components is arranged around the axis of rotation of the mixing rotor.
4. Mixer according to one of the preceding claims, where the passage (19, 69) is formed by a gap or multiple gaps between the circumference (18, 68) of the distributor body

- 13 -

(13, 63) and the wall (31, 51) of the rotor housing (25) and/or of the rotor housing cover (45).

5 5. Mixer according to one of the preceding claims, wherein the inlet opening (54) for the second component is arranged such that the latter is delivered essentially transversally to the axis of rotation of the mixing rotor (10, 60).

10 6. Mixer according to one of the preceding claims, wherein the mixing rotor (10, 60) includes a disk portion (14, 64) having at least one passage aperture (20, 70) which is arranged after the antechamber (32) as seen in the flow direction of the components.

15 7. Mixer according to claim 6, wherein the mixing chamber (36) is essentially formed by a wall of the rotor housing (25), of the outlet side (18, 68) of the distributor body (13, 63) and of the outlet side of the disk portion (14, 64), and wherein the passage aperture(s) (20, 70) is (are) designed such that the components, while flowing through the mixing chamber, are essentially deflected toward the axis of rotation.

25 8. Mixer according to claim 6 or 7, wherein the rotor housing (25) has a constricting step (35) that serves as a support for the disk portion (14, 64) and which seals the mixing chamber against a following post-mixing chamber (37) at its periphery.

30 9. Mixer according to one of the preceding claims, wherein the distributor body (63) is provided with conveyor blades (17) arranged thereon.

- 14 -

10. Mixer according to one of the preceding claims, wherein the mixing rotor (10, 60) is provided with mixing blades (15, 16) located in the post-mixing chamber (37).

5 11. Mixer according to claim 9, wherein the mixing blades (15, 16) are designed for favorable flow characteristics and have an essentially rhomboid cross-section, two opposite mixing blades per plane or all mixing blades having a drop- or hook-shaped end on their sides turned away from the
10 direction of rotation.

12. Dispensing assembly including a double cartridge or a dispensing appliance and a dynamic mixer according to one of claims 1 to 11, the double cartridge or the dispensing
15 appliance having outlets and the mixer inlets whose diameters are different, wherein the larger outlet is slidable over the larger inlet and the smaller outlet insertable in the smaller inlet.

20 13. Dispensing assembly including a double cartridge or a dispensing appliance and a dynamic mixer according to one of claims 1 to 12, wherein the rotor housing cover (45) of the mixer and the cartridge (3) or the dispensing appliance comprise corresponding coding means (56) in order to allow
25 the attachment of the mixer in only one particular orientation.

- - - - -