

REDUCED LATENCY SERVER- MEDIATED AUDIO-VIDEO COMMUNICATION

BACKGROUND

1. Technical Field

The field of the present disclosure relates to communications and particularly relates to a
5 platform for audio-video communications.

2. Description of Related Art

An Internet service such as SKYPE™ enables audio or audio-video conversations between two
or more users. A server is used to initiate the conversation and negotiation of the type of media.
The actual audio or video streams between the users are transferred in a peer-to-peer session
10 without further server mediation.

In services such as SKYPE™, the peer-to-peer session is established to avoid creating a bottle-
neck caused by overloading a server with traffic and to avoid introducing latency through the
server.

iMessage™ is a service that allows users to send texts, photos, videos, contact information, and
15 group messages.

AOL Instant Messenger (AIM) is a service to allow users to communicate in real time.

WhatsApp™ Messenger is a proprietary, cross-platform instant messaging service for smart
phones. In addition to text messaging, users can send to each other images, video, and audio
media messages.

20 A traditional radio frequency half-duplex communications system provides communications
from a single transmitter to one or more receivers. Only one transmitter may be broadcasting at a
time because the same physical channel is shared for broadcasting to all receiving parties. Once
receivers begin to receive a signal, the receiving parties need to wait for the transmitter to stop
transmitting, before replying since the physical communications channel is unavailable.

25

BRIEF SUMMARY

Various data communications systems are disclosed herein of video communications between multiple computer systems configured as client computer systems. One (or more) of the client computer systems when transmitting is a client transmitter and one (or more) of the client computer systems when receiving or consuming is a client recipient. The client transmitter is enabled to transmit or record a video message for display on the client recipient. The client transmitter is configured to establish a connection with a video server and to transmit the video message to the video server. The video message is archived by the video server. If the client recipient is unavailable during the beginning of the transmission of the video message and when the client recipient is available later during the transmission of the video message, then the client recipient is enabled to display the video message from the beginning of the video message while the transmission of the video message is still ongoing.

The client computer systems may be configured to alternate between being a client transmitter and a client receiver and to alternately transmit and receive video content.

A management server may be adapted to receive from the client transmitter a first character string including a reference to the client recipient and in response transmit to the client recipient a second character string including a reference to the client transmitter. In response to the second character string, the client recipient is configured to transmit a third character string to the video server. The third character string references the video message and upon receipt by the video server of the third character string, the video server transmits the video message to the client recipient.

When the client recipient is unavailable, the client recipient may be adapted to retrieve the video message from a message archive of the video server when the client recipient is later available. Multiple client computer systems configured as client transmitters may transmit respective video messages simultaneously to the client recipient.

Various client computer systems and/or software applications thereof may be configured for use in the data communications network. The client computer system and/or software applications may include a transmitter module configured to: establish the connection with the video server, transmit a first video message to the video server and transmit to the management server the first character string. The client computer system and/or software applications may include a receiver

module configured to: transmit the second character string to the video server, receive a second video message; and display the second video message.

Various management servers and/or software applications thereof may be configured for use in the data communications network. The management server may include: a management receiver
5 module adapted to receive from the client transmitter the first character string and a management transmitter module adapted to transmit the second character string to the client recipient.

Various video servers may be configured for use in the data communications network. The video server includes: a network adapter configured to establish the connection with the client transmitter and receive the video message and a video data storage adapted to archive the video
10 message. The network adapter is configured to receive the third character string and to transmit the video message to the client recipient responsive to the third character string.

Various methods are disclosed herein for management of video communications between multiple computer systems. One (or more) of the client computer systems when transmitting is a client transmitter and one or more of the client computer systems when receiving or consuming
15 is a client recipient. The client transmitter is enabled to transmit a video message for display on the client recipient. The client transmitter is configured to establish a connection with a video server, to transmit a video message to the video server. The video message is archived by the video server. When the client recipient is unavailable during the beginning of the transmission of the video message and when the client recipient is available later during the transmission of the
20 video message, the client recipient is enabled to display the video message from the beginning of the video message during the transmission of the video message to the video server.

The video message may be received and displayed by the client recipient.

The client computer systems may be configured to alternate between being a client transmitter and a client receiver and to alternately transmit and receive respectively.

25 The client recipient may be selected for receiving or consuming the video message while the video message is being transmitted to the video server. The connection may be established autonomously without intervention by a user of the client transmitter. The connection may be established responsive to a program previously installed in the client transmitter by monitoring actions of a user of the client transmitter and the connection is established based on said
30 monitored actions of the user. Transmission by the client recipient of the second character string to the video server may be performed without prior notification to a user of the client recipient.

Latency is reduced by transmitting the video message from the video server to the client recipient while transmitting the video message from the client transmitter to the video server.

Various computer readable media may be encoded with processing instructions for causing a processor of the client computer system and/or a processor of the video server and/or a processor
5 of the management server the execute the methods as disclosed herein.

The foregoing and/or other aspects will become apparent from the following detailed description when considered in conjunction with the accompanying drawing figures.

BRIEF DESCRIPTION OF THE DRAWINGS

10 The invention is herein described, in a non-limiting manner, by way of example only, with reference to the accompanying drawings, wherein:

Figure 1 illustrates a simplified block diagram of a mobile computer system according to features of the present invention.

Figure 2 shows a simplified block diagram of a system, according to features of the present
15 invention.

Figures 3a, 3b and 4 show flow charts for methods, according to features of the present invention.

Figure 5 illustrates a sub-process which may be performed when a client recipient is available, according to features of the present invention.

20 Figure 6 illustrates a sub-process which may be performed when a client recipient is unavailable at the original time of transmission of a video message, according to a feature of the present invention.

Figure 7 illustrates a simplified timing diagram of a client transmitter transmitting two messages to a client recipient, according to a feature of the present invention.

25 Figure 8 illustrates a timing diagram of messages communicated between clients of a group thread, according to a feature of the present invention.

The foregoing and/or other aspects will become apparent from the following detailed description when considered in conjunction with the accompanying drawing figures.

DETAILED DESCRIPTION

Reference will now be made in detail to embodiments of the present invention, examples of which are illustrated in the accompanying drawings, wherein like reference numerals refer to the like elements throughout. The embodiments are described below to explain the present invention
5 by referring to the figures.

By way of introduction, embodiments of the present invention are directed to provide a video communications system and method with a user experience similar to half-duplex communications (sometimes known as "walkie-talkie" or "push-to-talk") as well known in radio-frequency communications. The average length of a "full-duplex" session using a service such as
10 Skype™ may be over ten minutes. The initialization time needed by existing technology to initiate a video stream using a prior art video service may range between 10 and 30 seconds depending on the network and the implementation used. This initialization time may be acceptable in prior art video services such as Skype™. Assuming a ten minute video session, for example, thirty seconds of initialization time for the 10 minute session amounts to 4.76%
15 overhead. Embodiments of the present invention are intended to accommodate audio and/or video messages or bursts of average length 20 to 30 seconds. An initialization time of 30 seconds to transfer a 25 second audio and/or video message would amount to 54.5% overhead which would not be acceptable. Therefore, one of the technical problems being solved in embodiments of the present invention is to provide a user experience of "half-duplex" communications system
20 while minimizing initialization time and other time latencies so the user experiences near real time message transfer.

In sum, embodiments of the present invention are directed to an audio-video messaging communications platform appropriate for conversations including short audio-video message bursts, *e.g.* 10-30 seconds long, with a reduced initialization time and overall latency of less than
25 three to five seconds. Within one to two seconds after initiating transmission, the video content being recorded by a user is already being archived at a server and available to or being consumed by all the users sharing a communications thread. A user of an embodiment of the present invention may participate with other users to share video content in near real time. If the user is not available, *e.g.* not online, then the video content and the messages may be consumed later by
30 streaming from the archive. If a user is an intended recipient and is unavailable at the time transmission began and becomes available thereafter and as a result enters late into a communications thread, then the user may consume the video content from the beginning of the

thread when transmission of the video content began and participate in the thread without missing the beginning of the thread. Streaming from the archive enables multiple users to transmit to the same recipient at the same time and the recipient may receive and consume all the video content from all the users, for instance in the order of transmission.

5 Before explaining embodiments of the invention in detail, it is to be understood that the invention is not limited in its application to the details of design and the arrangement of the components set forth in the following description or illustrated in the drawings. The invention is capable of other embodiments or of being practiced or carried out in various ways. Also, it is to be understood that the phraseology and terminology employed herein is for the purpose of
10 description and should not be regarded as limiting.

Referring now to the drawings, Figure 1 illustrates a simplified block diagram of a mobile computer system **100** according to features of the present invention. Mobile computer system **100** is may connect through a cellular base station **119** to cellular network **121**. A cellular communications module **117** connects processor **110** to cellular network **121**. Mobile computer
15 system **100** may also connect over a data communications network **106** to a server **205** and to a server **206**. Mobile computer system **100** includes a processor **110** connected to local data storage **101**. A data communications module **104** operatively connects processor **110** to data communications network **106**. An audio-video encoder **202** and an audio-video decoder **204** are used to encode and decode respectively audio-video content sent from and received by mobile
20 computer system **100**. Audio-video content of audio-video encoder **202** and audio-video decoder **204** may include audio or video which includes multiple channels, for example stereoscopic video or sound each of which include right and left audio channels. Mobile computer system **100** may include peripheral accessory devices such as a display **109**, global positioning system (GPS) receiver **107**, a camera **105**, a microphone **111**, a speaker **113**, a vibrator **115**, accelerometer
25 /gravity sensor(not shown), near field communication (NFC) (not shown), radio-frequency identification (RFID) (not shown), Bluetooth™(not shown) and IR sensor (not shown).

Reference is now also made to Figure 2 which shows a simplified block diagram of a system **20**, according to features of the present invention. System **20** may include a first mobile computer system **100** acting as a client transmitter **100T** and a second mobile computer system **100** acting
30 as client recipient **100R**. A video data system **206** including video server **206a**, video database **206b** and video data storage **206c** connects with client transmitter **100T** and client recipient

100R. A management data system **205** including a management server **205a** and a management database **205b** connects with client transmitter **100T** and client recipient **100R**. An audio-video message **250** is shown as being transmitted from client transmitter **100T** to video data system **206**. Message **250** may be recorded live using camera **105** while transmitting or message **250** may be previously recorded and stored in local storage **101**. Video data system **206** and management data system **205** may be collocated in the same installation or even in the same hardware unit and while operating share the same power supply, for instance. Video data system **206** and management data system **205** may be implemented in different threads of a multi-threaded processor.

Reference is now also made to Figures 3a and 3b which show flow charts for respective methods **301** and **300**, according to features of the present invention. Methods **301** and **300** illustrate a process of client transmitter **100T** connecting and transmitting to video data system **206** in system **20**, to allow a user to transmit video messages **250** to other users. Method **301** (Figure 3a) illustrates process steps performed by client transmitter **100T** and method **300** (Figure 3b) illustrates process steps performed by server data system **206**.

Referring now to system **20** and methods **301** and **300**, a transmitter application according to an embodiment of the present invention is previously installed and stored in memory **101** of client transmitter **100T**. The transmitter application of client transmitter **100T** may connect (step **302**) to video data system **206** and to video server **206a** without yet receiving an explicit user instruction to transmit video message **250**. Specifically, the transmitter application of client transmitter **100T** based on previous user actions or prior programming may open a URI of the next video message **250** expected to be transmitted to video data storage **206c**. In parallel, video server **206a** of video data system **206** receives the connection (step **306**). Client transmitter application in step **307** begins to transmit video message **250** and in parallel in step **308**, video message **250** is being archived by video data system **206** in video data storage **206c**. Video compression may be performed while recording video message **250** using camera **105**. The user may be notified in step **304** that one or more video messages will be prepared for transmission. In parallel, the archiving of video data message may be completed (step **310**) at video data system **206**. Client transmitter **100T** application may select (step **305**) one or more recipients or the user of client transmitter **100T** may select (step **305**) one or more recipients. In step **309**, a text message, including a URI, character string or message block including a reference to the recipient(s) is sent to management server **205a** in management data system **205**. Step **309** does

not generally require an acknowledgment from management server **205a**. The URI referencing audio-video message **250**, is intended for relaying to the recipient(s) to expect the audio-video message and to prepare client recipient **100R** for the upcoming receipt of audio-video message **250**.

5 Several options are available for transfer of the message block from management data system **205** to client recipient **100R**. The message block may include: the URI to reference video message **250**, a command for client **100** to expect a video message, a command for client **100** to prepare to play video message **250**. Alternatively, the message block may include only the URI to reference the message **250**. Client recipient **100R** is programmed so that whenever it receives
10 a URI, a video message, **250** is expected and client recipient **100R** prepares to play video message **250**. In an alternative embodiment of the present invention, management server **205** may be avoided and message blocks may be transferred over a mesh network between client computer systems **100**.

In method **301**, transmission latency may be reduced if based on previous user interaction or
15 prior programming, the transmitter application deems the user has a high probability that he/she is going to record using camera **105** one or more video messages **250** and to transmit within the next few seconds. The transmitter application may prepare (step **303**) client transmitter **100T** accordingly and/or may begin to transmit (step **307**), prior to the user being notified (step **304**) that video message **250** is being or has been transmitted and prior to selecting recipients (step
20 **305**).

Referring again also to Figure 1, preparation to transmit (step **303**) may include steps such as turning on a camera **105** application and opening shutter of camera **105**, allocating space in memory **101** for video message **250**, beginning to record and encoding video message **250** by encoder **204**. Preparation to transmit (step **303**) may include opening a folder in storage **101**
25 which includes images, audio-video clips, or other multimedia messages that have not been previously received and archived (step **308**) and beginning to transmit (step **307**) the contents of that folder.

Reference is now also made to Figure 4 which illustrates a flow diagram of a method **320**, according to an aspect of the present invention. Method **320** provides for receipt of an audio-
30 video message when client recipient **100R** is available and/or subsequent audio-video message retrieval for instance when client recipient **100R** is not available or unavailable during the

original transmission from client transmitter **100T**. In decision block **311**, if client recipient **100R** is available during or shortly after (within a few seconds) beginning of transmission (step **307**) then the flow continues with sub-process **501** as shown in Figure 5. If in decision block **311**, if client recipient **100R** is not available during or shortly after transmission, then the flow
5 continues with sub-process **701** shown in Figure 7.

Reference is now made also to Figure 5 which illustrates sub-process **501** which may be performed when client recipient **100R** is available, according to features of the present invention. In step **503**, client recipient **100R** receives character string, including a URI, which includes a reference to audio-video message **250**. A character string, is sent (step **505**) from client recipient
10 **100R** to video data system **206** and video data system **206** on receiving the character string referring to video message **250** reads from video storage **206c** video message **250** and transmits video message **250** to client recipient **100R**. In the meantime, in step **506**, client recipient **100R** prepares for playback and receipt of video message **250**. In step **407**, video message **250** is received and played by client recipient **100R**. Alternatively, when client recipient **100R** is
15 available, video message **250** may be copied during transmission from client transmitter **100T** and relayed by video data system **206** to client recipient **100R** so that client recipient **100R** is not receiving message **250** from archive **206c**,

According to a feature of the present invention, when client recipient **100R** becomes available after beginning of transmission of video message **250** from client transmitter **100T**, then video
20 data system **206** may transmit video message **250** from the beginning of the message. The time delay between the time of the beginning of transmission to the time when client recipient **100R** becomes available may be reduced during the remainder of the message thread. During the subsequent interchanges between client transmitters **100T** and client recipients **100R**, the client recipient will eventually catch up with the other participants in the conversation.

25 Reference is now made also to Figure 6 which illustrates sub-process **701** which may be performed when client recipient **100R** is not available at the original time of transmission (step **307**, Figure 3) of video message **250**. When client recipient **100R** is available (decision block **702**) at an undetermined later time, client recipient **100R** synchronizes (step **703**) message history with management database **205b**. In step **705**, the user of client recipient **100R** is notified
30 of missed messages, *e.g.* video message **250**. At the same time, client recipient **100R** may send (step **505**) a character string, including a URI, to video data system **206** referring to one or more

of the missed messages. Client recipient **100R** application may anticipate user choice and send (step **505**) character string to video data system **206** whilst receiving a response to the query in step **705** regarding missed messages. The character string is received in video data system **206**, and in step **406**, video message **250** is retrieved from archive **206c** and video message **250** is being received by client recipient **100R**. Client recipient **100R** may prepare for playback, i.e. turn on the media player application, in step **706**, based on previous user actions. The application running in client recipient **100R** may deem that there is a high probability that the user is going to select viewing video message **250** already being received. If the user selects in decision box **707** playing of video message **250**, then client recipient **100R** is already prepared to play message **250** being received or already received and step **407** of receiving and playing incoming video message **250** may be performed with low overall latency.

System 20 latency compared with prior art services

The following three equations summarize communications times for a process in which a user A sends a video message, user B listens to or displays video message sent by user A, user B creates a video message in response and User A receives, displays, listens to or views the response

$$5 \quad \text{ContentTime} = \text{time for transfer of content of message A} + \text{time for transfer of message B}$$

$\text{TotalTime} = \text{time from beginning of the process to the end of the process}$

$\text{Latency} = \text{TotalTime} - \text{ContentTime}$

For services such as WhatsApp™, iMessage™, Windows™ Messenger, AOL™ Instant Messenger, the following formula may be used to calculate total communication time T for: a.

$$10 \quad T = RA1 + CA1 + UA1 + DB1 + VB1 + RB2 + CB2 + UB2 + DA2 + VA2$$

No.	Step	Parameter	Value (seconds)
1	User A records message	RA1	30
2	User A's message is compressed	CA1	5
3	User A's message is uploaded	UA1	5
4	User B downloads user A's message	DB1	5
5	User B views user A's message	VB1	30
6	User B records a response	RB2	30
7	User B's response is compressed	CB2	5
8	User B's response is uploaded	UB2	5
9	User A downloads user B's response	DA2	5
10	User A views user B's response	VA2	30
		Total	150

The process of user A to send a 30 second video to user B and subsequently for user B to watch the video and send back a 30 second response to user A and for user A to view the response requires about 150 seconds. For 60 seconds of content, 150 seconds is required for the content to be transferred and viewed. In the example, the communication using a prior art service has 90 seconds of latency, 60 seconds of content for a total time of communication T of 150 seconds where latency is 71% of the total time of communication.

In contrast, using system **20** and methods **300**, **301** and **501** messages **250** are transmitted by user A and received by user B in real time with a point-to-point total communication time of approximately two seconds. The result is that the user recipient has completed watching the incoming message at nearly the same time that the user transmitter began recording the message.

- 5 Using methods **300**, **301** and **501**, total communication time TI using embodiments of the present invention may be simplified as follows:

BR = Transmit Time

TI = Time of communication between users

TI=BRA1 + LA1 + BRB2 + LB2

10

No.	Step	Parameter	Value (seconds)
1	User A transmits a message	BRA1	30
2	Network Delay	LA1	2
3	User B transmits a response	BRB2	30
4	Network delay	LB2	2
		Total	64

- A communications process using an embodiment of the present invention, in which user A sends a video message **250** of 30 second duration to user B, user B views video message **250** and in response transmits to user A a video message response **250**, and user A views video message response **250**, requires 64 seconds. Hence, using an embodiment of the present invention, 60 seconds of content is viewed which requires about 64 seconds to be transferred and displayed. A process using an embodiment of the present invention has a latency time of about **6.25%** of the total time of communication TI.

User experience

- 20 In embodiments of the present invention, two or more users need not be available to participate in a conversation since every video message **250** is archived (step **308**) at server video data system **206**. Users may be added to a group and view all prior video messages **250** that were transmitted prior to the addition of the new user.

In embodiments of the present invention, video message **250** may be transmitted (step **307**) and compressed while recording message **250** in camera **105** to reduce compression and transmission latency times.

The user recipient(s) may begin streaming (step **407**) a received message **250** for viewing within a few seconds of the user transmitter beginning to transmit (step **307**), reducing latency time. In sum, low latency performance found according to features of the present invention create a dramatic change in user experience over prior art systems.

Queuing messages within a thread

Video communication system **20**, according to embodiments of the present invention enables users of client computer systems **100** to alternately send and receive messages **250** as unicast (one to one) or multicast (one-to-many).

In system **20**, that includes playback of incoming messages **250** in near real time, multiple incoming messages **250** may be viewed contiguously although when transmitted in real time messages **250** may overlap.

In near real time streaming video messaging system **20**, according to embodiments of the present invention, video message **250** has a start time of transmission by streaming to video data system **206**, a latency time until message **20** begins to be consumed at client recipient **100R**, and an end time when streaming ends of message **250** being received at client recipient **100R**.

According to a feature of the invention, a client **100** may either receive/consume or record/transmit video message **250** at any time but client **100** may not both consume and transmit content at the same time. A client **100** may be forced to stop one interaction to begin another, for example to stop consuming content in order to create content or vice versa.

When client recipient **100R** detects an incoming message **250**, various actions may happen. In one example, client recipient **100R** is playing another video message **250**. The user may be presented with a notification of incoming message **250** either a visual message, an audible message and/or vibration using vibrator **115** as notification. The user may select the notification via a tap or swipe on client recipient **100R** which causes video message **250** currently playing to stop or pause and video message **250** relevant to the notification begins to play.

In another example, when client recipient **100R** is not currently engaged playing a video message **250**, client recipient **100R** may be configured to play incoming message **250** without need for any interaction by the user.

Reference is now made to Figure 7 which illustrates a simplified timing diagram **801** of client **100** (of user A) transmitting two messages **250(1)** and **250(2)** to another client **100** of user Z . The passage of time is identified by going from the top of diagram **901** to the bottom of diagram **901**.

1. User **A** transmits message **250(1)** to User **Z**.
2. User **Z** receives message **250(1)** with a latency of a few seconds and begins viewing message **250(1)**.
3. After User **A** completes transmitting message **250(1)**, an amount of time less than the latency between the transmission of User **A** of message **250(1)** and playback of User **Z** of message **250(1)** passes.
4. User **A** begins transmitting message **250(2)** to User **Z**.
5. User **Z** is unable to begin viewing message **250(2)** because user Z is still viewing earlier message **250(1)**.
6. System **20** recognizes that message **250(1)** and message **250(2)** are contextually related based on the thread between the users users and creates a queue that plays message **250(2)** upon completion of viewing of message **250(1)** by User **Z**.

Reference is now made to Figure 8 which illustrates a timing diagram **801** of messages **250** communicated between clients **100** of group thread, according to a feature of the present invention. The passage of time is identified by going from the top of diagram **801** to the bottom of diagram **801**.

1. The User **Z** is engaged in a group thread with users **A**, **B** and **C**.
2. The User **Z** creates a message **250T Z**.
3. While the User **Z** is recording and transmitting message **250T Z**, user **A**, part of the same group thread, creates message **250T A**.
4. Message **250T A** is streamed in real time to the other members of the group thread, including User **Z**.
5. User **Z** is unable to immediately view incoming message **250T** in real time because client **100** of user Z is still recording and transmitting outgoing message **250T Z**

6. While client **100** of User **A** is transmitting message **250T A**, client **100** of user **B** begins transmitting message **250T B**.
7. While client **100** of user **B** is transmitting message **250T B**, client **100** of user **C** begins transmitting message **250T C**.
- 5 8. Messages are archived in real time by video data system **206** and client **100** of user **Z** is notified of incoming messages **250R A**, **250R B** and **250R C**.
9. Client **100** of User **Z** forms a queue and time shifts the playback of incoming messages **250R A**, **250R B** and **250R C**.
10. Messages **250R A**, **250R B** and **250R C** are played contiguously typically in time sequence
10 of transmission.

An outcome of steps 1-10 outlined above in reference to Figure 8 is that User **Z** experiences messages **250** which are transmitted while overlapping in time as if each user of the thread transmitting the messages waits until the queue is clear before creating and transmitting respective video messages **250T A**, **250T B** and **250T C**

- 15 User **Z** may or may not be notified that he/she is consuming video messages **250R A**, **250R B** and **250R C** as shifted in time.

Compensating for sub-optimal network conditions during transmission

Sub-optimal network conditions may exist which may cause high latency of or loss of information from video messages **250** when users of client computer systems **100** send video
20 messages **250**. According to a feature of the present invention, client transmitter **100T** may detect local network quality. If sub-optimal network quality exists, in order to maintain low latency quasi-real-time messaging, information content of messages **250** may be reduced prior to during or subsequent to recording of video message **250**. Reducing information content of messages **250** may include: decreasing the video frame rate of video messages **250**, reducing
25 color resolution or even switching to monochrome video messages **250**, and/or reducing video frame size, by way of examples. A reduced quality video message **250** may be transmitted and stored on video data storage **206c** and available for consuming or receiving by client recipients **100R**.

In order to subsequently recover the original high quality message **250**, the original reduced
30 quality message **250** or at least the dropped information thereof may be stored locally in client transmitter **100T** or another device, *e.g.* removable disk, attachable thereto. High quality

message **250** may be uploaded to replace the lower quality version previously stored on video data storage **206c** so that client recipients **100R** may consume or download video message **250** in higher quality subsequent to original lower quality transmission. Alternatively, the dropped information may be used to repair original message **250** on either client transmitter **100T**, on
5 video data system **206** or on client receiver **100R**. Thus, reduction of video quality may be used to maintain quasi-real-time low latency messaging even under sub-optimal network conditions while allowing subsequent consumption of the same message in the original quality. An example: User A is transmitting a video message **250** to User B. User A is on a network that is less than the required bandwidth for full quality video, so client transmitter **100T** sends a
10 reduced quality video message **250** to user B.

In the case that User B is watching at the time of the transmission, User B receives/consumes the reduced quality video of the video message **250** of user A.

Subsequent to the transmission of the reduced quality video message **250** from user A, client transmitter **100T** may transmit the dropped information from the reduced quality video of the
15 video message **250** of user A to user B. The dropped information may then be used to fill in the missing video information of the reduced quality video of the video message **250** as originally transmitted. So that in the case that User B is unavailable to watch the transmission live and chose to watch at a later time or, having watched the message at the time of the broadcast, returns later to re-watch video message **250**, User B may view the full quality video of video
20 message **250**.

Multi-function button

System **20** may be implemented using a smart phone **100**, *e.g.* iPhone, equipped with a touch sensitive display **109**. When a client application is installed on smart phone **100** for executing method **301**, **501** and/or **701**, a virtual button may be implemented on touch sensitive display
25 **109**. Alternatively, or in addition, a non-virtual or physical button may be designed into a smart phone **100** with similar functionality as the virtual button.

The button, virtual or physical may include the following modes of function:

1) Audio-Video Operation: The button may be tapped , *e.g.* for less than one second duration, and video recording begins using camera **205** and microphone **111** and simultaneously beginning
30 transmission (step **307**) of the video recording begins. A second tap stops the recording and stops

transmission and enables reception (step 407). Toggling between states of recording/transmission and enabling reception (step 407) may be performed by successively tapping the button.

2) Audio-Video ("Push-to-talk") The button is held or touched for a defined period of time, *e.g.* 2 seconds. Video recording begins using camera 205 and microphone 111 and simultaneously beginning transmission (step 307) of the video recording as in mode 1. Release of the button then ends recording/ transmission and enables receiving (step 407) of video content.

3) Audio Only: The button is slid up and released immediately and audio recording (without live images captured from camera 205) using microphone 111 and transmission (step 307) begins. When the button is slid back to its original position audio recording/transmission is stopped and receiving is enabled (step 407). The button may be held down for a period, *e.g.* two seconds, while in the slid up position and the button behaves as in mode 2 above but with audio recording/transmission only. Releasing the button in the slid up position stops audio-recording and transmission.

Example: Client 100 under Computer Control

15 According to other embodiments of the present invention, one or more client computer systems 100 may operate autonomously without requiring intervention of a (human) user. Processor 110 and/or another processor attached to computer system 100 may be programmed to control the operation of client computer system 100. Processor 110 may be configured to receive and transmit messages 250 simultaneously for instance within two independent message threads.

20 Processor 110 may be programmed to analyze, process and/or parse audio only and/or audio-video messages 250 being received and to respond accordingly, by transmitting a message 250 to other users of the thread relevant to the received message 250. Processor 110 may be programmed to respond with a message 250 including educational or advertising content relevant to the audio and or visual content being shared by the users of the thread. An example, a user

25 while shopping may in a message transmit an image of a product for which he/she wishes to receive more information. Client 100 receiving message 250 may process the images in message 250 and recognize the product, for instance using optical character recognition or bar code. Client 100 may respond with a message 250 including advertising or other information such as price and/or service information.

30 Example: A camera security system

Another example of an embodiment of the present invention in which clients **100** are under processor control is a camera security system. . Multiple security cameras may be attached individually to client transmitters **100T** and programmed to transmit by unicast or multicast to one or more client recipients **100R**. A user, *e.g.* security personnel, may view the display of client transmitter **100T** for suspicious activity at any/all of the sites of client transmitters **100T**. One or more client recipients **100R** may be fixed or mobile computer systems. The decision to transmit (decision block **304**), may be previously programmed based on time interval or local image processing, *e.g.* significant features in a difference images between image frames. Alternatively, image processing may be performed elsewhere in network **106**. Client recipient **100R** may receive video messages **250** in a round-robin or random fashion, for example. If a significant event occurs such as suspicious activity based on one of messages **250**, an interrupt to the round robin may be signaled by one of client transmitters **100T** through management server **205a**, by one of the users of client recipients **100R** through management server **205a**, video server **206** or by management server **205** based on the on-the-fly image processing. Central archiving of all the video messages is maintained at video data system **206** as is required in a security system for providing evidence.

Examples of Character Strings:

Example of Character string transmitted by client transmitter **100T**

type: "video"

videoUrl: "testvsrv.video.glidetalk.com;83;6744802_www.video.glidetalk.com_vs00002.video.glidetalk.com_89026060_v1;90;44100;1"
thumbUrl: "http://testvsrv.video.glidetalk.com:83/getthumb?sid=6744802_www.video.glidetalk.com_vs00002.video.glidetalk.com_89026060_v1&Size=2"
threadId: "50aa977de43be50200000126"

25

A portion of a character string is transmitted by client transmitter **100T** to management data system **205** referencing video message **250**.

videoUrl: "89026060_v1;90;44100;1"

In response, video data system **206** may receive the following character string with the reference to video message **250**.

{

```
"videoUrl": "89026060_v1;90;44100;1"
```

```
}
```

Example of Character string received by client recipient 100R

```
{
```

```
5  "context": "message",
```

```
    "key": "new",
```

```
    "threadId": "50aa977de43be50200000126",
```

```
    "messageId": "50aa97fa9377370200000159",
```

```
    "senderId": "50aa11a4ab55b6020000004c",
```

```
10  "senderInfo": {
```

```
        "fbId": "514969962",
```

```
        "name": "Jonathan Joseph Caras",
```

```
        "picUrl": "http://profile-b.xx.fbcdn.net/hprofile-  
snc6/273765_514969962_1714973208_s.jpg"
```

```
15        },
```

```
    "status": "active",
```

```
    "type": "video",
```

```
    "createdAt": 1355984953,
```

```
    "isHidden": "false",
```

```
20  "isDelivered": "false",
```

```
    "videoUrl":
```

```
"testvsrv.video.glidetalk.com;83;6744802_www.video.glidetalk.com_vs00002.video.glidetalk.com_  
89026060_v1;90;44100;1",
```

```
    "thumbUrl": "http://testvsrv.video.glidetalk.com:83/getthumb?
```

```
25  sid=6744802_www.video.glidetalk.com_vs00002.video.glidetalk.com_89026060_v1&Size=2"
```

```
}
```

Definitions

The embodiments of the present invention may comprise a general-purpose or special-purpose computer system including various computer hardware components, which are discussed in greater detail below. Embodiments within the scope of the present invention also include
5 computer-readable media for carrying or having computer-executable instructions, computer-readable instructions, or data structures stored thereon. Such computer-readable media may be any available media, which is accessible by a general-purpose or special-purpose computer system. By way of example, and not limitation, such computer-readable media can comprise physical storage media such as RAM, ROM, EPROM, flash disk, CD-ROM or other optical disk
10 storage, magnetic disk storage or other magnetic storage devices, or any other media which can be used to carry or store desired program code means in the form of computer-executable instructions, computer-readable instructions, or data structures and which may be accessed by a general-purpose or special-purpose computer system.

In this description and in the following claims, a "computer system" is defined as one or more
15 software modules, one or more hardware modules, or combinations thereof, which work together to perform operations on electronic data. For example, the definition of computer system includes the hardware components of a personal computer, as well as software modules, such as the operating system of the personal computer. The physical layout of the modules is not important. A computer system may include one or more computers coupled via a computer
20 network. Likewise, a computer system may include a single physical device (such as a phone or Personal Digital Assistant PDA) where internal modules (such as a memory and processor) work together to perform operations on electronic data. While any computer system may be mobile, the term "mobile computer system" especially includes laptop computers, notebook computers, cellular telephones, smart phones, wireless telephones, personal digital assistants, portable
25 computers with touch sensitive screens and the like.

In this description and in the following claims, a "network" is defined as any architecture where two or more computer systems may exchange data. The term "network" may include wide area network, Internet local area network, Intranet, wireless networks such as "Wi-fi", virtual private networks, mobile access network using access point name (APN) and Internet. Exchanged data
30 may be in the form of electrical signals that are meaningful to the two or more computer systems. When data is transferred or provided over a network or another communications connection (either hardwired, wireless, or a combination of hardwired or wireless) to a computer system or

computer device, the connection is properly viewed as a computer-readable medium. Thus, any such connection is properly termed a transitory computer-readable medium. Combinations of the above should also be included within the scope of computer-readable media. Computer-executable instructions comprise, for example, instructions and data which cause a general-
5 purpose computer system or special-purpose computer system to perform a certain function or group of functions. The term "server" as used herein, refers to a computer system including a processor, data storage and a network adapter generally configured to provide a service over the computer network. The term "client" as used herein is a computer system which receives a service provided by the server

10 The term "video" refers to capture and display of an image or more than one image optionally in a time sequence. The term "video" includes audio when there is sound accompanying the image or images according to any of the known techniques for combining video and audio information. The terms "video" and "audio-video" are used herein interchangeably. The terms "video" and "audio-video" may include multiple signals such as stereo audio combined with video and/or
15 three dimensional video combined with audio.

The term "message" as used herein refers to an audio-video content or audio accompanying one or more images captured live by a camera or a previously captured image or video.

The term "multicast" as used herein is the delivery of an audio-video message to a group of destination computer systems simultaneously in a single transmission from the source or
20 transmitting computer system.

The term "unicast" as used herein refers to transmitting an audio-video message to a single designated computer system.

The term "broadcast" as used herein refers to transmitting an audio-video message to all possible destinations.

25 The term "upload" as used herein refers to a data file previously stored locally on a client computer system in local storage and copied to storage in a server.

The term "download" as used herein refers to a data file previously stored on a server and copied to a client computer system into local storage.

The term "uniform resource identifier" or "URI" as used herein is a string of characters used to
30 identify a name or a resource and enables interaction with representations of the resource over a

network (typically the World Wide Web) using specific protocols. Schemes specifying a concrete syntax and associated protocols define each URI. URIs can be classified as uniform resource locators (URLs), and/or as uniform resource names (URNs).

The term "character string" or "message block" as used herein includes identifiers of a name
5 and/or location of a network resource, *e.g.* a video message and/or identifiers to one or more client recipients. The character string or message block may include URI, URN and URL or portion thereof. The "character string" may be encoded into binary code transmitted and received in binary code and decoded at the receiver to determine identifiers of the recipient and the video message as applicable.

10 The terms "client transmitter" and "client recipient" as used herein refer to a client computer system for which an example is shown as mobile computer system **100** in Figure 1. The roles of transmitter and recipient referring to one-way communication may be reversible.

The term "alternately" in the context of transmitting and receiving video messages refers to a computer system configured to either transmit or receive but not to both transmit and receive
15 video content simultaneously at the same time.

The term "streaming" as used herein refers to consuming video content while optionally using client storage **101** as temporary cache storage while avoiding saving an accessible copy of the video content in a local file in storage **101** in client computer system **100**.

The term "consuming" in the context of video and/or audio content refers to displaying the video
20 content to the user including the accompanying audio, or in the case of audio content, playing the audio content to the user. The terms "consume", "play" and "display" are used herein interchangeably.

The term "receive" as used herein in the context of receiving a video message and/or video content includes in different embodiments of the present invention: streaming and consuming the
25 video content; and/or copying the video content into local storage **101** and later consuming the video content from the storage **101**.

The term "latency" as used herein refers to the time between a client transmitter begins to transmit a video message and the time when the video message is received and displayed by streaming to the client recipient when the client recipient is available.

The terms "reduced latency or "low latency" are used herein interchangeably and refers in different embodiments to the latency less than six seconds or less than five seconds or less than four seconds or less than three seconds or less than two seconds.

The term "available" refers to a client computer system which is connected to a data communications network over which an embodiment of the present invention is operable and with the client application for performing method **301** running.

The term "unavailable" refers to a client computer system which is not connected to a data communications network over which an embodiment of the present invention is operable or connected to a data communications network **20** but with the client application for performing method **301** running in the background or with the client application not installed or otherwise disabled.

The term "conversation" as used herein refers to sharing one or more messages over a network between two or more people.

The term "thread" in the context of messages is used herein to refer to multiple messages transmitted and received between two or more client computer systems **100** while optionally maintaining the time order of transmission of the messages.

The indefinite articles "a", "an" is used herein, such as "a connection", "a server", a "message" have the meaning of "one or more" that is "one or more connection", "one or more servers" and "one or more messages".

20 Other embodiments of the present invention

Various buttons may be installed on the client computer system for control of the client computer system according to methods as disclosed herein. A button may include a mode when the button is tapped for less than one second duration, then video recording begins and simultaneously transmission begins of the video recording. A second tap may stop the recording and thereby stop transmission and enable reception. Toggling between states of recording/transmission and enabling reception may be performed by successively tapping the button intermittently.

The button may also include a mode in which the button is held or touched for a defined period of time, *e.g.* 2 seconds. Video recording may begin and simultaneous transmission may begin of a video recording. Release of the button may end recording/ transmission and enable receiving of video content. In another mode, the button is slid in a previously defined direction and released

immediately within a previously defined time period. Audio recording (without simultaneous capture of images) and transmission may begin. When the button is slid back to its original position audio recording/transmission may be stopped and receiving is enabled. The button may be held down for a time period, *e.g.* two seconds, while in the slid position for audio
5 recording/transmission only. Releasing the button in the slid position stops audio-recording and transmission.

Various data communications systems are disclosed herein video communications between multiple computer systems configured to transmit and receive video content. One (or more) of the client computer systems when transmitting is a client transmitter and one (or more) of the
10 client computer systems when receiving is a client recipient. The client transmitter is enabled to transmit a video message for display on the client recipient. The client transmitter is configured to establish a connection with a video server, to transmit the video message to the video server. The video message is archived by the video server. A first client computer system may transmit multiple messages to a second client computer system, The multiple messages includes a first
15 message and a second message. The time interval TTX between the beginning of the first message and the end of the second message when transmitted by the client transmitter may be greater than the time interval TRX between the beginning of the first message and the end of the second message when received by the client recipient, so that the client recipient receives the first and the second messages contiguously while transmission of at least one of the multiple
20 messages is ongoing.

Various data communications systems are disclosed herein video communications between multiple computer systems configured to transmit and receive video content. One (or more) of the client computer systems when transmitting is a client transmitter and one (or more) of the client computer systems when receiving is a client recipient. The client transmitter is enabled to
25 transmit a video message for display on the client recipient. The client transmitter is configured to establish a connection with a video server, to transmit the video message to the video server. The video message is archived by the video server. Multiple messages intended for the same client recipient may at least partially overlap in time during respective transmission of the multiple messages from multiple client transmitters. The multiple messages are received at the
30 client recipient contiguously and shifted in time while the transmission of at least one of the messages from at least one of the client transmitters is ongoing.

Various data communications systems are disclosed herein video communications between multiple computer systems configured to transmit and receive video content. One (or more) of the client computer systems when transmitting is a client transmitter and one (or more) of the client computer systems when receiving is a client recipient. The client transmitter is enabled to
5 transmit a video message for display on the client recipient. The client transmitter is configured to establish a connection with a video server, to transmit the video message to the video server. The video message is archived by the video server. One or more of the client computer systems may be controlled by a processor configured to receive a message by streaming from the video server, to process the received message and in response to the received message to transmit a
10 response message to other client computer systems sharing the same thread. If the client transmitter detects or is otherwise aware of sub-optimal network conditions, the video message may be reduced into a video message of reduced information content so that the second video message may be received/consumed when the transmission from the client transmitter of the video message is still ongoing. Subsequent to the original transmission of the video message of
15 reduced information content, the original video message of higher quality may be restored or replaced for subsequent reception/consumption by the client recipient.

Various data communications systems are disclosed herein including a video communications between multiple client computer systems configured to transmit and receive video content. A client computer system is configured to establish a connection with a video server, to transmit a
20 transmit video message to the video server and to receive a receive video message from the video server. The transmit video message and the receive video message are archived by the video server. If the receive message begins to be received while the transmit video message is being transmitted, then, the receive message is stored locally at least in part in local storage in the client computer system for display to the user of the client computer system subsequent to the
25 transmission of the transmit video message. Otherwise, if the receive message is received not overlapping the transmission of the transmit message then the receive message is displayed to the user as a stream from the video server while avoiding storage of the receive message in local storage. in the client computer system.

A user interface is provided herein of a client computer system connectible to a data
30 communications system. The user interface allows the user to experience selectably either: transmitting a transmit video message or consuming a receive video message. The transmit video message may include an image frame being captured simultaneously during the transmission . If

a receive message is being consumed during the capture of image frames or during the transmission/recording of the transmit message, the receive message may be stored at least in part in local storage attached to the client computer system. The receive message may be displayed to the user when the transmission of the transmit message is complete by retrieving the
5 receive message from the local storage. If an incoming message is being consumed a transmit message may be transmitted in the background of the client computer system at the same time by retrieving the transmit message from local storage.

Although selected embodiments of the present invention have been shown and described, it is to be understood the present invention is not limited to the described embodiments.

CLAIMS

1. A system for providing multimedia messaging, the system comprising:
at least one processor configured to:
receive, at an intermediary location in a network, streaming multimedia data from a transmitting messaging client without an indication of an identity of any receiving messaging client;
receive, at the intermediary location, after the streaming of the multimedia data begins and before the streaming of multimedia data ends, an identification of the receiving messaging client; and
provide the multimedia data to the receiving messaging client.
2. The system of claim 1, wherein the at least one processor is configured to send the multimedia data to the receiving messaging client in response to a received request for the multimedia data.
3. The system of claim 1, wherein the at least one processor includes at least one server.
4. The system of claim 1, wherein the at least one processor is configured to send to the transmitting messaging client a token, the token identifying a predetermined storage location reserved on the intermediary location for the streaming multimedia data before receiving the streaming multimedia data.
5. The system of claim 1, wherein the at least one processor includes at least one multimedia server configured to receive the streaming multimedia data from the transmitting messaging client and at least one management server configured to receive the identification of the receiving messaging client.
6. The system of claim 1, wherein the identification of the receiving messaging client is received as part of a message including an identifier associated with the streaming multimedia data.

7. The system of claim 1, wherein the identification of the receiving messaging client includes a group identifier associated with more than one receiving messaging client.
8. The system of claim 1, wherein the at least one processor is configured to send the multimedia data to the receiving messaging client from the beginning of the streaming multimedia data.
9. The system of claim 1, wherein the at least one processor is configured to provide the multimedia data to the receiving messaging client while receiving the streaming multimedia data from the transmitting messaging client.
10. A computer-implemented method for providing multimedia messaging, the method comprising:
 - receiving, at an intermediary location in a network, streaming multimedia data from a transmitting messaging client without an indication of an identity of any receiving messaging client;
 - receiving, at the intermediary location, after the streaming of the multimedia data begins and before the streaming of multimedia data ends, an identification of the receiving messaging client; and
 - providing the multimedia data to the receiving messaging client.
11. The computer-implemented method of claim 10, further comprising:
 - establishing a connection with the transmitting messaging client before receiving the streaming multimedia data; and
 - providing to the transmitting messaging client an identifier associated with the streaming multimedia data to be received.
12. The computer-implemented method of claim 10, wherein the identification of the receiving messaging client is received as part of a message including an identifier associated with the streaming multimedia data.

13. The computer-implemented method of claim 10, further comprising:
sending to the transmitting messaging client a token, the token identifying a predetermined storage location reserved on the intermediary location for the streaming multimedia data, before receiving the streaming multimedia data.
14. The computer-implemented method of claim 10, wherein the identification of the receiving messaging client includes a group identifier associated with more than one receiving messaging client.
15. The computer-implemented method of claim 10, wherein sending the multimedia data to the receiving messaging client includes sending the multimedia data to the receiving messaging client from the beginning of the streaming multimedia data.
16. The computer-implemented method of claim 10, wherein sending the multimedia data to the receiving messaging client comprises sending the multimedia data to the receiving messaging client while receiving the streaming multimedia data from the transmitting messaging client.
17. A non-transitory computer readable medium including instructions that, when executed by at least one processor, cause the at least one processor to perform operations comprising:
sending, from a transmitting messaging client to an intermediary location in a network, streaming multimedia data, without an indication of an identity of any receiving messaging client; and
sending, from the transmitting messaging client to the intermediary location, after the streaming of the multimedia data begins and before the streaming of multimedia data ends, an identification of the receiving messaging client.
18. The non-transitory computer readable medium of claim 17, wherein the operations further comprise:
connecting to the intermediary location before sending the streaming multimedia data; and

receiving from the intermediary location an identifier associated with the streaming multimedia data.

19. The non-transitory computer readable medium of claim 17, wherein the operations further comprise sending to the intermediary location a request for a predetermined storage location reserved on the intermediary location for the streaming multimedia data.

20. The non-transitory computer readable medium of claim 17, further comprising receiving from the intermediary location a token, the token identifying a predetermined storage location reserved on the intermediary location for the streaming multimedia data before sending the streaming of multimedia data to the intermediary location.

21. The non-transitory computer readable medium of claim 20, wherein the operations further comprise sending to the predetermined storage location the streaming multimedia data.

22. The non-transitory computer readable medium of claim 17, wherein the intermediary location includes at least one server.

23. A system for providing multimedia messaging, the system comprising:
at least one processor configured to:

send, from an intermediary location in a network, to a transmitting messaging client, a token, the token identifying a predetermined storage location reserved on the intermediary location for a streaming multimedia data, wherein the token is sent before receiving the streaming multimedia data;

receive, at the intermediary location in the network, from the transmitting messaging client, the token and a streaming multimedia data; and

provide the multimedia data to a receiving messaging client upon receiving the token from the receiving messaging client.

24. A computer-implemented method for providing multimedia messaging, the method comprising:

sending to a transmitting messaging client a token, the token identifying a predetermined storage location reserved at an intermediary location in a network for streaming multimedia data, wherein the token is sent before receiving the streaming multimedia data;

receiving, at the intermediary location in the network, streaming multimedia data from the transmitting messaging client; and

providing the multimedia data to a receiving messaging client upon receiving the token from the receiving messaging client.

25. A non-transitory computer readable medium including instructions that, when executed by at least one processor, cause the at least one processor to perform operations comprising:

receiving, from an intermediary location in a network, a token, the token identifying a predetermined storage location reserved on the intermediary location for streaming multimedia data;

sending, from a transmitting messaging client to the intermediary location in a network, the token and the streaming multimedia data.