

CLAIMS:

1. A system for providing an augmented reality, a virtual reality, and/or a mixed reality experience to a user, wherein the user views a real-world environment through a first display and a second display, the system comprising:

a wearable visualization device comprising the first display, wherein the first display is configured to display a first layer of virtual features;

a fixed visualization device comprising the second display, wherein the second display is configured to display a second layer of virtual features; and

a processor configured to generate the first layer of virtual features and the second layer of virtual features, and wherein the processor is configured to operatively communicate with the wearable visualization device and the fixed visualization device to coordinate presentation of the first layer of virtual features and the second layer of virtual features.

2. The system of claim 1, wherein the first display is a transparent or semi-transparent display and is configured to enable the user, when wearing the wearable visualization device, to view the second display through the first display.

3. The system of claim 1, wherein the second display comprises a transparent light emitting diode display or a transparent organic light emitting diode display.

4. The system of claim 1, wherein the second display is coupled to a passenger ride vehicle.

5. The system of claim 1, wherein the processor is configured to coordinate the presentation of the first layer of virtual features and the second layer of virtual features with an element associated with an attraction at an amusement park.

6. The system of claim 1, wherein the first layer of virtual features comprises a virtual image of an object within a cabin of a passenger ride vehicle, and the second layer of virtual features comprises a virtual image of a feature on a window of the passenger ride vehicle.
7. The system of claim 1, wherein the first layer of virtual features comprises a virtual image of an object external to a cabin of a passenger ride vehicle.
8. The system of claim 1, comprising one or more cameras or sensors configured to monitor the real-world environment to facilitate coordination of the presentation of the first layer of virtual features and the second layer of virtual features.
9. A system for providing an augmented reality, a virtual reality, and/or a mixed reality experience to a user, the system comprising:
 - a passenger ride vehicle configured to traverse a path during a ride in an amusement park;
 - a fixed visualization device comprising a transparent display coupled to the passenger ride vehicle, wherein the fixed visualization device is configured to overlay virtual features onto a real-world environment that is visible through the transparent display; and
 - a processor configured to generate the virtual features and to coordinate presentation of the virtual features with ride effects of the ride.
10. The system of claim 9, comprising a wearable visualization device comprising another transparent display that is configured to display additional virtual features, wherein the wearable visualization device is configured to be worn by the user within the passenger ride vehicle during the ride.

11. The system of claim 10, wherein the processor is configured to coordinate presentation of the additional virtual features with the presentation of the virtual features and the ride effects.
12. The system of claim 9, wherein the transparent display comprises a transparent light emitting diode display or a transparent organic light emitting diode display.
13. The system of claim 9, wherein the processor is configured to coordinate the presentation of the virtual features with the ride effects by instructing the fixed visualization device to overlay the virtual features at a predetermined time during a ride cycle of the ride.
14. The system of claim 9, wherein the virtual features comprise cracks, condensation, charring, rain drops, snow, or a combination thereof.
15. The system of claim 9, wherein the transparent display is configured to be opaque when energized, thereby providing an illusion that a cabin of the passenger ride vehicle is enclosed by solid walls.
16. A method for providing an augmented reality, a virtual reality, and/or a mixed reality experience to a user, the method comprising:
 - generating, using a processor, a first layer of virtual features and a second layer of virtual features;
 - displaying at a first display time, in response to instructions from the processor, the first layer of virtual features on a first display, wherein the first display is disposed within a wearable visualization device; and
 - displaying at a second display time, in response to instructions from the processor, the second layer of virtual features on a second display, wherein the second display is

disposed within a fixed visualization device that is physically separate from the wearable visualization device.

17. The method of claim 16, wherein the second display comprises a transparent display coupled to a passenger ride vehicle.

18. The method of claim 16, wherein the first display time and the second display time result in a coordinated display of the first layer of virtual features and the second layer of virtual features.

19. The method of claim 16, wherein the first display time and the second display time result in a coordinated display of the first layer of virtual features and the second layer of virtual features with a ride effect of a ride in an amusement park.

20. The method of claim 16, comprising receiving, at the processor, signals indicative of a real-world environment from one or more cameras or sensors, wherein the processor utilizes the received signals to determine the first display time and the second display time to facilitate coordination of presentation of the first layer of virtual features and the second layer of virtual features with elements in the real-world environment.