What is claimed is:

1. A cutting apparatus that cuts, along cutting lines, an object to be cut in which a plurality of separating elements are connected together by means of connecting portions, and in which the cutting lines within the separating elements that are mutually adjacent to each other are set on mutually different straight lines, comprising:

a cutting table on which the object to be cut is held by means of suction;

a cutting mechanism that, using a blade, cuts the object to be cut that is being held on the cutting table; and

a transporting mechanism that transports the object to be cut to the cutting table, wherein

the cutting table includes a first table suctioning portion that, regarding the mutually adjacent separating elements, suctions one of the separating elements, and a second table suctioning portion that is independent of the first table suctioning portion and suctions the other of the separating elements, and

the transporting mechanism has a transporting suction portion that suctions only the one or only the other one of the mutually adjacent separating elements.

2. The cutting apparatus according to Claim 1, wherein, in a state in which the connecting portions have been cut by the cutting mechanism so that the mutually adjacent separating elements have been separated from each other, the cutting table stops the suctioning of the separating elements by either the first table suctioning portion or the second table suctioning portion, and

the transporting mechanism firstly suctions the separating element whose suctioning by the cutting table has been stopped, and then aligns the cutting lines of the

mutually adjacent separating elements so that these are on the same straight lines.

3. The cutting apparatus according to Claim 1 or Claim 2, wherein the transporting mechanism comprises:

a first transport suctioning portion that suctions the one of the separating elements; and

a second transport suctioning portion that suctions the other of the separating elements.

4. A cutting apparatus that cuts, along cutting lines, an object to be cut in which a plurality of separating elements are connected together by means of connecting portions, and in which the cutting lines within the separating elements that are mutually adjacent to each other are set on mutually different straight lines, comprising:

a cutting table on which the object to be cut is held by means of suction; and

a cutting mechanism that, using a blade, cuts the object to be cut that is being held on the cutting table, wherein

the cutting table includes a first table suctioning portion that, regarding the mutually adjacent separating elements, suctions one of the separating elements, and a second table suctioning portion that is independent of the first table suctioning portion and suctions the other of the separating element, and

the plurality of separating elements are arranged in rows in the direction in which they will be cut by the blade, and their placement modes are divided into at least two groups, and the cutting lines of the separating elements of one group are positioned on the same straight lines, while the cutting lines of the separating elements of another group are positioned on the same straight lines, and wherein

the first table suctioning portion suctions the separating elements of the one group, and

the second table suctioning portion suctions the separating elements of the other group.

5. A method of manufacturing a cut product using the cutting apparatus according to any one of Claim 1 through Claim 4.