PCT WORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification 6 : F02F 1/20, F16J 10/04 — A1

(11) International Publication Number: **WO 98/53192**

(43) International Publication Date: 26 November 1998 (26.11.98)

(21) International Application Number: PCT/DK98/00184

(22) International Filing Date: 11 May 1998 (11.05.98)

(30) Priority Data:
0568/97 16 May 1997 (16.05.97) DK

(71) Applicant *(for all designated States except US)*: MAN B & W DIESEL A/S [DK/DK]; Teglholmsgade 41, DK–2450 Copenhagen SV (DK).

(72) Inventors; and
(75) Inventors/Applicants *(for US only)*: ANDERSEN, Erling, Bredal [DK/DK]; Sankt Ibs Allé 90, DK–2630 Taastrup (DK). ØSTERGAARD, Allan [DK/DK]; Grønnegården 327, DK–2670 Greve (DK).

(74) Agents: INDAHL, Peter et al.; Internationalt Patent-Bureau, 23 Høje Taastrup Boulevard, DK–2630 Taastrup (DK).

(81) Designated States: AL, AM, AT, AT (Utility model), AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, CZ (Utility model), DE, DE (Utility model), DK, DK (Utility model), EE, EE (Utility model), ES, FI, FI (Utility model), GB, GE, GH, GM, GW, HU, ID, IL, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SK (Utility model), SL, TJ, TM, TR, TT, UA, UG, US, UZ, VN, YU, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG).

Published
With international search report.

(54) Title: A CYLINDER LINER FOR AN INTERNAL COMBUSTION ENGINE OF THE DIESEL TYPE

(57) Abstract

A cylinder liner (1) for an internal combustion engine of the diesel type has at least one inwardly open oil groove with external supply of lubricating oil and at least a first and a second group of inwardly open recesses, each group having at least two recesses (14) which have a discontinuous extent in the circumferential direction of the liner. The recesses (14) in the groups are located in the top 15 per cent of the length of the running surface (6) and the recesses (14) in the different groups are arranged with mutual separation in the longitudinal direction of the liner (1), and with a mutual arrangement in the circumferential direction of the liner (1).

