

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
27 December 2001 (27.12.2001)

PCT

(10) International Publication Number
WO 01/98589 A2

(51) International Patent Classification⁷: **E01C 13/08**

(21) International Application Number: PCT/CA01/00922

(22) International Filing Date: 21 June 2001 (21.06.2001)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
09/598,149 21 June 2000 (21.06.2000) US

(71) Applicant (for all designated States except US): **FIELD-TURF HOLDINGS INC.** [CA/CA]; 5050 Pare Street, Suite 280, Montreal, Québec H4P 1P3 (CA).

(72) Inventor; and

(75) Inventor/Applicant (for US only): **PREVOST, Jean** [CA/CA]; 6763 Louis Pasteur, Côte St-Luc, Québec H4W 2X1 (CA).

(74) Agent: **SWABEY OGILVY RENAULT**; Suite 1600, 1981 McGill College Avenue, Montréal, Québec H3A 2Y3 (CA).

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW.


(84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).

Published:

— without international search report and to be republished upon receipt of that report

[Continued on next page]

(54) Title: SYNTHETIC GRASS WITH RESILIENT GRANULAR TOP SURFACE LAYER



(57) Abstract: A synthetic grass assembly for installation on a supporting substrate comprising a pile fabric with a flexible sheet backing (1) and a plurality of upstanding synthetic ribbons (2) of a selected length, the ribbons (2) extending upwardly from an upper surface of the backing (1), an infill layer (3) of particulate material disposed interstitially between the upstanding ribbons (2) upon the upper surface of the backing (1) with a depth less than the length of the ribbons, the particulate material selected from the group consisting of hard and resilient granules. The infill layer (3) comprises a bottom course (5) of intermixed hard and resilient granules of substantially identical size distribution, disposed upon the top surface of the backing (1), and a top course (6) substantially exclusively of resilient granules disposed upon the bottom course (5), an upper portion of the synthetic ribbons (2) extends upwardly from a top surface of the top course (6).



For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.