

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
17 July 2003 (17.07.2003)

PCT

(10) International Publication Number
WO 03/058845 A3

(51) International Patent Classification⁷: **H04B 7/08**,
H04L 25/03

(21) International Application Number: PCT/US02/41743

(22) International Filing Date:
31 December 2002 (31.12.2002)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
10/039,072 2 January 2002 (02.01.2002) US

(71) Applicant: **INTEL CORPORATION** [US/US]; 2200
Mission College Boulevard, Santa Clara, CA 95052 (US).

(72) Inventors: **YELLIN, Daniel**; 71 Hertz Street, 43353
Raanana (IL). **EHRENWALD, Liron**; 23 Smuts Avenue,
Tel Aviv 62009 (IL).

(74) Agent: **TROP, Timothy, N.**; Trop, Pruner & Hu, P.C.,
8554 Katy Freeway, Suite 100, Houston, TX 77024 (US).

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU,
AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU,
CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH,
GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC,
LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW,
MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SD, SE, SG,
SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, UZ, VN, YU,
ZA, ZM, ZW.


(84) Designated States (*regional*): ARIPO patent (GH, GM,
KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),
Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE,
ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, SI, SK,
TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ,
GW, ML, MR, NE, SN, TD, TG).

Published:
— with international search report

(88) Date of publication of the international search report:
4 December 2003

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: ROBUST LOW COMPLEXITY MULTI-ANTENNA ADAPTIVE MINIMUM MEAN SQUARE ERROR EQUALIZER



(57) Abstract: Over a channel, a signal including a desired portion associated with a desired channel and an undesired portion mixed with said desired portion may be received. Based on prior knowledge and/or empirical estimation of the desired channel and an empirical estimate of the signal cross-covariance, the desired portion from the received signal may be recovered by adaptively equalizing the channel. In one embodiment, a receiver (10), such as a mobile device (e.g., a cellular phone) includes a processor (75) operably coupled to a communication interface (15) including at least two antennas (55) to receive the signal. The receiver (10) may further include a MODEM (70) that may be operably coupled to the processor (75), that includes an adaptive equalizer (86) capable of detecting the signal in the presence of co-channel interference from several independent sources, inter-symbol interference and fading, for recovering the desired portion in a cellular environment with time division multiple access (TDMA) to enable digital transmission of the signal. Thus, a blind adaptive space-time equalization on the signal based on minimum mean square error (MMSE) may be provided.