

(51) International Patent Classification:
G06F 13/16 (2006.01)(21) International Application Number:
PCT/IB2014/063189(22) International Filing Date:
17 July 2014 (17.07.2014)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
2013902678 18 July 2013 (18.07.2013) AU
2013904532 25 November 2013 (25.11.2013) AU(71) Applicant: SYNAPTIC LABORATORIES LIMITED
[MT/MT]; Synaptic Laboratories Limited, 13 Nadur
Heights, Nadur Gozo, NDR-1390 (MT).(72) Inventor: GITTINS, Benjamin; Synaptic Laboratories
Limited, 13 Nadur Heights, Nadur Gozo, NDR-1390 (MT).(81) Designated States (unless otherwise indicated, for every
kind of national protection available): AE, AG, AL, AM,
AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY,
BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM,
DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT,HN, HR, HU, ID, IL, IN, IR, IS, JP, KE, KG, KN, KP, KR,
KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME,
MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ,
OM, PA, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SA,
SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM,
TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM,
ZW.(84) Designated States (unless otherwise indicated, for every
kind of regional protection available): ARIPO (BW, GH,
GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, SZ, TZ,
UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU, TJ,
TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK,
EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV,
MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM,
TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW,
KM, ML, MR, NE, SN, TD, TG).

Declarations under Rule 4.17:

— as to the identity of the inventor (Rule 4.17(i))

Published:

— without international search report and to be republished
upon receipt of that report (Rule 48.2(g))

(54) Title: COMPUTING ARCHITECTURE WITH PERIPHERALS




FIGURE 1

(57) Abstract: A shared memory computing architecture (300) has M interconnect masters (350, 351, 352, 353, 354), one interconnect target (370), and a timeslot based interconnect (319). The interconnect (319) has a unidirectional timeslot based interconnect (320) to transport memory transfer requests with T timeslots and a unidirectional timeslot based interconnect (340) to transport memory transfer responses with R timeslots. For each of the R timeslots, that timeslot corresponds to one memory transfer request timeslot and starts at least L clock cycles after the start time of that corresponding memory request timeslot. The value of L is ≥ 3 and $< T$. Interconnect target (370) is connected to interconnect (319). Each interconnect master (350, 351, 352, 353, 354) is connected to interconnect (319).