

☒ Description : paged3... to paged7...
☒ Claim(s) : paged15... to paged18...
☐ Drawing(s) : paged to paged
☒ Abstract : paged19... to paged

DISK DRIVE HEAD ASSEMBLY

DESCRIPTION

5 This invention relates to data recording disk drives, and more particularly to a head assembly for use in such disk drives.

10 Disk drives, also called disk files, are information storage devices that use a rotatable disk with concentric data tracks containing the information, a head or transducer for reading and/or writing data onto the various tracks, and an actuator connected to a carrier for the head for moving the head to the desired track and maintaining it over the track centerline during read or write operations. There are typically a plurality of disks separated by spacer rings and stacked on
15 a hub that is rotated by a disk drive motor. A housing supports the drive motor and head actuator and surrounds the head and disk to provide a substantially sealed environment for the head-disk interface.

20 In conventional magnetic recording disk drives, the head carrier is an air-bearing slider that rides on a bearing of air above the disk surface when the disk is rotating at its operational speed. The slider is maintained next to the disk surface by a relatively fragile suspension that connects the slider to the actuator. The slider is either biased toward the disk surface by a small spring force from the suspension, or is "self-loaded" to the disk surface by means of a
25 "negative-pressure" air-bearing surface on the slider. Contact start/stop (CSS) disk drives operate with the slider in contact with the disk surface during start and stop operations when there is insufficient disk rotational speed to maintain the air bearing. In contrast to CSS
30 disk drives, "load/unload" disk drives mechanically unload the slider from the disk when the power is turned off, typically by means of a ramp which contacts the suspension when the actuator is moved to a predetermined location, and then load the slider back to the disk when the disk has reached a speed sufficient to generate the air bearing.
35 Both types of disk drives maintain a relatively thin lubricant film on the disk surface to prevent damage to the head and disk caused by any contact between the head and disk.

It has been known since the early days of magnetic recording that minimizing the head-disk spacing is desirable because the amplitude of the read signal from the disk increases with decreasing head-disk spacing. Higher recording densities can thus be achieved. In conventional, commercially available air-bearing disk drives the minimum achievable head-disk spacing is typically between 1000-2000 Angstroms. In addition, this spacing is not maintained constant, but varies with disk radius because the air velocity beneath the air-bearing slider is directly proportional to the relative velocity of the disk beneath the slider. To both minimize the head-disk spacing and to maintain it constant with disk radius, liquid bearings have been proposed as possible alternatives to the conventional air bearing at the head-disk interface in magnetic recording disk drives. For example, in assignee's pending application, U.S. Serial No. 264,604, filed October 31, 1988, and published May 9, 1990, as European published application EP 367510, a disk drive is described which uses a continuously recirculating, low-viscosity liquid lubricant which is maintained as a relatively thick layer on the disk, and a transducer carrier that has triangular-shaped feet to plow through the low-viscosity liquid layer. The EP 367510 reference suggests that a head-disk spacing of approximately 500 Angstroms can be obtained with a liquid film having a thickness of approximately 10,000 Angstroms. Similarly, in U.S. Patent 5,097,368 assigned to Conner Peripherals, filed December 20, 1989, and issued March 17, 1992, a recirculating liquid-bearing disk drive is described in which a head-disk spacing of approximately 300-700 Angstroms can be achieved at the operating speed of a conventional air-bearing disk drive if a load of approximately 45 grams is applied to force the head carrier against the liquid bearing (see Fig. 6 of the '368 patent).

In U.S. Patent 4,901,185 assigned to Toshiba, filed in the U.S. on July 10, 1986, and issued February 13, 1990, the problems of minimizing and maintaining constant the head-disk spacing are addressed by a disk drive which uses a combined air and liquid bearing to support the transducer carrier. An air-bearing slider provides support for the forward portion of the carrier while the rear portion, which includes the magnetic head, contacts and is supported by a conventional liquid lubricant film. This patent suggests that a head-disk spacing of less than approximately 800 Angstroms can be achieved using a lubricant film of greater than approximately 200 Angstroms thickness.

More recently, in assignee's U.S. Patent 5,202,803, filed July 2, 1991, and issued April 13, 1993, a disk drive is described in which a conventional nonrecirculating, high-viscosity lubricant film is maintained on the disk and the transducer carrier is a modified three-rail air-bearing slider that has a rear "ski" pad. When the disk drive reaches operating speed, the air-bearing effect of the slider rails provides the primary support for the carrier, while the rear ski pad, which supports the magnetic head, contacts the lubricant film. The thickness of the lubricant film on the disk is approximately 20-100 Angstroms, which would also be the approximate head-disk spacing between the rear pad and the disk surface, assuming a perfectly smooth disk surface.

While liquid-bearing disk drives present the opportunity for closer head-disk spacing than air-bearing disk drives, they also present several difficulties. The carrier must provide a low-static friction ("stiction") interface when the carrier is at rest on the disk because liquid-bearing disk drives have thicker lubricant films and smoother disks than air-bearing disk drives. The carrier must also be designed to create small drag through the liquid film and to minimize liquid depletion from the disk. In addition, the carrier must be able to perform adequately over a wide range of relative carrier-disk velocities which occur at different disk radii.

Accordingly the invention provides a head assembly for a disk drive comprising: a transducer for writing data to or reading data from the disk; and a carrier supporting the transducer and having a disk side, a front end and a trailing end, the carrier comprising an air-bearing pad on the disk side near the front end, an air-bearing pad on the disk side near the trailing end, and a nonair-bearing surface separating the front and rear air-bearing pads. Typically the transducer is located near the trailing end of the carrier.

Such a head assembly provides an improved head-disk interface that takes advantage of an air bearing to avoid the problems associated with liquid bearings, yet provides a head-disk spacing that is significantly less than achievable even by a liquid bearing, and is less sensitive to variation with disk radius and to variations in head-carrier manufacturing parameters.

This Sheet Has Been Replaced



In a preferred embodiment, the front air-bearing pad comprises a pair of air-bearing pads generally equally spaced about the longitudinal centerline of the carrier, having a length-to-width ratio of between 0.25 and 2; a higher ratio would not produce enough lift, a lower ratio might lead to problems with roll stiffness and manufacturing tolerances. It is also preferred that the air-bearing surfaces of all the pads are substantially coplanar, and the rear air-bearing pad is located on the longitudinal centerline of the carrier.

In general it is advantageous for the surface area of the front air-bearing pad or pads to be greater than the surface area of the rear air-bearing pad. This ensures that the carrier is pitched up during operation of the disk drive. It is also beneficial for the front air-bearing pad or pads to have a leading edge with an essentially convex curvature, to minimise air drag and to push away any particulate contamination on the disk surface.

In a preferred embodiment the rear air-bearing pad has a leading edge wider than its trailing edge. This produces low drag, and also helps to avoid depleting liquid in the lubricant layer on the disk. In order to achieve this affect over the whole disk surface, preferably the sides of the rear air-bearing pad connecting the leading edge with the trailing edge define an angle which is greater than the maximum amount of skew of the carrier relative to data tracks on a disk when the carrier is operational in a disk drive. It is further preferred that the leading edge of the rear air-bearing pad is nonparallel with its trailing edge, to compensate for the skew of the slider to minimize the flying height variation from the disk inside diameter to outside diameter.

In a preferred embodiment, the front and rear ends of the carrier are generally parallel ridge sections oriented transversely to the longitudinal centerline of the carrier and the nonair-bearing surface separating the ridge sections is recessed from the ridge sections. Having the nonair-bearing section recessed prevents it from producing any lift. Generally the nonair-bearing surface extends across substantially the entire width of the carrier. It is also possible for the front ridge section to comprise a pair of laterally spaced-apart ridge areas, each ridge area supporting an air-bearing pad. Preferably

This Sheet Has Been Replaced



the front ridge section includes a tapered surface, which better directs air onto the front air-bearing pad or pads.

It is also possible for the head assembly to include a strut located on at least one front air-bearing pad for supporting the front of the carrier substantially off the lubricant film when the carrier is on the disk (typically if there are two front air-bearing pads, there is a strut on each of them). The struts serve to reduce start up friction and low velocity drag, as well as providing increased lift. Another possible way of reducing start up friction is to include a carbon film on at least one front air-bearing pad for supporting the front of the carrier substantially off the lubricant film when the carrier is on the disk.

Such a head assembly can be incorporated into a disk drive, also including at least one data disk having a lubricant film thereon; a motor connected to the disk for rotating the disk; an actuator for moving the head assembly generally radially across the disk so the transducer may access different regions of data on the disk; means connecting the head assembly to the actuator for maintaining the head assembly near the disk; and means for supporting the motor and actuator.

It is preferred that the connecting means includes a suspension attached to the side of the carrier opposite the disk for biasing the carrier toward the disk in order to maintain the air-bearing pads of the slider near the disk during operation of the disk drive. Preferably the head assembly-to-actuator connecting means includes means for providing generally gimbaled movement of the carrier, whereby the carrier may pitch and roll during operation of the disk drive. It is also preferred that the disk drive also includes means attached to the motor and actuator supporting means for unloading the carrier from the disk when the disk drive is not operating.

Typically in operation the pad near the trailing end of the head assembly supports the trailing end on the lubrication film when the carrier is near the inside diameter portion of the data region on the disk and generates an air-bearing support for the trailing end when the carrier is near the outside diameter portion of the data region on the disk. The trailing end pad generates an air bearing to partially support

This Sheet Has Been Replaced




the trailing end when the trailing end pad is in contact with the lubricant film on the disk when the disk is rotating at its operational speed. Generally the lubricant film is liquid.

5 In one preferred embodiment, the disk drive is a contact start/stop disk drive and further comprises a strut located on the front air-bearing pad for supporting the front of the carrier substantially off the lubricant film when the disk drive is stopped. In another preferred embodiment, the disk drive is a contact start/stop disk drive
10 and further comprises a carbon film located on the front portion of the front air-bearing pad for supporting the front of the carrier substantially off the lubricant film when the disk drive is stopped.

15 Thus a disk drive having an improved head-disk interface is provided by a transducer carrier that is essentially a low-flying, air-bearing slider designed to also function in contact and near contact with the lubricant film on the disk. The slider has a front air-bearing surface in the form of a pair of air-bearing pads, a rear centrally-located air-bearing pad, and a central nonair-bearing surface that
20 separates the front and rear air-bearing pads. The two front pads have a surface area greater than that of the rear pad and thus provide a positive pitch up of the slider. This causes the rear pad to also be pitched up. This pitch, coupled with a step taper at the rear pad, permits air to flow beneath the rear pad to generate an air bearing in
25 the rear portion of the slider. The presence of the central nonair-bearing region eliminates any lift in the central part of the slider, which allows for tight tolerances at the low-flying height. The flying height of the rear pad of the slider above the disk is controlled by the width of the rear air-bearing pad. The rear pad has its leading edge
30 wider than its trailing edge so that it can withstand contact with the lubricant film on the disk, typically at the lower disk velocities near the disk inside diameter, without generating unacceptable drag forces or depleting the lubricant. The rear pad also has a skewed leading edge that compensates for skew of the slider to minimize the flying height
35 variation from the disk inside diameter to outside diameter. In the preferred embodiment, the disk drive is a load/unload disk drive so that, under normal conditions, the slider does not contact the disk when the disk is not rotating.

This Sheet Has Been Replaced



In other words, there is provided a carrier supporting the transducer and having a disk side, a front end, and a trailing end, the carrier comprising an air-bearing pad on the disk side near the front end for generating an air-bearing support for the front end when the disk is rotating at its operational speed, and a pad on the disk side near the trailing end for supporting the trailing end on the liquid film when the carrier is near the inside diameter portion of the data region on the disk and for generating an air-bearing support for the trailing end when the carrier is near the outside diameter portion of the data region on the disk.

Various embodiments of the invention will now be described in detail by way of example, with reference to the following drawings:

Fig. 1 is a view in section of a schematic of a disk drive;

Fig. 2 is an open top view of the disk drive depicted schematically in Fig. 1;

Fig. 3 is a plan view of the bottom or disk side of a preferred embodiment of the head assembly of the present invention;


Fig. 4 is a sectional view of the slider-disk interface of the head assembly of Figure 3, illustrating the front and rear air-bearing pads and the intermediate nonair-bearing surface;

Figs. 5A-5E are sectional views of the head assembly illustrating sequential steps in its fabrication; and

Figs. 6, 7, and 8 are plan views of the disk sides of alternative embodiments of the head assembly.

Referring first to Fig. 1, there is illustrated in sectional view a schematic of the disk drive. The disk drive comprises a base 10 to which are secured a disk drive motor 12 and an actuator 14, and a cover 11. The base 10 and cover 11 provide a substantially sealed housing for the disk drive. Typically, there is a gasket 13 located between base 10 and cover 11 and a small breather port (not shown) for equalizing pressure between the interior of the disk drive and the outside environment. This type of disk drive is described as being substantially sealed since the drive motor 12 is located entirely within the housing and there is no external forced air supply for cooling the interior components. A magnetic recording disk 16 is connected to drive motor 12 by means of hub 18 to which it is attached for rotation by the drive motor 12. A thin continuous film 50 of a relatively high-

This Sheet Has Been Replaced



viscosity lubricant is maintained on the surface of disk 16. In the preferred embodiment, the lubricant is a conventional perfluoropolyether (PFPE) disk lubricant, such as Demnum SP brand from Daikin, and is formed to a thickness of approximately 40 Angstroms. A

5 read/write head or transducer 42 is formed on the trailing end of an air-bearing slider 20. Transducer 42 may be an inductive read and write transducer or an inductive write transducer with a magnetoresistive (MR) read transducer formed by thin film deposition techniques as is known in the art. The slider 20 is connected to the actuator 14 by means of a

10 rigid arm 22 and a suspension 24, the suspension 24 providing a biasing force which urges the slider 20 onto the surface of the recording disk 16. During operation of the disk drive, the drive motor 12 rotates the disk 16 at a constant speed, and the actuator 14, which is typically a linear or rotary voice coil motor (VCM), moves the slider 20 generally

15 radially across the surface of the disk 16 so that the read/write head may access different data tracks on disk 16.

Fig. 2 is a top view of the interior of the disk drive with the cover 11 removed, and illustrates in better detail the suspension 24

20 which provides a force to the slider 20 to urge it toward the disk 16. The suspension may be a conventional type of suspension such as the well-known Watrous suspension, as described in U.S. Patent 4,167,765 assigned to IBM. This type of suspension also provides a gimbaled attachment of the slider which allows the slider to pitch and roll as it

25 rides on the air bearing. In the preferred embodiment of the disk drive, a load/unload ramp 30 is mounted to the base 10. Ramp 30 contacts suspension 24 and lifts the slider 20 away from the disk 16 when the actuator 14 rotates the slider 20 toward the disk outside diameter when the disk drive is powered down. Examples of conventional

30 types of load/unload ramps are described in U.S. Patents 3,984,873 assigned to Information Storage Systems, Inc. (see Fig. 5), and 5,027,241 assigned to Quantum Corporation. The data detected from disk 16 by the transducer 42 is processed into a data readback signal by signal amplification and processing circuitry in the integrated circuit

35 chip 15 located on arm 22. The signals from transducer 42 travel via flex cable 17 to chip 15, which sends its output signals via cable 19.

The bottom or disk side of slider 20 is shown in Fig. 3, and the side view of slider 20 in its air-bearing relationship with disk 16 and

lubricant film 50 is shown in Fig. 4. The front air-bearing surface has a pair of air-bearing pads 25, 27 which provide the air-bearing effect to support the front end of slider 20 above the disk 16 when the disk is at its operational speed. The pads 25, 27 extend from a front ridge section 23 that acts as a step taper for the pads. The pads 25, 27 are generally equally spaced about the slider longitudinal centerline 60. The front pads 25, 27 have convex curved leading edges to minimize the air drag and to brush aside any particulate debris that may be present on the disk. A rear air-bearing pad 29 extends from a rear ridge section 26 that also acts as a step taper. Ridge sections 23, 26 are oriented generally parallel with each other and perpendicular to longitudinal centerline 60. The ridge sections 23, 26 are separated by a central nonair-bearing surface 28 which extends across the entire width of slider 20. The nonair-bearing surface 28 removes any air lift in that region of the slider 20, thus minimizing the total air lift on slider 20 and assuring that the front end is pitched up to enable air to flow under pitched-up rear pad 29.

The rear pad 29 has a leading edge 31 which is wider than its trailing edge 33. The sides 35, 37 of rear pad 31 are thus slanted relative to the length of the slider. In the preferred embodiment, the sides 35, 37 are angled approximately 20 degrees relative to the longitudinal axis of the slider. By making the rear pad 29 wider in the front than in the back, the rear pad 29 is prevented from acting as a plow, thereby minimizing depletion of the lubricant in the wake of movement of the disk 16 under the rear pad 29 during any contact of the pad 29 with the lubricant film 50. This also maintains low drag and minimizes thinning of the lubricant under the pad 31.

In disk drives with rotary actuators, the longitudinal axis of the slider is tangent to the disk at only one track position. For example, in one commercially available 2.5-inch disk drive the slider is skewed at approximately minus 4 degrees at the inside diameter (ID) and positive 17 degrees at the outside diameter (OD). By making the angle of the sides 35, 37 of rear pad 31 greater than the maximum absolute value of skew, for example approximately 20 degrees, it is assured that the rear pad remains nonplowing over the complete angle range of operation of the disk drive as the slider moves from disk ID to disk OD.

The rear pad 29 is also asymmetric in that its leading edge 31 is nonparallel or slanted relative to the trailing edge 33. This skewed leading edge provides extra air-bearing lift at the disk ID where the local disk velocity is low and less lift at the disk OD where the air-bearing effect is greater due to the higher local disk velocity.

As shown in Fig. 3, the total surface area of front air-bearing pads 25, 27 is greater than the surface area of rear pad 29. This feature, and the presence of the nonair-bearing surface 28 separating the two ridge sections 23, 26, results in a positive pitch up of the slider 20 (see Fig. 4) which causes rear pad 29 to also have a positive pitch, thereby enabling the air-bearing effect beneath pad 29 to support the rear portion of slider 20.

The area of the front pads 25, 27 and the depth of the step taper surface of ridge section 23 relative to the pads affect the slider-to-disk stiction, the flying height of the front pads, and the lift on the rear pad 29. The stiction has been found to be directly proportional to the area of the slider wetted by the lubricant from film 50 and inversely proportional to the separation between the slider and the disk, where "separation" is the distance from the disk to the part of the slider which is just wetted.

Since low stiction is desired, the area of the pads 25, 27 must be kept low in combination with a large depth of the surface of ridge section 23. However, the area of pads 25, 27 must also be sufficient to provide the positive pitch of the slider in operation. With the same pad area, different combinations of length-to-width ratio (L/W) of each of the pads 25, 27 can be used. ("Length" of the pads 25, 27 is the direction parallel to centerline 60.) It has been determined that as L/W increases for a given pad area, the total lift begins to decrease and thus L/W should not exceed approximately 2. If L/W is made too small, however, the slider loses roll stiffness, and the tolerances due to manufacturing variances become unacceptable. Thus, L/W should not be less than approximately 0.25.

The depth of the step taper surface of ridge section 23 must also be chosen with regard to flyability. For example, if this depth is too low, the lift will be too small and the pad area will have to be

increased. It is also desirable to select a depth such that any change in the depth due to manufacturing tolerances will cause only a very small resulting change in the flying height of the front pads 25, 27. Taking these considerations into account, it has been determined that
5 the depth must be greater than the flying height of the slider in the rear, and less than approximately 3 times the flying height of the slider in the front. For cases where the slider is designed to be in contact, the "flying height" becomes essentially the waviness and effective roughness of the disk.

10

In one experimental example the slider 20 was designed, by appropriate selection of suspension preload and air-bearing pad size and shape, to fly at the disk ID on a theoretically smooth disk with a spacing between the front pads 25, 27 and disk 16 of approximately
15 1000 Angstroms and a spacing between the rear pad 29 and disk 16 of approximately 100 Angstroms. The leading edge 31 of rear pad 29 was slanted or skewed at an angle of approximately 20 degrees relative to trailing edge 33. This slider was tested on a disk having a conventional amorphous carbon overcoat and a lubricant film of
20 approximately 40 Angstroms of Demnum SP. The ID velocity was 4.4 m/sec with a skew of -6.7 degrees, and the OD velocity was 9.5 m/sec with a +14 degree skew angle. The suspension preload was 5 gm. Under these conditions, the slider-disk spacing (the spacing between the top of the disk carbon overcoat and the bottom of rear pad 29) was approximately
25 100 Angstroms at the ID and 150 Angstroms at the OD. Measurements of the drag force on the slider indicated that it dropped from a relatively high value to an essentially constant relatively low value at a velocity of approximately 3.5 m/sec, which is the approximate velocity at which the rear pad 29 is making minimal contact with the lubricant film.
30 Because the disk 16 is not perfectly smooth but has a peak-to-peak waviness within the range of the designed flying height, it is believed that the rear pad 29 is at least partially contacting the lubricant film 50 up until approximately 7 m/sec, at which point the air bearing is fully supporting the rear pad 29. Based on correlations of drag
35 force with flying height, it is estimated that during the period the rear pad 29 is in contact with the lubricant film 50, the air bearing generated beneath pad 29 due to its positive pitch and ion-milled step taper provides approximately 90% of the support for the rear half of slider 20. The designed flying height is controlled by the width of the

rear pad 29. For example, decreasing this width by 60 microns, while maintaining all other parameters the same, caused the drag profile to flatten out at approximately 5.5 m/sec rather than 3.5 m/sec. The fact that lift is concentrated over small areas of the slider, compared to
5 conventional sliders where it is distributed over essentially the whole slider surface, makes the slider substantially insensitive to manufacturing tolerances, especially tolerances for crown and camber.

The slider design enables the slider to function in both the air-
10 bearing and contact head-disk interface regimes. While the slider provides an extremely low-flying height air-bearing support over a substantial part of the disk, the unique design, particularly the design of the rear pad, enables the slider to also be in contact and near contact with the lubricant film on the disk without deleterious effects.
15 The result is a low-flying height disk drive which can also operate in the contact and near-contact regimes, yet without the disadvantages presented by conventional liquid bearings.

The preferred method of manufacturing the slider will be described
20 with reference to Figs. 5A-5E, which illustrate the steps of manufacturing the slider depicted in Figs. 3 and 4. Figs. 5A-5E are sectional views of the slider taken through a section intersecting the front air-bearing pad 27.

25 In Fig. 5A the body of the slider 20, which is typically formed of a conventional ceramic mixture of titanium carbide (TiC) and alumina (Al_2O_3), has been saw cut to remove its central portion and thereby define the center nonair-bearing surface 28, which separates front ridge section 23 from rear ridge section 26. The depth of the cut can be in
30 the range of 10-100 microns. (As is known in the art, the sliders are processed in rows and then cut into individual sliders, so that Fig. 5A is actually the end view of a row of sliders.) Next, as shown in Fig. 5B, the ends of the ridge sections 23, 26 are rough lapped and polished to the correct height for the transducer 42 (Fig. 4) to be
35 formed later. A layer of photoresist 63, such as Riston brand of poly methylmethacralate (PMMA), is then deposited on top of the ridge sections 23, 26 to a thickness of approximately 0.1 millimeters. The photoresist is then exposed through a suitable mask which defines a pattern corresponding to the air-bearing pads, including pad 27, as

shown in Fig. 5C. (Front pad 25 and rear pad 29 are also formed at this time but are not shown in Fig. 5C because it is a sectional view only through front pad 27.) The row of sliders is then ion milled or otherwise etched to the desired depth, e.g., 0.2 microns, to build the air-bearing pads, as shown in Fig. 5D. The photoresist is then removed (Fig. 5E) and the row of sliders cut into the individual sliders.

The design of the slider enables a manufacturing process which is simplified over the process for manufacturing conventional air-bearing sliders of the type having air-bearing rails. Because there are no rails with their typically complex geometries, it is not necessary to use reactive ion etching or other complex steps to remove material from the center of the slider body. Instead, a single and much simpler saw cut is used to define the parallel ridge sections 23, 26. Also, as can best be seen in Fig. 4, all of the air-bearing pads are coplanar and are thus formed by a single photoresist process step.

An alternative embodiment of the slider is illustrated in Fig. 6. The alternative slider 70 is similar to slider 20 (Fig. 3) except that the front ridge section comprises two laterally spaced-apart ridge areas 72, 74, and the rear ridge section 76 does not extend across the entire width of the slider 70. The slider 70 is used when the desired material removal step for the central part of the slider is by reactive ion etching (RIE), rather than the saw cut for the embodiment of Fig. 3. The whole area, including the area between ridge areas 72, 74 and the areas on the sides of ridge section 76, can be removed in a single RIE step, resulting in the central nonair-bearing region 77 separating ridge areas 72, 74 from ridge section 76.

The embodiment of slider 80 shown in Fig. 7 is identical to that of slider 20 of Fig. 3, with the exception that a taper 82 is added to the front of ridge section 84 to improve the pitch and to better direct the air beneath front pads 86, 88. The taper 82 is lapped at an angle relative to the flat surface of ridge section 84, and requires an additional processing step during manufacture.

The embodiment of slider 90 in Fig. 8 has front struts 91, 92 that extend from front air-bearing pads 93, 94, respectively, and a rear strut 95 that extends from rear air-bearing pad 96. The struts 91, 92,

95 extend out from their respective pads a distance of approximately 500 to 1500 Angstroms, which is sufficient to support the pads out of contact with the lubricant film, thereby minimizing the static friction and low-velocity drag of the slider 90 during start up of the disk drive when the slider 90 is in contact with the disk. In the manufacture of the slider 90, a first ion-milling step is required to form the struts 91, 92, 95, followed by a second ion-milling step to form the air-bearing pads 93, 94, 96 around their respective struts. The front struts 91, 92 can be formed to have a greater thickness, by deposition of material, than the rear strut 95 so that the slider 90 has a positive pitch up when at rest on the disk. The struts, as well as the air-bearing pads around them, provide lift in the front and rear.

The slider embodiments shown in Figs. 4, 6, 7, and 8 can also include an amorphous carbon film, as is known in the art for use on slider air-bearing surfaces, which is deposited on the entire front portion of the slider to a suitable thickness, e.g., 2000 Angstroms. The carbon film has the effect of jacking up the front part of the slider when the slider is at rest on the disk to thereby minimize the amount of pad surface area that is in contact with the disk and/or the lubricant. Since the carbon film is only on the front portion of the slider, it results in a reduction in stiction without otherwise affecting the performance of the slider. In this embodiment, the front pads are not coplanar with the rear pad.

The struts in Fig. 8 and the carbon film on the front portion of the carrier improve the performance of the drive in both CSS disk drives and in L/UL disk drives in the event of a failure of the L/UL system. In both cases, the struts and the carbon film raise up the carrier above the lubricant film when the carrier is on the disk and the disk drive is not operating.

CLAIMS

1. A head assembly for a disk drive comprising:
a transducer (42) for writing data to or reading data from the
5 disk; and
a carrier (20) supporting the transducer and having a disk side, a front end and a trailing end, the carrier comprising an air-bearing pad (25) on the disk side near the front end, an air-bearing pad (29) on the disk side near the trailing end, and a nonair-bearing surface (28)
10 separating the front and rear air-bearing pads.
2. The head assembly of claim 1 wherein the front air-bearing pad comprises a pair of air-bearing pads (25, 27) generally equally spaced about the longitudinal centerline (60) of the carrier.
- 15 3. The head assembly of claim 1 or 2, wherein the pad or pads have a length-to-width ratio of between 0.25 and 2.
4. The head assembly of any preceding claim, wherein the rear air-
20 bearing pad is located on the longitudinal centerline (60) of the carrier.
5. The head assembly of any preceding claim wherein the air-bearing surfaces of all the pads are substantially coplanar.
- 25 6. The head assembly of any preceding claim, wherein the surface area of the front air-bearing pad or pads is greater than the surface area of the rear air-bearing pad, whereby the carrier is pitched up during operation of the disk drive.
- 30 7. The head assembly of any preceding claim, wherein the front air-bearing pad or pads have a leading edge having an essentially convex curvature.
- 35 8. The head assembly of any preceding claim, wherein the rear air-bearing pad has a leading edge (31) wider than its trailing edge (33).
9. The head assembly of claim 8 wherein the sides of the rear air-bearing pad (35, 37) connecting the leading edge with the trailing edge

This Sheet Has Been Replaced





define an angle which is greater than the maximum amount of skew of the carrier relative to data tracks on a disk when the carrier is operational in a disk drive.

- 5 10. The head assembly of claim 8 or 9 wherein the leading edge of the rear air-bearing pad is nonparallel with its trailing edge.
- 10 11. The head assembly of any preceding claim, wherein the front and rear ends of the carrier are generally parallel ridge sections (23, 26) oriented transversely to the longitudinal centerline (60) of the carrier and wherein the nonair-bearing surface (28) separating the ridge sections is recessed from the ridge sections.
- 15 12. The head assembly claim 11, wherein the front ridge section includes a tapered surface.
- 20 13. The head assembly of claim 11 or 12, wherein the front ridge section includes a pair of laterally spaced-apart ridge areas (72, 74) each ridge area supporting an air-bearing pad.
- 25 14. The head assembly of any preceding claim, further comprising a strut (91, 92) located on at least one front air-bearing pad for supporting the front of the carrier substantially off the lubricant film when the carrier is on the disk.
- 30 15. The head assembly of any preceding claim, further comprising a carbon film on at least one front air-bearing pad for supporting the front of the carrier substantially off the lubricant film when the carrier is on the disk.
- 35 16. The head assembly of any preceding claim, wherein the nonair-bearing surface extends across substantially the entire width of the carrier.
17. The head assembly of any preceding claim, wherein the transducer is located near the trailing end of the carrier.
18. A data recording disk drive including:
 a head assembly as claimed in any preceding claim;

This Sheet Has Been Replaced





at least one data disk (16) having a lubricant film thereon;
a motor (12) connected to the disk for rotating the disk;
an actuator (14) for moving the head assembly generally radially
across the disk so the transducer may access different regions of data
on the disk;

means (22, 24) connecting the head assembly to the actuator for
maintaining the head assembly near the disk; and

means (10) for supporting the motor and actuator.

19. The disk drive of claim 18, wherein the connecting means includes
a suspension (24) attached to the side of the carrier opposite the disk
for biasing the carrier toward the disk in order to maintain the
air-bearing pads of the slider near the disk during operation of the
disk drive.

20. The disk drive of claim 18 or 19, wherein the head assembly-to-
actuator connecting means includes means for providing generally
gimbaled movement of the carrier, whereby the carrier may pitch and roll
during operation of the disk drive.


21. The disk drive of any of claims 18 to 20, wherein the pad near the
trailing end of the head assembly supports the trailing end on the
lubrication film when the carrier is near the inside diameter portion of
the data region on the disk and generates an air-bearing support for the
trailing end when the carrier is near the outside diameter portion of
the data region on the disk.

22. The disk drive of claim 21, wherein the trailing end pad further
comprises generates an air bearing to partially support the trailing end
when the trailing end pad is in contact with the lubricant film on the
disk when the disk is rotating at its operational speed.

23. The disk drive of any of claims 18 to 22, wherein the lubricant
film is liquid.

24. The disk drive of any of claims 20 to 23, wherein the disk drive
is a contact start/stop disk drive and further comprising a strut
located on the front air-bearing pad for supporting the front of the

This Sheet Has Been Replaced





carrier substantially off the lubricant film when the disk drive is stopped.

25. The disk drive of any of claims 20 to 24, wherein the disk drive is a contact start/stop disk drive and further comprising a carbon film located on the front portion of the front air-bearing pad for supporting the front of the carrier substantially off the lubricant film when the disk drive is stopped.
26. The disk drive of any of claims 18 to 23, further comprising means (30) attached to the motor and actuator supporting means for unloading the carrier from the disk when the disk drive is not operating.

This Sheet Has Been Replaced



DISK DRIVE HEAD ASSEMBLY

ABSTRACT

5 A data recording disk drive a low-flying air-bearing slider that
is also able to be in contact and near contact with the lubricant film
on the disk. The slider has a front air-bearing surface in the form of
a pair of equally-spaced air-bearing pads 25, 27, a rear air-bearing pad
29, and a central nonair-bearing recessed surface 28 which separates the
front and rear air-bearing pads. The two front pads have a surface area
greater than that of the rear pad and thus provide a positive pitch up
10 of the slider. This causes the rear pad to also be pitched up so that
air can flow beneath the rear pad to generate an air bearing in the rear
portion of the slider. The presence of the central monair-bearing
region eliminates any lift in the central part of the slider, which
allows for the low-flying height. The flying height of the rear pad of
15 the slider above the disk is controlled by the width of the rear air-
bearing pad. The rear pad has its leading edge 31 wider than its
trailing edge 33 so that it is able to withstand contact with the
lubricant film on the disk, typically at the lower disk velocities near
the disk inside diameter, without generating unacceptable drag forces or
20 depleting the lubricant from the disk. The rear pad also has a skewed
leading edge which compensates for skew of the slider to minimize the
flying height variation from the disk inside diameter to outside
diameter.

This Sheet Has Been Replaced






FIG. 1




FIG. 2




FIG. 3









FIG. 4

*FIG. 5A**FIG. 5B**FIG. 5C**FIG. 5D**FIG. 5E*




FIG. 6




FIG. 7




FIG. 8

DISK DRIVE HEAD ASSEMBLY

ABSTRACT

A data recording disk drive a low-flying air-bearing slider that is also able to be in contact and near contact with the lubricant film on the disk. The slider (20) has a front air-bearing surface in the form of a pair of equally-spaced air-bearing pads (25, 27) a rear air-bearing pad (29), and a central nonair-bearing recessed surface (28) which separates the front and rear air-bearing pads. The two front pads have a surface area greater than that of the rear pad and thus provide a positive pitch up of the slider. This causes the rear pad to also be pitched up so that air can flow beneath the rear pad to generate an air bearing in the rear portion of the slider. The presence of the central nonair-bearing region eliminates any lift in the central part of the slider, which allows for the low-flying.

Fig. 4

This Sheet Has Been Replaced



REPLACEMENT SHEET

26 APR 1996

THIS SHEET HAS BEEN
REPLACED

☒ Description	: paged 2 to paged 7
☒ Claim(s)	: paged 15 to paged 19
☐ Drawing(s)	: paged ... to paged ...
☒ Abstract	: paged 20 to paged ...
DATE OF RECEIPT 14 OCT 1997	


More recently, in assignee's U.S. Patent 5,202,803, filed July 2, 1991, and issued April 13, 1993, a disk drive is described in which a conventional nonrecirculating, high-viscosity lubricant film is maintained on the disk and the transducer carrier is a modified three-rail air-bearing slider that has a rear "ski" pad. When the disk drive reaches operating speed, the air-bearing effect of the slider rails provides the primary support for the carrier, while the rear ski pad, which supports the magnetic head, contacts the lubricant film. The thickness of the lubricant film on the disk is approximately 20-100 Angstroms, which would also be the approximate head-disk spacing between the rear pad and the disk surface, assuming a perfectly smooth disk surface.


While liquid-bearing disk drives present the opportunity for closer head-disk spacing than air-bearing disk drives, they also present several difficulties. The carrier must provide a low-static friction ("stiction") interface when the carrier is at rest on the disk because liquid-bearing disk drives have thicker lubricant films and smoother disks than air-bearing disk drives. The carrier must also be designed to create small drag through the liquid film and to minimize liquid depletion from the disk. In addition, the carrier must be able to perform adequately over a wide range of relative carrier-disk velocities which occur at different disk radii.

SUMMARY OF THE INVENTION

It is an object of the present invention to ameliorate one or more disadvantages of the prior art.

According to one aspect of the present invention there is provided a magnetic recording disk drive comprising: at least one magnetic recording disk having a lubricant film thereon; a motor connected to the disk for rotating the disk; a slider having a disk side, a side opposite the disk side, a front ridge section generally transverse to the slider





longitudinal centerline and supporting two front air-bearing pads generally equally spaced about the slider longitudinal centerline, a rear ridge section generally parallel to the front ridge section and supporting a rear air-bearing pad located on the slider longitudinal centerline, and a nonair-bearing surface recessed from and separating the front and rear ridge sections, the total surface area of the front air-bearing pads being greater than the surface area of the rear air-bearing pad and the rear air-bearing pad having a leading edge wider than its trailing edge, whereby the rear air-bearing pad is located closer than the front air-bearing pads to the lubricant film on the disk and interaction with the lubricant film on the disk by the rear air-bearing pad is minimized during operation of the disk drive; a magnetic head located on the slider near the rear air-bearing pad for reading data from or writing data to the disk; an actuator for moving the slider generally radially across the disk so the head may access different regions of data on the disk; a suspension attached to the side of the slider opposite the disk side and connecting the slider to the actuator for maintaining the air-bearing pads of the slider near the disk during operation of the disk drive; and means for supporting the motor and actuator.

According to another aspect of the present invention there is provided a transducer assembly for a magnetic recording disk drive having a disk with a lubricant film thereon, the assembly comprising: a slider having a disk side, a side opposite the disk side, a front ridge section generally transverse to the slider longitudinal centerline and supporting two front air-bearing pads generally equally spaced about the slider longitudinal centerline, a rear ridge section generally parallel to the front ridge section and supporting a rear air-bearing pad located on the slider longitudinal centerline, and a nonair-bearing surface recessed from and separating the front and rear ridge sections, the

total surface area of the front air-bearing pads being greater than the surface area of the rear air-bearing pad and the rear air-bearing pad having a leading edge wider than its trailing edge; and a magnetic head located on the slider near the rear air-bearing pad for reading data from or writing data to the disk, whereby when the assembly is located in an operating disk drive the differential surface area between the front and rear air-bearing pads pitches the slider up and the wider leading edge of the rear air-bearing pad minimizes interaction with the lubricant film if the rear-air bearing pad contacts the disk.

According to still another aspect of the present invention there is provided a magnetic recording disc drive comprising: at least one magnetic recording disk having a lubricant film thereon; a motor connected to the disk for rotating the disk; a slider having a disk side, a side opposite the disk side, a front ridge section generally transverse to the slider longitudinal centerline and supporting two front air-bearing pads generally equally spaced about the slider longitudinal centerline, a rear ridge section generally parallel to the front ridge section and supporting a rear air-bearing pad located on the slider longitudinal centerline, and a nonair-bearing surface recessed from and separating the front and rear ridge sections, the total surface area of the front air-bearing pads being greater than the surface area of the rear air-bearing pad, whereby the slider is pitched up during operation of the disk drive; a magnetic head located on the slider near the rear air-bearing pad for reading data from or writing data to the disk; an actuator for moving the slider generally radially across the disk so the head may access different regions of data on the disk; a suspension attached to the side of the slider opposite the disk side and connecting the slider to the actuator for maintaining the air-bearing pads of the slider near the disk during operation of the disk drive; and means for supporting the motor and actuator.

REPLACEMENT SHEET

14 OCT 1997

According to still yet another aspect of the present invention there is provided a transducer assembly for a magnetic recording disk drive having a disk with a lubricant film thereon, the assembly comprising: a slider having a disk side, a side opposite the disk side, a front ridge section generally transverse to the slider longitudinal centerline and supporting two front air-bearing pads generally equally spaced about the slider longitudinal centerline, a rear ridge section generally parallel to the front ridge section and supporting a rear air-bearing pad located on and being generally symmetric about the slider longitudinal centerline, and a nonair-bearing surface recessed from and separating the front and rear ridge sections, the total surface area of the front air-bearing pads being greater than the surface area of the rear air-bearing pad; and a magnetic head located on the slider near the rear air-bearing pad for reading data from or writing data to the disk, whereby when the assembly is located in an operating disk drive the differential surface area between the front and rear air-bearing pads pitches the slider up.

DESCRIPTION OF THE PREFERRED EMBODIMENT(S)


Various embodiments of the invention will now be described in detail by way of example, with reference to the following drawings:

Fig. 1 is a view in section of a schematic of a disk drive;

Fig. 2 is an open top view of the disk drive depicted schematically in Fig. 1;

Fig. 3 is a plan view of the bottom or disk side of a preferred embodiment of the head assembly of the present invention;


Fig. 4 is a sectional view of the slider-disk interface of the head assembly of Figure 3, illustrating the front and rear air-bearing pads and the intermediate nonair-bearing surface;



Figs. 5A-5E are sectional views of the head assembly illustrating sequential steps in its fabrication; and

Figs. 6, 7, and 8 are plan views of the disk sides of alternative embodiments of the head assembly.


Referring first to Fig. 1, there is illustrated in sectional view a schematic of the disk drive. The disk drive comprises a base 10 to which are secured a disk drive motor 12 and an actuator 14, and a cover 11. The base 10 and cover 11 provide a substantially sealed housing for the disk drive. Typically, there is a gasket 13 located between base 10 and cover 11 and a small breather port (not shown) for equalizing pressure between the interior of the disk drive and the outside environment. This type of disk drive is described as being substantially sealed since the drive motor 12 is located entirely within the housing and there is no external forced air supply for cooling the interior components. A magnetic recording disk 16 is connected to drive motor 12 by means of hub 18 to which it is attached for rotation by the drive motor 12. A thin continuous film 50 of a relatively high-





CLAIMS


1. A magnetic recording disk drive comprising:
 - at least one magnetic recording disk having a lubricant film thereon;
 - a motor connected to the disk for rotating the disk;
 - a slider having a disk side, a side opposite the disk side, a front ridge section generally transverse to the slider longitudinal centerline and supporting two front air-bearing pads generally equally spaced about the slider longitudinal centerline, a rear ridge section generally parallel to the front ridge section and supporting a rear air-bearing pad located on the slider longitudinal centerline, and a nonair-bearing surface recessed from and separating the front and rear ridge sections, the total surface area of the front air-bearing pads being greater than the surface area of the rear air-bearing pad and the rear air-bearing pad having a leading edge wider than its trailing edge, whereby the rear air-bearing pad is located closer than the front air-bearing pads to the lubricant film on the disk and interaction with the lubricant film on the disk by the rear air-bearing pad is minimized during operation of the disk drive;
 - a magnetic head located on the slider near the rear air-bearing pad for reading data from or writing data to the disk;
 - an actuator for moving the slider generally radially across the disk so the head may access different regions of data on the disk;
 - a suspension attached to the side of the slider opposite the disk side and connecting the slider to the actuator for maintaining the air-bearing pads of the slider near the disk during operation of the disk drive; and
 - means for supporting the motor and actuator.
2. The disk drive according to claim 1 wherein each of the pads has a length-to-width ratio of between approximately 0.25 and 2.
3. The disk drive according to claim 1 wherein the air-bearing surfaces of all the pads are substantially coplanar.





4. The disk drive according to claim 1 wherein each of the front air-bearing pads has a leading edge having an essentially convex curvature.
5. The disk drive according to claim 1 wherein the sides of the rear air-bearing pad connecting the leading edge with the trailing edge define an angle which is greater than the maximum amount of skew of the carrier relative to data tracks on the disk when the carrier is in the disk drive.
6. The disk drive according to claim 1 wherein the leading edge of the rear air-bearing pad is nonparallel with its trailing edge.
7. The disk drive according to claim 1 further comprising means attached to the motor and actuator supporting means for unloading the slider from the disk when the disk drive is not operating.
8. The disk drive according to claim 1 further comprising a strut located on the front air-bearing pads for supporting the front of the slider substantially off the lubricant film when the carrier is on the disk.
9. The disk drive according to claim 1 further comprising a carbon film on the front pads for supporting the front of the carrier substantially off the lubricant film when the carrier is on the disk.
10. A transducer assembly for a magnetic recording disk drive having a disk with a lubricant film thereon, the assembly comprising:

a slider having a disk side, a side opposite the disk side, a front ridge section generally transverse to the slider longitudinal centerline and supporting two front air-bearing pads generally equally spaced about the slider longitudinal centerline, a rear ridge section generally parallel to the front ridge section and supporting a rear air-bearing pad located on the slider longitudinal centerline, and a nonair-bearing surface recessed from and separating the front and rear ridge sections, the total surface area of the front air-bearing pads being greater than the surface area of the rear air-bearing pad and the rear air-bearing pad having a leading edge wider than its trailing edge; and





a magnetic head located on the slider near the rear air-bearing pad for reading data from or writing data to the disk, whereby when the assembly is located in an operating disk drive the differential surface area between the front and rear air-bearing pads pitches the slider up and the wider leading edge of the rear air-bearing pad minimizes interaction with the lubricant film if the rear-air bearing pad contacts the disk.

11. The transducer assembly according to claim 10 wherein each of the front air-bearing pads has a leading edge having an essentially convex curvature.

12. The transducer assembly according to claim 10 wherein the sides of the rear air-bearing pad connecting the leading edge with the trailing edge define an angle which is greater than the maximum amount of skew of the slider relative to data tracks on the disk when the slider is in the disk drive.

13. The transducer assembly according to claim 10 wherein the leading edge of the rear air-bearing pad is nonparallel with its trailing edge.


14. The transducer assembly according to claim 10 wherein the front ridge section includes a pair of laterally spaced-apart ridge areas, each ridge area supporting an air-bearing pad.

15. The transducer assembly according to claim 10 further comprising a strut located on each of the front air-bearing pads for supporting the front of the slider substantially off the lubricant film when the slider is on the disk.

16. The transducer assembly according to claim 10 further comprising a carbon film on the front air-bearing pad for supporting the front of the slider substantially off the lubricant film when the slider is on the disk.

17. The transducer assembly according to claim 10 wherein the length-to-width ratio of each of the front pads is between approximately 0.25 and 2.

18. The transducer assembly according to claim 10 further comprising means attached to the side of the slider opposite the disk side for connecting the slider to the actuator of the disk drive, whereby the slider is biased toward the disk during operation of the disk drive.





19. A magnetic recording disc drive comprising:

at least one magnetic recording disk having a lubricant film thereon;

a motor connected to the disk for rotating the disk;

a slider having a disk side, a side opposite the disk side, a front ridge section generally transverse to the slider longitudinal centerline and supporting two front air-bearing pads generally equally spaced about the slider longitudinal centerline, a rear ridge section generally parallel to the front ridge section and supporting a rear air-bearing pad located on the slider longitudinal centerline, and a nonair-bearing surface recessed from and separating the front and rear ridge sections, the total surface area of the front air-bearing pads being greater than the surface area of the rear air-bearing pad, whereby the slider is pitched up during operation of the disk drive;

a magnetic head located on the slider near the rear air-bearing pad for reading data from or writing data to the disk;


an actuator for moving the slider generally radially across the disk so the head may access different regions of data on the disk;

a suspension attached to the side of the slider opposite the disk side and connecting the slider to the actuator for maintaining the air-bearing pads of the slider near the disk during operation of the disk drive; and

means for supporting the motor and actuator.

20. A transducer assembly for a magnetic recording disk drive having a disk with a lubricant film thereon, the assembly comprising:

a slider having a disk side, a side opposite the disk side, a front ridge section generally transverse to the slider longitudinal centerline and supporting two front air-bearing pads generally equally spaced about the slider longitudinal centerline, a rear ridge section generally parallel to the front ridge section and supporting a rear air-bearing pad located on and being generally symmetric about the slider longitudinal centerline, and a nonair-bearing surface recessed from and separating the front and rear





ridge sections, the total surface area of the front air-bearing pads being greater than the surface area of the rear air-bearing pad; and

a magnetic head located on the slider near the rear air-bearing pad for reading data from or writing data to the disk, whereby when the assembly is located in an operating disk drive the differential surface area between the front and rear air-bearing pads pitches the slider up.

REPLACEMENT SHEET

14 OCT 1997

DISK DRIVE HEAD ASSEMBLY

ABSTRACT

A data recording disk drive a low-flying air-bearing slider that is also able to be in contact and near contact with the lubricant film on the disk. The slider (20) has a front air-bearing surface in the form of a pair of equally-spaced air-bearing pads (25, 27) a rear air-bearing pad (29), and a central nonair-bearing recessed surface (28) which separates the front and rear air-bearing pads. The two front pads have a surface area greater than that of the rear pad and thus provide a positive pitch up of the slider. This causes the rear pad to also be pitched up so that air can flow beneath the rear pad to generate an air bearing in the rear portion of the slider. The presence of the central nonair-bearing region eliminates any lift in the central part of the slider, which allows for the low-flying.

Fig. 4

