to the open position; air and/or water permeable or impermeable; non-slippery surface; extends at both sides of the wallet pivot axis; completely covers the pivoting wallet panels, preferably externally; easy pleatable and/or foldable, preferably elastically; substantially resistant against permanent deformation, e.g. pleads and/or folds and/or wrinkles; a permanent deformation, e.g. one or more of plead, fold or wrinkle, is absent; sheet or foil or membrane or cloth or textile like; puncture resistant; water resistant; tear resistant; easily conforms its shape elastically to contents of wallet; approximately rectangular shape; a dimension approximately twice the holder width; partly made from substantially non-elastic or non-stretch material or substantially less elastic material, e.g. natural leather or cloth; one or more of wrinkle free, fold free and plead free, in the open and/or closed position of the unloaded wallet, at least in the area covering the window; provides one or more of flat, smooth and level faces of the unloaded wallet in its open and/or closed position, at least in the area covering the window.

One or more of the following applies to the housing: thin walled; shaftless pivot; pivot axis extends along longer side; two mutually pivoting panels, preferably providing opposite main faces; panels have snap fit at the pivot; panels have integrated hinge parts to provide the pivot; at least one panel comprises a rigid space frame and/or one or more openings; space frame delimits a single opening; space frame provides the outer edges; space frame provides a cadre or framework or is circumferential; space frame is U-shaped and its distal leg ends are joined with the spine; a panel comprises metal, e.g. plate metal, e.g. the space frame of the panel, or part of it, comprises metal, e.g. plate metal; a panel is covered by a skin; an opening (also called window) is closed by a skin; the opening or openings associated with a main face or panel makes at least 50 or 60 or 70 or 80 or 90% of the surface area of the main face or panel; rectangular shape; length at least twice width; thickness (in unloaded, closed condition) not more than 20 or 25% or 50% or 75% of width; thickness (in unloaded, closed