

(43) International Publication Date
19 April 2012 (19.04.2012)(10) International Publication Number
WO 2012/051192 A2(51) International Patent Classification:
G06K 9/00 (2006.01)

(21) International Application Number:

PCT/US2011/055787

(22) International Filing Date:

11 October 2011 (11.10.2011)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

61/391,843	11 October 2010 (11.10.2010)	US
61/461,224	14 January 2011 (14.01.2011)	US

(71) Applicant (for all designated States except US):
GRAPHIC SECURITY SYSTEMS CORPORATION
[US/US]; 4450 Jog Road, Lake Worth, FL 33467 (US).

(72) Inventors; and


(75) Inventors/Applicants (for US only): **CVETKOVIC, Slobodan** [RS/US]; 6760 Columbia Avenue, Lake Worth, FL 33467 (US). **ALASIA, Thomas, C.** [US/US]; 10506Versailles Blvd, Wellington, FL 33449 (US). **ALASIA, Alfred, J.** [US/US]; 283 Cypress Trace, Royal Palm Beach, FL 33411 (US).(74) Agents: **MARTINEZ DE ANDINO, J., Michael** et al.;
Hunton & Williams LLP, Riverfront Plaza, East Tower,
951 East Byrd St., Richmond, VA 23219 (US).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, SZ, TZ,

[Continued on next page]

(54) Title: METHOD FOR CONSTRUCTING A COMPOSITE IMAGE INCORPORATING A HIDDEN AUTHENTICATION IMAGE



(57) Abstract: A method is provided for constructing a composite image having an authentication image formed therein. The authentication image is viewable using a decoder lens having one or more decoder lens frequencies. The method comprises generating a first plurality of component images in which corresponding tonal areas are tonally balanced around at least one tonal value. At least one of the component images is configured to include a representation of the authentication image. The method further comprises determining a pattern of component image elements for each of the component images. The pattern having at least one element frequency that is equal to or a multiple of a decoder lens frequency. At least a portion of the content of each component image element is extracted and used to construct a composite image element.



UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— *without international search report and to be republished upon receipt of that report (Rule 48.2(g))*