(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau

(43) International Publication Date
26 February 2004 (26.02.2004)

PCT

(10) International Publication Number
WO 2004/017438 A1

(51) International Patent Classification[7]: H01L 45/00

(21) International Application Number: PCT/US2002/025997

(22) International Filing Date: 14 August 2002 (14.08.2002)

(25) Filing Language: English

(26) Publication Language: English

(71) Applicants: INTEL CORPORATION [US/US]; 2200 Mission College Boulevard, Santa Clara, CA 95052 (US). OVONYX, INC. [US/US]; 1675 West Maple Road, Troy, MI 48084 (US).

(72) Inventors: LOWREY, Tyler, A.; 516 Mill River Lane, San Jose, CA 95134 (US). LEE, Sean, J.; 1660 Hope Drive, Apt. 1531, Santa Clara, CA 95054 (US). HO, Huei-Min; 18700 Saratoga-Los Gatos Road, Los Gatos, CA 95030 (US).

(74) Agents: MALLIE, Michael, J. et al.; Blakely, Sokoloff, Taylor & Zafman LLP, 12400 Wilshire Boulevard, 7th Floor, Los Angeles, CA 90025 (US).


(81) Designated States *(national)*: AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, UZ, VN, YU, ZA, ZM, ZW.

(84) Designated States *(regional)*: ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:
— *with international search report*

[Continued on next page]

(54) Title: ADHESIVE MATERIAL FOR PROGRAMMABLE DEVICE



(57) Abstract: In an aspect, an apparatus is provided that sets and reprograms the state of programmable devices. In an aspect, a method is provided such that an adhesive (215), like Ti or polysilicon, is formed on a dielectric (210) and on an electrode (230A), the adhesive patterned exposing the electrode, and a programmable material (404) is formed on the adhesive and on the electrode. In another aspect, a method is provided such that an adhesive (214) is formed on a dielectric (210), an opening (220) is formed through the dielectric exposing a contact (170) formed on a substrate, and a programmable material (404), preferably a chalcogenide, is formed on the adhesive and on a portion of the contact. A conductor (410) is formed on the programmable material and the contact transmits to a signal line.

WO 2004/017438 A1

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.