

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
10 April 2003 (10.04.2003)

PCT

(10) International Publication Number
WO 03/029775 A3

(51) International Patent Classification⁷: **G05D 23/00**

(21) International Application Number: PCT/US02/30494

(22) International Filing Date:
26 September 2002 (26.09.2002)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
60/326,357 1 October 2001 (01.10.2001) US

(71) Applicant (for all designated States except US): **MYKROLIS CORPORATION** [US/US]; 129 Concord Road, Billerica, MA 01821-4600 (US).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **PILLION, John, E.** [US/US]; 24 Westview Road, Brookline, NH 03033 (US).
SHYU, Jieh-Hwa [US/US]; 6 Starr Ave East, Andover,

MA 01810 (US). **BRIGGS, Alicia** [US/US]; 158 Parlmont Park, Billerica, MA 01862 (US). **MCLOUGHLIN, Robert** [US/US]; 2 Jefferson Drive, Pelham, NH 03076 (US).

(74) Agent: **KING, Timothy, J.**; Mykrolis Corporation, 129 Concord Road, Billerica, MA 01821-4600 (US).

(81) Designated States (national): CN, JP, KR, SG, US.

(84) Designated States (regional): European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, SK, TR).


Published:

- with international search report
- with amended claims and statement

(88) Date of publication of the international search report:
6 November 2003

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: THERMOPLASTIC APPARATUS FOR CONDITIONING THE TEMPERATURE OF A FLUID



(57) Abstract: This invention relates to an apparatus for conditioning the temperature of a fluid by utilizing a thermoplastic heat exchanger (50) comprised of a plurality of hollow tubes. The apparatus controls the temperature of a process fluid inside the heat exchanger (50) via a controller (46) by adjustment of a control valve (64) that regulates the flow of an exchange fluid. The apparatus can be used to maintain the temperature of a chemical bath (12) and also to prepare discrete dispensed volumes of temperature controlled liquid. The heat exchanger (50) is chemically inert and may be operated in extreme environments.



WO 03/029775 A3