

CORRECTED VERSION

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
18 July 2002 (18.07.2002)

PCT

(10) International Publication Number
WO 02/056481 A3

(51) International Patent Classification⁷: H03K 19/173,
H03M 13/41, H04B 1/10, H04L 27/00, G06F 15/00

(72) Inventor; and

(75) Inventor/Applicant (for US only): PUGH, Daniel, J.
[US/US]; 1595 Rebel Way, San Jose, CA 95118 (US).

(21) International Application Number: PCT/US01/49436

(22) International Filing Date: 25 October 2001 (25.10.2001)

(74) Agent: KREBS, Robert, E.; Thelen Reid & Priest LLP,
P.O. Box 649640, San Jose, CA 95164-0640 (US).

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
09/699,078 27 October 2000 (27.10.2000) US

(81) Designated States (national): AE, AG, AL, AM, AT, AU,
AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU,
CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH,
GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC,
LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW,
MX, MZ, NO, NZ, PH, PL, PT, RO, RU, SD, SE, SG, SI,
SK, SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU,
ZA, ZW.


(63) Related by continuation (CON) or continuation-in-part
(CIP) to earlier application:
US 09/699,078 (CON)
Filed on 27 October 2000 (27.10.2000)

(84) Designated States (regional): ARIPO patent (GH, GM,
KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian
patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European
patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE,
IT, LU, MC, NL, PT, SE, TR), OAPI patent (BF, BJ, CF,

(71) Applicant (for all designated States except US):
CHAMELEON SYSTEMS, INC. [US/US]; 161 Nortech
Parkway, San Jose, CA 95134 (US).

[Continued on next page]

(54) Title: SYSTEM AND METHOD OF IMPLEMENTING A WIRELESS COMMUNICATION SYSTEM USING A RECONFIGURABLE CHIP WITH A RECONFIGURABLE FABRIC



(57) Abstract: A wireless communication system can be implemented by using one or more reconfigurable chips, the reconfigurable chips having background and foreground configuration planes. The background plane can be loaded with one communication algorithm, while another portion of the communication algorithm is configured into the foreground plane and operating in the reconfigurable fabric. The switching between the foreground and background configurations can be done almost instantaneously. The system of the present invention allows a complicated communication system, such as a base station receiver for a wireless communication system, to be implemented on a small reconfigurable chip rather than a much larger FPGA.



WO 02/056481 A3



CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD,
TG).

(48) Date of publication of this corrected version:

30 May 2003

Published:

— *with international search report*

(15) Information about Correction:

see PCT Gazette No. 22/2003 of 30 May 2003, Section II

(88) Date of publication of the international search report:

6 September 2002

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.