

## DC Induction Electric Motor-Generator

5

## Background

## Related Applications

- [1] This application claims international priority from a prior filed U.S. Utility Patent  
10 Application having serial no. 11209525 and entitled "DC Induction Electric Motor-  
Generator" filed on 8/22/05.

## Field of the Present Disclosure

- 15 [2] This disclosure relates generally to electric motor-generators and more  
particularly to a DC rotating electromagnetic machine operating by induction.

## Description of Related Art

- 20 [3] The following art defines the present state of the field of the apparatus described  
and claimed herein:
- [4] Tu et al, US 2004/0135452, discloses a flat rotary electric generator that includes  
at least one toroidal coil structure for cutting magnetic lines to induce a current and at  
25 least one disc-shaped magnetic pole structure oriented parallel to the helical coil  
structure. If multiple toroidal coil structures and disc-shaped magnetic coil structures  
are included, the toroidal coil structures and disc-shaped magnetic coil structures are  
arranged in alternating manner. The toroidal coil structure and disc-shaped magnetic  
pole structure are not provided with a permeable material. When either the toroidal  
30 coil structures or the at least one disc-shaped magnetic pole structure is rotated by an  
external force, the toroidal coil structure cuts the magnetic lines passing therethrough

to generate an induced current. Neal, US 2002/0135263, discloses a plurality of stator arc segments that form a toroidal core for a stator assembly used to make a motor. In a preferred embodiment, a plurality of magnetic fields is created when electrical current is conducted through wire wound around poles on the toroidal core.

5 A monolithic body of phase change material substantially encapsulates the conductors and holds the stator arc segments in contact with each other in the toroidal core. Hard disc drives using the motor, and methods of constructing the motor and hard disc drives are also disclosed. Rose, US 6803691, discloses an electrical machine that comprises a magnetically permeable ring-shaped core centered on an

10 axis of rotation and having two axially-opposite sides. Coils are wound toroidally about the core and disposed sequentially along the circumferential direction. Each coil includes two side legs extending radially alongside respectively sides of the core. Coil-free spaces exist between adjacent side legs. A bracket has first and second side flanges that are connected by a bridging structure and respectively abut the first and

15 second sides of the coil. Mohler, US 6507257, discloses a bi-directional latching actuator that is comprised of an output shaft with one or more rotors fixedly mounted thereon. The shaft and rotor are mounted for rotation in a magnetically conductive housing having a cylindrical coil mounted therein and is closed by conductive end caps. The end caps have stator pole pieces mounted thereon. In one embodiment, the

20 rotor has at least two oppositely magnetized permanent magnets which are asymmetrically mounted, i.e., they are adjacent at one side and separated by a non-magnetic void on the other side. The stator pole piece has asymmetric flux conductivity and in one embodiment is axially thicker than the remaining portion of the pole piece. An abutment prevents the rotor from swinging to the neutral position

25 (where the rotor magnets are axially aligned with the higher conductivity portion of the pole piece). Thus, the rotor is magnetically latched in one of two positions being drawn towards the neutral position. Energization of the coil with an opposite polarity current causes the rotor to rotate towards its opposite latching position whereupon it is magnetically latched in that position. Mohler, US 5337030, discloses a permanent

30 magnet brushless torque actuator that is comprised of an electromagnetic core capable of generating an elongated toroidally shaped magnet flux field when energized. Outside the generally cylindrical coil is an outer housing with upper and

lower end plates at each end. Mounted to the end plates and extending towards each other are stator pole pieces separated from its opposing pole piece by an air gap. A permanent magnet rotor is disposed in the air gap and mounted on a shaft which in turn is rotatably mounted in each of the end plates. The permanent magnet rotor comprises at least two permanent magnets, each covering an arcuate portion of the rotor and having opposite polarities. Energization of the coil with current in one direction magnetizes the pole pieces such that each of the two pole pieces attracts one of the magnets of the rotor and repels the other magnet of the rotor resulting in a torque generated by the output shaft. Reversal of the current flow results in a reversal of the torque and rotation of the rotor in the opposite direction. Preferred embodiments are disclosed having multiple cells, i.e. a plurality of stator rotor combinations and/or cells in which there are a plurality of pole pieces at each stator pole plane. Kloosterhouse et al, US 5191255, discloses an electromagnetic motor that includes a rotor having a plurality of magnets mounted along a perimeter of the rotor. Preferably, adjacent magnets have opposite poles facing outward. One or more electromagnets are disposed adjacent to the perimeter of the rotor so that as the rotor rotates, the magnets mounted on the rotor are carried near the poles of the electromagnets. Current is supplied to the electromagnets by a drive circuit in a predetermined phase relationship with the rotation of the rotor such that, for substantially all angular positions of the rotor, magnetic attraction and repulsion between the poles of the electromagnets and the magnets mounted on the rotor urge the rotor to rotate in a desired direction. Reflective material is mounted on the rotor in predetermined angular positions. The drive circuit includes a photosensitive device which produces a signal whose value varies according to whether the device is receiving light reflected from the reflective material. The signal is amplified to produce drive current for the electromagnets. Westley, 4623809, discloses a stepper motor housing a pole structure in which a pair of identical stator plates, each having a plurality of poles, are positioned back to back with the poles projecting in opposite directions, the stator plates being positioned between a pair of substantially identical stator cups, each stator cup having a plurality of poles projecting inwardly from a back wall with a peripheral side wall terminating in an outwardly extending flange. A major surface of each flange is in contact with a face on one of the stator plates so as

to assure a low reluctance magnetic path. Fawzy, 4565938, discloses an electromechanical device which can be used as a motor or as a generator. The device has a housing, including bearing means to support a rotatable shaft. Disc magnet means are provided, and poled to have alternating polarity and are mounted on the shaft to define a rotor. The device includes at least one first pole shoe in contact with the magnet means, having a portion extending radially therefrom to define a virtual pole chamber, of a first polarity. Also included is at least one second pole shoe in contact with the magnet and having a portion extending radially therefrom to define a virtual pole chamber of the other polarity. A toroid stator is mounted on the housing and has windings thereon. The stator is positioned annularly around the disc magnets such that the virtual pole chambers of the first and second pole shoes surround portions of said windings with circumferentially alternating fields of alternating polarity. Means are provided for electrical contact with the stator to draw off current when the device is operated as a generator, or provide current to operate the device as a motor. Fawzy, 4459501, discloses an electromechanical device which can be used as a motor or as a generator that has a housing, including bearing means to support a rotatable shaft. A pair of disc magnets are poled to have opposite polarity on the two faces of each. The magnets are mounted face to face together on the shaft to define a rotor. The device includes at least one first pole shoe in contact with one face of each magnet, and having a portion extending radially therefrom to define, in its preferred form, a pair of virtual pole chambers, of the same polarity as said one face. Also included is at least one second pole shoe in contact with the other face of each magnet and having a portion extending radially therefrom to define in its preferred form a pair of virtual pole chambers of the same polarity as the other face. A toroidal stator is mounted on the housing and has windings thereon. The stator is positioned annularly around the disc magnets such that the virtual pole chambers of the first and second pole shoes surround portions of said windings with circumferentially alternating fields of alternating polarity. Means for electrical contact with the stator draw off current when the device is operated as a generator, or provide current to operate the device as a motor.

[5] Our prior art search with abstracts described above teaches rotating electromagnet machines; in both motor and generator forms. Thus, the prior art shows in Neal, a toroidal core with radial arc segments, in Fawzy, we see a N-N and S-S pole face adjacency, in Tu et al, a N-S and S-N pole adjacency with radial coil windings, in  
5 Rose, we find radially wound coils in sequence around a toroidal core and with permanent magnet segments with N-N and S-S adjacency. However, the prior art fails to teach a rotating electromagnetic machine that provides electromagnetic fields immersed in monopole permanent magnet fields of opposite polarities as is shown in the present apparatus and which provides operation by induction.

10

[6] The present disclosure distinguishes over the prior art providing heretofore unknown advantages as described in the following summary.

#### Summary

15

[7] This disclosure teaches certain benefits in construction and use which give rise to the objectives described below.

[8] An electromagnetic apparatus provides a rotating element acting as a transfer  
20 bridge between two active energetic suppliers, the rotating element providing a ferromagnetic core with plural electromagnet coils having induced electric energy from external permanent magnets; the ferromagnetic core transferring energy by induction to an inner stator wound active permanent magnet, whereby the wound permanent magnet functions as an energy collector and inductor for generating  
25 electricity.

[9] A primary objective inherent in the above described apparatus and method of use is to provide advantages not taught by the prior art.

30 [10] Another objective is to provide an electromagnetic rotating machine which develops a DC output or accepts a DC input while acting by induction.

[11] A further objective is to provide such a machine useful as an electric motor.

[12] A further objective is to provide such a machine useful as an electric generator.

5 [13] Other features and advantages of the described apparatus and method of use will become apparent from the following more detailed description, taken in conjunction with the accompanying drawings, which illustrate, by way of example, the principles of the presently described apparatus and method of its use.

10

#### Brief Description of the Drawings

[14] The accompanying drawings illustrate at least one of the best mode embodiments of the present apparatus and method of its use. In such drawings:

15 [15] Figure 1 is a vertical cross-sectional view taken in the lateral direction of the present apparatus; and

[16] Figure 2 is a vertical cross-sectional view taken in the longitudinal direction thereof.

20

#### Detailed Description

[17] The above described drawing figures illustrate the described apparatus and its method of use in at least one of its preferred, best mode embodiments, which is  
25 further defined in detail in the following description. Those having ordinary skill in the art may be able to make alterations and modifications to what is described herein without departing from its spirit and scope. Therefore, it must be understood that what is illustrated is set forth only for the purposes of example and that it should not be taken as a limitation in the scope of the present apparatus and method of use.

30

[18] Fig. 1 is a cross-sectional view of an embodiment of the apparatus defined in U.S. application serial number 11200920 of which the present application is a

Continuation-In-Part and which operates under the same principle; in which the linear-toroidal ferromagnetic core 140 has a shorted electric motor-generator solenoid coil 148, and which is a rotating autotransformer rotating between the active permanent magnets located externally on the stator's permanent magnet  
5 ferromagnetic support 154 and that the internal wound active permanent magnet or electro-magnet, as I said the energy collector & inductor 170.

This preferred embodiment provides a cylindrical orientation. The fix parts of this cylindrical linear-toroidal electric motor-generator are the same as in the discoidal  
10 embodiment, the active permanent magnets with their support, with the difference that the internal located active permanent magnet will have the energy collector & inductor 170 coil acting meantime as a transformer.

Operation of the present apparatus is determined by the moving part which in this  
15 case acts as a transfer bridge between the two active energetic suppliers.

The moving parts are the linear-toroidal ferromagnetic core 140 which, when rotating, each of its solenoid's coils independently have induced electric energy from the external permanent magnets and which then transfer by induction this energy to  
20 the inner stator's wound active permanent magnet, the energy collector and inductor 170, which, in this case acts as a generator.

To obtain a reverse effect, the energy collector and inductor 170 is fed a pulsed direct current at a selected frequency to produce a selected rotational speed. When charged  
25 by the induced electric energy from the internal energy collector and inductor 170, the coils of the ferromagnetic core have induced electric energy so that each solenoid becomes an active electromagnet. The coil UMP north and south interact with the external permanent magnet UMP and also with the ferromagnetic core's UMD with its own UMP which effect produces a sense of displacement of the rotor, as well as  
30 the mobile reversible mechanical transformer, the known electric motor.

The special feature of the presently described cylindrical version of the present apparatus does not use a commutator as this function is carried out by the energy collector and inductor 170".

5 [19] The enablements described in detail above are considered novel over the prior art of record and are considered critical to the operation of at least one aspect of the apparatus and its method of use and to the achievement of the above described objectives. The words used in this specification to describe the instant embodiments are to be understood not only in the sense of their commonly defined meanings, but  
10 to include by special definition in this specification: structure, material or acts beyond the scope of the commonly defined meanings. Thus if an element can be understood in the context of this specification as including more than one meaning, then its use must be understood as being generic to all possible meanings supported by the specification and by the word or words describing the element.

15

[20] The definitions of the words or drawing elements described herein are meant to include not only the combination of elements which are literally set forth, but all equivalent structure, material or acts for performing substantially the same function in substantially the same way to obtain substantially the same result. In this sense it is  
20 therefore contemplated that an equivalent substitution of two or more elements may be made for any one of the elements described and its various embodiments or that a single element may be substituted for two or more elements in a claim.

[21] Changes from the claimed subject matter as viewed by a person with ordinary  
25 skill in the art, now known or later devised, are expressly contemplated as being equivalents within the scope intended and its various embodiments. Therefore, obvious substitutions now or later known to one with ordinary skill in the art are defined to be within the scope of the defined elements. This disclosure is thus meant to be understood to include what is specifically illustrated and described above, what  
30 is conceptually equivalent, what can be obviously substituted, and also what incorporates the essential ideas.

## Claims

What is claimed is:

- 5       An electromagnetic apparatus comprising: a rotating element acting as a transfer bridge between two active energetic suppliers, the rotating element providing a ferromagnetic core with plural electromagnet coils having induced electric energy from external permanent magnets; the ferromagnetic core transferring energy by induction to an inner stator wound active permanent magnet, whereby the wound
- 10       permanent magnet functions as an energy collector and inductor for generating electricity.