

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
2 October 2003 (02.10.2003)

PCT


(10) International Publication Number
WO 03/081639 A2

- (51) International Patent Classification⁷: **H01L**
- (21) International Application Number: PCT/US03/08068
- (22) International Filing Date: 18 March 2003 (18.03.2003)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:
60/365,609 18 March 2002 (18.03.2002) US
10/390,101 17 March 2003 (17.03.2003) US
- (71) Applicant (for all designated States except US): **XANOP-TIX, INC.** [US/US]; 10 Al Paul Lane, Merrimack, NH 03054 (US).
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): **WYMAN, Theodore, Ted, J.** [US/US]; 37 Francestown TPK, Mont Vernon, NH 03057 (US). **MARTIN, Robert** [US/US]; 4510 Fontana Street, Orlando, FL 32807 (US). **GAHLSDORF, Rien** [US/US]; 6 Terry Street, Nashua, NH 03064 (US).
- (74) Agent: **STRAUSSMAN, Richard**; Morgan & Finnegan, L.L.P., 345 Park Avenue, New York, NY 10154 (US).
- (81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).
- Published:**
— without international search report and to be republished upon receipt of that report

[Continued on next page]

(54) Title: ON-CHIP AC COUPLED CIRCUIT

Note: R1 necessary only at
chip input for impedance matching



(57) Abstract: An alternating current coupling circuit is made up of a chip located within a chain of differential amplifier circuits having thereon a) a filter circuit, having an output, the filter circuit being constructed to filter out a direct current component in a low swing alternating current (AC) signal; and b) a current amplifier circuit, connected to the output of the filter, that amplifies a current associated with the AC signal.



WO 03/081639 A2



For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.