WHAT IS CLAIMED IS:

Claim 1.: A data center rack system, comprising:

an aisle comprising an aisle guidance track defining an aisle axis; and

a plurality of rack stations adjacent to the aisle,

wherein each rack station of the plurality of rack stations comprises a station guidance track defining a station axis and wherein an angle between the aisle axis and the station axis is less than 90 degrees, and wherein each rack station configured to:

receive a rack from the aisle guidance track; and after movement of the rack along the aisle axis;

upon receipt of the rack, permit movement of the rack along the station axis to position the rack in the respective rack station at a rack angle formed between the aisle axis and the station axis that is less than 90 degrees.; and

2. The data center position the rack system of claim 1, wherein eachin the respective rack station of the plurality ofat a spacing from adjacent rack stations further comprises an anchoring mechanism configured to anchorpermit a cooling air to flow between the rack at the rack stationand any adjacent racks.

3.Claim 2: The data center rack system of claim 1, wherein each rack station of the plurality of rack stations further comprises a connector configured to couple to a computing device in the rack positioned in the respective rack station of the plurality of rack stations and supply electrical power to the computing device.

4.Claim 3: The data center rack system of claim 32, wherein the connector is further configured to supply a cooling fluid to the rack positioned in the respective rack station of the plurality of rack stations.

~~5.~~Claim 4: The data center rack system of claim ~~4~~3, wherein the connector further comprises a control valve assembly configured to receive a temperature signal from ~~a~~the rack positioned in the respective rack station and control a flow of the cooling fluid to the respective rack station based on the temperature signal.

~~6.~~Claim 5: The data center rack system of claim 1, further comprising a cooling system configured to supply the cooling air to the plurality of rack stations.

~~7.~~Claim 6: The data center rack system of claim 1,

wherein the plurality of rack stations comprises a first plurality of rack stations on a first side of the aisle and a second plurality of rack stations on a second side of the aisle, and

wherein a minimum distance between adjacent rack stations of the first plurality of rack stations and between adjacent rack stations of the second plurality of rack stations is at least one inch.

~~8.~~Claim 7: The data center rack system of claim 1,

wherein the plurality of rack stations comprises a first plurality of rack stations on a first side of the aisle and a second plurality of rack stations on a second side of the aisle, and

wherein a minimum distance between each rack station of the first plurality of rack stations and each rack station of the second plurality of rack stations is at least 30 inches.

~~9.~~Claim 8: The data center rack system of claim 1, wherein the aisle guidance track is configured to:

receive the rack from the station guidance track; and

position the rack along the aisle axis.

~~10.~~Claim 9: The data center rack system of claim 1, wherein the aisle guidance track and each station guidance track of the plurality of rack stations comprises two tracks having a separation distance of 30 inches.

~~11.~~Claim 10: The data center rack system of claim 1, wherein the rack angle is between about 45 degrees and about 65 degrees.

~~12.~~Claim 11: The data center rack system of claim ~~1~~2, wherein the connector is configured to couple to a top of the rack.

~~13.~~Claim 12: The data center rack system of claim 1, wherein the data center rack system has an y-dimension parallel to the aisle axis less than or equal to about 20 feet and a x-dimension perpendicular to the aisle axis less than or equal to about 12 feet.

~~14.~~

Claim 13: The data center rack system of claim 1, wherein each rack station of the plurality of rack stations is configured to position ~~a~~the rack having a width between about 20 inches and about 32 inches and a length between about 40 inches and about 60 inches.

~~15.~~Claim 14: The data center rack system of claim 1, wherein the aisle guidance track and each station guidance track comprise depressions in a floor.

~~16.~~Claim 15: The data center rack system of claim 1, wherein the aisle guidance track and each station guidance track comprise raised tracks on a floor.

~~17.~~Claim 16: The data center rack system of claim 1, wherein each rack station of the plurality of rack stations further comprises an anchoring mechanism configured to anchor the rack at the respective rack station.

~~18.~~Claim 17: The data center rack system of claim ~~17~~16, wherein the anchoring mechanism comprises a depression in a floor configured to receive a wheel of the corresponding rack.

~~19.~~Claim 18: The data center rack system of claim ~~1~~2, further comprising a plurality of racks, each rack of the plurality of racks comprising:

a frame defining a rack volume;

a guidance mechanism coupled to the frame and configured to engage the aisle guidance track and ~~a~~the respective station guidance track; and

an anchoring mechanism coupled to the frame and configured to anchor the rack at the rack station.

~~20.~~Claim 19: The data center rack system of claim ~~19~~18, wherein the guidance mechanism comprises a set of wheels.

~~21.~~Claim 20: The data center rack system of claim ~~19~~18, wherein each rack of the plurality of racks further comprises a connection panel coupled to the frame and configured to receive the respective connector.

~~22.~~Claim 21: The data center rack system of claim ~~19~~18,

wherein the connector is further configured to supply a cooling fluid to the respective rack positioned in the respective rack station of the plurality of rack stations, and

wherein each rack of the plurality of racks comprises a rear door configured to open away from the aisle, each rear door comprising a heat exchanger configured to receive the cooling fluid.

~~23.~~Claim 22: The data center rack system of claim ~~22~~21, wherein each rear door further comprises at least one fan configured to discharge air through the heat exchanger into the rack volume.

Claim 23: The data center rack system of claim 4, further comprising:

a forced air cooling system configured to supply the cooling air to the plurality of rack stations at a baseline level of bulk cooling,

wherein the control valve assembly is configured to control the flow of the cooling fluid to the respective rack station in response to a value of the temperature signal exceeding a temperature threshold corresponding to the baseline level of bulk cooling.

Claim 24.: A data center rack system, comprising:

one or more rack sections, wherein each rack section comprises:

an aisle comprising an aisle guidance track defining an aisle axis; and

a plurality of rack stations adjacent to the aisle, wherein the plurality of rack stations comprises a first plurality of rack stations on a first side of the aisle and a second plurality of rack stations on a second side of the aisle,

wherein each rack station of the plurality of rack stations comprises a station guidance track defining a station axis and wherein an angle between the aisle axis and the station axis is less than 90 degrees, and wherein each rack station configured to:

receive a rack from the aisle guidance track; and after movement of the rack along the aisle axis;

upon receipt of the rack, permit movement of the rack along the station axis to position the rack in the respective rack station at a rack angle formed between the aisle axis and the station axis that is less than 90 degrees.; and

position the rack in the respective rack station at a spacing from adjacent rack stations to permit a cooling air to flow between the rack and any adjacent racks.

Claim 25.: The data center rack system of claim 24, wherein each rack section has an y-dimension parallel to the aisle axis less than or equal to about 20 feet and a x-dimension perpendicular to the aisle axis less than or equal to about 12 feet.

Claim 26.: The data center rack system of claim 24, wherein each rack station of the plurality of rack stations is configured to position a rack having a width between about 20 inches and about 32 inches and a length between about 40 inches and about 60 inches.

Claim 27.: The data center rack system of claims 24, wherein each of the first and second pluralities of rack stations comprise ten rack stations.

~~28. A method for providing cooling to a rack of a data center rack system, the method comprising:~~

~~receiving, by a controller, a temperature measurement for a rack of a plurality of racks, wherein each rack of the plurality of racks is positioned in a respective rack station at a rack angle formed between an aisle axis of an aisle and a station axis of the respective rack station that is less than 90 degrees;~~
~~determining, by the controller, whether the temperature measurement is greater than a threshold; and~~
~~in response to determining that the temperature measurement is greater than the threshold, increasing, by the controller, at least one of:~~
~~a flow rate of cooling air from a forced air cooling system to the plurality of racks; or~~
~~a flow rate of cooling liquid from a liquid cooling system to the rack of the plurality of racks.~~

~~29. The method of claim 28, further comprising:~~
~~determining, by the controller, whether the flow rate of the cooling air to the plurality of racks is at or greater than a threshold;~~
~~in response to determining that the flow rate is less than a threshold, increasing, by the controller, the flow rate of the cooling air from the forced air cooling system to the plurality of racks; and~~
~~in response to determining that the flow rate is at or greater than the threshold, increasing, by the controller, the flow rate of cooling liquid from the liquid cooling system to the rack of the plurality of racks.~~

~~30. The method of claim 28,~~
~~wherein the aisle comprising an aisle guidance track defining the aisle axis,~~
~~wherein a plurality of rack stations is adjacent to the aisle,~~
~~wherein the plurality of rack stations comprises a first plurality of rack stations on a first side of the aisle and a second plurality of rack stations on a second side of the aisle, and~~
~~wherein each rack station of the plurality of rack stations comprises a station guidance track defining the station axis and configured to:~~
~~receive a rack from the aisle guidance track; and~~
~~position the rack in the respective rack station at the rack angle formed between the aisle axis and the station axis that is less than 90 degrees.~~

~~31. A method for positioning a rack in a data center rack system, the method comprising:~~

~~transporting a rack along an aisle comprising an aisle guidance track defining an aisle axis;~~

~~receiving the rack from the aisle guidance track into a station guidance track of a rack station of a plurality of rack stations adjacent to the aisle, wherein each rack station of the plurality of rack stations comprises a station guidance track defining a station axis; and~~

~~positioning the rack in the respective rack station at a rack angle formed between the aisle axis and the station axis that is less than 90 degrees.~~