

PHOTOMULTIPLIER TUBE (PMT) HAVING A REFLECTIVE PHOTOCATHODE ARRAY

RELATED APPLICATION(S)

[0001] This application claims the benefit of U.S. Provisional Patent Application No. 62/079,985 filed November 14, 2014, the entire contents of which are incorporated herein by reference.

FIELD OF THE INVENTION

[0002] The present invention relates to photomultiplier tubes (PMTs).

BACKGROUND

[0003] Photomultiplier tubes (PMTs) are devices utilized to detect light. They convert light to photoelectrons that are then multiplied and detected. In the past, one particular type of PMT has been formed from a transmission photocathode and a chain of dynodes. An example of the internal structure of a PMT in accordance with the prior art is shown in Figure 1. As shown in Figure 1, light **102** makes contact with one side of a transparent photocathode **104** and as a result photoelectrons **106** are emitted from the other side of the transparent photocathode **104**. The photoelectrons **106** then make contact with a dynode structure **108** which in turn multiplies the photoelectrons **106**.

[0004] Unfortunately, prior art PMTs (such as that illustrated in Figure 1) have exhibited various limitations. For example, use of a transmission photocathode, as compared to a reflective photocathode, generally results in lower quantum efficiency and a shorter useful lifetime. However, the use of reflective photocathodes has sometimes been avoided in PMT devices for mainly geometric reasons (for instance, needing to have a compact PMT in order to have high bandwidth).

[0005] There is thus a need for addressing these and/or other issues associated with the prior art PMTs.

SUMMARY

[0006] An internal portion of a photomultiplier tube (PMT) having a reflective photocathode array, and a method for manufacturing the same, are provided. The internal portion of the PMT comprises the reflective photocathode array and at least one dynode structure corresponding to the array of reflective photocathodes. Each reflective photocathode receives light and from the light, generates photoelectrons which then travel towards the at least one dynode structure. Upon the photoelectrons making contact with the at least one dynode structure, the photoelectrons are multiplied.

BRIEF DESCRIPTION OF THE DRAWINGS

[0007] Figure 1 shows an internal portion of a photomultiplier tube (PMT) having a transparent photocathode, in accordance with the prior art.

[0008] Figure 2 shows an internal portion of a PMT having a reflective photocathode array, in accordance with an embodiment.

[0009] Figure 3A illustrates a reflective photocathode/dynode sub-structure of the PMT of Figure 2 having a housing with light incident head-on, in accordance with an embodiment.

[0010] Figure 3B illustrates a reflective photocathode/dynode sub-structure of the PMT of Figure 2 having a housing with light incident at an angle, in accordance with an embodiment.

[0011] Figure 4 illustrates a method for manufacturing an internal portion of a PMT having a reflective photocathode array, in accordance with an embodiment.

DETAILED DESCRIPTION

[0012] Figure 2 shows an internal portion of a PMT having a reflective photocathode array, in accordance with an embodiment. As shown, the internal portion of the PMT includes a reflective photocathode array **204A-C** where each of the reflective photocathodes **204A-C** are for receiving light **202** and where photoelectrons **206A-C** are generated from the received light **202** by the reflective photocathodes **204A-C**. The internal portion of the PMT further includes at least one dynode structure corresponding to the array of reflective photocathodes **204A-C** for multiplying the photoelectrons **206A-C** generated by the array of reflective photocathodes **204A-C**.

[0013] In the embodiment shown, a separate dynode structure **208A-C** corresponds to each of the reflective photocathodes **204A-C** for multiplying the photoelectrons **206A-C** generated by the corresponding reflective photocathode **204A-C**. In another contemplated embodiment (not shown), a single dynode structure may correspond to multiple of (e.g. all of) the reflective photocathodes **204A-C** in the array for multiplying the photoelectrons **206A-C** generated by the entire reflective photocathode **204A-C** array. Of course, the PMT may also include other sub-structures as is known in the art.

[0014] Gaps are provided between the reflective photocathodes **204A-C** in order to allow the photoelectrons **206A-C** from each of the reflective photocathodes **204A-C** to pass through to the dynode structure **208A-C**. It should also be noted that while only three sub-structures comprising a reflective photocathode and corresponding dynode structure are shown in the array (i.e. sub-structure **204A** and **208A**, sub-structure **204B** and **208B**, sub-structure **204C** and **208C**), any number of such sub-structures may be included within the PMT, as desired. In other embodiments, the array of reflective photocathodes **204A-C** may be any number larger than one, and the reflective photocathodes **204A-C** may be utilized in combination with any number of dynode structures **208A-C** (i.e. one or more).

[0015] Each reflective photocathode **204A-C** may be positioned at an angle within the PMT, so as to send the photoelectrons **206A-C** towards the dynode structure **208A-C**. Further, each dynode structure **208A-C** may be at a position within the PMT to be able to receive the photoelectrons **206A-C** from the corresponding reflective photocathode(s) **204A-C**. In an embodiment with the aforementioned sub-structures, each of the sub-structures within the PMT comprising the reflective photocathode **204A-C** and corresponding dynode structure **208A-C** may be identical (e.g. in position, material, etc.).

[0016] It should be noted that each reflective photocathode **204A-C** may be any photocathode with at least a reflective top surface capable of reflecting photoelectrons the **206 A-C** from the light **202** that is incident thereto. For example, the reflective photocathode **204 A-C** may be any existing reflective photocathode known in the art.

[0017] Further, each dynode structure **208A-C** may include a plurality of dynodes, each capable of multiplying photoelectrons received thereby. For example, the dynodes may be positioned in a chain for passing the photoelectrons **206A-C** therebetween. Again, the dynode structure **208A-C** may be that which is well known in the art with regard to PMTs.

[0018] By using the reflective photocathode array **204A-C** in the PMT, higher quantum efficiency may be provided (than that provided by the transparent photocathodes used in the prior art, as shown in Figure 1 for example), particularly because the reflective property of the reflective photocathodes **204A-C** allows for more photoelectrons **206A-C** to be captured from the light **202** and transmitted to the dynode structure **208A-C** than amount of the photoelectrons otherwise captured and emitted by the transparent photocathode of the prior art).

[0019] Furthermore, the reflective photocathode **204A-C** is capable of being formed from a more robust material than the traditional transparent photocathode. In particular, the reflective photocathode **204A-C** may be formed from any desired material that is then coated with a reflective surface.

This may accordingly increase the lifetime of the PMT when the PMT includes the reflective photocathode **204A-C** as described in the present embodiment, as opposed to the prior art PMT having the transparent photocathode.

[0020] More illustrative information will now be set forth regarding various optional architectures and features with which the foregoing framework may or may not be implemented, per the desires of the user. It should be strongly noted that the following information is set forth for illustrative purposes and should not be construed as limiting in any manner. Any of the following features may be optionally incorporated with or without the exclusion of other features described.

[0021] Figure **3A** illustrates a reflective photocathode/dynode sub-structure of the PMT of Figure **2** having a housing with light incident head-on, in accordance with an embodiment. While only one sub-structure comprising a single reflective photocathode **204** and corresponding dynode structure **208** is shown within the housing **300**, it should be noted that the context of the present description the housing **300** would enclose the array of reflective photocathodes **204A-C** and corresponding dynode structure(s) **208A-C** as described above with respect to Figure **2**.

[0022] As shown, the reflective photocathode **204** and the dynode structure **208** are included within the housing **300**. The housing **300** may be a tube or any other enclosed structure as is known in the art with respect to PMTs. Additionally, the reflective photocathode **204** is positioned at a diagonal angle from an end side of the housing **300**. The end side of the housing may be, at least in a part, a window through which the light **202** can pass. In the embodiment shown, the light **202** is directed perpendicularly to the end side of the housing **300** and is incident with the reflective photocathode **204** at an angle. In this case, the PMT may be considered a head-on PMT.

[0023] Figure **3B** illustrates a reflective photocathode/dynode sub-structure of the PMT of Figure **2** having a housing with light incident at an angle, in

accordance with an embodiment. Again, while only one sub-structure comprising a single reflective photocathode **204** and corresponding dynode structure **208** is shown within the housing **300**, it should be noted that the context of the present description the housing **300** would enclose the array of reflective photocathodes **204A-C** and corresponding dynode structure(s) **208A-C** as described above with respect to Figure 2.

[0024] As shown, the reflective photocathode **204** and the dynode structure **208** are included within the housing **300**. The housing **300** may be a tube or any other enclosed structure as is known in the art with respect to PMTs. Additionally, the reflective photocathode **204** is positioned at a diagonal angle from an end side of the housing **300**. The end side of the housing may be, at least in a part, a window through which the light **202** can pass. In the embodiment shown, the light **202** may be directed toward the end side of the housing **300** at an angle and is perpendicularly incident with the reflective photocathode **204**, in which case the PMT may not be considered a head-on nor a side-on PMT. As an option, the end side of the housing **300** and window included therein may be positioned such that it is perpendicular to the incident light in order to minimize reflection resulting from the window (not shown).

[0025] To this end, the light can be incident, at an angle, to the array of reflective photocathodes shown in Figure 2, or in another embodiment can be perpendicularly incident to the array of reflective photocathodes shown in Figure 2. Optionally, the angle at which the reflective photocathode **204** is positioned within the housing **300** may differ depending on whether the light is incident at an angle with respect to the array of reflective photocathodes (as in the embodiment shown in Figure 3A) or is incident perpendicular to the array of reflective photocathodes (as in the embodiment shown in Figure 3B).

[0026] Figure 4 illustrates a method for manufacturing an internal portion of a PMT having a reflective photocathode array, in accordance with an embodiment. It should be noted that the present method described in Figure

4 may be implemented in the context of the aforementioned figures and associated descriptions.

[0027] The method includes, in operation **402**, providing, within a housing, an array of reflective photocathodes, each of the reflective photocathodes being at a position capable of receiving light. The method further includes, in operation **404**, providing, within the housing, at least one dynode structure corresponding to the array of reflective photocathodes, the at least one dynode structure being at a position capable of receiving photoelectrons when generated by the array of reflective photocathodes from the received light.

[0028] While various embodiments have been described above, it should be understood that they have been presented by way of example only, and not limitation. Thus, the breadth and scope of a preferred embodiment should not be limited by any of the above-described exemplary embodiments, but should be defined only in accordance with the following claims and their equivalents.

CLAIMS

What is claimed is

1. An internal portion of a photomultiplier tube (PMT), comprising:
an array of reflective photocathodes, each of the reflective photocathodes for receiving light and generating photoelectrons from the received light; and
at least one dynode structure corresponding to the array of reflective photocathodes for multiplying the photoelectrons generated by the corresponding array of reflective photocathodes.
2. The internal portion of the PMT of claim 1, wherein the array of reflective photocathodes and the corresponding at least one dynode structure are included within a housing.
3. The internal portion of the PMT of claim 2, wherein the housing is a tube.
4. The internal portion of the PMT of claim 2, wherein each of the reflective photocathodes is positioned at a diagonal angle from an end side of the housing.
5. The internal portion of the PMT of claim 4, wherein the end side of the housing is, at least in a part, a window through which the light can pass.
6. The internal portion of the PMT of claim 1, wherein each of the at least one dynode structure includes a plurality of dynodes.
7. The internal portion of the PMT of claim 6, wherein the dynodes are positioned in a chain for passing the photoelectrons therebetween.

8. The internal portion of the PMT of claim 6, wherein each of the dynodes multiples photoelectrons received thereby.
9. The internal portion of the PMT of claim 1, wherein the at least one dynode structure includes a single dynode structure that correspond to multiple of the reflective photocathodes in the array.
10. The internal portion of the PMT of claim 9, wherein the single dynode structure corresponds to all of the reflective photocathodes in the array.
11. The internal portion of the PMT of claim 1, wherein the at least one dynode structure includes a separate dynode structure corresponding each of the reflective photocathodes in the array.
12. The internal portion of the PMT of claim 1, wherein the light is one of:
incident to the array of reflective photocathodes at an angle, and
perpendicularly incident to the array of reflective photocathodes.
13. The internal portion of the PMT of claim 12, wherein:
when the light is incident to the array of reflective photocathodes at the angle then each of the reflective photocathodes is situated at a first angle, and
when the light is perpendicularly incident to the array of reflective photocathodes then each of the reflective photocathodes is situated is situated at a second angle that is different from the first angle.
14. A method for manufacturing an internal portion of a photomultiplier tube (PMT), comprising:
providing, within a housing, an array of reflective photocathodes, each of the reflective photocathodes being at a position capable of receiving light;
and
providing, within the housing, at least one dynode structure corresponding to the array of reflective photocathodes, the at least one dynode structure being at a position capable of receiving photoelectrons when

generated by the corresponding array of reflective photocathodes from the received light.

15. The method of claim 14, wherein the housing is a tube.

16. The method of claim 14, wherein each of the reflective photocathodes is positioned at a diagonal angle from an end side of the housing.

17. The method of claim 16, wherein the end side of the housing is, at least in a part, a window through which the light can pass.

18. The method of claim 14, wherein each of the dynode structures includes a plurality of dynodes.

19. The method of claim 18, wherein the dynodes are positioned in a chain for passing the photoelectrons therebetween.

20. The method of claim 18, wherein each of the dynodes multiples photoelectrons received thereby.

21. The method of claim 14, wherein the light is one of:
incident to the array of reflective photocathodes at an angle, and
perpendicularly incident to the array of reflective photocathodes.

22. The method of claim 21, wherein:
when the light is incident to the array of reflective photocathodes at the angle then each of the reflective photocathodes is situated at a first angle, and
when the light is perpendicularly incident to the array of reflective photocathodes then each of the reflective photocathodes is situated at a second angle that is different from the first angle.

23. The method of claim 14, wherein the at least one dynode structure includes a single dynode structure that correspond to multiple of the reflective photocathodes in the array.

24. The method of claim 23, wherein the single dynode structure corresponds to all of the reflective photocathodes in the array.

25. The method of claim 14, wherein the at least one dynode structure includes a separate dynode structure corresponding each of the reflective photocathodes in the array.