

Information Input Method and Apparatus

The present application claims priority from Chinese patent application with an application number 201610710394.9 and invention title "Information Input Method and Apparatus" filed on August 23, 2016, the entirety of which is hereby incorporated by reference
5 into this application.

Technical Field

The present invention relates to computer technology, particularly to an information input method and apparatus.

Background

10 Mobile terminal APP often sets some input boxes at application pages, such as an input box instructing the user to input a password, or an input box for input of a transfer amount. When information is input into an input box, an input keyboard self-defined by the APP may be adopted. For example, the APP may monitor the focus event of an input box and displays this input keyboard when the event occurs, so that the user can input information by clicking this
15 keyboard. The APP may synchronize information to an input box. This method for inputting information to an input box is prone to focus confusion when the application page is complex. For example, when information is input to an input box at a web page, if the input box is clicked with a mouse, a flashing cursor will appear in the input box. It is equivalent to a focus. When a cursor flashes, it means information may be input to the input box. However, sometimes the
20 focus may disappear suddenly when information is input to the input box, resulting in failure of input to the input box, i.e., no information is input to the input box and the input operation needs to be repeated several times. For example, the input box may be clicked once again to make the appearance of the focus until the input is completed.

Summary

25 For this purpose, the present invention provides an information input method and apparatus to ensure that the information is input effectively.

Specifically, the present invention is achieved through the following technical solutions:

In the first aspect, an information input method is provided, which comprises:

30 obtaining attribute information of a page input box, wherein the page input box is located at a front-end page of a mobile application;
according to the attribute information, creating a native input box having the attribute information, wherein the native input box is created at a native layer; and
filling information, input by a user through the native input box, back to the page input box.

35 In the second aspect, an information input apparatus is provided, which comprises:

an attribute obtaining module for obtaining attribute information of a page input box, wherein the page input box is located at a front-end page of a mobile application;

an input processing module, for creating a native input box having the attribute information according to the attribute information, wherein the native input box is created at a native layer; and

an information synchronizing module, for filling information, input by a user through the native input box, back to the page input box.

The information input method and apparatus set forth in the embodiments of the present invention, whereby information is inputted through a native input box created at a native layer, after which the input information is filled back to a front-end page. As the input box for input of information is created at a native layer, this manner avoids the focus confusion at a web page during input of information to the input box, thus ensuring that the information is input rapidly and effectively.

Brief Description of the Drawings

FIG. 1 is a flow chart of an information input method according to the embodiments of the present invention;

FIG. 2 is a flow chart of an alternative information input method according to the embodiments of the present invention;

FIG. 3 is a flow chart of an alternative information input method according to the embodiments of the present invention;

FIG. 4 is a schematic diagram of an information input process according to the embodiments of the present invention;

FIG. 5 is a flow chart of an alternative information input method according to the embodiments of the present invention;

FIG. 6 is a schematic diagram of the structure of an information input apparatus according to the embodiments of the present invention.

Detailed Description

Mobile-terminal apps typically include many application pages, one type of which are web pages displayed through webview control (may also be referred to as front-end pages); in web pages, some input boxes may sometimes be set based on service needs, such as an input box for input of a password, or an input box for input of a transfer amount. Such input box may be obtained through webkit rendering. However, this method for inputting information to an input box is prone to focus confusion, affecting input efficiency, and unable to input information rapidly and effectively. Based on this, the embodiments of the present application provide an information input method to solve the foregoing problems.

FIG. 1 shows a flow chart of an information input method according to the embodiments of the present invention, which may comprise:

In step 101, obtaining attribute information of a page input box, wherein the page input box is located at a page, for example, a front-end page, of a mobile application.

5 In this example, the input box located at the webview page may be referred to as a page input box, and the user may input information needed for processing service in the page input box; for example, the user may input a password needed during transfer in the password input box, or input a transfer amount needed during transfer in the amount input box.

10 The attribute information of an input box, for example, may include: display location of the input box at the front-end page, or the appearance parameters of the input box. The appearance parameters may include: width, height and color of the input box, defined box input fonts, etc. In this embodiment, the obtained attribute information of an input box may be all or part of the attributes of the page input box.

15 In step 102, according to the attribute information, creating a native input box having the attribute information.

In this step, a native input box may be drawn according to the attribute information obtained in step 101. The native input box has the attribute information. For example, the drawn native input box and the page input box at the front-end page have the same width and height, and the native input box and the page input box may have the same box type, for example, both
20 may be password input boxes. The native input box is created at a native layer, which is a program created at the native layer based on a local operating system of a smart phone, such as iOS and Android, written and run with a native program language. For example, in iOS, objective-C is used to create the native input box.

25 In step 103, filling information input by a user through the native input box, back to the page input box.

In this step, a corresponding data filling-back event, such as keyup and keydown may be invoked, to fill in the information input in a native input box back to the page input box, so that input information is filled back to the front-end page, thus completing information input. Further, this example may have no limitation to the way to input information to a native input box, for
30 example, information may be input via a keyboard or voice.

In the information input method of this example, information is input through a native input box created at a native layer, and then filled back to a front-end page. As the input box for input of information is created at a native layer, this manner avoids focus confusion at the web page during input of information to the input box (e.g., the problem of the confusion may be
35 caused by webkit defects or complex page logic at the web page), thus ensuring that the

information is input rapidly and effectively.

In another example, in order that the user does not perceive a native input box and still feels like using the input box at the original front-end page to input information, thus improving user's usage experience, the embodiments of the present application may ensure the consistency of the native input box and the page input box when creating a native input box. Refer to the flow of information input as shown in FIG. 2, which may comprise:

In step 201, obtaining attribute information of a page input box.

For example, the attribute information obtained in this step may include: display location of the page input box at the front-end page and appearance parameters, for example, the appearance parameters may include: width and height of the page input box, and font and font color of the page input box, etc.

In step 202, based on the attribute information, creating a native input box having the same attribute information.

For example, the created native input box and the page input box have the same width and height and may have the same font and font color as the input information.

In step 203, covering the input display of the corresponding page box with the native input box.

For example, the native input box may also be displayed at the display location of the page input box. In this way, the user will think information is input in a page input box and will not perceive a native input box.

In step 204, filling information input by the user through the native input box, back to the page input box.

In another example, the native input box created at a native layer has an important feature, which is that it may be controlled. For example, the format of the information input in the native input box may be controlled, and the information input in the native input box can be encrypted; however, the input box rendered by webkit at a web page is not controllable. For example, only the default system keyboard of the operating system can be used to input information, and the input process is not controllable. The embodiments of the present application make the best use of the foregoing features of a native input box, may design the format of information input to ensure that information is input effectively, and may encrypt the input information to improve the security of information input. The embodiment shown in FIG. 3 below describes the information input method of this example. Alternatively, either limitation to information input format or information encryption, may be applied in the native input box. The example of FIG. 3 describes an application of these two items at the same time.

In step 301, obtaining attribute information of a page input box, including the type of the

input box.

Here, the box type is used to indicate the information type to be received by the page input box. For example, if the box type is an amount input box for input of a transfer amount, then the input information may allow figures only rather than a, b, c and other letters.

5 In step 302, according to the attribute information, creating a native input box having the attribute information, wherein the native input box and the page input box are in the same box type.

For example, if the page input box is an amount input box for input of a transfer amount, the correspondingly created native input box is an amount input box, too; if the page input box is
10 a password input box for input of a transfer password, the correspondingly created native input box is also a password input box.

In step 303, when it is detected that the user has clicked to input into the native input box, providing an input keyboard corresponding to the box type, and receiving information input through the input keyboard.

15 In this example, a few types of input keyboards corresponding to the box types may be defined. For example, if the box type is a password input box, a password input keyboard is provided accordingly, and the password input keyboard allows inputting a password only; if the box type is an amount input box, an amount input keyboard is provided accordingly, and the input keyboard allows inputting an amount only and a, b, c and other letters cannot be input. In
20 this way, the format of the information input to the input box can be effectively limited to ensure that information is input effectively.

In step 304, encrypting the information input by the user to the native input box through an input keyboard.

For example, when the information type is a password, and the input keyboard is a
25 password keyboard, the information input by the user through the input keyboard may be encrypted. Of course, for other types of keyboards, whether to encrypt input information or not may be set according to service requirements.

In step 305, filling encrypted input information back to the page input box.

Below an example using the method of the present application to input information in an
30 input box is described:

As shown in FIG. 4, at the front-end page (e.g., the page may be a webview page) there are two input boxes instructing the user to input “transfer amount” and “transaction password” (for example, the input boxes may be input boxes obtained through webkit rendering). These two input boxes may be called page input boxes. In the subsequent process, corresponding
35 information, such as transfer amount and password, will be input in these two page input boxes

using the method described in this example. Referring to FIG. 5, which shows the flow of an information input method according to this embodiment, this method may be executed by an information input apparatus which may monitor operation of the application and execute this method, the method comprising:

5 In step 501, obtaining attribute information of a page input box when it is detected that the front-end page where the page input box is located is open.

For example, a user opens APP and clicks and enters an APP page, which may be a front-end page including amount, password and other page input boxes as shown in FIG. 4. When the information input apparatus according to this embodiment detects that the page is open, it may
10 obtain attribute information of the page input box, which, for example, may include: display location of the input box, and width, height, color and other appearance parameters of the input box.

In this example, attribute information of a page input box may also include: type of page input box. The box type is used to indicate the information type to be received by the page input
15 box. Still taking FIG. 4 as an example, the box types of the two page input boxes include: amount type and password type. The amount type input box can receive input amount information such as “100” and “200” only and cannot receive non-amount information such as “*#” and “abc”. The password type of input box can only receive information that can be used as a password. When collecting attribute information of a page input box, this embodiment not only
20 collects information about location, width and height but also collects the foregoing box-type information.

In step 502, according to the attribute information, creating a native input box having the attribute information, and covering the display of the corresponding page input box with the native input box.

25 As shown in FIG. 4, this embodiment creates native input boxes corresponding to page input boxes. For example, box 21 corresponds to the “transfer amount” native input box at the original APP page, and box 22 corresponds to the “transaction password” native input box at the original APP page. When being created, each of the native input boxes has the same box type as the corresponding page input box and may cover the display of the corresponding page input
30 box. For example, as shown in FIG. 4, a native input box is overlapped on a page input box so that the user sees the native input box rather than the page input box and can see the native input box only when the user clicks input.

In step 503, when it is detected that a user has clicked a native input box, an input keyboard corresponding to the box type of the native input box pops up so that the user may
35 input information.

In this example, when the information input apparatus detects that a user has clicked a native input box, suggesting that the user wants to input information at the moment, a keyboard will pop up. Here, the input keyboard is a keyboard corresponding to the box type of the native input box clicked by the user.

5 For example, supposing that the native input box is an input box corresponding to “transfer amount”, an amount keyboard corresponding to box type “amount” may pop up; or when the native input box is an input box corresponding to “transaction password”, a password keyboard corresponding to box type “password” may pop up; or, in other application scenarios, a numeric keyboard, character keyboard, etc. may also pop up. This example may define various
10 types of keyboards, which pop up when corresponding types of native input boxes are clicked.

 Providing an input keyboard corresponding to a box type for a user to input information may be used to limit input information to the information type allowed by the box, so that the user is not allowed to arbitrarily input any format of information other than the valid information limited by the input box, thus effectively controlling the validity of the input data.

15 In step 504, filling information input by a user through the native input box back to the page input box.

 For example, when information synchronously input in the native input box is filled back to a page input box, paly back of the corresponding events maybe simulated, such as keydown and keyup, so that information is filled back to the page input box. Here, when the information
20 type is a password and the input keyboard is a password keyboard, the information obtained by the user through a keyboard (e.g., if the user types in abc123 through a keyboard as a password, abc123 is the information obtained through a keyboard) may be encrypted before being filled back to the page input box to ensure the security of password input.

 In the information input method of this example, native input boxes and input keyboards
25 developed at the native end are adopted to input information to page input boxes at the front-end page so that the input of information through native input boxes and input keyboards will not affect the APP page, thus avoiding focus confusion and other problems and ensuring that information is input effectively. Furthermore, native input boxes and input keyboards developed at the native layer are highly controllable, for example, native input boxes are controls developed
30 at the native end and may control encryption of information in the native input boxes to further enhance the security of information input.

 FIG. 6 shows an information input apparatus, which may execute the method in the
embodiments of the present application. As shown in FIG. 6, the apparatus may comprise: an attribute obtaining module 61, an input processing module 62 and an information synchronizing
35 module 63. Here:

The attribute obtaining module 61 is configured to obtain attribute information of a page input box, wherein the page input box is located at a front-end page of a mobile application;

The input processing module 62 is configured to create a native input box having the attribute information according to the attribute information, wherein the native input box is
5 created at a native layer; and

The information synchronizing module 63 is configured to fill information input by a user through the native input box back to the page input box.

In one example, the attribute obtaining module 61 is configured to obtain attribute information of a page input box when the front-end page where the page input box is located is
10 detected to be open.

In one example, the input processing module 62 is configured to create the native input box according to the display location and appearance parameters of the page input box and covering the display of the corresponding page input box with the native input box.

In one example, the attribute information includes: type of the page input box, the native
15 input box corresponding to the page input box with the same box type. The input processing module 62 is also configured to provide an input keyboard corresponding to the box type according to the type of the native input box. The input keyboard allows inputting information of the information type.

In one example, the information synchronizing module 63 is also configured to: fill the
20 information input by a user through the input keyboard back to the page input box after encryption, when the type of the information is password and the input keyboard is a password keyboard.

When the apparatus in the embodiments of the present application achieves its functions in the form of software function unit and is sold or used as a stand-alone product, it may be
25 stored in a computer-readable storage medium. Based on this understanding, the technical solution in the present application or the part making contribution to current technologies or part of the technical solution may in essence be reflected in the form of a software product. The computer software product is stored in a storage medium and includes a number of instructions for enabling a device to proceed to all or some of the steps of the method in the embodiments of
30 the present invention. The foregoing storage media include all kinds of media that may store program codes, such as USB disk, mobile hard disk, ROM (Read-Only Memory), RAM (Random Access Memory), diskettes and compact discs.

The foregoing descriptions are preferred embodiments of the present invention and are not intended to limit the present invention. All modifications, identical replacements and
35 improvements made without departing from the spirit and principle of the present invention shall

fall within the scope of the present invention.

Claims

What is claimed is:

1. An information input method, wherein the method comprises:
obtaining attribute information of a page input box, wherein the page input box is located at a front-end page of a mobile application;
according to the attribute information, creating a native input box having the attribute information, wherein the native input box is created at a native layer; and
filling information, input by a user through the native input box, back to the page input box.
2. The method according to claim 1, wherein obtaining attribute information of a page input box comprises:
performing the step of obtaining attribute information of a page input box when it is detected that the front-end page where the page input box is located is open.
3. The method according to claim 1, wherein, according to the attribute information, creating a native input box having the attribute information comprises:
creating the native input box according to display location and appearance parameters of the page input box and covering the display of the corresponding page input box with the native input box.
4. The method according to claim 1, wherein the attribute information includes type of the page input box and the native input box corresponding to the page input box has the same box type;
creating a native input box having the attribute information further comprising:
providing an input keyboard corresponding to the type of the native input box and the input keyboard allowing inputting information of the information type.
5. The method according to claim 4, wherein when the information type is a password and the input keyboard is a password keyboard, filling the information input by a user through the native input box back to the page input box comprises:
filling the information input by a user through the input keyboard back to the page input box after encryption.
6. An information input apparatus, wherein the apparatus comprises:
an attribute obtaining module configured to obtain attribute information of a page input box, wherein the page input box is located at a front-end page of a mobile application;
an input processing module configured to create a native input box having the attribute information according to the attribute information, wherein the native input box is created at a

native layer; and

an information synchronizing module configured to fill information, input by a user through the native input box, back to the page input box.

7. The apparatus according to claim 6, wherein

the attribute obtaining module is configured to obtain attribute information of the page input box when it is detected that the front-end page where the page input box is located is open.

8. The apparatus according to claim 6, wherein

the input processing module is configured to create the native input box according to display location and appearance parameters of the page input box and cover the display of the corresponding page input box with the native input box.

9. The apparatus according to claim 6, wherein the attribute information includes type of the page input box and the native input box corresponding to the page input box has the same box type;

the input processing module being further configured to provide an input keyboard corresponding to the type of the native input box and allowing inputting information of the information type.

10. The apparatus according to claim 9, wherein

the information synchronizing module is configured to fill the information input by a user through the input keyboard back to the page input box after encryption when the information type is password and the input keyboard is a password keyboard.