

SPECIFICATION

Self-Drive Blast Apparatus

TECHNICAL FIELD

The present invention relates to a self-drive
5 blast apparatus which is capable of moving along wall
surfaces while retaining suction-adhered condition onto the
wall surfaces.

BACKGROUND ART

As is widely known, a considerable difficulty is
10 involved in conducting by manual works, such kind of works
as the cleaning and the conditioning of the substrate
surface prior to painting of the inner and outer wall
surfaces, in a ship, high-rise building, huge tank, or the
like. For this reason, automating those works without
15 relying on manual works has been studied, and various
apparatus for the automation have been proposed.

For example, Japanese Examined Patent Publication
No. Sho 60-28715 discloses an apparatus which adheres onto
a wall surface and moves along the wall surface, wherein
20 the apparatus basically comprising a pressure-receiving
body, wheels for driving an apparatus body, seal for
defining a depressurized space in cooperation with the
pressure-receiving body and with the outer wall surface,
and a depressurization source for discharging fluid from
25 the depressurized space. Also, Japanese Examined Patent

Publication No. Sho 60-26752 discloses an apparatus comprising, in addition to that basic arrangement, a mechanism for blast cleaning by projecting blast material onto a wall surface which the apparatus suction-adheres
5 onto and moves along.

In these conventional apparatus, for the purpose of moving the apparatus along a wall surface, a space defined by a casing as the pressure-receiving body and the wall surface is depressurized, while to the casing is
10 attached a seal member which is made of a substantially unbreathable and pliable material, and through the seal member the casing closely adheres to the wall surface. The apparatus adheres by suction onto the wall surface by reducing the pressure within the substantially sealed space
15 between the apparatus and the wall surface lower than the pressure outside the apparatus. While maintaining the suction-adhered condition, the apparatus moves along the wall surface with driving wheels coupled to the apparatus. The apparatus is capable of conducting blast cleaning, for
20 example, by projecting blast material onto the wall surface along which the apparatus moves.

By the way, in conducting such works as the cleaning and the conditioning of the substrate surface prior to painting of the inner and outer wall surfaces, in
25 a ship, high-rise building, huge tank, or the like, it is

known that a difficulty is involved in the works in a corner where two wall surfaces intersect at a specified angle. The conventional apparatus, however, have not been capable of dealing with a corner where two wall surfaces intersect each other at a specified angle, though the apparatus are capable of dealing with one wall surface (which is typically a flat one).

It is a primary object of the present invention to provide a self-drive blast apparatus which is capable of moving along two wall surfaces which intersect at a specified angle while keeping suction-adhered onto the wall surfaces, and capable of conducting and blast cleaning by injecting blast material onto an portion wherein the two wall surfaces intersect and the vicinity thereof.

DISCLOSURE OF THE INVENTION

In order to achieve the above mentioned object, a self-drive blast apparatus according to a first aspect of the invention is characterized in comprising a casing which defines a space between the casing and two wall surfaces intersecting each other at a specified angle, a seal member which is attached to the circumferential portion of the casing to seal airtightly between the circumferential portion of the casing and the two wall surfaces, a depressurization path in which one end opens into the space and in which the other end side communicates with a

depressurizing apparatus, an blast material nozzle which is mounted to the casing and in which one end faces the wall surfaces in the space and the other end side is connected to an apparatus for supplying blast material, and moving
5 means which is capable of moving the casing along the two wall surfaces in the condition of the space being depressurized through the depressurization path by the activation of the depressurizing apparatus.

Further, a self-drive blast apparatus according
10 to a second aspect of the invention is characterized in the moving means comprises wheel members for rolling on the wall surfaces and motors for driving and rotating the wheel members.

Furthermore, a self-drive blast apparatus
15 according to a third aspect of the invention is characterized in further comprising vents for, during the depressurization of the space, allowing air to flow in toward an area where the two wall surfaces intersect each other.

20 Furthermore, a self-drive blast apparatus according to a fourth aspect of the invention is characterized in the angle of the projecting nozzle can be adjusted so that the projecting direction of blast material is altered.

25 The self-drive blast apparatus according to the

invention operates as follows.

In the self-drive blast apparatus according to the first aspect of the invention, the casing surrounds a part of the area where the two wall surfaces intersect at
5 a given angle and defines the space between the wall surfaces and the casing, and the seal member attached to the circumferential portion of the casing seals airtightly between the casing and the two wall surfaces. In the condition of the space being depressurized via the
10 depressurization path, the blast cleaning is conducted by projecting blast material onto the wall surfaces in the space through the blast material nozzle, while the casing moves along the two wall surfaces with the moving means provided in the apparatus.

15 Further, in the self-drive blast apparatus according to the second aspect of the invention, the wheels are held in positions generally perpendicular to the corresponding wall surface and the apparatus body is capable of moving along the two wall surfaces intersecting
20 at a specified angle.

Furthermore, in the self-drive blast apparatus according to the third aspect of the invention, the air which flows into the space, during the depressurization of the space, blows up the blast material, the dirt scrubbed
25 and removed by the blast material, or the like, which has

collected in the corner between the two wall surfaces intersecting each other at a specified angle, so that the projected blast material can be efficiently sucked up.

Furthermore, in the self-drive blast apparatus
5 according to the fourth aspect of the invention, the blast material nozzle guides the blast material passing through the nozzle to set a projecting direction of the blast material onto the wall surfaces. The angle of the projecting direction of the blast material nozzle can be
10 adjusted and therefore the area of the wall surfaces which can be blasted and cleaned is enlarged by altering the projecting direction during the projection of blast material.

BRIEF DESCRIPTION OF THE DRAWINGS

15 FIG. 1 is a partially sectional view illustrating a self-drive blast apparatus in accordance with an embodiment of the invention;

FIG. 2 is a perspective view illustrating the blast apparatus;

20 FIG. 3 is a plan view illustrating the blast apparatus;

FIG. 4 is a side view illustrating the blast apparatus;

FIG. 5 is a plan view illustrating a seal member
25 attached to the blast apparatus;

FIG. 6 is a side view illustrating the seal member;

FIG. 7 is a sectional view illustrating the seal member;

5 FIG. 8 is a sectional view illustrating a portion of the seal member having air vents, where the seal member is attached to a casing; and

 FIG. 9 is a perspective view illustrating a self-drive blast apparatus in accordance with another embodiment
10 of the invention.

BEST MODE FOR CARRYING OUT THE INVENTION

Embodiments of the invention will now be described in detail with reference to the accompanying drawings.

15 An apparatus in accordance with the embodiments is a self-drive blast apparatus (hereinafter referred to as "blasting apparatus" or simply as "apparatus, " as necessary) which moves along two wall surfaces 1 and 2 intersecting at a specified angle (e.g., at generally right
20 angles, in the embodiments) while retaining suction-adhered condition onto a corner portion between the two wall surfaces 1 and 2, in order to blast by projecting blast material.

 In FIG. 1 is illustrated a manner in which a
25 blast apparatus 10 in accordance with an embodiment of the

invention adheres by suction onto an area where the wall surfaces 1 and 2 intersect at generally right angles. And, in FIGs. 2, 3, and 4, the apparatus 10 disposed in a corner portion between the wall surfaces 1 and 2 is illustrated.

5 The blast apparatus 10 comprises a casing 3 which defines a space 20 between itself and the two wall surfaces 1 and 2 intersecting each other at generally right angles, and a seal member 9 which is attached to the circumferential portion of the casing 3 to seal airtightly
10 between the circumferential portion of the casing 3 and the two wall surfaces 1, 2. Further, in the apparatus 10, a depressurization path 13 in which one end opens into the space 20 and in which the other end side communicates with a depressurizing apparatus is attached to the casing 3.
15 The apparatus 10 further comprises an blast material nozzle 11 in which one end faces the wall surfaces in the space 20 and in which the other end side is connected to an apparatus for supplying blast material, and comprises wheel members 5, 6, 7, and 8 capable of moving the casing 3 along
20 the two wall surfaces 1, 2, in the condition of the space 20 being depressurized through the depressurization path 13 by the activation of the depressurizing apparatus.

FIG. 3 and FIG. 4 are a plan view and a side view, respectively, of the blast apparatus 10. The
25 apparatus 10 is placed so as to straddle a corner portion

between the two wall surfaces 1 and 2, which intersect each other at generally right angles, with the intermediation of the seal member 9 attached to the circumferential portion of the casing 3. As shown in the drawings, the wheel members 5, 6, 7, and 8 are held in positions generally perpendicular to the corresponding one of the wall surfaces 1, 2 so as to rotate on the corresponding wall surface. In the apparatus 10, a driving motor is provided for each wheel member, and the wheel members 5, 6, 7, and 8 are driven and rotated by the driving motors 15, 16, 17, and 18, respectively. In the embodiment, for the purpose of allowing the apparatus 10 to move while keeping suction-adhered condition onto the wall surfaces, the driving forces for the wheel members 5, 6, 7, and 8 which are driven by the driving motors are predetermined so that the frictional forces exerted between the two wall surfaces 1, 2 and the wheel members 5, 6, 7, 8 are larger than the frictional forces exerted between the two wall surfaces 1, 2 and the seal member 9.

As shown in FIG. 2, the casing 3 is provided with the blast material nozzle 11, from which the blast material is projected onto the wall surfaces in the space 20. A portion of the surface of the blast material nozzle 11 is spherical-shaped and a holder 12 holding and supporting the spherical portion has a constitution which allows the angle

of the blast material nozzle 11 to be adjusted. In the apparatus 10, for the purpose of ensuring the airtightness between the blast material nozzle 11 and the holder 12, the contact surfaces between both the members are sealed. The casing is also provided with the depressurization path 13 communicating with the depressurizing apparatus (not shown). In the embodiment, the depressurizing apparatus not only depressurizes the space 20 but, by the sucking action, sucks up and retrieves through the depressurization path 13 the blast material which has been projected from the blast material nozzle 11 into the space 20.

In FIG. 1 is illustrated a manner in which the blast apparatus 10 in accordance with the embodiment of the invention adheres by suction to an area where the wall surfaces 1 and 2 intersect at generally right angles. The apparatus 10 is initially placed so as to define the space 20 between the casing 3 and the two wall surfaces 1, 2 intersecting at generally right angles. In the apparatus 10, the seal member 9 has a shape which allows the member 9 to adhere closely to a corner 30 between the two wall surfaces 1 and 2 generally perpendicular to each other. The depressurization of the space 20 by the depressurizing apparatus communicating with the depressurization path 13 permits the apparatus 10 to adhere by suction onto both the wall surfaces 1 and 2. In the suction-adhered condition,

the blast material which has been accelerated with compressed air is projected toward the corner 30 of the wall surfaces through the blast material nozzle 11 provided on the casing 3. The wall surfaces undergo cleaning or
5 processes for painting by the collision of the blast material with the wall surfaces. As the blast material, for example, steel grit of 0.5 to 0.7 mm ϕ has been used.

The blast material which has collided with the wall surfaces is then recovered by the sucking action of
10 the depressurizing apparatus through the depressurization path 13. At this time, some blast material splashes over the corner 30 between the two wall surfaces in the space 20 after colliding with the wall surfaces; in this corner portion is thus prone to collect the blast material, the
15 dirt removed by the blast material, or the like, which would affect the efficiency of the works.

For this reason, the blasting apparatus 10 in accordance with the embodiment is provided with, for example, air vents 21, 22, so that air flows, through the
20 seal member 9 which is in contact with the wall surface 2, into the space 20 toward the area where the two wall surfaces intersect each other, by the pressure difference between the space and the outside of the apparatus. Providing such vents 21, 22, the air which flows into the
25 space 20 through the vents 21, 22 being provided in a flange

23 for attaching the seal member of the casing 3 and on the side facing the space of the seal member 9, blow up the blast material which has collided, the dirt removed by the abrasive material, or the like in the space, thereby
5 causing the retrieval through the depressurization path 13 to be done smoothly. The retrieved blast material is recycled and reused.

As opposed to the depressurization of the space by the depressurizing apparatus, the supply of blast
10 material and the introduction of air increase the pressure in the space; in the embodiment, the conditions of the supply and the influx are predetermined respectively so that the supply and the influx may not hinder the adhesion by suction of the apparatus body to the wall surfaces.

15 In FIGs. 5 and 6 is illustrated the seal member 9 having an L-shape in side view in accordance with the embodiment; even with respect to two wall surfaces intersecting at generally right angles, forming the seal member 9 in such a shape allows a corner 19 of the seal
20 member 9 to be in sufficiently intimate contact with the corner 30 between the wall surfaces.

FIG. 7 is a sectional view of the seal member 9; as shown in this figure, a semicircular section is employed so as to reduce the influence of the outside-air pressure
25 exerted during the depressurization of the space and the

influence of a frictional force exerted in the movement of the apparatus. The seal member having such a shape, does not curl up toward the space 20, and is capable of sufficiently preventing the outside air from penetrating.

5 Both the ends of the semicircle are provided with a mounting flange 23 which has openings 25 spaced apart. Via the openings 25, the seal member 5 is attached to the casing 3.

The seal member 9 is made of an unbreathable,
10 pliable material, and the contact of the seal member with the wall surfaces thus grows tighter as the space 20 is depressurized. Even in the case of wall surfaces having microscopic roughness, a bulging portion 21 of the seal member is capable of adhering closely onto the wall
15 surfaces while flexibly accommodating the asperities, thus ensuring a sufficient sealing.

In FIG. 8 is illustrated a section of the attaching portions of the casing 3 and the seal member 9, the portions having the vents 21, 22 for the air for
20 blowing up into the sealed space the blast material which has collided with the wall surfaces, as described above. As shown in the drawing, the air vents 21, 22 are provided in the flange 23 for attaching the seal member of the casing and on the surface of the seal member on the side of
25 the space.

In FIG. 9, a blast apparatus in accordance with another embodiment is illustrated. In the blast apparatus, a motor 51 is provided on the outside of a casing 33 and the driving force of the motor is transmitted through a link 53 coupled to the motor 51, to an blast material nozzle 41, which is movable. A portion of the surface of the blast material nozzle 41 is spherical-shaped and a holder which holds and supports the spherical portion is provided and arranged so that the angle of the nozzle can be adjusted. In the embodiment, for the purpose of ensuring the airtightness between the blast material nozzle 41 and the holder, the contact surfaces between both the members are sealed, though not shown specifically. As a result, the direction or angle of the projection of blast material onto wall surfaces can be automatically adjusted, and wider area of the wall surfaces in the space can be blasted and cleaned by altering the projecting direction of the blast material nozzle 41 during the projection of blast material. As auxiliary means for moving the apparatus smoothly, wheel members 55, 56 which have no drive source are provided.

The invention is not limited to the above embodiment but various modifications and the alterations to the design may be made without departing from the spirit and scope of the invention.

As described above, according to the first aspect of the invention, the casing and the seal member attached to the casing define the space between the two wall surfaces intersecting at generally right angles and the casing and, by depressurizing the space, the apparatus is capable of adhering by suction onto the wall surfaces. With the wheel members, the apparatus can be moved along the wall surfaces intersecting at generally right angles. With the blast material projected from the blast material nozzle, a blasting process can be performed on the corner between the wall surfaces. Besides, the projected abrasive material can be retrieved through the depressurization path communicating with the depressurizing apparatus. Accordingly, the apparatus is capable of automatically moving on the corner between the two wall surfaces, and conducting blast cleaning by projecting blast material onto the corner.

Further, according to the second aspect of the invention, the same effects as the first aspect can be attained basically. Besides, with the wheels held in positions generally perpendicular to the corresponding wall surface, the apparatus is capable of moving on the wall surfaces while retaining suction-adhered condition onto the wall surfaces.

Furthermore, according to the third aspect of the

invention, the same effects as the first or second aspect can be attained basically. Besides, the blast material projected onto the wall surfaces, the dirt removed by the blast material, and the like can be efficiently retrieved
5 by blowing up the blast material into the space so that the blast material, the dirt, and the like may not collect in the corner between the wall surfaces.

Furthermore, according to the fourth aspect of the invention, the same effects as any one of the first to
10 third aspects can be attained basically. Besides, the blast material nozzle is movable and the angle of the projecting direction can be adjusted; therefore, wider area of the wall surfaces in the space can be blasted and cleaned by projecting blast material while altering the
15 projecting direction.

INDUSTRIAL APPLICABILITY

As described above, the self-drive blast apparatus according to the invention is capable of moving along two wall surfaces intersecting at a given angle, and
20 capable of blast cleaning by projecting blast material onto the wall surfaces; the apparatus can be effectively applied to the blasting work on a corner where two wall surfaces intersect, which work especially involves a difficulty in such works required to be automated as the cleaning of the
25 inner and outer wall surfaces and the conditioning of the

- 17 -

substrate surface prior to painting in, for example, a ship, high-rise building, huge tank, or the like.



- 18 -

What is claimed is:

1. A self-drive blast apparatus comprising a casing which defines a space between the casing and two wall surfaces intersecting each other at a specified angle, a
5 seal member which is attached to a circumferential portion of the casing to seal airtightly between the circumferential portion of the casing and the two wall surfaces, a depressurization path in which one end opens into the space and the other end side communicates with a
10 depressurizing apparatus, a blast material nozzle which is mounted to the casing and in which one end faces the wall surfaces in the space and the other end side is connected to an apparatus for supplying blast material, and moving means which is capable of moving the casing along the two
15 wall surfaces in the condition of the space being depressurized through the depressurization path by activating the depressurizing apparatus.

2. A self-drive blast apparatus as claimed in claim
20 1, wherein the moving means comprises wheel members for rolling on the wall surfaces and motors for driving and rotating the wheels, and the wheels are held in positions generally perpendicular to the corresponding wall surface.

25 3. A self-drive blast apparatus as claimed in claim



- 19 -

1 or 2, further comprising an air vent for, during the depressurization of the space, allowing air to flow in toward an area where the two wall surfaces intersect each other.

5

4. A self-drive blast apparatus as claimed in any one of claims 1 to 3, wherein the angle of the blast material nozzle is adjustable to alter the projecting direction of blast material.