



159159

-1-

**INFLATABLE DEVICE WITH RECESSED FLUID CONTROLLER AND
MODIFIED ADJUSTMENT DEVICE**

Background

5 **1. Field of the Application**

The application is related to inflatable devices, and, more specifically, to an inflatable device with a recessed fluid controller and modified adjustment device.

10 **2. Description of the Related Art**

Inflatable devices are used in a variety of contexts , such as where buoyancy or a cushioned support is needed, where space is limited or portability is desired. For example, inflatable mattresses, cushions and other body supports are used for applications such as camping, hospital bedding, and both occasional and everyday bedding in the home. Such inflatable devices have the additional advantage that the degree of inflation of the support
15 can be adjusted to provide selective support of an irregular object, such as a person. Other examples of inflatable devices include boats, rafts and other devices for use in the water.

A variety of methods are known for providing a fluid, such as air, to inflate an inflatable device. Typically, a pump is used to supply fluid to an orifice in the inflatable device. In most instances, fluid is introduced into inflatable devices through an inlet that
20 may be sealed to retain fluid within the inflatable device. The inlet may also serve as an outlet for deflating the inflatable device. A pump for use with an inflatable device may include a motor that drives an impeller, moving the fluid into, or out of, the inflatable device. Motorized pumps may be powered by electricity. Typically, such electricity is provided by a connection to standard house current or, where portability is desired, batteries.

25 One known inflatable device is illustrated in FIG. 1. This inflatable device is adapted for use as a mattress and includes a bladder 20 constructed to contain air in the shape of a mattress. The inflatable device also includes a fluid controller 80 connected to bladder 20 comprising a pump adapted to inflate bladder 20 when connected to household electric current. One such pump is described in U.S. Patent No. 5,267,363, herein
30 incorporated by reference.



G00002

Summary

In one embodiment, the application is directed to an inflatable device comprising a substantially fluid impermeable bladder and a fluid controller comprising an electrically powered pump at least partly positioned within the bladder.

5 In another embodiment, the application is directed to a combination of a fluid controller comprising an electrically powered pump and an inflatable device. The combination comprises the fluid controller connected to the inflatable device such that the exterior profile of the fluid controller and inflated inflatable device in combination is essentially the same as the exterior profile of the inflated inflatable device.

10 In another embodiment, the application is directed to an inflatable system comprising a substantially fluid impermeable bladder and a fluid controller comprising pump in fluid communication with the bladder. The fluid controller further comprises a first locking mechanism and a adjustment device including a second locking mechanism sized and adapted to reversibly mate with the first locking mechanism.

15

Brief Description Of Drawings

The foregoing and other advantages of the application will be more fully appreciated with reference to the following drawings in which:

FIG. 1 is a top, plan view of a prior art inflatable device;

20 FIG. 2 is a top, plan view of an inflatable device according to one embodiment of the application;

FIG. 3 is a perspective, plan view of a fluid controller according to one embodiment of the application;

25 FIG. 4 is a perspective, plan view of a fluid controller according to another embodiment of the application;

FIG. 5 is a top, cross-sectional view of one embodiment of the application;

FIG. 6 is a side, cross-sectional view of another embodiment of the application;

FIG. 7 is a side, cross-sectional view of another embodiment of the application;

FIG. 8 is a perspective, plan view of another embodiment of the application; and

30 FIG. 9 is a perspective, plan view of another embodiment of the application.

Detailed Description

The application is directed to an inflatable device with a recessed fluid controller and modified adjustment device. As used herein, a fluid controller is a device capable of regulating fluid flow and may include various components, such as a housing, valve, fluid conduit, pump, and the like. In one embodiment, the application is directed to an inflatable device including a substantially fluid impermeable bladder and a fluid controller comprising an electrically powered pump at least partly positioned within the bladder. As used herein, an object, such as a fluid controller, that is "positioned within" a bladder occupies a portion of the volume that would normally be occupied by the bladder, but need not be within the wall of the bladder. For example, a fluid controller could be located within a recess in the wall of a bladder and be "positioned within" the bladder, as this term is defined and used herein.

Referring now to the figures, and, in particular FIG. 2, one embodiment of an inflatable device according to the application will be described by way of example. The embodiment illustrated in FIG. 2 includes an inflatable device 10 having a substantially fluid impermeable bladder 20 and a fluid controller 80 comprising an electrically powered pump at least partly positioned within bladder 20.

Bladder 20 may be constructed in any manner and of any material(s) capable of retaining a desired fluid under a degree of pressure necessary for its intended application. For example, bladder 20 may be constructed of a substantially fluid impermeable barrier and may be shaped in accordance with its intended use. Where bladder 20 is intended for use as a mattress, bladder 20 may be constructed in the shape and thickness of a conventional mattress.

Bladder 20 may include internal structure, such as ribs or partitions. For example, bladder 20 may be divided into two or more separate fluid containing compartments. Bladder 20 may also include internal structure to control the movement of fluid within bladder 20. For example, bladder 20 may include baffles or walls within bladder 20 to improve the flow of fluid when bladder 20 is inflated or deflated.

A wall of bladder 20 may be any thickness required to substantially contain a fluid under pressures at which bladder 20 will be used. A thickness of the wall of bladder 20 may depend upon material from which bladder 20 is constructed. For example, more durable or elastic materials may not require the wall of bladder 20 to be as thick as less durable or elastic materials. Typically, the wall of bladder 20 may be 4-16 mils thick for polyvinyl chloride (PVC) film and polyurethane materials.

Bladder 20 may be constructed of any material or materials capable of substantially containing a fluid and forming a bladder 20 strong enough to withstand a pressure at which bladder 20 is to be used. For example, bladder 20 may be constructed of a polymeric material, such as a thermoplastic. Bladder 20 may be constructed from a relatively
5 inexpensive, easy to work with and durable material. Some example materials include polyvinyl chloride (PVC) film and polyester. The manner of making bladder 20 may depend on its material of construction and configuration, as will be recognized by one of ordinary skill in the art.

Bladder 20 may include additional materials to improve the utility and comfort of
10 bladder 20. For example, bladder 20 may include outer layers or coatings for durability, support or comfort. In some embodiments, bladder 20 may be coated with a material that is more pleasant to the touch than the material from which bladder 20 is constructed. Where inflatable device 10 is for use in supporting a person, bladder 20 may also include a layer to provide additional comfort, particularly where the person is to contact bladder 20. For
15 example, bladder 20 may include a comfort layer. The comfort layer may be located on any surface of bladder 20 that may come into contact with a user of inflatable device 10. The comfort layer may improve the texture and feel of bladder 20 and, further, may allow air and moisture to pass between a person and bladder 20, preventing discomfort.

Fluid controller 80 may be constructed in any manner and using any materials that
20 allow fluid controller 80 to control the flow of fluid into and/or out of bladder 20. In one embodiment, fluid controller 80 includes a pump that may be constructed in any manner and using any materials that allow it to inflate and/or deflate bladder 20. For example, as illustrated in FIG. 5, the pump may be a conventional fluid pump including a motor 84 that drives an impeller 86 moving air into, or out of, bladder 20. Where the pump includes
25 motor 84, motor 84 may be powered by electricity. Electricity may be provided by a connection to standard house current or, where portability is desired, by batteries. Other types of pumps, such as diaphragm pumps, may also be used so long as they allow the pump to inflate bladder 20 to within a desired pressure range, which may include a pressure range that can be adjusted by, for example, another fluid pumping device, such as someone
30 blowing into a conventional valve stem within the bladder, a foot pump, and the like.

Fluid controller 80 may direct fluid flow in any manner consistent with its construction. For example, where fluid controller 80 includes a pump with motor 84 and impeller 86, impeller 86 may draw fluid into, or out of, bladder 20 through a conduit 88. In some embodiments, conduit 88 may be positioned between motor 84 and a housing 90, as an

annulus. For example, in the embodiment illustrated in FIG. 5, fluid controller 80 includes a housing 90 that surrounds the inner workings of the pump. Housing 90 may also serve, for example, to protect the inner workings of the pump and to provide a connection between fluid controller 80 and bladder 20.

5 Preferably, where a pump is included in fluid controller 80, the pump is able to inflate bladder 20 in a relatively short time period, such as in less than a minute for an inflatable mattress. The pump may be designed to include an appropriately powerful fluid moving mechanism to achieve a desired pumping time to fill a particular inflatable device. The pump also may be small and consume as little power as possible. Low power
10 consumption is particularly desirable where the pump is to be powered by batteries, as it may extend battery life. The pump may also be configured to be quiet in operation. A balance of pumping capacity, size, power consumption, noise generation and cost may be selected for a particular application as will be recognized by those of skill in the art.

 Fluid controller 80 may be constructed of any material or materials that allow it to
15 function as desired. Typical materials of construction of the various components of fluid controller 80 will vary with the nature of fluid controller 80 and any pump and are known to those of skill in the art.

 Fluid controller 80 may be connected to bladder 20 in any manner that allows a pump to supply bladder 20 with fluid, inhibits undesired escape of fluid from bladder 20 and
20 does not interfere with the use of bladder 20. For example, inflatable device 10 may be constructed with at least a portion of fluid controller 80 positioned within bladder 20. Where fluid controller 80 is positioned at least partially within bladder 20, fluid controller 80 will not interfere with the use of inflatable device 10. In one embodiment, the exterior profile (total volume and shape) of the fluid controller and inflated device in combination
25 are essentially the same as the exterior profile of the inflated device absent the combination, thus reducing the opportunity for fluid controller 80 to impact or interfere with the use of inflatable device 10. For example, where fluid controller 80 is located substantially within bladder 20 in a mattress application, it allows an inflatable standard sized mattress to fit into a standard sized bed frame. Where fluid controller 80 is located within bladder 20, it may
30 be sized such that it will not come into contact with bladder 20 when bladder 20 is inflated, except at the point(s) of connection.

 Where at least a portion of fluid controller 80 is positioned within bladder 20, it may be connected to bladder 20 in any manner that will not interfere with the use of inflatable device 10 or allow undesired escape of fluid from bladder 20. For example, bladder 20 may

be adhered or sealed to a portion of fluid controller 80, such as with an adhesive or heat seal. In one embodiment, an outlet 120 (illustrated in FIG. 8) of fluid controller 80 is sealed to bladder 20.

Fluid controller 80 may include structure to facilitate connection to bladder 20. For example, fluid controller 80 may include a portion adapted to connect to bladder 20, such as a flange 82 as illustrated in FIGS. 3-5. Flange 82 may, for example, extend from housing 90 or may be a separate component connected to housing 90. As best seen in FIG. 5, flange 82 may include additional structure, such as a fluid impermeable wall 83, that may allow it to perform other functions in fluid controller 100 in addition to providing a connection point for bladder 20. Where flange 82 is connected to housing 90, it may be connected anywhere and in any manner that allows it to fluid tightly connect fluid controller 80 and bladder 20. For example, where flange 82 includes a fluid impermeable wall 83, flange 82 may be connected to housing 90 at or near outlet 120 from housing 90.

Flange 82 may be constructed of any material that allows it to durably and fluid tightly connect fluid controller 80 to bladder 20. For example, flange 82 may be constructed of a material that is more flexible than housing 90, but less flexible than bladder 20, bridging the flexibility gap between the two structures and resulting in a durable seal that may be performed, for example, by heat sealing. One example suitable material of construction of flange 82 is PVC. The thickness of flange 82 may also affect its flexibility, with thinner flanges generally being more flexible than thicker flanges. Thus the thickness of flange 82 may be selected to provide a desired flexibility with a given material.

Where flange 82 connects to housing 90 or another portion of fluid controller 80, it is preferred that such connection be reversible. For example flange 82 may snap or screw together with another portion of fluid controller 80. Additional structure may be included to promote a fluid seal between flange 82 and the remainder of fluid controller 80. For example, a seal, such as an o-ring, may be placed between flange 82 and the remainder of fluid controller 80. It is also possible to construct the inflatable device such that bladder 20 and fluid controller 80 are reversibly connected, rather than two portions of fluid controller 80 being reversibly connected. In either case, the reversible connection allows the removal of portions of fluid controller 80 for repair or replacement, preventing the entire inflatable device from having to be disposed of in the event of a failure of one component.

Bladder 20 may also include structure to facilitate the connection between bladder 20 and fluid controller 80. For example, bladder 20 may have a portion constructed to facilitate connection of fluid controller 80 to bladder 20, such as a retainer 22 as illustrated

in FIGS. 7 and 13. Retainer 22 may be constructed in any manner that will facilitate connection between bladder 20 and fluid controller 80, such as by mechanically supporting fluid controller 80. For example, retainer 22 may be constructed as a strap positioned across fluid controller 80.

5 It will now be clear that fluid controller 80 may be positioned within bladder 20 in a variety of ways. For example, fluid controller 80 may include a flange 82 that positions it at least partially within bladder 20. The size and shape of flange 82 may be selected to control the portion of pump 80 that is positioned within bladder 20. Alternatively, bladder 20 may include a recess and fluid controller 80 may be positioned within the recess and attached to
10 bladder only at a pump outlet, or at other locations within the recess.

Fluid controller 80 may be operated by any conventional control mechanism, such as a conventional power switch. Fluid controller 80 may also include a structure for controlling fluid controller 80, such as an adjustment device 100. Adjustment device 100 may be separate or separable from fluid controller 80 to allow fluid controller 80 to be controlled remotely.
15 In one embodiment, adjustment device 100 is a hand-held device for controlling fluid controller 80.

Adjustment device 100 may include structure for controlling the operation of fluid controller 80. For example, adjustment device 100 may include a conventional power switch 102 that energizes and de-energizes a pump within fluid controller 80. Switch 102
20 may be any of the many well-known mechanisms for selectively connecting two conductors to supply electricity to a point of use. Switch 102 may allow the pump to be energized such that it inflates bladder 20. Adjustment device 100 may also include structure that directs the deflation of bladder 20. For example, a second switch may reverse the direction of the pump to deflate bladder 20. In some embodiments, fluid controller 80 may incorporate a
25 valve which must be opened to allow deflation of bladder 20. In these embodiments, adjustment device 100 may also include structure to mechanically or electro-mechanically open a valve to allow deflation of bladder 20. For example, a switch 106 may act upon a mechanical opening mechanism or activate a solenoid 104 to open a valve, such as valve 122, and allow deflation of bladder 20. In one embodiment, the valve that is opened is a
30 self-sealing valve, meaning that it is held closed, at least in part, by pressure within bladder 20. For example, a self sealing valve may include a diaphragm 124 that is urged against a valve seat 126 by fluid pressure from within bladder 20. Optionally, switch 106 may also energize the pump to withdraw fluid from bladder 20.

In one embodiment, adjustment device 100 is connectable to fluid controller 80. In this embodiment, adjustment device 100 may be connected to fluid controller 80 at a conveniently located position such that it is easily found, particularly when inflatable device 10 is in use. For example, where inflatable device 10 is a bed, fluid controller 80 may be located at the head of the bed such that adjustment device 100 may be connected thereto for easy access when the bed is in use. Any control elements on adjustment device 100, such as switches 102, 106 or a button 108 may be located on adjustment device 100 for easy access. For example, the control elements may be located on a top portion of adjustment device 100, as illustrated in FIG. 4. Attachment of adjustment device 100 to fluid controller 80 may also facilitate deflation of bladder 20 with adjustment device 100. For example, where a valve must be opened to deflate bladder 20, adjustment device 100 may be in mechanical communication with fluid controller 80 to disengage the valve. In one embodiment, a button 108 on adjustment device 100 may be in mechanical communication with fluid controller 80 to open a valve.

The connection between adjustment device 100 and fluid controller 80 may be secure. For example, in one embodiment, adjustment device 100 reversibly locks to fluid controller 80. Where adjustment device 100 locks to fluid controller 80, adjustment device 100 and fluid controller 80 may include mating locking mechanisms 110, 112. Locking mechanisms 110 and 112 may be constructed in any manner and using any material(s) that allow locking mechanisms 110, 112 to reversibly lock together. By "lock" it is meant that two mechanisms fit together in such a way that a force must be overcome to separate them. In one embodiment, one locking mechanism 110 includes one or more spring latches 114 that mate with impressions 116 in other locking mechanism 112. Either locking mechanism 110, 112 may be located on either of adjustment device 100 or fluid controller 80.

Having thus described certain embodiments of the inflatable device of the application, various alterations, modifications and improvements will be apparent to those of ordinary skill in the art. Such alterations, variations and improvements are intended to be within the spirit and scope of the application. Accordingly, the foregoing description is by way of example and is not intended to be limiting.

There is provided an inflatable device, comprising:

- a substantially fluid impermeable bladder; and
- a fluid controller comprising an electrically powered pump and at least partly positioned within the bladder.

The fluid controller may be constructed and arranged such that a majority of the fluid controller is positioned within the bladder.

The fluid controller may be constructed and arranged such that substantially all of the fluid controller is positioned within the bladder.

The bladder may comprise a recess sized to accommodate at least a portion of the fluid controller.

The fluid controller may comprise a housing.

The housing may comprise a flange that connects to the bladder.

The fluid controller may comprise a flange that connects to the bladder.

A remainder of the fluid controller may be constructed and arranged to be removable from the flange.

The flange may comprise a fluid impermeable wall that connects to a housing of the inflatable device.

The flange may connect to the housing at an outlet of the housing.

The fluid controller may comprise a first locking mechanism and an adjustment device including a second locking mechanism sized and adapted to reversibly mate with the first locking mechanism.

The adjustment device may further comprise

- a first switch electrically connected to the pump and a power source such that first switch may selectively energize the pump; and

- a second switch mechanically connected to a valve of the fluid controller such that it may selectively open the valve;

- wherein the first switch and the second switch are in fixed proximity to one another.

The adjustment device may further comprise a top portion and the first switch and the second switch may be positioned on the top portion.

The inflatable device may further comprise an adjustment device including:

- a first switch electrically connected to the pump and a power source such that the first switch may selectively energize the pump; and

- a second switch electrically connected to a power source and electro-mechanically connected to a valve of the fluid controller such that it may selectively open the valve.

The electro-mechanical connection may comprise a solenoid.

The fluid controller may comprise a valve and a member connected to the valve that moves the valve between an open and a closed position.

The member may be adapted to be actuated by a switch on an adjustment device.

The member may be a stem.

There is also provided a combination of a fluid controller comprising an electrically powered pump and an inflatable device, comprising:

- the fluid controller connected to the inflatable device such that the exterior profile of the fluid controller and inflatable device in combination is essentially the same as the exterior profile of the inflatable device.

There is also provided an inflatable system comprising:

- a substantially fluid impermeable bladder; and

- a fluid controller comprising;

- a pump in fluid communication with the bladder and comprising a first locking mechanism; and

- an adjustment device including a second locking mechanism sized and adapted to reversibly mate with the first locking mechanism.

The adjustment device may further comprise

- a top portion

- a first switch having a first position and a second position, positioned on the top portion and electrically connected to the pump and a power source; and

- a second switch positioned on the top portion and mechanically connected to a valve.

The pump may be an electrically powered pump and the fluid controller may be at least partly positioned within the bladder.

The majority of the fluid controller may be positioned within the bladder.

Substantially all of the fluid controller may be positioned within the bladder.

The bladder may include a recess sized and configured to accommodate at least a portion of the pump.

The pump may include a housing and the housing may include a flange that connected to the bladder.

There is also provided an inflatable device comprising:

- a substantially fluid impermeable bladder; and

a fluid controller comprising:

an electrically powered pump,

a self-sealing valve, and

an adjustment device, comprising:

a first switch electrically connected to the pump and a power source such that the first switch may selectively energize the pump, and

a second switch electrically connected to a power source and electro-mechanically connected to a valve of the fluid controller such that it may selectively open the valve.

The electro-mechanical connection may comprise a solenoid.

Claims

1. An inflatable device, comprising:
a substantially fluid impermeable bladder; and
a fluid controller comprising an electrically powered pump, the pump being
5 disposed at least partially within a profile of the bladder, and the fluid controller being
coupled to the inflatable bladder in a position, and in the position the fluid controller
being adapted to permit air to exit the bladder through the fluid controller and to be
provided to the bladder through the fluid controller.
- 10 2. An inflatable device according to claim 1, wherein the fluid controller is
constructed and arranged such that a majority of the fluid controller is positioned within
the profile of the bladder.
3. An inflatable device according to claim 2, wherein the fluid controller is
15 constructed and arranged such that substantially all of the fluid controller is positioned
within the profile of the bladder.
4. An inflatable device according to any one of the preceding claims, wherein the
fluid controller comprises a housing.
- 20 5. An inflatable device according to claim 4, wherein the housing comprises a
flange impermeably connected to the bladder.

6. An inflatable device according to any one of the preceding claims, wherein the fluid controller comprises a flange impermeably connected to the bladder.
7. An inflatable device according to claim 6, wherein the flange comprises a fluid impermeable wall that connects to a housing of the inflatable device.
8. An inflatable device according to claim 7, wherein the flange is in contact with the housing at an outlet of the housing.
9. An inflatable device according to any one of claims 6 to 8, wherein a remainder of the fluid controller is constructed and arranged to be removable from the flange.
10. An inflatable device according to any one of claims 6 to 9, wherein the flange comprises a recess.
11. An inflatable device according to any one of the preceding claims, wherein the fluid controller comprises a first locking mechanism and an adjustment device including a second locking mechanism sized and adapted to mate with the first locking mechanism.
12. An inflatable device according to claim 11, wherein the adjustment device further comprises:
a first switch electrically connected to the pump and a power source such that the first switch may selectively energize the pump; and

a second switch mechanically connected to a valve of the fluid controller such that it may selectively open the valve;

wherein the first switch and second switch are in fixed proximity to one another.

5 13. An inflatable device according to claim 12, wherein the adjustment device further comprises a top portion and the first switch and the second switch are positioned on the top portion.

14. An inflatable device according to any one of the preceding claims further
10 comprising an adjustment device, including:

a first switch electrically connected to the pump and a power source such that the first switch may selectively energize the pump; and

a second switch electrically connected to a power source and electro-
mechanically connected to a valve of the fluid controller such that it may selectively
15 open the valve.

15. An inflatable device according to claim 14, wherein the electro-mechanical connection comprises a solenoid.

20 16. An inflatable device according to any one of the preceding claims, wherein the fluid controller comprises a valve and a member connected to the valve that moves the valve between an open and a closed position.

17. An inflatable device according to claim 16, wherein the member is adapted to be actuated by a switch on an adjustment device.

18. An inflatable device according to claim 16 or claim 17, wherein the member is a
5 stem.

19. An inflatable device according to any one of the preceding claims, wherein the fluid controller is connected to the substantially fluid impermeable bladder such that the exterior profile of the fluid controller and substantially fluid impermeable bladder in
10 combination is essentially the same as the exterior profile of the substantially fluid impermeable bladder.

20. An inflatable device according to any one of the preceding claims, wherein a recess is formed by the fluid controller.

15

21. An inflatable device according to any one of the preceding claims, wherein the pump is at least partially positioned within a recess in the wall of the bladder.

22. An inflatable device according to any one of the preceding claims, wherein the
20 pump is entirely external to the bladder.

23. An inflatable device according to any one of the preceding claims, wherein the fluid controller is permanently coupled to the bladder.

24. An inflatable device according to any one of the preceding claims, wherein the pump is externally accessible.
25. An inflatable device according to any one of the preceding claims, further
5 comprising a flange impermeably connected to the bladder, the flange forming a recess, wherein the pump is at least partially positioned within the profile of the bladder.
26. An inflatable device according to any one of the preceding claims, wherein the fluid controller is configured to permit air to exit the bladder at a user selectable rate.
- 10 27. An inflatable device according to any one of the preceding claims, wherein the pump is at least partially external to the bladder.
28. An inflatable device according to any one of the preceding claims, wherein the
15 bladder forms a mattress.
29. An inflatable device according to any one of the preceding claims, wherein the fluid controller comprises a valve through which the air exits the bladder.
- 20 30. An inflatable device, comprising:
an inflatable bladder; and
a fluid controller including an electrically powered pump, the fluid controller being at least partially positioned within a profile of the bladder such that the exterior profile of the fluid controller and inflatable bladder in combination is essentially the

same as the exterior profile of the inflatable bladder, at least a portion of the fluid controller that is positioned within the profile of the bladder being accessible from the exterior of the bladder, and the fluid controller being adapted to permit exhaustion of air at a user selectable rate from the bladder through the fluid controller.

5

31. An inflatable device according to claim 30, wherein the fluid controller is permanently connected to the bladder.

32. An inflatable device according to claim 30 or claim 31, wherein the fluid
10 controller comprises:

a valve, and

a user interface mechanically coupled to the valve, the user interface being adapted to permit a user to mechanically manipulate the valve.

15 33. An inflatable device according to claim 32, wherein the user interface is configured to permit a user to release air from the bladder at a selectable rate.

34. An inflatable device according to any one of claims 30 to 33, wherein the pump is at least partially accessible from the exterior of the bladder.

20

35. An inflatable device according to any one of claims 30 to 34, wherein the pump is at least partially accessible from the exterior of the bladder.

36. An inflatable device according to any one of claims 30 to 35, wherein the bladder forms a mattress.

37. An inflatable device according to any one of claims 30 to 36, wherein the fluid
5 controller comprises a valve through which the air exits the bladder.

38. An inflatable system, comprising:

a substantially fluid impermeable bladder; and

a fluid controller comprising:

10 a pump in fluid communication with the bladder through a valve and
comprising a first locking mechanism; and

an adjustment device including a first switch mechanically connected to
the valve and adapted to mechanically actuate the valve, and a second locking
mechanism sized and adapted to connect with the first locking mechanism.

15

39. An inflatable system according to claim 38, wherein the adjustment device
further comprises:

a top portion;

20 a second switch having a first portion and a second position, positioned on the
top portion and electrically connected to the pump and a power source; and
wherein the first switch is positioned on the top portion.

40. An inflatable system according to claim 38 or claim 39, wherein the pump is an electrically powered pump and the fluid controller is at least partly positioned within the profile of the bladder.

5 41. An inflatable system according to claim 40, wherein a majority of the fluid controller is positioned within the profile of the bladder.

42. An inflatable system according to claim 41, wherein substantially all of the fluid controller is positioned within the profile of the bladder.

10

43. An inflatable system according to any one of claims 40 to 42, wherein the bladder includes a recess sized and configured to accommodate at least portion of the fluid controller.

15 44. An inflatable system according to any one of claims 40 to 43, wherein the fluid controller includes a housing and the housing includes a flange that connects to the bladder.

45. An inflatable system according to any one of claims 38 to 44, wherein the
20 adjustment device is adapted such that, when the first locking mechanism is connected to the second locking mechanism, the first switch is mechanically connected to the valve.

46. An inflatable system according to any one of claims 38 to 45, wherein the bladder forms a mattress.

47. An inflatable device, comprising:

5

a substantially fluid impermeable bladder;

a fluid controller comprising:

an electrically powered pump, and

a self-sealing valve; and

10

an adjustment device, comprising:

a first switch electrically connected to the pump and an at least one power source such that the first switch may selectively energize the pump, and

15

a second switch electrically connected to the at least one power source and electro-mechanically connected to the self-sealing valve of the fluid controller, such that it may selectively open the self-sealing valve.

48. An inflatable device according to claim 47, wherein the electro-mechanical connection comprises a solenoid.

20

49. An inflatable device according to claim 47 or claim 48, wherein the bladder forms a mattress.

50. An inflatable device, comprising:

a substantially fluid impermeable bladder; and

a fluid controller comprising an electrically powered pump;

wherein the fluid controller is fixedly connected to the bladder in a position such that the pump is located only partially within a profile of the bladder, and when in the
5 position, the fluid controller is adapted to permit air to exit the bladder through the fluid controller and be provided to the bladder through the fluid controller.

51. An inflatable device according to claim 50, wherein the fluid controller is constructed and arranged such that a majority of the fluid controller is positioned within
10 the profile of the bladder.

52. An inflatable device according to claim 50 or 51, wherein the fluid controller comprises a housing having a flange that connects to the bladder.

15 53. An inflatable device according to any one of claims 50 to 52, wherein the bladder forms a mattress.

54. An inflatable device according to any one of claims 50 to 53, wherein the fluid controller comprises a valve through which the air exits the bladder.

20

55. An inflatable device, comprising:

a substantially fluid impermeable bladder; and

a fluid controller comprising an electrically powered pump, the fluid controller being permanently connected to the inflatable bladder, and the fluid controller being at

least partially positioned within a profile of the bladder such that the external profile of the fluid controller and inflatable bladder in combination is essentially the same as the exterior profile of the inflatable bladder alone, at least a portion of the fluid controller being accessible from the exterior of the bladder, and the fluid controller being adapted to permit exhaustion of air from the bladder through the fluid controller at a selectable rate.

56. An inflatable device according to claim 55, wherein the fluid controller comprises a valve through which the air exits the bladder.

10

15

20