



(43) International Publication Date
20 October 2005 (20.10.2005)

PCT

(10) International Publication Number
WO 2005/099202 A3

(51) International Patent Classification⁷: H05K 1/02

(21) International Application Number: PCT/US2005/009752

(22) International Filing Date: 23 March 2005 (23.03.2005)

(25) Filing Language: English

(26) **Publication Language:** English

(30) Priority Data:
10/814,606 31 March 2004 (31.03.2004) US

(71) **Applicant** (for all designated States except US): **SILICON LABORATORIES INC.** [US/US]; 4635 Boston Lane, Austin, TX 78735 (US).

(72) Inventor; and

(75) **Inventor/Applicant (for US only):** JOHNSON, Richard, A. [US/US]; 311 Larkspur Circle, Buda, TX 78610 (US).

(74) **Agents:** ROZMAN, Mark, J. et al.; TROP, PRUNER & HU, P.C., 8554 Katy Freeway, Ste. 100, Houston, 44 77024 (US).


(81) Designated States (*unless otherwise indicated, for every kind of national protection available*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SM, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (*unless otherwise indicated, for every kind of regional protection available*): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GO, GW, ML, MR, NE, SN, TD, TG).

Published:
— *with international search report*

[Continued on next page]

(54) Title: MAGNETICALLY DIFFERENTIAL INPUT



(57) Abstract: A magnetically differential input circuit (20) is arranged to define at least two loops (L1 and L2), wherein each of the loops traverses the input (231) of a receiving circuit. The loops (L1 and L2) are physically arranged so that a source of interference (L3) induces opposing signals in the loops (L1 and L2), thereby effecting cancellation of the interference at the input (231) of the receiving circuit. In one embodiment, the input circuit (20) is arranged to be electrically differential as well as magnetically differential.



— *before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments*

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(88) Date of publication of the international search report:

15 December 2005