CLAIMS

1. A device for transferring fluid, comprising:

a planar sheet having a first planar surface, a second planar surface, and a plurality of openings, wherein each opening of the plurality of openings extends between the first planar surface and the second planar surface;

a plurality of primary extensions, wherein each primary extension of the plurality of primary extensions protrudes from the first planar surface and comprises a primary lumen; and

a plurality of secondary extensions, wherein each secondary extension of the plurality of secondary extensions protrudes from the second planar surface and comprises a secondary lumen, and wherein each secondary lumen is aligned with an opening and a primary lumen to create a continuous transfer lumen.

2. The device of claim 1, wherein each primary extension of the plurality of primary extensions has an inner cross-sectional area and an outer cross-sectional area, and wherein the inner cross-sectional area is greater than the outer cross-sectional area~~.~~; and/or

~~3. The device of claim 1 or 2,~~ wherein each primary extension has at least two regions, and wherein each of the at least two regions has a different angle relative to the planar sheet.

3~~4~~. The device of claim 2~~3~~, wherein each primary extension has at least two regions, the at least two regions comprise a first region proximal to the planar sheet and a second region distal to the planar sheet, and the angle of the first region relative to the planar sheet is greater than the angle of the second region relative to the planar sheet.

4~~5~~. The device of any one of claims 1-3~~4~~, wherein each primary extension of the plurality of primary extensions comprises at least one structure configured to fluidly connect to the primary lumen.

5~~6~~. The device of claim 4~~5~~, wherein the at least one structure comprises an aperture, a hole, a slit, a gap, a notch, a groove, or a channel~~.~~; and/or

~~7. The device of claim 6,~~ wherein the primary extension comprises four slits configured to fluidly connect to the primary lumen.

68. A system for transferring fluid, comprising:

a transfer adapter, wherein the transfer adapter comprises a first side, a second side, and a plurality of openings, and wherein each opening of the plurality of openings extends between the first side and the second side; and

a receiver plate, wherein the receiver plate is configured to removably couple to the second side of the transfer adapter.

79. The system of claim 68, further comprising a donor plate comprising one well or a plurality of wells, wherein the donor plate is configured to removably couple to the first side of the transfer adapter.

810. The system of claim 79, wherein each opening of the plurality of openings aligns with a different well of the plurality of wells when the transfer adapter and the donor plate are removably coupled.; and/or

~~11. The system of claim 9 or 10,~~ wherein the transfer adapter comprises a plurality of primary extensions, and wherein each primary extension of the plurality of primary extensions is configured to seal against an interior surface of a different well of the plurality of wells of the donor plate.

912. The system of any one of claims 6-8-11, comprising at least one of the following features:

(i) wherein the receiver plate comprises a plurality of receiver wells, and wherein each opening of the plurality of openings aligns with a different receiver well of the plurality of receiver wells when the transfer adapter and the receiver plate are removably coupled.;

(ii) ~~13. The system of any one of claims 8-12,~~ wherein the transfer adapter comprises a plurality of secondary extensions, and wherein each secondary extension of the plurality of secondary extensions is configured to be inserted into a different receiver well of the plurality of receiver wells.;

(iii) ~~14.The system of any one of claims 8-13,~~ wherein the transfer adapter comprises an adhesive on the first side and/or the second side.;

(iv) ~~15.The system of any one of claims 8-14,~~ wherein the transfer adapter comprises a plurality of leaflets adjacent to each opening of the plurality of openings, wherein at least one leaflet is moveable between an open position and a closed position.; and/or

(v) ~~16. The system of any one of claims 8-15,~~ wherein the transfer adapter is configured to allow the flow of a fluid through the plurality of openings only when an external force is applied to the fluid.

10~~17~~. A method for transferring fluid, comprising:

coupling a transfer adapter, a donor plate, and a receiver plate to form a transfer assembly in a first position (*e.g.*, an upright position), wherein in the first position the transfer adapter is positioned below the receiver plate and above the donor plate; and

centrifuging the transfer assembly around an axis of rotation, wherein when the transfer assembly is centrifuged, the donor plate is positioned closer to the axis of rotation than the transfer adapter and the receiver plate,

wherein the transfer adapter comprises a plurality of openings and the donor plate comprises a plurality of wells, and wherein each opening of the plurality of openings is aligned with a different well of the plurality of wells when the transfer assembly is in the first position and when the transfer assembly is centrifuged.

11~~18~~. The method of claim 10~~17~~, further comprising uncoupling the donor plate from the transfer adapter~~.~~; and/or

~~19. The method of claim 17 or 18,~~ wherein a seal is formed between each well of the plurality of wells and the transfer adapter when the donor plate and the transfer adapter are coupled.

12~~20~~. The method of claim 11~~9~~, wherein a seal is formed, ~~wherein~~ the seal allows fluid to flow from the plurality of wells through the plurality of openings but blocks the flow of fluid between wells of the plurality of wells.

13~~21~~. The method of any one of claims 10~~17~~-12~~20~~, wherein each well of the plurality of wells comprises a target agent attached the well and a fluid.

14~~22~~. The method of claim 13~~21~~, wherein the target agent remains attached to the well after centrifuging~~.~~; and/or

~~23. The method of claim 21 or 22,~~ wherein the fluid is transferred to the receiver plate after centrifuging.

15~~24~~. The method of any one of claims 10~~17~~-14~~23~~, wherein the receiver plate comprises a plurality of receiver wells, and wherein each opening of the plurality of openings is aligned with a different receiver well of the plurality of receiver wells when the transfer assembly is in the first position and when the transfer assembly is centrifuged.

16~~25~~. The method of claim 15~~24~~, wherein a seal is formed between each receiver well of the plurality of receiver wells and the transfer adapter when the receiver plate and the transfer adapter are coupled.

17~~26~~. The method of claim 16~~25~~, wherein the seal allows fluid to flow through the plurality of openings to the plurality of receiver wells but blocks the flow of fluid between receiver wells of the plurality of receiver wells.

18~~27~~. A method for transferring fluid from and/or to wells of a donor plate comprising a plurality of wells, wherein at least one well comprises a plurality of target agents attached to the well and a fluid, comprising: applying a fluid transfer force to the donor plate, wherein the fluid transfer force has a simultaneous and substantially uniform effect on the plurality of target agents in the at least one well.

19~~28~~. The method of claim 18~~27~~, wherein each of at least two wells of the plurality of wells comprises a plurality of target agents attached to the well and a fluid, and wherein the fluid transfer force has a simultaneous and substantially uniform effect on the plurality of target agents in every well of the at least two wells.

20~~29~~. A device for transferring fluid, comprising:

a planar sheet having a first planar surface on a first side and a second planar surface on a second side,

a plurality of enclosures (*e.g.*, wells) on the first side having openings on the second side,

a plurality of extensions on the second side protruding from the second planar surface and comprising a lumen connected to the openings of the enclosures.

21~~30~~. The device of claim 20~~29~~, wherein each extension is configured to be inserted into a different receiver well of a receiver plate~~.~~; or

~~31. The device of claim 29,~~ wherein each extension is configured to seal against a different receiver well of a receiver plate.

22~~32~~. The device of ~~any one of~~ claim~~s~~ 20 or 21~~29-31~~, wherein an inner surface of the extension is configured to form an angle with an inner wall of the receiver well, and the angle is about 7 degrees or less~~.~~; and/or

~~33. The device of any one of claims 29-32,~~ further comprising an agent in the plurality of enclosures, such as a liquid agent, *e.g.*, a lyophilized agent.

2334. The device of any one of claims 20-2229-33, wherein each enclosure comprises a structure configured to retain and/or dispense an agent.

2435. The device of claim 2334, wherein the structure comprises a protrusion.

2536. A method for transferring an agent, comprising:

coupling the device of any one of claims 2029-2435 with a receiver plate to form a transfer assembly in a first position (*e.g.*, an upright position); and

centrifuging the transfer assembly around an axis of rotation, wherein when the transfer assembly is centrifuged, the device is positioned closer to the axis of rotation than the receiver plate,

wherein each opening of the device is aligned with a different receiver well of the receiver plate, whereby an agent in at least one enclosure of the device is transferred to the corresponding receiver well.