

Description

The invention is related to a connector for insulated conductors such as cables, particularly for electrical telecommunication cables.

DESCRIPTION OF THE PRIOR ART

Connectors of the kind mentioned typically include insulation-penetrating cutting terminals within at least one passageway. Further, suitable retaining means are provided retaining the cable in position and restrict removal of the cable from the passageway if the normally attached cover is removed. In case the cable is urged out of the passageway, the danger is encountered that electrical contact will be interrupted. Particularly for telecommunication cables it is undesired that the transfer of data is interrupted if work is undertaken at the connectors.

The German patent specification 36 22 164 discloses retaining means for connection wires in a connector wherein the side walls of an entrance slot include flexible barbs such that cables of different diameters can be introduced and secured against an outward movement. With respect to the retaining purposes, this problem is satisfactorily solved by the known retaining means. However, the known retaining means do not enable a strain relief which normally is additionally required. Strain relief means that a tension force at the cable is not immediately transmitted to the contact area, rather, a structural feature is necessary to maintain the electrical contact by forming a sufficient resistance against the cable being pulled out of the connector.

US patent No. 4 262 985 discloses a connector for connecting wires wherein retaining means and means for a strain relief are integrally formed with a housing of plastic material. The retaining means is defined by resilient tongues formed on opposite walls of a passageway receiving the cable from above. The tongues define a slot with an entrance portion thereof having a smaller width than below the entrance portion so that movement of the cable out of the slot is restricted. The strain relief means are defined by the tongues for which purpose they extend at an oblique angle with respect to the longitudinal axis of the cable, the tongues being resiliently deformed toward the contacting element if the cable is inserted.

The German patent specification 24 56 977 and 26 37 378 disclose separate retaining and strain relief means consisting of metal.

The German patent specification 24 46 670 discloses an electrical connector terminal integrally formed of sheet metal. At the lower side, the terminal has two contact extensions by which it can be inserted in apertures of a circuit board. First bent portions of the terminal form contact edges which penetrate the insulation and contact the conductor if the cable

is pressed into the contact terminal from above. Second bent portions form a slot, the width thereof increasing toward the lower area so that the cable is secured against an outward movement from the slot. Further, the edges of the slot form indentations in the insulation so that a strain relief is contemporarily achieved. The known contact terminals are not suited for example in connection with telecommunication connectors structured as modules. A further disadvantage is that with larger diameter wires the danger is encountered that the edges of the slot dig into the insulation up to the conductor so that the conductor undesiredly is engaged. The cutting through the insulation also reduces or eliminates the strain relief. With the known contact terminal, the strain relief decreases with increasing wire diameter. Finally, the known terminal can be used only for a small diameter range.

The present invention provides a connector for insulated conductors, particularly for electrical telecommunication wherein the retaining means for the conductor is simply combined with a strain relief.

SUMMARY OF THE INVENTION

According to the invention, a connector for an electrical cable is provided as defined in Claim 1.

Thus, the invention may include an integrally molded basic body of plastic material having one or a plurality of passageways adapted to receive insulated conductors. In the connector according to the invention, flexible tongues are formed at opposing walls. The tongues, extend in a plane approximately perpendicular to the longitudinal axis of the passageway. At the free ends of the tongues, a relatively narrow slot is formed, the most narrow portion of the slot being adjacent the open upper side of the passageway and it has a width smaller than the diameter of the smallest cable for which the connector is suitable. The lower portion of the slot has a larger width so that by this, a movement of the cable out of the passageway is resisted. It is further essential to the invention that the tongues are shaped and are connected to the walls of the passageway such that the tongues are uni-directionally resiliently deformed toward one end of the passageway and toward the contacting element within the passageway. In other words, the ends of the tongues face toward the free end of the cable or opposite to the extraction direction so that an effective strain relief is achieved.

With the known connectors it may occur that the cables move out of the passageway as soon as the cover on the passageway is opened. This danger increases with increasing diameter of the cable. With the connector according to the invention, however, the strain relief increases with increasing diameter, the flexibility of the tongues being adapted to retain cables within a large diameter range. Depending on the elasticity and the strength of the insulating mate-

rial, the tongues mold into the insulating material more or less whereby the cable is effectively secured against displacement out of the connector. The deformation of the tongues and the embedding into the insulation are such that a cutting into the insulation and thus an elimination of the strain relief is avoided.

As already mentioned, it has to be assured that the tongues are deformed in a predetermined manner when the cable is pressed into the slot. In this connection, an embodiment of the invention provides that deflecting surfaces are formed on the tongues adjacent the slot which cause the tongues to be deformed resiliently by a cable such that the ends of the tongues face toward the cable end within the passageway. Different modifications for the deflecting surfaces can be used. According to an embodiment of the invention, the deflecting surfaces can be defined by chamfers formed at the side of the tongues oppositely located of the cable end. The chamfers form oblique surfaces which converge toward the cable end. They assure that both tongues are deflected toward the cable end.

If possible, the tongues should be deflected in total upon an insertion of the cable into the slot. An embodiment of the invention provides that the wall of the tongues facing away from the cable end merge into the wall of the passageway through a radius while the opposite wall of the tongues have a relieving flute adjacent the wall of the passageway. By such a hinging of the tongues to the passageway walls, the tongues can be relatively simply and uni-directionally deflected toward the cable end as the cable is pressed into the slot.

The entrance portion of the slot is funnel-like enlarged in an upward direction in order to facilitate the insertion of the cable.

BRIEF DESCRIPTION OF THE DRAWINGS

The invention is explained in more detail with reference to the accompanying drawings.

Figure 1 is a perspective view of a connector according to the invention.

Figure 2 is a cross-sectional view of part of the connector of Figure 1.

Figure 3 is a similar illustration as Figure 2 including a pressed-in cable as can be seen also in the right hand illustration of Figure 1.

Figure 4 is a front view of the illustration of Figure 2.

DETAILED DESCRIPTION OF THE DRAWINGS

Figure 1 shows a basic body 10 of a connector for electrical telecommunication cables. The basic body 10 is integrally molded of plastic material and shaped as a module. It includes two transverse passageways 11, 12 extending parallel at a distance from each

other throughout the width of the basic body 10. It is understood that the basic body 10 could have a greater length for the receipt of a plurality of cables. Furthermore, it can be combined with a cover which closes the passageways 11, 12 from above. Further, a plurality of such basic bodies 10 could be stacked with each upper basic body defining a cover for the lower one. Connectors of the kind described are generally known.

Known U-shaped contact elements 14 and 15 and knives 16 and 17 of metal are positioned in the passageways 11 and 12. An insulated conductor or cable 20 is introduced in the right passageway 12 from above with its front end being cut off by knife 17 while the contact element 15 cuts into the insulation cable 20 contacting the conductor of cable 20 in a manner known per se to establish an electrical contact.

Tongues 21, 22 and 23, 24, respectively, are formed at the walls of the passageways 11, 12 in front of the contact elements 14, 15. As can be particularly seen in Figures 1 and 2, passageways 11, 12, respectively, have recesses 25, 26 which are formed in the area of the tongues 21, 22 and 23, 24, respectively, whereby the joints of the tongues have a larger distance from each other so that they have a relatively large length. In the following, only tongues 21, 22 are described since the tongues 23, 24 are identically formed.

The tongues, 21, 22 merge into the passageway wall through a radius 27, 28 or radiused surface at the side facing away from the contact element 14. A flute 29, 30 is formed in the tongues 21, 22 adjacent the wall of the passageway on the side facing the contact element 14, whereby the thickness of the tongues 21, 22 is reduced. A slot 31 is formed between the free ends of tongues 21, 22 which continuously enlarges from the top to the bottom as can be seen in Figure 4. The most narrow width of the slot 31 is such that it is smaller than the diameter of the smallest cable to be inserted in passageway 11. Oblique surfaces or chamfers 32, 33 are formed on the side of the tongues 21, 22 facing away from the contact element 14. The chamfers 32, 33 are reduced in width toward the bottom of the passageway as can be seen in Figure 1. As can be particularly seen in Figure 4, the entrance portion of slot 31 is funnel-like, enlarged in its upward direction as shown at 34.

In Figure 3 a cable 40 can be seen including a conductor wire 41 and an insulation 42 which is pressed into passageway 11. The chamfers 32, 33 on the tongues 21, 22 cause the tongues to be deformed toward one end of the passageway 11 upon insertion of the cable 40 from above the passageway and the free end of the tongues 21, 22 being engaged by the insulation cause the insulation to be deformed and indentations are formed in the insulation by which a retraction of cable 40 in direction of arrow F is restricted. A

force on the cable 40 in the direction of the arrow F causes the tongues to bite deeper into the cable insulation. The cable 40 within passageway 12 deforms the tongues 23, 24 in a corresponding manner. It can be seen in Figure 3 that the tongues 21, 22 are deflected in total by their hinging to the walls of the passageway toward the contact element. It is understood that by a corresponding shape of the tongues 21, 22 or by a corresponding hardness of the insulation 42, the tongues themselves could be deformed or bent in order to achieve a strain relief. It can be recognized moreover that the strain relief increases with increasing diameter of cable 40. The cable 40 is retained within the passageway in that the slot 30 narrows upwardly whereby movement of the cable upward out of the slot is also resisted.

As can be seen in Figure 4, the tongues 20, 21 are free to move relative to the bottom of recesses 25, 26 of the passageway 11, 12, the bottom being indicated at 60.

Claims

1. A connector for an electrical cable, particularly for electrical telecommunication, comprising a housing of plastic material including a basic body having at least one transverse passageway (11, 12), which passageway (11, 12) has an open upper side and an axis, a contacting element (14, 15) disposed in said passageway (11, 12) and flexible retaining elements integrally formed with said basic body and being positioned in said passageway (11, 12), said elements being suitable to be resiliently deformed when said cable (20, 40) is introduced into said passageway (11, 12) from above to retain said cable (20, 40) against outward movement, said flexible elements being tongues (21, 22, 23, 24) formed on opposite walls of said passageway (11, 12), the free opposing ends of said tongues (21, 22, 23, 24) forming a narrow slot (31) having a first entrance portion which is funnel-like enlarged in the direction of the open side of said passageway (11, 12) the most narrow portion (34) of said slot (31) being adjacent the open upper side of the passageway and having a width smaller than the diameter of the smallest cable (20, 40) for which the connector (10) is suitable, said slot (31) enlarges toward the bottom of said passageway (11, 12) such that the portion of said slot (31) adjacent the bottom of said passageway (11, 12) has a larger width than the most narrow portion of said slot (31), wherein said slot (31) continuously enlarges toward the bottom of said passageway (11, 12) below said most narrow portion (34), said tongues (21, 22, 23, 24) extend in a plane approximately perpendicular to said axis and said tongues (21,

22, 23, 24) being hinged to the wall of said passageway (11, 12) and are shaped such that said tongues (21, 22, 23, 24) are resiliently deformed toward one end of said passageway (11, 12) and toward the contacting element (14, 15) within said passageway (11, 12) when a cable is inserted into said passageway (11, 12) from above.

2. The connector according to claim 1, characterized in that deflecting surfaces (32, 33) are formed on said tongues (21, 22, 23, 24) adjacent said slot (31, 31').
3. The connector according to claim 2, characterized in that said deflecting surfaces are defined by chamfers (32, 33) which are formed at the sides of said tongues (21, 22) facing away from said contacting element.
4. The connector according to one of the claims 1 to 3, characterized in that said tongues (21, 22, 23, 24) merge into the wall of the passageway through a radius (27, 28) on the side facing away from said contacting element while a relieving flute (29, 30) is formed into the tongue adjacent said wall of the passageway on the side of said tongues facing said contacting element.
5. The connector according to one of the claims 1 to 4, characterized in that the tongues (21, 22, 23, 24, 21', 22') are at least partially free to move relative to the bottom (60, 60') of said passageway.

Patentansprüche

1. Verbinder für einen isolierten Leiter, insbesondere für elektrische Telekommunikation, mit einem Gehäuse aus Kunststoffmaterial, das ein Basisteil mit mindestens einem querlaufenden Kanal (11, 12) aufweist, wobei der Kanal (11, 12) eine offene Oberseite und eine Achse, ein in dem Kanal (11, 12) angeordnetes Kontaktierungselement (14, 15) und flexible, einteilig mit dem Basisteil geformte und in dem Kanal (11, 12) positionierte Halteelemente hat, die Elemente geeignet sind, elastisch verformt zu werden, wenn der Leiter in den Kanal (11, 12) von oben eingesetzt wird, um den Leiter (20, 40) gegenüber einem Herausbewegen aus dem Kanal zu halten, die flexiblen Elemente auf gegenüberliegenden Wänden des Kanals (11, 12) angeformte Zungen (21, 22, 23, 24) sind, deren freie, einander zugekehrte Enden einen engen Spalt (31) bilden, der einen ersten, trichterartig in Richtung der offenen Seite des Kanals (11, 12) vergrößerten Eingangsabschnitt hat, der engste Bereich (34) des Spalts (31) an die offene Oberseite des Kanals



force on the cable 40 in the direction of the arrow F causes the tongues to bite deeper into the cable insulation. The cable 40 within passageway 12 deforms the tongues 23, 24 in a corresponding manner. It can be seen in Figure 3 that the tongues 21, 22 are deflected in total by their hinging to the walls of the passageway toward the contact element. It is understood that by a corresponding shape of the tongues 21, 22 or by a corresponding hardness of the insulation 42, the tongues themselves could be deformed or bent in order to achieve a strain relief. It can be recognized moreover that the strain relief increases with increasing diameter of cable 40. The cable 40 is retained within the passageway in that the slot 30 narrows upwardly whereby movement of the cable upward out of the slot is also resisted.

As can be seen in Figure 4, the tongues 20, 21 are free to move relative to the bottom of recesses 25, 26 of the passageway 11, 12, the bottom being indicated at 60.

Claims

1. A connector for an electrical cable, particularly for electrical telecommunication, comprising a housing of plastic material including a basic body having at least one transverse passageway (11, 12), which passageway (11, 12) has an open upper side and an axis, a contacting element (14, 15) disposed in said passageway (11, 12) and flexible retaining elements integrally formed with said basic body and being positioned in said passageway (11, 12), said elements being suitable to be resiliently deformed when said cable (20, 40) is introduced into said passageway (11, 12) from above to retain said cable (20, 40) against outward movement, said flexible elements being tongues (21, 22, 23, 24) formed on opposite walls of said passageway (11, 12), the free opposing ends of said tongues (21, 22, 23, 24) forming a narrow slot (31) having a first entrance portion which is funnel-like enlarged in the direction of the open side of said passageway (11, 12) the most narrow portion (34) of said slot (31) being adjacent the open upper side of the passageway and having a width smaller than the diameter of the smallest cable (20, 40) for which the connector (10) is suitable, said slot (31) enlarges toward the bottom of said passageway (11, 12) such that the portion of said slot (31) adjacent the bottom of said passageway (11, 12) has a larger width than the most narrow portion of said slot (31), wherein said slot (31) continuously enlarges toward the bottom of said passageway (11, 12) below said most narrow portion (34), said tongues (21, 22, 23, 24) extend in a plane approximately perpendicular to said axis and said tongues (21,

22, 23, 24) being hinged to the wall of said passageway (11, 12) and are shaped such that said tongues (21, 22, 23, 24) are resiliently deformed toward one end of said passageway (11, 12) and toward the contacting element (14, 15) within said passageway (11, 12) when a cable is inserted into said passageway (11, 12) from above.

2. The connector according to claim 1, characterized in that deflecting surfaces (32, 33) are formed on said tongues (21, 22, 23, 24) adjacent said slot (31, 31').
3. The connector according to claim 2, characterized in that said deflecting surfaces are defined by chamfers (32, 33) which are formed at the sides of said tongues (21, 22) facing away from said contacting element.
4. The connector according to one of the claims 1 to 3, characterized in that said tongues (21, 22, 23, 24) merge into the wall of the passageway through a radius (27, 28) on the side facing away from said contacting element while a relieving flute (29, 30) is formed into the tongue adjacent said wall of the passageway on the side of said tongues facing said contacting element.
5. The connector according to one of the claims 1 to 4, characterized in that the tongues (21, 22, 23, 24, 21', 22') are at least partially free to move relative to the bottom (60, 60') of said passageway.

Patentansprüche

1. Verbinder für einen isolierten Leiter, insbesondere für elektrische Telekommunikation, mit einem Gehäuse aus Kunststoffmaterial, das ein Basisteil mit mindestens einem querlaufenden Kanal (11, 12) aufweist, wobei der Kanal (11, 12) eine offene Oberseite und eine Achse, ein in dem Kanal (11, 12) angeordnetes Kontaktierungselement (14, 15) und flexible, einteilig mit dem Basisteil geformte und in dem Kanal (11, 12) positionierte Halteelemente hat, die Elemente geeignet sind, elastisch verformt zu werden, wenn der Leiter in den Kanal (11, 12) von oben eingesetzt wird, um den Leiter (20, 40) gegenüber einem Herausbewegen aus dem Kanal zu halten, die flexiblen Elemente auf gegenüberliegenden Wänden des Kanals (11, 12) angeformte Zungen (21, 22, 23, 24) sind, deren freie, einander zugekehrte Enden einen engen Spalt (31) bilden, der einen ersten, trichterartig in Richtung der offenen Seite des Kanals (11, 12) vergrößerten Eingangsabschnitt hat, der engste Bereich (34) des Spalts (31) an die offene Oberseite des Kanals



angrenzt und eine Breite hat, die kleiner ist als der Durchmesser des kleinsten Leiters (20, 40), für den der Verbinder (10) geeignet ist, der Schlitz (31) sich zum Boden des Kanals (11, 12) hin vergrößert, so daß der an den Boden des Kanals (11, 12) angrenzende Bereich des Spalts (31) eine größere Breite aufweist als der engste Bereich des Spalts (31), wobei der Spalt (31) sich kontinuierlich zum Boden des Kanals (11, 12) hin unterhalb des engsten Bereichs (34) vergrößert, die Zungen (21, 22, 23, 24) sich in einer zu der Achse ungefähr senkrechten Ebene erstrecken und die Zungen (21, 22, 23, 24) an die Wand des Kanals (11, 12) angelenkt und so geformt sind, daß die Zungen (21, 22, 23, 24) elastisch zu einem Ende des Kanals (11, 12) und dem Halteelement (14, 15) hin innerhalb des Kanals (11, 12) verformt werden, wenn ein Leiter von oben in den Kanal (11, 12) eingesetzt wird.

2. Verbinder gemäß Anspruch 1, dadurch gekennzeichnet, daß nahe dem Spalt (31) Ablenkflächen (32, 33) auf den Zungen (21, 22, 23, 24) geformt sind.
3. Verbinder gemäß Anspruch 2, dadurch gekennzeichnet, daß die Ablenkflächen von Fasen (32, 33) gebildet sind, die an den dem Kontaktierungselement entgegengesetzten Seiten der Zungen (21, 22) geformt sind.
4. Verbinder gemäß einem der Ansprüche 1 bis 3, dadurch gekennzeichnet, daß die Zungen (21, 22, 23, 24) auf der vom Kontaktierungselement abgewandten Seite in einem Radius (27, 28) in die Kanalwand übergehen, während auf der gegenüberliegenden Seite eine entlastende Kehle (29, 30) neben der Kanalwand in die Zunge eingeformt ist.
5. Verbinder nach einem der Ansprüche 1 bis 4, dadurch gekennzeichnet, daß die Zungen (21, 22, 23, 24) zumindest teilweise frei sind, um sich relativ zu dem Boden (60) des Kanals zu bewegen.

Revendications

1. Connecteur pour un câble électrique, en particulier pour de la télécommunication électrique, qui comprend une boîte de matière plastique comprenant un corps de base ayant au moins un passage transversal (11, 12), qui a un côté supérieur ouvert et un axe, un élément de contact (14, 15) disposé dans le passage (11, 12) et des éléments flexibles de retenue faisant intégralement partie du corps de base et étant positionnés dans le passage (11, 12), ces éléments étant adaptés

pour être déformés de façon élastique quand le câble (20, 40) est introduit dans le passage (11, 12) par le haut pour retenir le câble (20, 40) d'un mouvement vers l'extérieur, les éléments flexibles étant des languettes (21, 22, 23, 24) formées sur des parois opposées du passage (11, 12), les bouts libres opposés des languettes (21, 22, 23, 24) formant une fente étroite (31) ayant une première partie d'entrée qui est élargie comme un entonnoir dans la direction du côté ouvert du passage (11, 12), la partie la plus étroite (34) de la fente (31) étant près du côté supérieur ouvert du passage et ayant une largeur plus petite que le diamètre du câble le plus mince (20, 40) pour lequel le connecteur (10) convient, la fente (31) s'élargissant vers le fond du passage (11, 12) de telle façon que la partie de la fente (31) près du fond du passage (11, 12) ait une largeur plus grande que la partie la plus étroite de la fente (31), la fente (31) s'élargissant continuellement vers le fond du passage (11, 12) en dessous de la partie la plus étroite (34), les languettes (21, 22, 23, 24) s'étendant dans un plan à peu près perpendiculaire à l'axe et les languettes (21, 22, 23, 24) étant attachées à la paroi du passage (11, 12) et ayant une forme telle que les languettes (21, 22, 23, 24) sont déformées de façon élastique vers une extrémité du passage (11, 12) et vers l'élément de contact (14, 15) à l'intérieur du passage (11, 12) quand un câble est introduit dans le passage (11, 12) par le haut.

2. Connecteur selon la revendication 1, caractérisé en ce que des surfaces de déviation (32, 33) sont formées sur les languettes (21, 22, 23, 24) près de la dite fente (31, 31').
3. Connecteur selon la revendication 2, caractérisé en ce que les surfaces de déviation sont définies par des biseaux (32, 33) qui sont formés aux côtés des languettes (21, 22) situées à l'opposé des éléments de contact.
4. Connecteur selon l'une des revendications 1 à 3, caractérisé en ce que les languettes (21, 22, 23, 24) se fondent dans la paroi du passage par un arrondi (27, 28) du côté situé à l'opposé de l'élément de contact tandis qu'une rainure de dépouille (29, 30) est formée dans la languette près de la paroi du passage du côté des languettes faisant face à l'élément de contact.
5. Connecteur selon l'une des revendications 1 à 4, caractérisé en ce que les languettes (21, 22, 23, 24, 21', 22') sont au moins partiellement libres de se déplacer de façon relative au fond (60, 60') du passage.