

LASER RADIATION DESORPTION DEVICE FOR MANIPULATING A LIQUID
SAMPLE IN THE FORM OF INDIVIDUAL DROPS, THEREBY MAKING IT
POSSIBLE TO CARRY OUT THE CHEMICAL AND BIOLOGICAL TREATMENT
THEREOF

5

This present invention concerns an integrated system for the microfluidic analysis of a liquid sample, which in particular though not uniquely, finds its application in analysis by laser radiation desorption, which includes
10 handling the liquid sample in the form of individual drops to allow their chemical and biological treatment.

Desorption by laser radiation allows the vaporisation of a substance present on a surface. This effect combines with ionisation molecules present at the surface. This phenomenon
15 has been used in mass spectrometry under the name of MALDI (matrix assisted laser desorption ionisation) in which the energy of the laser beam is stored and then restored by the matrix, which is organic in most cases but which can also contain nanoparticles whose absorption is in the wavelength
20 range of the laser beam.

In order to achieve satisfactory results in MALDI mass spectrometry, the sample must contain a very small quantity of inorganic salts, typically a concentration of the order of less than one in a thousand. Typically the sample is therefore
25 demineralised before its analysis by MALDI mass spectrometry, and this is followed by additional stages, and reduces the sensitivity of the method. The techniques most used currently are demineralisation in hydrophobic columns of the grafted alkyl chain type. Special demineralisations using cationic or
30 anionic resins can also be used.

More generally, either wetting or hydrophylic additives can then be used in order to create wettability in relation to

any liquid, and non-wetting or hydrophobic additives to create non-wettability in relation to any liquid.

In addition, most biological samples are complex, and include hundreds or even thousands of different molecules. Typically, a tryptic digestate of the proteins contained in tissue contains ten thousand to one hundred thousand different peptides. This is why these samples are subjected to a preliminary fractionation, using affinity columns as in the ICAT technology (isotope coded affinity tags) which, in addition to its complexity, considerably reduces the sensitivity of the method. These biological samples are moreover available in very small quantities, and it is thus necessary to be in possession of a biopsy gram for the execution of a proteomic analysis, which renders these analyses impossible on human samples.

The MALDI technique is most frequently used on a metal surface. In order to minimise the drawbacks mentioned previously, various arrangements of these metal surfaces have been described. The first solutions had as their objective to improve sensitivity. To begin with, surfaces or only small zones are metallic, leading to a local concentration of the sample. In order to remove the salts, surfaces are created from a polymer of the brush type, which allows a demineralisation of the sample in situ. In order to perform the fractionating, surfaces of the cationic or anionic resin type allow the immobilisation of a single family of compound of opposite polarity. And finally, surfaces are grafted by biological compounds (biotine, avidine, antibodies) to allow purification by affinity of complex mixtures.

All of these surfaces are static and include no fluidic system allowing the movement and the treatment of the sample on the plate. Deposition is effected either manually or by an

automatic control system that includes a head for the aspiration-deposition of an external liquid.

The microfluidic technique is currently becoming very popular, and is attempting to introduce innovative solutions, with new methods of analysis for example, in the areas of biology, analytical chemistry and chemical engineering. The reduction in the size of the systems is engendering many positive aspects such as a reduction in volumes, shorter reaction times or shorter exchange times, and the integration of several modules with different functions, such as transportation, treatment and analysis modules on a single wafer of silicon for example.

Two types of fluidic movement are possible, namely the pumping of a continuous flow and the movement of calibrated microvolumes of liquid. The pumping of calibrated microvolumes requires smaller volumes of liquid than continuous flow pumping, and allows easier control of the flow. By control of the time constants, the mixing of liquids for example, are thus easier to perform. Several pumping methods of this type are described in the literature, employing pumping by pneumatic action or by acoustic surface waves, pumping by dielectrophoretic effect, and pumping by electrowetting and electrowetting on dielectric. This last pumping method makes use of a simple technological process, and allows control over the flow and the circulation of the liquid in a network of microchannels.

Currently, the movement devices using the electrowetting principle require two substrates opposite to each other, or one single substrate (Creating, Transporting, Cutting, and Merging Liquid Droplets by Electrowetting-Based Actuation for Digital Microfluidic Circuits" Sung Kwon Cho, Hyejin Moon, and Chang-Jin Kim, Journal of Microelectromechanical Systems, VOL. 12, No. 1, Feb. 2003, pp. 70-80).

The system with two substrates opposite to each other requires interdigitated electrodes on at least one of the two substrates, at least one insulating layer composed of inorganic oxides of non-metal metals, of transition metals, of polymers or of a combination of these different substances on one of the two substrates, and a hydrophobic layer on each substrate. The system with one single substrate requires interdigitated electrodes, an insulating layer composed of inorganic oxides of non-metal metals, of transition metals, of polymers or of a combination of these different substances, and a hydrophobic layer, with or without an earth line. The hydrophobic layer is the key of the movement, without which the movement is impossible as it is described in the article mentioned (Electrowetting-based microfluidic devices: design issues, C.Y. Chen, E.F. Fabrizio, A. Nadim and J.D. Sterling, Summer Bioengineering Conference 2003, pp. 1241-1242).

The hydrophobic layer is a material with a low surface energy and an excellent chemical resistance. As a consequence, it is very difficult to perform local chemical surface treatment, depositions or grafts on a hydrophobic layer without changing and/or damaging the whole of the surface of this hydrophobic layer, and this reduces or cancels out the effectiveness of the electrowetting regarding the movement of liquid. Thus, the use of this system covered by a hydrophobic layer is mainly limited to liquid movement only.

Thus in order to achieve a system that allows the treatment of biological samples for example, it is necessary to have functionalised zones that interact with the liquid. Now the hydrophobic layer forbids any prior functionalisation of zones with which the liquid may be in contact. In order to remedy this, the proposed solution consists of creating hydrophilic openings in the hydrophobic material. These hydrophilic openings, which are also known as open zones or

openings, can then be treated chemically and the liquid can interact with this surface.

This present invention concerns devices for desorption by laser radiation that include handling the liquid sample in the form of individual drops to allow chemical and biological treatment.

In accordance with a first aspect of the present invention, there is provided a device for laser radiation desorption analysis of a liquid sample comprising drops, including means for moving the said drops of the said sample, and at least one means for routing the drops to at least one independent analysis pad, characterized in that the said moving means, includes at least one conducting pad, covered by a partially wetting layer that includes at least one wetting zone opposite to the said conducting pad.

The device for desorption by laser radiation may include at least one pad for loading the liquid sample, at least one transportation track composed of interdigitated electrodes, at least one chemical or biochemical treatment zone, and a system for routing to at least one conducting pad where a process of desorption by laser radiation can be effected.

Embodiments of the invention may take the form of an insulating substrate onto which interdigitated electrodes are placed, isolated from the samples moved via an insulating and functionalisable upper layer, of inorganic oxides of non-metals, metals, transition metals or polymers, or of a combination of these different substances. A non-wetting layer, allowing the appearance of wetting zones, may then be deposited. This layer, said to be partially wetting, may allow the functionalisable insulation layer to appear. After treatment, these openings in the non-wetting layer may constitute the functionalised zones of the treatment module.

The system can come in the form of two substrates opposite to each other. On one of the substrates, there rests

a transportation track for the samples or reagents. The functionalised zones rest on the second substrate. The whole of the two substrates may be separated by a space that is intended to be filled with an electrically insulating fluid which may not be miscible in relation to the liquids transported.

In addition to a treatment module, the system can also include:

- a module which allows the introduction of a biological sample, as well as of the liquids necessary for the analysis (rinsing solution, etc.),

- a module used for the the fractionation of liquids into several drops,

- one or more biochemical interaction modules. Example for the analysis of proteins - affinity, digestion, demineralisation module,

- a transition module between the treatment zone and the analysis zone,

- an analysis module which, for example, places the samples to be analysed on pads where a matrix can be added, and on which an analysis by mass spectrometry of the MALDI type is possible, or indeed by optical detection or fluorescence.

In accordance with a second aspect of the present invention, there is provided an integrated system for the microfluidic analysis of a liquid sample that includes at least one means (100) for preparing the liquid sample, where the said preparation means (100) includes a moving means (101) for the introduction of the said sample and of reagents, and then their migration to at least one means (200) for the chemical or biochemical treatment of drops of the said liquid sample, with the said treatment means (200) including means (201) for moving the said drops of the said sample, and then their migration to at least one means (300) for the analysis of the said drops of the said liquid sample, with the said analysis means being an analysis means by laser radiation desorption and including firstly means for moving the said drops of the said sample,

and secondly at least one means for routing the drops to independent analysis pads, characterized in that at least one of the said moving meanss includes at least one conducting pad covered by a partially wetting layer that includes at least one wetting zone opposite to the said conducting pad.

The means (100) for preparing the liquid sample can include at least a liquid loading dock.

The preparation means (100) can include at least one zone (102) for the deposition of liquid.

At least one of the moving meanss (101, 201, 301) can include at least one conducting pad, covered by a partially wetting layer that includes at least one wetting zone facing the said conducting pad.

The system can also include an insulating layer inserted between the conducting pad and the partially wetting layer.

The wetting zones may be functionalised, chemically or biochemically.

The means (201) for moving, in the chemical or biochemical treatment means (200), can include two substrates, opposite to each other, and/or at least one means for the fractionating of one drop from several, and/or at least one means for the removal of excess or exhausted reagents.

At least one of the moving meanss (101, 201, 301) may be of the movement by electrowetting on dielectric type.

The chemically or biochemically functionalised zones may be hydrophilic zones for interaction with the moved liquid.

The analysis means (300) may include means for analysis of the MALDI type by laser radiation with desorption-ionisation, and/or of the optical detection type.

Embodiments of the invention may also relate to a device (300) for the analysis of a liquid sample by laser radiation desorption, characterised in that it includes means (301) for moving the drops of the sample, and at least one means for routing the drops to independent analysis pads.

The moving means (301) can possibly include at least one conducting pad, covered by a partially wetting layer that includes at least one wetting zone opposite to the said conducting pad.

Preferably, the device includes an insulating layer inserted between the conducting pad and the said partially wetting layer.

Possibly, the wetting zones are functionalised chemically or biologically. These zones can be hydrophilic zones for interaction with the moved liquid.

Again preferably, the moving means (301) is of the movement by electrowetting on dielectric type. The device can possibly finally include an analysis means of the MALDI type by laser radiation desorption-ionisation, and/or of the optical detection type.

Other characteristics and advantages of the invention will appear more clearly and more fully on reading the description that follows of the preferred implementation variants for execution of the method and for creation of the device, which are given by way of non-limiting examples and with reference to the following appended drawings:

- figures 1a to 1c schematically present a device for the analysis of biological samples, with integrated MALDI target;
- figure 2 schematically presents a device for moving a drop between 2 tracks;
- figure 3 schematically presents a device for moving a drop between 2 tracks, with functionalised zones on the upper track;
- figure 4 schematically presents a device for moving a drop on a track;
- figure 5 schematically presents a device for the analysis of biological samples by MALDI mass spectrometry;
- figure 6 schematically presents a device for the analysis of proteins from biological samples, with MALDI target integrated with 3 biochemical treatments before analysis (concentration, digestion and demineralisation).

Figures 1a to 1c schematically show a device for the analysis of biological samples, with MALDI target, seen in perspective in 1a and 1b, and seen in section perpendicular to the direction for moving the drop in 1c.

5 In these figures 1a to 1c, the device includes a track with a substrate 1. The interdigitated electrodes 2 are located above this substrate 1.

On these electrodes 2 there is an insulating dielectric layer 3, composed, for example, of oxides or polymers. On this
10 electric insulating layer 3 there is a non-wetting layer 4. Between layer 3 and layer 4, a conducting line 5 acts as a counter-electrode.

Opposite to the first track is placed a second track formed from a partially wetting layer 6, itself covered with a
15 top layer 7 on which biochemical functions 8 can be grafted. The layer 7 is on a substrate 9 that can be used as a counter-electrode. The use of spacers 10 allows a movement space 11 to be maintained, intended to be filled with an electrically insulating fluid which is non-miscible in relation to the drop
20 transported. On this substrate, the pads 12 are conductors and are used to immobilise the drops transporting the materiel to be analysed before matrix deposition for the MALDI analysis.

The liquids (the drops of samples or reagents for example) are deposited on the pad 13. The liquid then enters
25 into the chemical or biochemical treatment zone between the substrates 1 and 9, and interacts with the functionalised zones 8. The movement pads 2 then allow the conveyance of each individual drop (14) up to one of the pads 12. Then follows a stage of matrix deposition, crystallisation and MALDI
30 analysis.

Figure 2 schematically shows the movement of a drop between two tracks, seen in section in the direction of the movement. The device includes a first track composed of layers

1, 2, 3, and 4, and a second track composed of layer 7, a substrate 9, and a non-wetting layer 15. By putting a potential difference between electrode 2b and substrate 9, the drop is contained between electrode 2b and substrate 9, and the result is a movement of the drop from electrode 2a to electrode 2b.

Figure 3 schematically presents a device for moving a drop 14 between two tracks with functionalised zones on the upper track, seen in section in the direction of the movement. The device includes a first track composed of layers 1, 2, 3, and 4, and a second track composed of layers 6 and 7, a substrate 9 and functionalised zones 8a to 8d. By putting a potential difference between electrode 2b and substrate 9, the drop is contained between electrode 2b and substrate 9, and the result is a movement from electrode 2a to electrode 2b. The drop then interacts with the functionalised zone 8c and 8d.

Figure 4 schematically presents a device for moving a drop on a track. Figure 4a is seen in section perpendicular to the direction of the movement of the drop, and figure 4b is a top view of the device. The device includes a track composed of layers 1, 2, 3, 4 and 5. By putting a potential difference between electrode 2c and line 5, the result is a movement of the drop (14) from electrode 2b to electrode 2c.

Figure 5 presents, schematically and in perspective, a device for the analysis of biological samples by MALDI mass spectrometry. By successively applying potential differences between electrodes 2a to 2h and line 5, it is possible to move the drop 14 and to immobilise it on one of the pads 12a to 12f. Then follows a stage of matrix deposition, crystallisation and MALDI analysis.

Figures 6a to 6c schematically show a device for the analysis of proteins of biological samples with integrated

targets, with three chemical or biochemical treatments before analysis (concentration, digestion and demineralisation) seen in perspective 6a and 6b, and seen in section perpendicular to the direction of the movement of the drop 6c.

5 The device includes a first track composed of layers 1, 2, 3, 4 and 5, a second track composed of layers 6 and 7, a substrate 9 and spacers 10. This device includes a pad 16 allowing the removal of excess or exhausted reagents, pads 12 for the MALDI analysis, and three functionalised zones for the
10 affinity 8a, for the digestion 8b and for the demineralisation 8c.

 The liquids (sample, reagent or rinsing drops for example) are deposited on the pads 13. The liquid then enters into the biochemical treatment zone between substrates 1 and 9
15 as a result of applying a potential difference. The transition between pads 17a and 17b allows fractionation of the liquid introduced in several drops. The drops are then routed to a first affinity pad 8a where the proteins of interest will be fixed. The drops are then conducted up to pad 16. A rinsing
20 solution is then used to rinse the pad 8a using the same movement principle as previously. Then, a special solution (such as a denaturing buffer mixture) is used to free the molecules of interest and the proteins are brought to a protein digestion pad 8b. After the digestion stage, the drop
25 is routed onto the demineralisation pad 8c before being conducted to one of the pads for the analysis of the MALDI type.

 The following examples illustrate the functionalisation and the use of the devices described previously:

30

Example 1. Affinity reactor used for the treatment of biological samples.

In the device, the zones not covered by the hydrophobic layer are subjected to surface treatment and transform them into reactive surfaces for example, using a surface support that includes amino groups (NH₂) onto which streptavidine is grafted. The drop of liquid moving in the electrode path in a treated zone is thus immobilised, and the molecules of interest (proteins for example) which have an affinity for the grafted surfaces will be fixed onto these surfaces. When the chemical reaction has ended, the drop continues on its way in the device. Then, the passage of a special mixture (a denaturing buffer mixture for example) on these zones will free the molecules of interest (with destruction of the non-covalent reactions, for example) and will draw them along with it. This device is thus used to isolate molecules of interest.

Example 2. Digestion reactor used for the treatment of biological samples.

In the device, the zones not covered by the hydrophobic layer are subjected to surface treatment which converts them into reactive surfaces for example, using a surface support that includes amino groups (NH₂) onto which trypsin is grafted. The drop of liquid moving in the electrode path in a treated zone is thus immobilised, and the molecules of interest (proteins for example) react with the grafted surfaces which cuts the molecules, so as to obtain peptides for example in the case of digestion by trypsin. Then the drop continues on its way in the device. This device can be used for example to analyse long chains of molecules by prior cutting using special enzymes by mass spectrometry.

Example 3. Treatment of biological samples - demineralisation module.

In the device, the zones not covered by the hydrophobic layer are subjected to surface treatment which converts them into reactive surfaces for example by the grafting of hydrocarbonated chains of 18 carbons leading to the equivalent of a reverse chromatography phase known as C18. The drop of liquid moving in the electrode path on a treated zone is thus immobilised, and the molecules of interest (proteins for example) react with the grafted surfaces which cut the molecules. Then the drop continues on its way in the device. This device can be used, for example, to perform demineralisation before analysis by MALDI mass spectrometry.

CLAIMS

1. A device for laser radiation desorption analysis of a liquid sample comprising drops, including means for moving the said drops of the said sample, and at least one means for routing the drops to at least one independent analysis pad, characterised in that the said moving means, includes at least one conducting pad, covered by a partially wetting layer that includes at least one wetting zone opposite to the said conducting pad.

2. A device according to claim 1, characterised in that it includes an insulating layer inserted between the said conducting pad and the said partially wetting layer.

3. A device according to either of claims 1 and 2, characterised in that the said wetting zones are functionalised chemically or biochemically.

4. A device according to claim 3, characterised in that the said chemically or biochemically functionalised zones are hydrophilic zones of interaction with the moved liquid.

5. A device according to any of claims 1 to 4, characterised in that the moving means is of the movement by electrowetting on dielectric type.

6. A device according to any of claims 1 to 5, characterised in that it includes an analysis means of the MALDI type by laser radiation desorption-ionisation, and/or of the optical detection type.

7. An integrated system for the microfluidic analysis of a liquid sample that includes at least one means for preparing the liquid sample, where the said preparation means includes a moving means for the introduction of the said sample and of reagents, and then their migration, to at least one means for the chemical or biochemical treatment of drops of the said liquid sample, with the said treatment means including means for moving the said drops of the said sample and then their migration to at least one means for analysis of the said drops of the said liquid sample, with the said analysis means being an analysis means by laser radiation desorption and including firstly means for moving the said drops of the said sample, and secondly at least one means for routing the drops to independent analysis pads, characterised in that at least one of the said moving means includes at least one conducting pad covered by a partially wetting layer that includes at least one wetting zone opposite to the said conducting pad.

8. A system according to claim 7, characterised in that the said means for preparing the liquid sample includes at least one liquid loading dock.

9. A system according to either of claims 7 and 8, characterised in that the said preparation means includes at least one zone for the deposition of liquid.

10. A system according to either of claims 7 to 9, characterised in that it includes an insulating layer inserted between the said conducting pad and the said partially wetting layer.

11. A system according to any of claims 7 to 10, characterised in that the said wetting zone is functionalized chemically or biochemically.

12. A system according to claim 11, characterised in that the chemically or biochemically functionalised zone is a hydrophilic zone of interaction with the moved liquid.

13. A system according to any of claims 7 to 12, characterised in that the said means for moving in the said chemical or biochemical treatment means includes two substrates opposite to each other, and/or at least one means for fractionating one drop in several, and/or at least one means for removing excess or exhausted reagents.

14. A system according to any of claims 7 to 13, characterised in that at least one of the said moving means is of the movement by electrowetting on dielectric type.

15. A system according to any of claims 7 to 14, characterised in that the analysis means includes an analysis means of the MALDI type by laser radiation desorption-ionisation, and/or of the optical detection type.