Image Forming System in Which Image Processing Apparatus Is Connected to Image Forming Apparatus

BACKGROUND OF THE INVENTION

Field of the Invention

The present invention relates to an image forming system in which an image processing apparatus is connected to an image forming apparatus.

Related Background Art

Conventionally, an image formed by a personal computer or the like is printed out by a printer. However, such a printer has only one ejecting paper tray and cannot sort printed recording paper sheets. A printer has been proposed which is connected to a sorter so as to sort printed recording paper sheets. However, such a printer only controls the storage destination in the sorter from the printer side. An operator operating in front of a personal computer has no means for detecting a specific storage unit in the sorter, resulting in difficulty in finding recorded paper sheets destinated for the operator.

REPLACED SHEETS SG
☑ Description : paged ...1.... to paged ...11a....
☑ Claim(s) : paged ...12.... to paged ...20....
☑ Drawing(s) : paged ...1/6.... to paged ...6/6....
☑ Abstract : paged ...21.... to paged .....
DATE OF RECEIPT .....

This Sheet Has Been Replaced

SUMMARY OF THE INVENTION

It is an object of the present invention to provide an image forming system for solving the above problem.

It is another object of the present invention to provide an image forming system in which an operator can detect the status of each storage unit of an image forming apparatus from an image processing apparatus side, thereby selecting the storage unit.

It is still another object of the present invention to provide an image forming system in which an operator at an image processing apparatus can certify an automatically selected storage unit of an image forming apparatus.

It is still another object of the present invention to provide an image forming system in which the operator at an image processing apparatus can change an automatically selected storage unit of an image forming apparatus.

Other objects and features of the invention will be apparent from the following detailed description in conjunction with the accompanying drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

Fig. 1 is a block diagram showing an image forming system of an embodiment of the present invention;

This Sheet Has Been Replaced

Fig. 2 is a view showing the outer appearance of the image forming system;

Fig. 3 is a view for explaining a communication operation of the image forming system;

Fig. 4 is a view for explaining a communication operation of the image forming system;

Fig. 5 is a view for explaining a communication operation of the image forming system;

Fig. 6 is a view for explaining a communication operation of the image forming system; and

Fig. 7 is a view for explaining a communication operation of the image forming system.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

[First Embodiment]

Figs. 1 to 3 are views showing the first embodiment of the present invention. Referring to Figs. 1 and 2, an image forming apparatus 1 records image data from a computer 8. A sensor 2 detects the presence/absence of recording paper sheets on an ejecting paper tray 13. A sensor 3 detects the presence/absence of recording paper sheets on an ejecting paper tray 14. A sensor 4 detects the presence/absence of recording paper sheets on an ejecting paper tray 15. A control circuit 5 controls all operations in the image forming apparatus, including processing of signals from the sensors 3 to

This Sheet Has Been Replaced

4. An ejecting paper tray switching unit 6 switches the ejecting paper tray for receiving recording paper sheets in accordance with a signal from the control circuit. An interface (I/F) 7 on the image forming apparatus side connects the image forming apparatus 1 to the computer 8 through communication. The computer 8 generates or stores image data. An interface (I/F) 9 on the computer 8 side connects the image forming apparatus 1 to the computer 8 through communication. A CPU 10 controls the computer 8. A keyboard 11 is used by an operator to input an instruction to the computer 8. A CRT 12 serves as the display unit of the computer 8. The ejecting paper tray 13 serves as one of the storage units for storing recording paper sheets. The ejecting paper tray 14 serves as one of the storage units for storing recording paper sheets. The ejecting paper tray 15 serves as one of the storage units for storing recording paper sheets. A cable 16 connects the image forming apparatus 1 to the computer 8 for communication. Recording paper sheets 17 are selectively ejected onto the ejecting paper trays. The operation of the first embodiment is sequentially described in Fig. 3.

The operation in the above arrangement will be described below with reference to Fig. 3.

When an image generated or stored in the computer 8 is to be printed out, the operator inputs a print

This Sheet Has Been Replaced



instruction from the keyboard 11 to the computer 8. Upon reception of this instruction, the CPU 10 of the computer 8 transmits a printer occupancy command to the image forming apparatus 1 through the I/F 9. Upon reception of the printer occupancy command through the I/F 7, the control circuit 5 of the image forming apparatus 1 certifies the occupancy status of the image forming apparatus itself. If a recording enable state is set, a command for permission of occupancy is transmitted to the computer 8 (at this time, if the image forming apparatus is connected to a plurality of computers, and recording of an image from one of the remaining computers is being performed, or if the image forming apparatus singly has a copy function, and a copying operation is being performed, a command for rejection of occupancy is sent. However, this status is not the subject matter, and a detailed description thereof will be omitted).

Upon reception of the command for permission of occupancy, the computer 8 sends a status request to grasp the status of the image forming apparatus 1. Upon reception of the status request, the image forming apparatus 1 sends a status containing information of the presence/absence of recording paper sheets on each ejecting paper tray. Upon reception of this status, the computer 8 indicates the status of each ejecting paper tray on the CRT 12, thereby prompting the

This Sheet Has Been Replaced

operator to select an ejecting paper tray. In Fig. 2, the recording paper sheets are present on the ejecting paper tray 13. Therefore, the status indication of the ejecting paper tray 13 is the "presence of recording paper sheets", and the status indication of the ejecting paper trays 14 and 15 is the "absence of recording paper sheets". Upon checking the indication, the operator selects the ejecting paper tray 14 or 15 when the recording paper sheets are to be stored on an available ejecting paper tray, and inputs a designation of the ejecting paper tray from the keyboard 11 to the computer 8. In this case, assume that the ejecting paper tray 14 is selected. Upon reception of the designation of the ejecting paper tray, the computer 8 transmits a command for designation of the ejecting paper tray to the image forming apparatus 1 such that the recording paper sheets are output onto the ejecting paper tray 14. Upon reception of the command for designation of the ejecting paper tray, the control circuit 5 sends a signal to the ejecting paper tray switching unit 6. The ejecting paper tray switching unit 6 switches a convey path (not shown) to the ejecting paper tray such that the recording paper sheets are ejected onto the ejecting paper tray 14. The computer 8 transmits the image data to the image forming apparatus 1 during this time, though no problem is posed because a time required for switching of the

This Sheet Has Been Replaced

convey path is sufficiently shorter than that required from reception of the image data to the end of print. Upon reception of the image data, the image forming apparatus executes print and stores the recording paper sheets on the designated ejecting paper tray 14.

[Second Embodiment]

Figs. 1, 2, and 4 are views showing the second embodiment. A description of Figs. 1 and 2 is the same as that in the first embodiment and will be omitted.

A description will be made with reference to Fig. 4. An operation before reception of a status signal by a computer 8 is the same as that in the first embodiment, and a detailed description thereof will be omitted. An operation after reception of the status by the computer 8 will be described. Upon reception of the status, the computer 8 automatically selects an available ejecting paper tray and transmits a command for designation of the ejecting paper tray to an image forming apparatus 1. Upon reception of the command for designation of the ejecting paper tray, a control circuit 5 in the image forming apparatus 1 sends a selection signal to an ejecting paper tray switching unit 6. The ejecting paper tray switching unit 6 switches a convey path to the ejecting paper tray such that recording paper sheets are ejected onto an ejecting paper tray 14. The computer 8 transmits image data to the image forming apparatus 1 during this time,

This Sheet Has Been Replaced

and at the same time, indicates the ejecting paper tray number selected by the computer 8 on a CRT 12, thereby informing an operator of the ejecting paper tray for receiving the recording paper sheets. Upon reception of the image data, the image forming apparatus 1 executes print and ejects the recording paper sheets onto the ejecting paper tray 14.

[Third Embodiment]

Figs. 1, 2, and 5 are views showing the third embodiment. A description of Figs. 1 and 2 is the same as that in the first embodiment and will be omitted. In Fig. 5, an operation from reception of a status signal by a computer 8 to automatic selection of an available tray is the same as that in the second embodiment, and a detailed description thereof will be omitted. The subsequent operation will be described with reference to Fig. 5.

Upon selection of the ejecting paper tray, the computer 8 indicates the selection result and the status of each ejecting paper tray on a CRT 12, thereby requesting an operator for certification. Upon checking the indication, the operator inputs data representing acknowledgement or change of selection of the ejecting paper tray selected by the computer 8 from a keyboard 11. The computer 8 transmits a command for designation of the ejecting paper tray to an image forming apparatus 1 in accordance with the data input

This Sheet Has Been Replaced



from the keyboard 11. Thereafter, the same operation as that in the first embodiment is performed to store recording paper sheets on an ejecting paper tray 14.

[Fourth Embodiment]

Figs. 1, 2, and 6 are views showing the fourth embodiment. A description of Figs. 1 and 2 is the same as that in the first embodiment and will be omitted. An operation before transmission of a command for permission of occupancy by an image forming apparatus 1 is the same as that in the first embodiment. The subsequent operation will be described with reference to Fig. 6.

Upon transmission of the command for permission of occupancy, a control circuit 5 automatically selects an available ejecting paper tray and sends a selection signal to an ejecting paper tray switching unit 6. The ejecting paper tray switching unit 6 switches a convey path such that recording paper sheets are ejected onto the selected ejecting paper tray and transmits data representing the selection result to a computer 8. Upon reception of the data representing the selection result, the computer 8 indicates the selection result on a CRT 12 in accordance with the data to inform an operator of it, and sends image data to the image forming apparatus 1.

This Sheet Has Been Replaced



Thereafter, the same operation as that in the first embodiment is performed to store the recording paper sheets on an ejecting paper tray 14.

[Fifth Embodiment]

Figs. 1, 2, and 7 are views showing the fifth embodiment. A description of Figs. 1 and 2 is the same as that in the first embodiment and will be omitted. An operation before reception of data representing the selection result of an ejecting paper tray is the same as that in the fourth embodiment, and a detailed description thereof will be omitted. The subsequent operation will be described with reference to Fig. 7.

Upon reception of the data representing the selection result, a computer 8 indicates the selection result on a CRT 12, thereby requesting an operator for certification.

Thereafter, the same operation as that in the third embodiment is performed to store recording paper sheets on an ejecting paper tray 14.

In the above embodiments, the image forming apparatus has been described as a printer. However, it is not limited to a printer and may also be applied to a copying machine or the like having a facsimile communication function. In the above embodiments, a single computer and a single printer are used for the descriptive convenience. However, a plurality of computers and printers connected with each other in a

This Sheet Has Been Replaced

LAN may also be used. The computer and the image forming apparatus may also be set at different locations.

As has been described above, available recording paper sheet storage units can be detected, and the information can be transmitted to a computer or the like to designate a storage unit from the computer or the like. With this arrangement, the conventional problem can be solved, thereby realizing an image forming system having excellent operability.

The present invention can be applied to selection of a sheet feeding unit in an image forming apparatus. More specifically, the presence/absence or size of sheets in a plurality of feeding units is detected. The detection result is indicated on the CRT of a computer. An operator is prompted to select a feeding unit, or the image forming apparatus or the computer automatically selects a feeding unit. The selected feeding unit and the detection result may be indicated on the CRT of the computer.

In addition, the feeding unit automatically selected by the image forming apparatus or the computer may be changed by operating the keyboard of the computer.

This Sheet Has Been Replaced



An image forming system, of the present invention, which has an image forming apparatus for forming an image on a paper sheet in accordance with image data output from a computer includes a plurality of storage units, provided to the image forming apparatus, for storing the paper sheet, a plurality of detecting units for detecting the paper sheet on each of the plurality of storage units, a display unit, provided to the computer for displaying a detection result from each of the plurality of detecting units, an input unit, provided to the computer, for inputting an instruction for selecting the storage unit, and a control unit, provided to the image forming apparatus, for selecting the storage unit in accordance with the instruction input from the input unit. With this arrangement, the operator of the computer can detect the sheet storage status of the storage unit while staying in front of the computer, thereby selecting a desired storage unit.

This Sheet Has Been Replaced

WHAT IS CLAIMED IS:

1. An image forming system having an image forming apparatus for forming an image on a paper sheet in accordance with image data output from an image processing apparatus, comprising:

a plurality of storage means, provided to said image forming apparatus, for storing the paper sheet;

a plurality of detecting means for detecting the paper sheet on each of said plurality of storage means;

display means, provided to said image processing apparatus, for displaying a detection result from each of said plurality of detecting means;

input means, provided to said image processing apparatus, for inputting an instruction for selecting said storage means; and

control means, provided to said image forming apparatus, for selecting said storage means in accordance with the instruction input from said input means.

2. A system according to claim 1, wherein said storage means stores the paper sheet on which an image is formed, and said detecting means detects a presence/absence of the paper sheet on said storage means.

This Sheet Has Been Replaced

3. A system according to claim 1, wherein said storage means stores the paper sheet on which an image is not formed, and said detecting means detects a presence/absence of the paper sheet on said storage means.

4. A system according to claim 1, wherein said storage means stores the paper sheet on which an image is not formed, and said detecting means detects a size of the paper sheet stored on said storage means.

5. An image forming system having an image forming apparatus for forming an image on a paper sheet in accordance with image data output from an image processing apparatus, comprising:

a plurality of storage means, provided to said image forming apparatus, for storing the paper sheet;

a plurality of detecting means for detecting the paper sheet on each of said plurality of storage means;

determining means, provided to said image processing apparatus, for determining said storage means to be selected on the basis of a detection result from each of said detecting means;

display means, provided to said image processing apparatus, for displaying a determination result from said determining means; and

This Sheet Has Been Replaced

control means, provided to said image forming apparatus, for selecting said storage means in accordance with the determination result from said determining means.

6. A system according to claim 5, wherein said storage means stores the paper sheet on which an image is formed, and said detecting means detects a presence/absence of the paper sheet on said storage means.

7. A system according to claim 5, wherein said storage means stores the paper sheet on which an image is not formed, and said detecting means detects a presence/absence of the paper sheet on said storage means.

8. A system according to claim 5, wherein said storage means stores the paper sheet on which an image is not formed, and said detecting means detects a size of the paper sheet stored on said storage means.

9. A system according to claim 5, further comprising input means, provided to said image processing apparatus, for inputting an instruction for a change of said storage means determined by said determining means.

This Sheet Has Been Replaced



10. An image forming system having an image forming apparatus for forming an image on a paper sheet in accordance with image data output from an image processing apparatus, comprising:

a plurality of storage means, provided to said image forming apparatus, for storing the paper sheet;

a plurality of detecting means for detecting the paper sheet on each of said plurality of storage means;

determining means, provided to said image forming apparatus, for determining said storage means to be selected on the basis of a detection result from each of said detecting means;

display means, provided to said image processing apparatus, for displaying a determination result from said determining means; and

control means, provided to said image forming apparatus, for selecting said storage means in accordance with the determination result from said determining means.

11. A system according to claim 10, wherein said storage means stores the paper sheet on which an image is formed, and said detecting means detects a presence/absence of the paper sheet on said storage means.

This Sheet Has Been Replaced



12. A system according to claim 10, wherein said storage means stores the paper sheet on which an image is not formed, and said detecting means detects a presence/absence of the paper sheet on said storage means.

13. A system according to claim 10, wherein said storage means stores the paper sheet on which an image is not formed, and said detecting means detects a size of the paper sheet stored on said storage means.

14. A system according to claim 10, further comprising input means, provided to said image processing apparatus, for inputting an instruction for a change of said storage means determined by said determining means.

15. A control method for an image forming system having an image forming apparatus which has image forming means for forming an image on a paper sheet in accordance with image data output from an image processing apparatus and a plurality of storage means for storing the paper sheets, comprising the steps of:

detecting the paper sheet on each of the plurality of storage means in the image forming apparatus;

displaying a detection result in the image processing apparatus;

This Sheet Has Been Replaced

inputting an instruction for selecting the storage means in the image processing apparatus; and

selecting the storage means in accordance with the input instruction in the image forming apparatus.

16. A method according to claim 15, wherein the storage means stores the paper sheet on which an image is formed, and the step of detecting comprises detecting a presence/absence of the sheet on the storage means.

17. A method according to claim 15, wherein the storage means stores the paper sheet on which an image is not formed, and the step of detecting comprises detecting a presence/absence of the paper sheet on the storage means.

18. A method according to claim 15, wherein the storage means stores the paper sheet on which an image is not formed, and the step of detecting comprises detecting a size of the paper sheet stored on the storage means.

19. A control method for an image forming system having an image forming apparatus which has image forming means for forming an image on a paper sheet in accordance with image data output from an image

This Sheet Has Been Replaced

processing apparatus and a plurality of storage means for storing the paper sheets, comprising the steps of:

detecting the paper sheet on each of the plurality of storage means in the image forming apparatus;

determining the storage means to be selected on the basis of a detection result in the image processing apparatus;

displaying a determination result in the image processing apparatus; and

selecting the storage means in accordance with the determination result in the image forming apparatus.

20. A method according to claim 19, wherein the storage means stores the paper sheet on which an image is formed, and the step of detecting comprises detecting a presence/absence of the sheet on the storage means.

21. A method according to claim 19, wherein the storage means stores the paper sheet on which an image is not formed, and the step of detecting comprises detecting a presence/absence of the paper sheet on the storage means.

22. A method according to claim 19, wherein the storage means stores the paper sheet on which an image is not formed, and the step of detecting comprises

This Sheet Has Been Replaced

detecting a size of the paper sheet stored on the storage means.

23. A method according to claim 19, further comprising the step of inputting of an instruction for a change of the storage means determined by determining means in the image processing apparatus.

24. A control method for an image forming system having an image forming apparatus which has image forming means for forming an image on a paper sheet in accordance with image data output from an image processing apparatus and a plurality of storage means for storing the paper sheets, comprising the steps of:

detecting the paper sheet on each of the plurality of storage means in the image forming apparatus;

determining the storage means to be selected on the basis of a detection result in the image forming apparatus;

displaying a determination result in the image processing apparatus; and

selecting the storage means in accordance with the determination result in the image forming apparatus.

25. A method according to claim 24, wherein the storage means stores the paper sheet on which an image is formed, and the step of detecting comprises

This Sheet Has Been Replaced

detecting a presence/absence of the sheet on the storage means.

26. A method according to claim 24, wherein the storage means stores the paper sheet on which an image is not formed, and the step of detecting comprises detecting a presence/absence of the paper sheet on the storage means.

27. A method according to claim 24, wherein the storage means stores the paper sheet on which an image is not formed, and the step of detecting comprises detecting a size of the paper sheet stored on the storage means.

28. A method according to claim 24, further comprising the step of inputting of an instruction for a change of the storage means determined by determining means in the image processing apparatus.

This Sheet Has Been Replaced

ABSTRACT OF THE DISCLOSURE

An image forming system, of the present invention, which has an image forming apparatus for forming an image on a paper sheet in accordance with image data output from a computer includes a plurality of storage units, provided to the image forming apparatus, for storing the paper sheet, a plurality of detecting units for detecting the paper sheet on each of the plurality of storage units, a display unit, provided to the computer for displaying a detection result from each of the plurality of detecting units, an input unit, provided to the computer, for inputting an instruction for selecting the storage unit, and a control unit, provided to the image forming apparatus, for selecting the storage unit in accordance with the instruction input from the input unit. With this arrangement, the operator of the computer can detect the sheet storage status of the storage unit while staying in front of the computer, thereby selecting a desired storage unit.

This Sheet Has Been Replaced

FIG. 1






FIG. 2



This Sheet Has Been Replaced


This Sheet Has Been Replaced

FIG. 3




This Sheet Has Been Replaced

FIG. 4




This Sheet Has Been Replaced

FIG. 5




This Sheet Has Been Replaced

FIG. 6



This Sheet Has Been Replaced

FIG. 7



9604583-1 3005

REPLACEMENT SHEET
17 OCT 1996

Image Forming System in Which Image Processing Apparatus Is Connected to Image Forming Apparatus

BACKGROUND OF THE INVENTION

Field of the Invention

The present invention relates to an image forming system in which an image processing apparatus is connected to an image forming apparatus.

Related Background Art

Conventionally, an image formed by a personal computer or the like is printed out by a printer. However, such a printer has only one ejecting paper tray and cannot sort printed recording paper sheets. A printer has been proposed which is connected to a sorter so as to sort printed recording paper sheets. However, such a printer only controls the storage destination in the sorter from the printer side. An operator operating in front of a personal computer has no means for detecting a specific storage unit in the sorter, resulting in difficulty in finding recorded paper sheets destinated for the operator.

REPLACED SHEETS SG
☐ Description : paged ..... to paged .....
☑ Claim(s) : paged ...13... to paged ...21.....
☐ Drawing(s) : paged ..... to paged .....
☑ Abstract : paged ...22... to paged ...23.....
DATE OF RECEIPT .....

SG
✓ ... paged 12.
✓ ... paged 21.
✓ ... paged 1/6.
✓ ... paged 23.
DATE OF RECEIPT 17/10/96

REPLACEMENT SHEET
17 OCT 1996

SUMMARY OF THE INVENTION

It is an object of the present invention to provide an image forming system for solving the above problem.

It is another object of the present invention to provide an image forming system in which an operator can detect the status of each storage unit of an image forming apparatus from an image processing apparatus side, thereby selecting the storage unit.

It is still another object of the present invention to provide an image forming system in which an operator at an image processing apparatus can certify an automatically selected storage unit of an image forming apparatus.

It is still another object of the present invention to provide an image forming system in which the operator at an image processing apparatus can change an automatically selected storage unit of an image forming apparatus.

Other objects and features of the invention will be apparent from the following detailed description in conjunction with the accompanying drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

Fig. 1 is a block diagram showing an image forming system of an embodiment of the present invention;

REPLACEMENT SHEET
17 OCT 1996

Fig. 2 is a view showing the outer appearance of the image forming system;

Fig. 3 is a view for explaining a communication operation of the image forming system;

Fig. 4 is a view for explaining a communication operation of the image forming system;

Fig. 5 is a view for explaining a communication operation of the image forming system;

Fig. 6 is a view for explaining a communication operation of the image forming system; and

Fig. 7 is a view for explaining a communication operation of the image forming system.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

[First Embodiment]

Figs. 1 to 3 are views showing the first embodiment of the present invention. Referring to Figs. 1 and 2, an image forming apparatus 1 records image data from a computer 8. A sensor 2 detects the presence/absence of recording paper sheets on an ejecting paper tray 13. A sensor 3 detects the presence/absence of recording paper sheets on an ejecting paper tray 14. A sensor 4 detects the presence/absence of recording paper sheets on an ejecting paper tray 15. A control circuit 5 controls all operations in the image forming apparatus, including processing of signals from the sensors 3 to

REPLACEMENT SHEET
17 OCT 1996

4. An ejecting paper tray switching unit 6 switches the ejecting paper tray for receiving recording paper sheets in accordance with a signal from the control circuit. An interface (I/F) 7 on the image forming apparatus side connects the image forming apparatus 1 to the computer 8 through communication. The computer 8 generates or stores image data. An interface (I/F) 9 on the computer 8 side connects the image forming apparatus 1 to the computer 8 through communication. A CPU 10 controls the computer 8. A keyboard 11 is used by an operator to input an instruction to the computer 8. A CRT 12 serves as the display unit of the computer 8. The ejecting paper tray 13 serves as one of the storage units for storing recording paper sheets. The ejecting paper tray 14 serves as one of the storage units for storing recording paper sheets. The ejecting paper tray 15 serves as one of the storage units for storing recording paper sheets. A cable 16 connects the image forming apparatus 1 to the computer 8 for communication. Recording paper sheets 17 are selectively ejected onto the ejecting paper trays. The operation of the first embodiment is sequentially described in Fig. 3.

The operation in the above arrangement will be described below with reference to Fig. 3.

When an image generated or stored in the computer 8 is to be printed out, the operator inputs a print

REPLACEMENT SHEET
17 OCT 1996

instruction from the keyboard 11 to the computer 8. Upon reception of this instruction, the CPU 10 of the computer 8 transmits a printer occupancy command to the image forming apparatus 1 through the I/F 9. Upon reception of the printer occupancy command through the I/F 7, the control circuit 5 of the image forming apparatus 1 certifies the occupancy status of the image forming apparatus itself. If a recording enable state is set, a command for permission of occupancy is transmitted to the computer 8 (at this time, if the image forming apparatus is connected to a plurality of computers, and recording of an image from one of the remaining computers is being performed, or if the image forming apparatus singly has a copy function, and a copying operation is being performed, a command for rejection of occupancy is sent. However, this status is not the subject matter, and a detailed description thereof will be omitted).

Upon reception of the command for permission of occupancy, the computer 8 sends a status request to grasp the status of the image forming apparatus 1. Upon reception of the status request, the image forming apparatus 1 sends a status containing information of the presence/absence of recording paper sheets on each ejecting paper tray. Upon reception of this status, the computer 8 indicates the status of each ejecting paper tray on the CRT 12, thereby prompting the

REPLACEMENT SHEET
17 OCT 1996

operator to select an ejecting paper tray. In Fig. 2, the recording paper sheets are present on the ejecting paper tray 13. Therefore, the status indication of the ejecting paper tray 13 is the "presence of recording paper sheets", and the status indication of the ejecting paper trays 14 and 15 is the "absence of recording paper sheets". Upon checking the indication, the operator selects the ejecting paper tray 14 or 15 when the recording paper sheets are to be stored on an available ejecting paper tray, and inputs a designation of the ejecting paper tray from the keyboard 11 to the computer 8. In this case, assume that the ejecting paper tray 14 is selected. Upon reception of the designation of the ejecting paper tray, the computer 8 transmits a command for designation of the ejecting paper tray to the image forming apparatus 1 such that the recording paper sheets are output onto the ejecting paper tray 14. Upon reception of the command for designation of the ejecting paper tray, the control circuit 5 sends a signal to the ejecting paper tray switching unit 6. The ejecting paper tray switching unit 6 switches a convey path (not shown) to the ejecting paper tray such that the recording paper sheets are ejected onto the ejecting paper tray 14. The computer 8 transmits the image data to the image forming apparatus 1 during this time, though no problem is posed because a time required for switching of the

REPLACEMENT SHEET
17 OCT 1996

convey path is sufficiently shorter than that required from reception of the image data to the end of print. Upon reception of the image data, the image forming apparatus executes print and stores the recording paper sheets on the designated ejecting paper tray 14.

[Second Embodiment]

Figs. 1, 2, and 4 are views showing the second embodiment. A description of Figs. 1 and 2 is the same as that in the first embodiment and will be omitted.

A description will be made with reference to Fig. 4. An operation before reception of a status signal by a computer 8 is the same as that in the first embodiment, and a detailed description thereof will be omitted. An operation after reception of the status by the computer 8 will be described. Upon reception of the status, the computer 8 automatically selects an available ejecting paper tray and transmits a command for designation of the ejecting paper tray to an image forming apparatus 1. Upon reception of the command for designation of the ejecting paper tray, a control circuit 5 in the image forming apparatus 1 sends a selection signal to an ejecting paper tray switching unit 6. The ejecting paper tray switching unit 6 switches a convey path to the ejecting paper tray such that recording paper sheets are ejected onto an ejecting paper tray 14. The computer 8 transmits image data to the image forming apparatus 1 during this time,

REPLACEMENT SHEET
17 OCT 1996

and at the same time, indicates the ejecting paper tray number selected by the computer 8 on a CRT 12, thereby informing an operator of the ejecting paper tray for receiving the recording paper sheets. Upon reception of the image data, the image forming apparatus 1 executes print and ejects the recording paper sheets onto the ejecting paper tray 14.

[Third Embodiment]

Figs. 1, 2, and 5 are views showing the third embodiment. A description of Figs. 1 and 2 is the same as that in the first embodiment and will be omitted. In Fig. 5, an operation from reception of a status signal by a computer 8 to automatic selection of an available tray is the same as that in the second embodiment, and a detailed description thereof will be omitted. The subsequent operation will be described with reference to Fig. 5.

Upon selection of the ejecting paper tray, the computer 8 indicates the selection result and the status of each ejecting paper tray on a CRT 12, thereby requesting an operator for certification. Upon checking the indication, the operator inputs data representing acknowledgement or change of selection of the ejecting paper tray selected by the computer 8 from a keyboard 11. The computer 8 transmits a command for designation of the ejecting paper tray to an image forming apparatus 1 in accordance with the data input

REPLACEMENT SHEET
17 OCT 1996

from the keyboard 11. Thereafter, the same operation as that in the first embodiment is performed to store recording paper sheets on an ejecting paper tray 14.

[Fourth Embodiment]

Figs. 1, 2, and 6 are views showing the fourth embodiment. A description of Figs. 1 and 2 is the same as that in the first embodiment and will be omitted. An operation before transmission of a command for permission of occupancy by an image forming apparatus 1 is the same as that in the first embodiment. The subsequent operation will be described with reference to Fig. 6.

Upon transmission of the command for permission of occupancy, a control circuit 5 automatically selects an available ejecting paper tray and sends a selection signal to an ejecting paper tray switching unit 6. The ejecting paper tray switching unit 6 switches a convey path such that recording paper sheets are ejected onto the selected ejecting paper tray and transmits data representing the selection result to a computer 8. Upon reception of the data representing the selection result, the computer 8 indicates the selection result on a CRT 12 in accordance with the data to inform an operator of it, and sends image data to the image forming apparatus 1.

REPLACEMENT SHEET
17 OCT 1994

Thereafter, the same operation as that in the first embodiment is performed to store the recording paper sheets on an ejecting paper tray 14.

[Fifth Embodiment]

Figs. 1, 2, and 7 are views showing the fifth embodiment. A description of Figs. 1 and 2 is the same as that in the first embodiment and will be omitted. An operation before reception of data representing the selection result of an ejecting paper tray is the same as that in the fourth embodiment, and a detailed description thereof will be omitted. The subsequent operation will be described with reference to Fig. 7.

Upon reception of the data representing the selection result, a computer 8 indicates the selection result on a CRT 12, thereby requesting an operator for certification.

Thereafter, the same operation as that in the third embodiment is performed to store recording paper sheets on an ejecting paper tray 14.

In the above embodiments, the image forming apparatus has been described as a printer. However, it is not limited to a printer and may also be applied to a copying machine or the like having a facsimile communication function. In the above embodiments, a single computer and a single printer are used for the descriptive convenience. However, a plurality of computers and printers connected with each other in a

REPLACEMENT SHEET
17 OCT 2004

LAN may also be used. The computer and the image forming apparatus may also be set at different locations.

As has been described above, available recording paper sheet storage units can be detected, and the information can be transmitted to a computer or the like to designate a storage unit from the computer or the like. With this arrangement, the conventional problem can be solved, thereby realizing an image forming system having excellent operability.

The present invention can be applied to selection of a sheet feeding unit in an image forming apparatus. More specifically, the presence/absence or size of sheets in a plurality of feeding units is detected. The detection result is indicated on the CRT of a computer. An operator is prompted to select a feeding unit, or the image forming apparatus or the computer automatically selects a feeding unit. The selected feeding unit and the detection result may be indicated on the CRT of the computer.

In addition, the feeding unit automatically selected by the image forming apparatus or the computer may be changed by operating the keyboard of the computer.

REPLACEMENT SHEET
17 OCT 1996

An image forming system, of the present invention, which has an image forming apparatus for forming an image on a paper sheet in accordance with image data output from a computer includes a plurality of storage units, provided to the image forming apparatus, for storing the paper sheet; a plurality of detecting units for detecting the paper sheet on each of the plurality of storage units, a display unit, provided to the computer for displaying a detection result from each of the plurality of detecting units, an input unit, provided to the computer, for inputting an instruction for selecting the storage unit, and a control unit, provided to the image forming apparatus, for selecting the storage unit in accordance with the instruction input from the input unit. With this arrangement, the operator of the computer can detect the sheet storage status of the storage unit while staying in front of the computer, thereby selecting a desired storage unit.

REPLACEMENT SHEET
17 OCT 1996

WHAT IS CLAIMED IS:

1. An image forming system having an image forming apparatus for forming an image on a paper sheet in accordance with image data output from an image processing apparatus, comprising:

a plurality of storage means, provided to said image forming apparatus, for storing the paper sheet;

a plurality of detecting means for detecting the paper sheet on each of said plurality of storage means;

display means, provided to said image processing apparatus, for displaying a detection result from each of said plurality of detecting means;

input means, provided to said image processing apparatus, for inputting an instruction for selecting said storage means; and

control means, provided to said image forming apparatus, for selecting said storage means in accordance with the instruction input from said input means.

2. A system according to claim 1, wherein said storage means stores the paper sheet on which an image is formed, and said detecting means detects a presence/absence of the paper sheet on said storage means.

This Sheet Has Been Replaced

REPLACEMENT SHEET
17 OCT 1996

3. A system according to claim 1, wherein said storage means stores the paper sheet on which an image is not formed, and said detecting means detects a presence/absence of the paper sheet on said storage means.

4. A system according to claim 1, wherein said storage means stores the paper sheet on which an image is not formed, and said detecting means detects a size of the paper sheet stored on said storage means.

5. An image forming system having an image forming apparatus for forming an image on a paper sheet in accordance with image data output from an image processing apparatus, comprising:

a plurality of storage means, provided to said image forming apparatus, for storing the paper sheet;

a plurality of detecting means for detecting the paper sheet on each of said plurality of storage means;

determining means, provided to said image processing apparatus, for determining said storage means to be selected on the basis of a detection result from each of said detecting means;

display means, provided to said image processing apparatus, for displaying a determination result from said determining means; and

This Sheet Has Been Replaced

REPLACEMENT SHEET
17 OCT 1996

control means, provided to said image forming apparatus, for selecting said storage means in accordance with the determination result from said determining means.

6. A system according to claim 5, wherein said storage means stores the paper sheet on which an image is formed, and said detecting means detects a presence/absence of the paper sheet on said storage means.

7. A system according to claim 5, wherein said storage means stores the paper sheet on which an image is not formed, and said detecting means detects a presence/absence of the paper sheet on said storage means.

8. A system according to claim 5, wherein said storage means stores the paper sheet on which an image is not formed, and said detecting means detects a size of the paper sheet stored on said storage means.

9. A system according to claim 5, further comprising input means, provided to said image processing apparatus, for inputting an instruction for a change of said storage means determined by said determining means.

This Sheet Has Been Replaced

REPLACEMENT SHEET
17 OCT 1994

10. An image forming system having an image forming apparatus for forming an image on a paper sheet in accordance with image data output from an image processing apparatus, comprising:

a plurality of storage means, provided to said image forming apparatus, for storing the paper sheet;

a plurality of detecting means for detecting the paper sheet on each of said plurality of storage means;

determining means, provided to said image forming apparatus, for determining said storage means to be selected on the basis of a detection result from each of said detecting means;

display means, provided to said image processing apparatus, for displaying a determination result from said determining means; and

control means, provided to said image forming apparatus, for selecting said storage means in accordance with the determination result from said determining means.

11. A system according to claim 10, wherein said storage means stores the paper sheet on which an image is formed, and said detecting means detects a presence/absence of the paper sheet on said storage means.

This Sheet Has Been Replaced

REPLACEMENT SHEET
17 OCT 1996

12. A system according to claim 10, wherein said storage means stores the paper sheet on which an image is not formed, and said detecting means detects a presence/absence of the paper sheet on said storage means.

13. A system according to claim 10, wherein said storage means stores the paper sheet on which an image is not formed, and said detecting means detects a size of the paper sheet stored on said storage means.

14. A system according to claim 10, further comprising input means, provided to said image processing apparatus, for inputting an instruction for a change of said storage means determined by said determining means.

15. A control method for an image forming system having an image forming apparatus which has image forming means for forming an image on a paper sheet in accordance with image data output from an image processing apparatus and a plurality of storage means for storing the paper sheets, comprising the steps of:

detecting the paper sheet on each of the plurality of storage means in the image forming apparatus;

displaying a detection result in the image processing apparatus;

This Sheet Has Been Replaced

This Sheet Has Been Replaced

inputting an instruction for selecting the storage means in the image processing apparatus; and

selecting the storage means in accordance with the input instruction in the image forming apparatus.

16. A method according to claim 15, wherein the storage means stores the paper sheet on which an image is formed, and the step of detecting comprises detecting a presence/absence of the sheet on the storage means.

17. A method according to claim 15, wherein the storage means stores the paper sheet on which an image is not formed, and the step of detecting comprises detecting a presence/absence of the paper sheet on the storage means.

18. A method according to claim 15, wherein the storage means stores the paper sheet on which an image is not formed, and the step of detecting comprises detecting a size of the paper sheet stored on the storage means.

REPLACEMENT S
17 OCT 199

19. A control method for an image forming system having an image forming apparatus which has image forming means for forming an image on a paper sheet in accordance with image data output from an image

This Sheet Has Been Replaced

processing apparatus and a plurality of storage means for storing the paper sheets, comprising the steps of:

detecting the paper sheet on each of the plurality of storage means in the image forming apparatus;

determining the storage means to be selected on the basis of a detection result in the image processing apparatus;

displaying a determination result in the image processing apparatus; and

selecting the storage means in accordance with the determination result in the image forming apparatus.

20. A method according to claim 19, wherein the storage means stores the paper sheet on which an image is formed, and the step of detecting comprises detecting a presence/absence of the sheet on the storage means.

REPLACEMENT SHE
17 OCT 1996

21. A method according to claim 19, wherein the storage means stores the paper sheet on which an image is not formed, and the step of detecting comprises detecting a presence/absence of the paper sheet on the storage means.

22. A method according to claim 19, wherein the storage means stores the paper sheet on which an image is not formed, and the step of detecting comprises

This Sheet Has Been Replaced

detecting a size of the paper sheet stored on the storage means.

23. A method according to claim 19, further comprising the step of inputting of an instruction for a change of the storage means determined by determining means in the image processing apparatus.

24. A control method for an image forming system having an image forming apparatus which has image forming means for forming an image on a paper sheet in accordance with image data output from an image processing apparatus and a plurality of storage means for storing the paper sheets, comprising the steps of:

detecting the paper sheet on each of the plurality of storage means in the image forming apparatus;

determining the storage means to be selected on the basis of a detection result in the image forming apparatus;

displaying a determination result in the image processing apparatus; and

selecting the storage means in accordance with the determination result in the image forming apparatus.

25. A method according to claim 24, wherein the storage means stores the paper sheet on which an image is formed, and the step of detecting comprises

REPLACEMENT SH
17 OCT 1996

REPLACEMENT SHEET
17 OCT 1996

detecting a presence/absence of the sheet on the storage means.

26. A method according to claim 24, wherein the storage means stores the paper sheet on which an image is not formed, and the step of detecting comprises detecting a presence/absence of the paper sheet on the storage means.

27. A method according to claim 24, wherein the storage means stores the paper sheet on which an image is not formed, and the step of detecting comprises detecting a size of the paper sheet stored on the storage means.

28. A method according to claim 24, further comprising the step of inputting of an instruction for a change of the storage means determined by determining means in the image processing apparatus.

This Sheet Has Been Replaced

IMAGE FORMING SYSTEM IN WHICH IMAGE PROCESSING APPARATUS IS CONNECTED TO IMAGE FORMING APPARATUS

ABSTRACT OF THE DISCLOSURE

An image forming system, of the present invention, which has an image forming apparatus for forming an image on a paper sheet in accordance with image data output from a computer includes a plurality of storage units, provided to the image forming apparatus, for storing the paper sheet, a plurality of detecting units for detecting the paper sheet on each of the plurality of storage units, a display unit, provided to the computer for displaying a detection result from each of the plurality of detecting units, an input unit, provided to the computer, for inputting an instruction for selecting the storage unit, and a control unit, provided to the image forming apparatus, for selecting the storage unit in accordance with the instruction input from the input unit. With this arrangement, the operator of the computer can detect the sheet storage status of the storage unit while staying in front of the computer, thereby selecting a desired storage unit.

FIGURE 2

REPLACEMENT SHEET
17 OCT 1996

This Sheet Has Been Replaced

REPLACEMENT SHEET
17 OCT 1996

FIG. 1




FIG. 2





FIG. 3



REPLACEMENT SHEET
17 OCT 1996

FIG. 4




IMAGE FORMING APPARATUS 1
COMPUTER 8
OPERATOR
PRINT INSTRUCTIONS
PRINTER OCCUPANCY COMMAND
CERTIFICATION OF OCCUPANCY STATUS PERMISSION OF OCCUPANCY
STATUS REQUEST
CERTIFICATION STATUS OF STATUS
SELECTION OF AVAILABLE EJECTING PAPER TRAY
DESIGNATION OF EJECTING PAPER TRAY
SWITCHING OF EJECTING PAPER TRAY
SENDING OF IMAGE DATA
INDICATION OF EJECTING PAPER TRAY SELECTED
EXECUTION OF PRINT
CERTIFICATION OF EJECTING PAPER TRAY
REPLACEMENT SHEET
17 OCT 1996

FIG. 5



REPLACEMENT SHEET
17 OCT 1996

FIG. 6




IMAGE FORMING APPARATUS 1
COMPUTER 8
OPERATOR
PRINT INSTRUCTIONS
PRINTER OCCUPANCY COMMAND
CERTIFICATION OF OCCUPANCY STATUS
PERMISSION OF OCCUPANCY
SELECTION OF AVAILABLE EJECTING PAPER TRAY
SELECTION RESULT
SWITCHING OF EJECTING PAPER TRAY
INDICATION OF EJECTING PAPER TRAY SELECTED
SENDING OF IMAGE DATA
EXECUTION OF PRINT
CERTIFICATION OF EJECTING PAPER TRAY
5
REPLACEMENT SHEET
17 OCT 1996

FIG. 7



REPLACEMENT SHEET
17 OCT 1996

REPLACEMENT SHEETS SG
... to paged .....
✓ ... to paged 20.
... to paged .....
✓ ... to paged ...
4/12/99

* C L M S *

REPLACEMENT SHEET

WHAT IS CLAIMED IS:

1. **An image forming system having an image forming apparatus (1) for forming an image on a paper sheet in accordance with image data output from an image processing apparatus (8), comprising:**

a plurality of storage means (13, 14, 15), provided to said image forming apparatus (1), for storing the paper sheet;

a plurality of detecting means (2, 3, 4) for detecting the paper sheet on each of said plurality of storage means (13, 14, 15);

display means (12), provided to said image processing apparatus (8), for displaying a detection result from each of said plurality of detecting means (2, 3, 4);

input means (11), provided to said image processing apparatus (8), for inputting an instruction for selecting said storage means; and

control means (5), provided to said image forming apparatus (1), for selecting said storage means in accordance with the instruction input from said input means (11).

2. A system according to claim 1, wherein said storage means stores the paper sheet on which an image is formed, and said detecting means detects a presence/absence of the paper sheet on said storage means.

3. A system according to claim 1, wherein said storage means stores the paper sheet on which an image is not formed, and said detecting means detects a presence/absence of the paper sheet on said storage means.

REPLACEMENT SHEET
09 DEC 1999

REPLACEMENT SHEET
09 DEC 1999

4. A system according to claim 1, wherein said storage means stores the paper sheet on which an image is not formed, and said detecting means detects a size of the paper sheet stored on said storage means.

5. An image forming system having an image forming apparatus (1) for forming an image on a paper sheet in accordance with image data output from an image processing apparatus (8), comprising:

a plurality of storage means (13, 14, 15), provided to said image forming apparatus (1), for storing the paper sheet;

a plurality of detecting means (2, 3, 4) for detecting the paper sheet on each of said plurality of storage means (13, 14, 15);

determining means (10), provided to said image processing apparatus (8), for determining said storage means to be selected on the basis of a detection result from each of said detecting means (2, 3, 4);

display means (12), provided to said image processing apparatus (8), for displaying a determination result from said determining means; and

control means (5), provided to said image forming apparatus (1), for selecting said storage means in accordance with the determination result from said determining means.

6. A system according to claim 5, wherein said storage means stores the paper sheet on which an image is formed, and said detecting means detects a presence/absence of the paper sheet on said storage means.

7. A system according to claim 5, wherein said storage means stores the paper sheet on which an image is not formed, and said detecting means detects a



REPLACEMENT SHEET
09 DEC 1999

REPLACEMENT SHEET

~~presence/absence~~ of the paper sheet on said storage means.

8. A system according to claim 5, wherein said storage means stores the paper sheet on which an image is not formed, and said detecting means detects a size of the paper sheet stored on said storage means.

9. A system according to claim 5, further comprising input means, provided to said image processing apparatus, for inputting an instruction for a change of said storage means determined by said determining means.

10. An image forming system having an image forming apparatus (1) for forming an image on a paper sheet in accordance with image data output from an image processing apparatus (8), comprising:

a plurality of storage means (13, 14, 15), provided to said image forming apparatus (1), for storing the paper sheet;

a plurality of detecting means (2, 3, 4) for detecting the paper sheet on each of said plurality of storage means (13, 14, 15);

determining means (5), provided to said image forming apparatus (1), for determining said storage means to be selected on the basis of a detection result from each of said detecting means (2, 3, 4);

display means (12), provided to said image processing apparatus (8), for displaying a determination result from said determining means; and

control means (5), provided to said image forming apparatus (1), for selecting said storage means in accordance with the determination result from said determining means.

REPLACEMENT SHEET
09 DEC 1999

11. A system according to claim 10, wherein said storage means stores the paper sheet on which an image is formed, and said detecting means detects a presence/absence of the paper sheet on said storage means.

12. A system according to claim 10, wherein said storage means stores the paper sheet on which an image is not formed, and said detecting means detects a presence/absence of the paper sheet on said storage means.

13. A system according to claim 10, wherein said storage means stores the paper sheet on which an image is not formed, and said detecting means detects a size of the paper sheet stored on said storage means.

14. A system according to claim 10, further comprising input means, provided to said image processing apparatus, for inputting an instruction for a change of said storage means determined by said determining means.

15. **A control method for an image forming system having an image forming apparatus (1) which has image forming means for forming an image on a paper sheet in accordance with image data output from an image processing apparatus (8) and a plurality of storage means (13, 14, 15) for storing the paper sheets, comprising the steps of:**

detecting the paper sheet on each of the plurality of storage means (13, 14, 15) in the image forming apparatus (1);

displaying a detection result in the image processing

* C L M S *

REPLACEMENT SHEET
09 DEC 1999

REPLACEMENT SHEET

apparatus (8);

inputting an instruction for selecting the storage means in the image processing apparatus (8); and

selecting the storage means in accordance with the input instruction in the image forming apparatus (1).

16. A method according to claim 15, wherein the storage means stores the paper sheet on which an image is formed, and the step of detecting comprises detecting a presence/absence of the sheet on the storage means.

17. A method according to claim 15, wherein the storage means stores the paper sheet on which an image is not formed, and the step of detecting comprises detecting a presence/absence of the paper sheet on the storage means.

18. A method according to claim 15, wherein the storage means stores the paper sheet on which an image is not formed, and the step of detecting comprises detecting a size of the paper sheet stored on the storage means.

19. A control method for an image forming system having an image forming apparatus (1) which has image forming means for forming an image on a paper sheet in accordance with image data output from an image processing apparatus (8) and a plurality of storage means (13, 14, 15) for storing the paper sheets, comprising the steps of:

detecting the paper sheet on each of the plurality of storage means (13, 14, 15) in the image forming apparatus (1);

determining the storage means to be selected on the basis of a detection result in the image processing apparatus (8);

REPLACEMENT SHEET
09 DEC 1999

REPLACEMENT SHEET

displaying a determination result in the image processing apparatus (8); and

selecting the storage means in accordance with the determination result in the image forming apparatus (1).

20. A method according to claim 19, wherein the storage means stores the paper sheet on which an image is formed, and the step of detecting comprises detecting a presence/absence of the sheet on the storage means.

21. A method according to claim 19, wherein the storage means stores the paper sheet on which an image is not formed, and the step of detecting comprises detecting a presence/absence of the paper sheet on the storage means.

22. A method according to claim 19, wherein the storage means stores the paper sheet on which an image is not formed, and the step of detecting comprises detecting a size of the paper sheet stored on the storage means.

23. A method according to claim 19, further comprising the step of inputting of an instruction for a change of the storage means determined by determining means in the image processing apparatus.

24. A control method for an image forming system having an image forming apparatus (1) which has image forming means for forming an image on a paper sheet in accordance with image data output from an image processing

* C L M S *

REPLACEMENT SHEET
09 DEC 1999

REPLACEMENT SHEET

apparatus (8) and a plurality of storage means (13, 14, 15) for storing the paper sheets, comprising the steps of:

detecting the paper sheet on each of the plurality of storage means (13, 14, 15) in the image forming apparatus (1);

determining the storage means to be selected on the basis of a detection result in the image forming apparatus (1);

displaying a determination result in the image processing apparatus (8); and

selecting the storage means in accordance with the determination result in the image forming apparatus (1).

25. A method according to claim 24, wherein the storage means stores the paper sheet on which an image is formed, and the step of detecting comprises detecting a presence/absence of the sheet on the storage means.

26. A method according to claim 24, wherein the storage means stores the paper sheet on which an image is not formed, and the step of detecting comprises detecting a presence/absence of the paper sheet on the storage means.

27. A method according to claim 24, wherein the storage means stores the paper sheet on which an image is not formed, and the step of detecting comprises detecting a size of the paper sheet stored on the storage means.

28. A method according to claim 24, further comprising the step of inputting of an instruction for a change of the storage means determined by determining means in the image processing apparatus.

* C L M S *

REPLACEMENT SHEET
09 DEC 1999

29. A control method for an image forming system having an image forming apparatus (1) which has image forming means for forming an image on a paper sheet in accordance with image data output from an image processing apparatus (8) and a plurality of storage means (13, 14, 15) for storing the paper sheet, comprising the steps of:

inputting a detection result of the paper sheet on each of the plurality of storage means from the image forming apparatus (1);

displaying the detection result in the image processing apparatus (8);

inputting an instruction for selecting the storage means in the image processing apparatus (8) by an operator; and

outputting a command for selecting the storage means in accordance with the input instruction to the image forming apparatus (1).

30. A method according to Claim 29, wherein the storage means stores the paper sheet on which an image is formed, and the detection result includes information concerning whether there is the paper sheet in the storage means.

31. A method according to Claim 29, wherein the storage means stores the paper sheet on which an image is not formed, and the detection result includes information concerning whether there is the paper sheet in the storage means.

32. A method according to Claim 29, wherein the storage means stores the paper sheet on which an image is not formed, and the detection result includes information concerning the size of the paper sheet stored in the storage means.

* C L M S *

REPLACEMENT SHEET
09 DEC 1999

IMAGE FORMING SYSTEM IN WHICH IMAGE PROCESSING APPARATUS IS CONNECTED TO IMAGE FORMING APPARATUS

ABSTRACT OF THE DISCLOSURE

An image forming system, of the present invention, which has an image forming apparatus for forming an image on a paper sheet in accordance with image data output from a computer includes a plurality of storage units, provided to the image forming apparatus, for storing the paper sheet, a plurality of detecting units for detecting the paper sheet on each of the plurality of storage units, a display unit, provided to the computer for displaying a detection result from each of the plurality of detecting units, an input unit, provided to the computer, for inputting an instruction for selecting the storage unit, and a control unit, provided to the image forming apparatus, for selecting the storage unit in accordance with the instruction input from the input unit. With this arrangement, the operator of the computer can detect the sheet storage status of the storage unit while staying in front of the computer, thereby selecting a desired storage unit.

FIGURE 2